

DualCheck: Certificates and Skolem Strategies for Expansion-Based QBF Solving

Sidhant Bhavnani^[0000-0000-0000-0000]

No Institute Given

Abstract. Keywords: Quantified Boolean Formulas · Proof Certification · Expansion-Based Solving · Strategy Extraction.

1 Introduction

2 Preliminaries and Background

2.1 Quantified Boolean Formulas

A *quantified Boolean formula* (QBF) in prenex conjunctive normal form (PCNF) is defined as $\Phi = \Pi.\phi$, where $\Pi = Q_1v_1 \dots Q_nv_n$ is the *quantifier prefix* with $Q_i \in \{\forall, \exists\}$, and ϕ is the *matrix*, consisting of a conjunction of clauses $\{C_1, \dots, C_m\}$. The prefix Π establishes a strict linear order $<_\Pi$ on the set of propositional variables $V_\Phi := \{v_1, \dots, v_n\}$. The variable set V_Φ is partitioned into existential variables $E_\Phi := \{v_i \mid Q_i = \exists\}$ and universal variables $U_\Phi := \{v_i \mid Q_i = \forall\}$, such that $V_\Phi = E_\Phi \cup U_\Phi$. Throughout this paper, we assume closed formulas without free variables.

For any variable $v \in V_\Phi$, its *dependency domain* under prefix Π is the set of preceding variables:

$$D_\Pi(v) := \{w \in V_\Phi \mid w <_\Pi v\}. \quad (1)$$

An *assignment* τ over a set of variables V is a function $\tau : V \rightarrow \{\perp, \top\}$. For any subset $W \subseteq V$, the *restriction* of τ to W is denoted by $\tau|_W : W \rightarrow \{\perp, \top\}$, where $\tau|_W(v) = \tau(v)$ for all $v \in W$. For a variable $v \in V_\Phi$, we write $\tau|_{<_\Pi v} := \tau|_{D_\Pi(v) \cup \{v\}}$ for the restriction of τ to the variables preceding v under the prefix order $<_\Pi$.

We denote by $\text{vars}(\cdot)$ the set of variables occurring in a literal, clause, or formula. For each clause $C \in \phi$, we partition its literals into existential and universal subclauses:

$$C = C_E \vee C_U, \quad \text{vars}(C_E) \subseteq E_\Phi, \quad \text{vars}(C_U) \subseteq U_\Phi. \quad (2)$$

The truth value of a closed QBF is defined by recursively expanding quantifiers from innermost to outermost. Let $\phi_n := \phi$ and, for $1 \leq i \leq n$, define:

$$\phi_{i-1} := \begin{cases} \phi_i[v_i/\top] \wedge \phi_i[v_i/\perp] & \text{if } Q_i = \forall, \\ \phi_i[v_i/\top] \vee \phi_i[v_i/\perp] & \text{if } Q_i = \exists. \end{cases} \quad (3)$$

The resulting formula ϕ_0 contains no variables; Φ is *true* if $\phi_0 \equiv \top$ and *false* otherwise.

For a quantifier $Q \in \{\forall, \exists\}$, let $\overline{Q}$ denote its dual quantifier ($\overline{\forall} = \exists$ and $\overline{\exists} = \forall$). The *negation* of a PCNF formula $\Phi = \Pi.\phi$ is the prenex disjunctive normal form (PDNF) formula:

$$\neg\Phi := \overline{\Pi}.\neg\phi, \quad \overline{\Pi} := \overline{Q}_1 v_1 \dots \overline{Q}_n v_n, \quad \neg\phi \equiv \bigvee_{C \in \phi} \neg C. \quad (4)$$

Under negation, quantifier roles invert: $U_{\neg\Phi} = E_\Phi$ and $E_{\neg\Phi} = U_\Phi$. Semantically, $\neg\Phi$ is true if and only if Φ is false.

2.2 QBF Strategies

Definition 1 (Strategies). Let $\Phi = \Pi.\phi$ be a PCNF QBF. An admissible strategy for a quantified variable set $X \in \{E_\Phi, U_\Phi\}$ is a tuple of Boolean functions $f = (f_x)_{x \in X}$ such that each f_x depends on preceding variables in the prefix:

$$\text{vars}(f_x) \subseteq D_\Pi(x). \quad (5)$$

We write $\phi[f]$ for the propositional formula obtained by sequentially substituting f_x for $x \in X$ in reverse prefix order.

- An admissible strategy $s = (s_e)_{e \in E_\Phi}$ is a winning Skolem strategy for Φ if $\phi[s] \equiv \top$.
- An admissible strategy $h = (h_u)_{u \in U_\Phi}$ is a winning Herbrand strategy for Φ if $\phi[h] \equiv \perp$.

A closed QBF Φ is true if and only if it admits a winning Skolem strategy, and false if and only if it admits a winning Herbrand strategy [1].

Remark 1 (Strategy Duality under Negation). Because quantifier types invert under negation ($U_{\neg\Phi} = E_\Phi$) while the prefix order is preserved ($D_{\overline{\Pi}} = D_\Pi$), any admissible Herbrand strategy h for $\neg\Phi$ satisfies $\text{vars}(h_e) \subseteq D_\Pi(e)$ for each $e \in E_{\neg\Phi}$. Since substitution commutes with negation, $(\neg\phi)[h] \equiv \neg(\phi[h])$, which yields:

$$(\neg\phi)[h] \equiv \perp \iff \phi[h] \equiv \top. \quad (6)$$

Therefore, h is a winning Herbrand strategy for $\neg\Phi$ if and only if it is a winning Skolem strategy for Φ .

2.3 Expansion-Based Solving

Expansion-based solving evaluates QBFs by eliminating quantifiers through propositional instantiation [2, 4, 5], eliminating variables of only one quantifier kind at a time. Given an assignment to all variables of one quantifier kind, assigned variables are replaced by their truth values, while variables of the opposite quantifier kind are replicated and *annotated* by the assignment restricted

to preceding variables in the prefix. Formally, given a universal assignment $\alpha : U_\Phi \rightarrow \{\perp, \top\}$, each existential variable $x \in E_\Phi$ is instantiated as the distinct propositional variable x^ω , where $\omega = \alpha|_{<_{\Pi} x}$. For an existential literal ℓ with variable $x = \text{vars}(\ell) \in E_\Phi$, its annotated literal is $\ell^{\alpha|_{<_{\Pi} x}}$, defined as $x^{\alpha|_{<_{\Pi} x}}$ if $\ell = x$ and $\neg x^{\alpha|_{<_{\Pi} x}}$ if $\ell = \neg x$.

Instantiating $\Phi = \Pi.\phi$ under a complete universal assignment $\alpha : U_\Phi \rightarrow \{\perp, \top\}$ yields a propositional CNF formula $\phi^\alpha := \bigwedge_{C \in \phi} C^\alpha$ over annotated existential variables, where each clause $C = C_E \vee C_U$ instantiates according to:

$$C^\alpha := \begin{cases} \top & \text{if } \alpha \models C_U, \\ \{\ell^{\alpha|_{<_{\Pi} \text{vars}(\ell)}} \mid \ell \in C_E\} & \text{if } \alpha \not\models C_U. \end{cases} \quad (7)$$

The *complete expansion* of Φ is the conjunction over all $2^{|U_\Phi|}$ universal assignments:

$$\text{exp}(\Phi) := \bigwedge_{\alpha : U_\Phi \rightarrow \{\perp, \top\}} \phi^\alpha. \quad (8)$$

A formula Φ is false if and only if there exists a set of universal assignments A such that the partial expansion $\bigwedge_{\alpha \in A} \phi^\alpha$ is propositionally unsatisfiable [2, 4].

Dually, instantiating Φ under an existential assignment $\sigma : E_\Phi \rightarrow \{\perp, \top\}$ yields a formula ϕ^σ over universal variables. A QBF Φ is true if and only if there exists a set of existential assignments S such that the disjunction $\bigvee_{\sigma \in S} \phi^\sigma$ is valid, or equivalently, the conjunction of negated instantiations:

$$\bigwedge_{\sigma \in S} \neg \phi^\sigma \equiv \perp \quad (9)$$

is unsatisfiable [2, 4].

Modern expansion solvers (e.g., RReQS [4], Ijtihad [2]) solve QBFs by maintaining two propositional SAT instances in parallel within a Counterexample Guided Abstraction Refinement (CEGAR) loop:

- The *primal instance* accumulates instantiations $\bigwedge_{\alpha \in A} \phi^\alpha$ under universal assignments $\alpha : U_\Phi \rightarrow \{\perp, \top\}$. A refutation of this instance proves that Φ is false.
- The *dual instance* accumulates negated instantiations $\bigwedge_{\sigma \in S} \neg \phi^\sigma$ under existential assignments $\sigma : E_\Phi \rightarrow \{\perp, \top\}$. A refutation of this instance proves that Φ is true.

2.4 Expansion-Based Proof Systems

Proof systems for expansion-based QBF solving are parameterized by an underlying propositional proof system $\mathcal{P}$ [5, 8]. Formally, an expansion proof system $\forall\text{-Exp}+\mathcal{P}$ over a QBF $\Psi = \Pi.\psi$ is defined by:

1. **Axiom Rule (Universal Expansion):** Given a universal assignment $\alpha : U_\Psi \rightarrow \{\perp, \top\}$, instantiating the universal variables of Ψ under α and evaluating Boolean constants yields the propositional formula $\psi^\alpha = \psi[\alpha]$. Each

clause of ψ^α (over annotated existential literals $\ell^{\alpha|_{<\Pi \text{vars}(\ell)}}$) is introduced as an expansion axiom under α . When Ψ is in PCNF, this corresponds to the standard clause-by-clause rule: given a clause $C = C_E \vee C_U \in \psi$ such that $\alpha \not\models C_U$, the rule introduces the annotated clause:

$$\frac{}{\{\ell^{\alpha|_{<\Pi \text{vars}(\ell)}} \mid \ell \in C_E\}} \quad (\alpha \not\models C_U), \quad (10)$$

where each surviving existential literal $\ell \in C_E$ is annotated exclusively by the assignment to universal variables that precede its underlying variable in Π .

2. **Propositional Refutation in $\mathcal{P}$:** A refutation of the accumulated set of annotated clauses in the propositional proof system $\mathcal{P}$, deriving the empty clause $\perp$.

When $\mathcal{P}$ is propositional resolution (Res), this defines the classical $\forall$ -Exp+Res calculus [5], where inferences are resolution steps over annotated existential variables with matching annotation prefixes:

$$\frac{C_1 \vee x^\omega \quad C_2 \vee \neg x^\omega}{C_1 \vee C_2} \quad (x \in E_\Psi, \omega = \alpha|_{<\Pi x}). \quad (11)$$

The $\forall$ -Exp+Res calculus is sound and complete for false PCNF QBFs [5].

In modern automated reasoning, the propositional proof system $\mathcal{P}$ is commonly instantiated with clausal proof systems such as Reverse Unit Propagation (RUP) or Resolution Asymmetric Tautologies (RAT), yielding the $\forall$ -Exp+RUP and $\forall$ -Exp+RAT calculi [8]. This allows modern CDCL SAT solvers emitting clausal proofs to serve directly as the refutation engine. While RAT is presently the most common proof system for SAT solving, RUP refutations are of particular importance because they can be efficiently elaborated into resolution derivations, which in turn admit interpolation for strategy extraction.

2.5 Expansion Certification for False QBFs

To verify expansion-based solver results independently of solver heuristics, certification frameworks decouple verification into a two-phase architecture [3, 8]. Before detailing the verification algorithm, we review the structural contents of an expansion certificate for false QBFs.

Certificate Contents. An expansion certificate for a false QBF $\Phi = \Pi.\phi$ consists of four components:

1. An *annotation block* that defines the provenance of each propositional variable v appearing in the proof via two maps:
 - A *variable mapping* $\varepsilon(v) \in E_\Phi$, identifying the original existential variable of Φ that v represents.
 - An *assignment mapping* $\text{ann}(v)$, recording the partial universal assignment under which v was instantiated.

2. An *axiom clause set*, containing the annotated clauses generated by universal expansion.
3. An *origin map* orig , mapping each axiom clause in the proof to an original matrix clause of Φ from which it was derived.
4. A *propositional refutation* in proof system $\mathcal{P}$ (e.g., resolution in FERPMo-els [3] or DRAT in FERAT [8]), deriving $\perp$ from the axiom clause set.

Two-Phase Verification Pipeline. Verification proceeds in two independent passes:

1. **Phase 1 (Expansion Check):** An independent polynomial-time algorithm validates that every clause C in the axiom clause set is a legal universal expansion axiom of Φ . For each clause C , the checker retrieves its originating matrix clause $D = \phi[\text{orig}(C)]$ and verifies:
 - *Existential literal correspondence:* $\varepsilon(C) = D_E$. This confirms that the propositional literals of C accurately mirror the existential subclause of D .
 - *Universal literal falsification:* gathering the universal assignment $\tau := \bigcup_{l \in C} \text{ann}(\text{vars}(l))$ from the literal annotations, the checker confirms that every universal literal of D is falsified by τ :

$$\forall \ell \in D_U, \quad \neg \ell \in \tau. \quad (12)$$

This guarantees that the universal subclause was legally falsified by the assignment τ rather than satisfying the clause outright (which would render the clause redundant).

2. **Phase 2 (Propositional Refutation Check):** The verified axiom clause set and the propositional refutation are passed to an external certifying checker (such as `drat-trim`), which validates that $\perp$ is derived soundly.

3 Certifying Expansion Refutations (Proof Checking)

In this section, we present the proof-checking foundations of DualCheck. We first analyze the structural obstacle preventing direct certification in the true case, and formalize the solver’s dual instance as a well-defined QBF denoted $\text{PG}(\neg\Phi)$. We then prove the Axiom Correspondence Lemma, establishing that every clause emitted by an expansion solver into its dual instance is an exact $\forall\text{-Exp+Res}$ axiom of $\text{PG}(\neg\Phi)$. Finally, we introduce the unified DualCheck proof format `(.dc)` and the two-phase verification algorithms that validate both true and false solver outcomes.

3.1 The Clausal Barrier in True QBF Solving

As established in Section 2.3, modern expansion solvers decide whether a QBF $\Phi = \Pi.\phi$ is true by refuting its dual instance $\bigwedge_{\sigma \in S} \neg\phi^\sigma$, accumulated over candidate existential witnesses $\sigma : E_\Phi \rightarrow \{\perp, \top\}$. Recall that $U_{\neg\Phi} = E_\Phi$; thus,

an existential candidate assignment σ is identically a universal assignment to the universal variables of the negation $\neg\Phi$.

Under a candidate witness $\sigma : E_\Phi \rightarrow \{\perp, \top\}$, each clause $C_i = C_{i,E} \vee C_{i,U} \in \phi$ is evaluated on its existential literals:

- If $\sigma \models C_{i,E}$, the clause is satisfied by σ ($C_i^\sigma = \top$), and provides no constraint.
- If $\sigma \not\models C_{i,E}$, the clause survives as its universal subclause $C_{i,U}$.

Let $\phi^\sigma := \{C_i \in \phi \mid \sigma \not\models C_{i,E}\}$ denote the set of matrix clauses unsatisfied by σ . The formula added to the dual instance on branch σ is the negation of their conjunction:

$$\neg\phi^\sigma = \bigvee_{C_i \in \phi^\sigma} \neg C_{i,U}^\sigma = \bigvee_{C_i \in \phi^\sigma} \bigwedge_{\ell \in C_{i,U}} \neg\ell^\sigma. \quad (13)$$

Because each term $\bigwedge_{\ell \in C_{i,U}} \neg\ell^\sigma$ is a conjunction of literals, $\neg\phi^\sigma$ is a disjunction of cubes—a DNF formula. Converting $\neg\phi^\sigma$ into CNF via distributivity would incur an exponential explosion in clause count.

To preserve polynomial size, expansion solvers apply a structure-preserving Plaisted–Greenbaum (PG) transformation [6]. Each universal subclause $C_{i,U}$ is associated with a fresh auxiliary variable t_i , so that the negated clause—that is, the cube $\neg C_{i,U}^\sigma = \bigwedge_{\ell \in C_{i,U}} \neg\ell^\sigma$ —is represented by the auxiliary literal $\neg t_i^\sigma$. The negated conjunction $\neg\phi^\sigma$ is then represented clausally by the reference clause:

$$R^\sigma := \bigvee_{C_i \in \phi^\sigma} \neg t_i^\sigma, \quad (14)$$

coupled with the definition clauses $(t_i \vee \neg\ell)$ for each literal $\ell \in C_{i,U}$. Because $(t_i \vee \neg\ell)$ is equivalent to $\neg t_i \rightarrow \neg\ell$, these definition clauses encode the implication:

$$\neg t_i \rightarrow \bigwedge_{\ell \in C_{i,U}} \neg\ell, \quad (15)$$

asserting that the auxiliary literal $\neg t_i$ in the reference clause implies the negated clause, i.e., the cube $\neg C_{i,U}$.

Consequently, the dual SAT solver refutes instantiations not of the input formula Φ , but of an encoded formula containing auxiliary variables t_i . This transformation breaks the direct clause-to-clause correspondence that false-case certification frameworks rely upon: the reference clauses R^σ and definition clauses do not exist in the original matrix ϕ .

3.2 The Encoded Negation $\text{PG}(\neg\Phi)$ and Axiom Correspondence

To place dual refutations on a rigorous proof-theoretic foundation, we formalize the solver’s clausal encoding at the QBF level. Refuting the dual instance witnesses that Φ is true, which is semantically equivalent to refuting the negation $\neg\Phi = \overline{\Pi}.\neg\phi$. The formula $\text{PG}(\neg\Phi)$ lifts the solver’s auxiliary variables and definition clauses into a formal QBF.

Definition 2 (Plaisted–Greenbaum Encoding $\text{PG}(\neg\Phi)$). Let $\Phi = \Pi.\phi$ be a PCNF QBF with $\phi = \{C_1, \dots, C_m\}$. For each clause $C_i \in \phi$, let t_i be an auxiliary variable associated with C_i such that $\neg t_i$ represents the negated universal subclause (cube) $\neg C_{i,U} = \bigwedge_{\ell \in C_{i,U}} \neg \ell$, and let $T := \{t_1, \dots, t_m\}$. The QBF $\text{PG}(\neg\Phi) := \Pi'.\phi'$ is defined by:

- **Prefix:** Π' is obtained from the dual prefix $\overline{\Pi}$ by inserting each auxiliary variable t_i existentially immediately after $v_i^* := \max_{<_{\Pi}} \text{vars}(C_{i,U})$, so that

$$U_{\text{PG}(\neg\Phi)} = U_{\neg\Phi} = E_{\Phi}, \quad E_{\text{PG}(\neg\Phi)} = E_{\neg\Phi} \cup T = U_{\Phi} \cup T. \quad (16)$$

- **Matrix:** ϕ' consists of the definition clauses and the reference formula:
 1. Definition clauses: for each clause $C_i \in \phi$ and each literal $\ell \in C_{i,U}$, the binary clause:

$$(t_i \vee \neg \ell), \quad (17)$$

encoding the implication $\neg t_i \rightarrow \neg \ell$, and collectively $\neg t_i \rightarrow \bigwedge_{\ell \in C_{i,U}} \neg \ell$ (i.e., $\neg t_i \rightarrow \neg C_{i,U}$).

2. Reference formula: the formula

$$\bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg t_i). \quad (18)$$

Quantifying each t_i immediately after v_i^* ensures that every variable in the definition of t_i precedes t_i in the prefix Π' :

$$\forall \ell \in C_{i,U}, \quad \text{vars}(\ell) \leq_{\Pi'} v_i^* <_{\Pi'} t_i. \quad (19)$$

Because each auxiliary variable t_i is existential and quantified after all variables in its defining subclause $C_{i,U}$, setting $t_i \equiv \bigvee_{\ell \in C_{i,U}} \ell$ is prefix-admissible, reduces each definition clause $(t_i \vee \neg \ell)$ to a tautology, and transforms the reference formula $\bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg t_i)$ into $\bigvee_{C_i \in \phi} \neg C_i \equiv \neg \phi$. Hence, $\text{PG}(\neg\Phi)$ is an equisatisfiable definitional encoding of $\neg\Phi$, false if and only if $\neg\Phi$ is false.

When the dual solver explores a candidate assignment $\sigma : U_{\neg\Phi} \rightarrow \{\perp, \top\}$, it accumulates definition clauses and reference clauses over annotated existential variables. We now prove that all such clauses are valid universal expansion axioms of $\text{PG}(\neg\Phi)$.

Lemma 1 (Axiom Correspondence). Every clause introduced into the dual instance by an expansion solver on branch σ is a valid universal expansion axiom of $\text{PG}(\neg\Phi)$ under the universal assignment $\sigma : U_{\neg\Phi} \rightarrow \{\perp, \top\}$.

Proof. We analyze the two classes of clauses generated on branch σ :

1. **Definition clauses.** For each clause $C_i \in \phi$ and literal $\ell \in C_{i,U}$, the binary clause $(t_i \vee \neg \ell)$ is an explicit clause of the matrix ϕ' of $\text{PG}(\neg\Phi)$. Both $t_i \in T$ and $\text{vars}(\ell) \in U_{\Phi} = E_{\neg\Phi}$ are existential variables in $\text{PG}(\neg\Phi)$; neither is assigned by the universal assignment $\sigma : U_{\neg\Phi} \rightarrow \{\perp, \top\}$. Under universal assignment σ , the $\forall$ -Exp+Res axiom rule simply annotates each literal with

the restriction of σ to preceding universal variables in Π' , yielding the annotated clause:

$$(t_i^{\sigma|_{<\Pi'^{t_i}}} \vee \neg \ell^{\sigma|_{<\Pi', \text{vars}(\ell)}}). \quad (20)$$

Hence, every definition clause emitted by the solver is a valid $\forall$ -Exp+Res axiom of $\text{PG}(\neg\Phi)$.

2. **Reference clauses.** On branch σ , the solver emits the reference clause:

$$R^\sigma = \bigvee_{C_i \in \phi^\sigma} \neg t_i^{\sigma|_{<\Pi'^{t_i}}}, \quad (21)$$

where $\phi^\sigma = \{C_i \in \phi \mid \sigma \not\models C_{i,E}\}$. In $\text{PG}(\neg\Phi)$, the reference formula is $\bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg t_i)$. Because $\text{vars}(C_{i,E}) \subseteq E_\Phi = U_{\neg\Phi}$, every literal in $C_{i,E}$ is universal in $\text{PG}(\neg\Phi)$. Under the full universal assignment $\sigma : U_{\neg\Phi} \rightarrow \{\perp, \top\}$, each term $(\neg C_{i,E} \wedge \neg t_i)$ is evaluated as follows:

- If $\sigma \models C_{i,E}$, then $\neg C_{i,E}$ evaluates to $\perp$, and the term evaluates to $\perp \wedge \neg t_i \equiv \perp$.
- If $\sigma \not\models C_{i,E}$ (i.e., $C_i \in \phi^\sigma$), then $\neg C_{i,E}$ evaluates to $\top$, leaving the unassigned existential literal $\neg t_i^{\sigma|_{<\Pi'^{t_i}}}$.

The disjunction of surviving terms yields precisely the reference clause R^σ . Therefore, under universal assignment σ , the reference formula simplifies under Boolean constant evaluation directly to the clause R^σ .

Thus, all initial clauses refuted in the dual instance are clauses of the instantiated matrix $\phi'[\sigma]$, confirming that they are valid universal expansion axioms of $\text{PG}(\neg\Phi)$. $\square$

Theorem 1 (Refutation Certification). *Let π be a propositional resolution refutation of the dual instance produced by an expansion solver. Then π is an $\forall$ -Exp+Res refutation of $\text{PG}(\neg\Phi)$, soundly certifying that $\text{PG}(\neg\Phi)$ is false and that Φ is true.*

Proof. By Lemma 1, every initial clause of π is a valid $\forall$ -Exp+Res axiom of $\text{PG}(\neg\Phi)$. Every resolution step in π operates on annotated existential literals with identical prefixes. Because π derives the empty clause $\perp$, π is an $\forall$ -Exp+Res refutation of $\text{PG}(\neg\Phi)$. By soundness of $\forall$ -Exp+Res, $\text{PG}(\neg\Phi)$ is false. By Definition 2, $\text{PG}(\neg\Phi)$ is an equisatisfiable definitional encoding of $\neg\Phi$. Therefore, $\neg\Phi$ is false, which by QBF duality (Remark 1) soundly certifies that Φ is true. $\square$

3.3 The DualCheck Proof Format

To enable independent verification, DualCheck defines a unified proof format (.dc) to support both true and false QBFs. The format uses standard ASCII representation, organized into distinct sections:

Status and Problem Header. Every proof begins with a status line declaring whether the certified result is false or true:

s 0 (false QBF) or **s** 1 (true QBF).

This is immediately followed by the dimension header:

p **dc** $\langle num_prop_vars \rangle$ $\langle clause_count \rangle$

specifying the dimensions of the proof:

- $\langle num_prop_vars \rangle$: the highest propositional variable index used anywhere in the proof (following the standard DIMACS upper-bound convention);
- $\langle clause_count \rangle$: the number of initial propositional clauses in the expansion formula—specifically, the count of axiom clauses (**a**) for false QBFs, or the combined count of definition (**h**) and reference (**n**) clauses for true QBFs, excluding subsequent derived resolution clauses (**d**).

Expansion Lines. Lines starting with **x** state the variables introduced in the certificate, what original QBF variables they represent, and the assignment under which they were instantiated:

x $v_1 \dots v_k$ 0 $q_1 \dots q_k$ 0 $l_1 \dots l_p$ 0

where $v_1 \dots v_k$ are the variables in the certificate, $q_1 \dots q_k$ are the original variables they represent, and $l_1 \dots l_p$ is the assignment under which they were instantiated. Variables appearing in clauses that are not declared in any **x** line are auxiliary definition variables T .

Expansion Clauses. Initial clauses are tagged by single-character identifiers and store all required semantic provenance inline:

- **Axiom clauses** (**a**, false QBFs):

a *id* $l_1 \dots l_k$ 0 *orig* 0

storing the sequential clause identifier *id*, the instantiated literals $l_1 \dots l_k$, and the 1-based index *orig* of the originating matrix clause $D \in \phi$.

- **Definition clauses** (**h**, true QBFs):

h *id* l_1 l_2 0

storing the sequential clause identifier *id* and the binary definition clause $(t_i \vee \neg \ell)$ defining the auxiliary variable t_i .

- **Reference clauses** (**n**, true QBFs):

n *id* $l_1 \dots l_k$ 0 $o_1 \dots o_k$ 0 $a_1 \dots a_m$ 0

containing three zero-terminated sequences:

1. The literals $l_1 \dots l_k$ forming the reference clause R^σ ;
2. The inline literal origins $o_1 \dots o_k$, supplying the 1-based index of the originating matrix clause $D_j \in \phi$ for each corresponding literal l_j ;
3. The inline candidate existential witness assignment $a_1 \dots a_m$, recording the explicit existential assignment $\sigma : E_\phi \rightarrow \{\perp, \top\}$ explored on this branch.

Refutation Trace. The propositional refutation is recorded as a sequence of derived resolution clauses:

$$\text{d } id \ l_1 \dots l_k \ 0 \ c_1 \dots c_p \ 0$$

where id is the derived clause identifier, $l_1 \dots l_k$ are the resolvent literals (empty for the final refuting clause $\perp$), and $c_1 \dots c_p$ are antecedent clause identifiers in the proof.

3.4 Certificate Verification

DualCheck verifies certificates via a two-phase architecture:

1. **Phase 1 (Expansion Check):** The checker first processes the **x** lines to recover the mapping from each propositional variable to its original QBF variable and the assignment under which it was instantiated. Using these mappings, the checker validates that every initial clause in the certificate is a sound $\forall$ -Exp+Res axiom of Φ (for false QBFs) or of $\text{PG}(\neg\Phi)$ (for true QBFs).
2. **Phase 2 (Refutation Check):** Validates that the derived resolution steps (**d** lines) form a sound refutation deriving the empty clause $\perp$.

False QBF Verification ($s \ 0$). For false instances, Phase 1 validates each axiom clause (**a** line) against its originating matrix clause $D = \phi[\text{orig}]$ by executing the expansion check defined in Section 2.5: verifying existential correspondence under ε and ensuring that the accumulated literal annotations consistently falsify all universal literals in D_U .

True QBF Verification ($s \ 1$). For true instances, Phase 1 validates the initial clauses of the certificate against the matrix ϕ and the candidate existential assignments σ recorded on each reference clause (**n** line):

1. *Cube encoding and definition validation:* For each auxiliary literal $\neg t_i$ in a reference clause with originating matrix clause $D = \phi[o_j]$, the checker validates that the definition clauses (**h** lines) for t_i are of the form $(t_i \vee \neg \ell)$ such that the literals $\{\ell\}$ constitute precisely the universal subclause D_U .
2. *Annotation agreement:* The explicit existential assignment σ recorded in the reference clause agrees with the assignment recovered from the annotation of each literal $\ell \in D_U$.
3. *Clause satisfaction:* Every matrix clause omitted from the reference clause (claimed to be eliminated on this branch) is verified to be satisfied by the assignment ($\sigma \models C_E$).
4. *Definition liveness:* Every auxiliary variable defined in a definition clause (**h** line) appears negated in at least one reference clause, ensuring that no unreferenced definitions remain in the certificate.

Both checking routines operate in linear time with respect to the certificate and matrix size:

Theorem 2 (Complexity of Expansion Checking). *Phase 1 executes in time $O(|\mathcal{C}| \cdot \|\phi\|)$, where $|\mathcal{C}|$ is the number of clauses in the certificate and $\|\phi\|$ is the size of the input QBF matrix.*

Proof. For false QBFs, Phase 1 validates each of the $O(|\mathcal{C}|)$ axiom clauses in $O(|D|) \leq O(\|\phi\|)$ time by verifying literal correspondence and universal falsification via direct array lookups. For true QBFs, validating each reference clause involves checking definition clauses and literal annotations in $O(|D_U|) \leq O(\|\phi\|)$ time. Verifying clause satisfaction for omitted matrix clauses requires testing $\sigma \models C_E$, which takes $O(\|\phi\|)$ total time per reference clause. Definition liveness is verified in a single linear pass over the certificate clauses in $O(|\mathcal{C}|)$ time. Summing over all certificate clauses yields an overall verification time of $O(|\mathcal{C}| \cdot \|\phi\|)$. $\square$

4 Skolem Strategy Extraction

Beyond deciding truth values and verifying proofs, a primary practical application of QBF solving is strategy synthesis: extracting winning moves for the winning player as computable Boolean circuits. For false QBFs, strategy extraction from $\forall$ -Exp+Res refutations is well understood: symmetric Craig interpolation produces an admissible winning Herbrand strategy [7, 9]. For true QBFs, however, strategy extraction in expansion solving has remained an open challenge due to the clausal disruption introduced by structure-preserving definitional transformations. We now show that the clausal duality established in Section 3 resolves this challenge, enabling polynomial-time extraction of winning Skolem strategies from dual expansion refutations.

Eliminating Auxiliary Variables via Definition Substitution. Now let $\Phi = \Pi.\phi$ be a true QBF, and let π be the resolution refutation of the dual propositional instance produced by an expansion solver. By Theorem 1, π is an exact $\forall$ -Exp+Res refutation of the encoded negation $\text{PG}(\neg\Phi)$. In $\text{PG}(\neg\Phi)$, the quantifier roles are inverted relative to Φ : the original existential variables E_Φ become universal ($U_{\text{PG}(\neg\Phi)} = E_\Phi$), while the original universal variables U_Φ and the auxiliary definition variables T become existential ($E_{\text{PG}(\neg\Phi)} = U_\Phi \cup T$).

By the strategy extraction framework of Slivovsky [9], symmetric Craig interpolation applied to an $\forall$ -Exp+Res resolution refutation DAG directly yields an admissible winning Herbrand strategy. Applying this extraction to π on $\text{PG}(\neg\Phi)$ yields an admissible winning Herbrand strategy $h = (h_e)_{e \in E_\Phi}$ for $\text{PG}(\neg\Phi)$, guaranteeing that $\phi'[h] \equiv \perp$. However, because π contains resolution steps on auxiliary definition variables $t_i \in T$ that precede some $e \in E_\Phi$ in the prefix Π' ($t_i <_{\Pi'} e$), the component circuits h_e may read variables in T . Because T are auxiliary variables not present in Φ , h cannot serve directly as a Skolem strategy for Φ . To eliminate the auxiliary variables, we substitute each t_i with its defining disjunction:

$$\psi^* := \psi[t_1 / \bigvee_{\ell \in C_{1,U}} \ell] \dots [t_m / \bigvee_{\ell \in C_{m,U}} \ell]. \quad (22)$$

Applying this substitution to each component circuit h_e yields the substituted strategy $h^* := (h_e^*)_{e \in E_\Phi}$.

Lemma 2 (Strategy Correspondence). *If h is a winning Herbrand strategy for $\text{PG}(\neg\Phi)$, then h^* is an admissible winning Herbrand strategy for $\neg\Phi$.*

Proof. Admissibility. Let $e \in E_\Phi = U_{\neg\Phi}$. Any variable $w \in \text{vars}(h_e^*)$ either appears directly in h_e (in which case $w <_{\Pi'} e$ by the admissibility of h), or was introduced by substituting for an auxiliary variable $t_i \in \text{vars}(h_e)$ with $t_i <_{\Pi'} e$. In the latter case, $w \in \text{vars}(C_{i,U})$. By construction of the prefix Π' (Definition 2), t_i is placed immediately after $v_i^* = \max_{<_{\Pi}} \text{vars}(C_{i,U})$. Therefore, $w \leq_{\Pi} v_i^* <_{\Pi'} t_i <_{\Pi'} e$. Since $w \in U_\Phi = E_{\neg\Phi}$ and $e \in E_\Phi = U_{\neg\Phi}$, their relative order is preserved under quantifier inversion: $w <_{\Pi} e$. Hence $\text{vars}(h_e^*) \subseteq D_{\Pi}(e)$, confirming that h_e^* depends exclusively on variables strictly preceding e in the original prefix Π .

Soundness. To prove that h^* is a winning Herbrand strategy for $\neg\Phi$, we must show that $(\neg\phi)[h^*] \equiv \perp$. Recall from Definition 2 that the matrix ϕ' of $\text{PG}(\neg\Phi)$ is the conjunction of the definition clauses and the reference formula $\bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg t_i)$. Because h is a winning Herbrand strategy for $\text{PG}(\neg\Phi)$, it falsifies the matrix: $\phi'[h] \equiv \perp$. We evaluate the effect of the definition substitution $(\cdot)^*$ in four steps:

1. *Definition clauses star to $\top$:* For each clause $C_i \in \phi$ and each literal $\ell \in C_{i,U}$, applying $[t_i / \bigvee_{\ell' \in C_{i,U}} \ell']$ gives:

$$(t_i \vee \neg\ell)^* = \left(\bigvee_{\ell' \in C_{i,U}} \ell' \right) \vee \neg\ell \equiv \top,$$

due to the complementary literal pair $\ell \vee \neg\ell$. Hence all definition clauses evaluate to $\top$ under $(\cdot)^*$.

2. *The reference formula stars to $\neg\phi$:* Applying $(\cdot)^*$ to the reference formula replaces each $\neg t_i$ with $\neg(\bigvee_{\ell \in C_{i,U}} \ell) = \bigwedge_{\ell \in C_{i,U}} \neg\ell = \neg C_{i,U}$. Because $C_{i,E}$ contains no auxiliary variables from T , we have:

$$\begin{aligned} \left(\bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg t_i) \right)^* &= \bigvee_{C_i \in \phi} (\neg C_{i,E} \wedge \neg C_{i,U}) \\ &= \bigvee_{C_i \in \phi} \neg(C_{i,E} \vee C_{i,U}) = \bigvee_{C_i \in \phi} \neg C_i \equiv \neg\phi. \end{aligned}$$

Combined with step 1, the entire matrix stars to $\neg\phi$: $(\phi')^* \equiv \top \wedge \neg\phi \equiv \neg\phi$.

3. *$(\cdot)^*$ and $[h]$ commute:* Because the domain of $(\cdot)^*$ is T , the domain of h is E_Φ , $T \cap E_\Phi = \emptyset$, and the substituted strategy is defined componentwise by $h_e^* := (h_e)^*$, the substitutions commute:

$$((\phi')^*)[h^*] \equiv ((\phi')[h])^*.$$

4. *Substitution preserves unsatisfiability:* Because h is winning for $\text{PG}(\neg\Phi)$, $\phi'[h] \equiv \perp$. Any substitution instance of a contradiction is contradictory:

$$((\phi')[h])^* \equiv \perp^* \equiv \perp.$$

Chaining these equivalences establishes:

$$(\neg\phi)[h^*] \equiv ((\phi')^*)[h^*] \equiv ((\phi')[h])^* \equiv \perp.$$

Therefore, h^* is an admissible winning Herbrand strategy for $\neg\Phi$. $\square$

Theorem 3 (Skolem Strategy Extraction). *Let Φ be a true PCNF QBF and let π be an $\forall$ -Exp+Res refutation of $\text{PG}(\neg\Phi)$. Applying the interpolation framework of Slivovsky [9] to π followed by the definition substitution of Lemma 2 yields an admissible winning Skolem strategy $s = (s_e)_{e \in E_\Phi}$ for Φ in time $O(|\pi| \cdot \|\phi\|)$.*

Proof. We construct the winning Skolem strategy s in three stages:

1. *Refutation Structure:* By Theorem 1, π is a valid $\forall$ -Exp+Res refutation DAG of $\text{PG}(\neg\Phi)$ deriving the empty clause $\perp$. The leaves of π are universal expansion axioms of $\text{PG}(\neg\Phi)$ under candidate universal assignments $\sigma : U_{\text{PG}(\neg\Phi)} \rightarrow \{\perp, \top\}$ (where $U_{\text{PG}(\neg\Phi)} = E_\Phi$). Each internal node $v \in \pi$ represents a propositional resolution step on an annotated existential pivot literal x^τ , where $x \in E_{\text{PG}(\neg\Phi)} = U_\Phi \cup T$.
2. *Interpolation and Herbrand Strategy Synthesis:* Following Slivovsky [9], symmetric Craig interpolation applied to the refutation DAG π extracts an admissible winning Herbrand strategy $h = (h_e)_{e \in E_\Phi}$ for $\text{PG}(\neg\Phi)$ in time $O(|\pi|)$, ensuring that $\phi'[h] \equiv \perp$.
3. *Definition Substitution and Strategy Duality:* Because π contains resolution steps on auxiliary variables $t_i \in T$ with $t_i <_{\Pi'} e$, each circuit h_e may read inputs from T . Applying the definition substitution of Eq. (22) replaces each auxiliary input t_i with the disjunction $\bigvee_{\ell \in C_{i,U}} \ell$. Since each clause $C_i \in \phi$ has $|C_{i,U}| \leq \|\phi\|$, this substitution adds at most $O(|T| \cdot \|\phi\|)$ gates and executes in linear time $O(|h| + |T| \cdot \|\phi\|) = O(|\pi| \cdot \|\phi\|)$. By Lemma 2, the substituted circuit family $h^* = (h_e^*)_{e \in E_\Phi}$ is an admissible winning Herbrand strategy for $\neg\Phi$, satisfying $(\neg\phi)[h^*] \equiv \perp$. By strategy duality under negation (Remark 1), setting $s := h^*$ yields an admissible winning Skolem strategy for Φ satisfying $\phi[s] \equiv \top$.

The entire extraction procedure operates in time $O(|\pi| \cdot \|\phi\|)$. $\square$

5 Related Work

6 Conclusion

References

1. Beyersdorff, O., Blinkhorn, J., Mahajan, M.: Building strategies into QBF proofs. *Journal of Automated Reasoning* **65**(1), 125–154 (2020). <https://doi.org/10.1007/s10817-020-09560-1>

Table 1. Summary of foundational symbols, notations, and domains.

Symbol	Type	Domain / Definition	Role / Meaning
<i>Formula Syntax and Semantics</i>			
$\Phi = \Pi.\phi$	PCNF QBF	$\phi = \{C_1, \dots, C_m\}$	Input formula with linear prefix Π and CNF matrix ϕ
E_Φ, U_Φ	Variable sets	$V_\Phi = E_\Phi \cup U_\Phi$	Existential and universal variable sets of Φ
$D_\Pi(v)$	Variable set	$\{w \in V_\Phi \mid w <_\Pi v\}$	Dependency domain of variable v under Π
$C_i = C_{i,E} \vee C_{i,U}$	Clause	$\text{vars}(C_{i,E}) \subseteq E_\Phi, \text{vars}(C_{i,U}) \subseteq U_\Phi$	Clause partitioned into existential and universal parts
$\neg\Phi = \overline{\Pi}.\neg\phi$	PDNF QBF	$U_{\neg\Phi} = E_\Phi, E_{\neg\Phi} = U_\Phi$	Negation of Φ ; false QBF targeted in dual solving
<i>Strategies and Duality</i>			
$s = (s_e)_{e \in E_\Phi}$	Skolem strategy	$\text{vars}(s_e) \subseteq D_\Pi(e)$	Winning strategy for Φ ($\phi[s] \equiv \top$)
$h = (h_u)_{u \in U_\Phi}$	Herbrand strategy	$\text{vars}(h_u) \subseteq D_\Pi(u)$	Winning strategy for false Φ ($\phi[h] \equiv \perp$)
<i>Expansion Solving and Proof Calculus</i>			
α	Assignment	$\alpha : U_\Phi \rightarrow \{\perp, \top\}$	Universal assignment explored in primal solving
σ	Assignment	$\sigma : E_\Phi \rightarrow \{\perp, \top\}$	Existential candidate assignment explored in dual solving
ϕ^α	Prop. CNF	$\bigwedge_{C \in \phi} C^\alpha$	Instantiation of ϕ under universal branch α
ϕ^σ	Clause set	$\{C_i \in \phi \mid \sigma \not\models C_{i,E}\}$	Clauses unsatisfied by existential candidate σ
$\neg\phi^\sigma$	Prop. DNF	$\bigvee_{C_i \in \phi^\sigma} \neg C_{i,U}^\sigma$	Negated instantiation on branch σ
$\forall\text{-Exp+Res}$	Proof system	Universal expansion + resolution	Background proof calculus for expansion refutations
<i>Clausal Negation Encoding and Strategy Extraction</i>			
$t_i \in T$	Aux. variable	$v_i^* <_{\Pi'} t_i$	Abbreviation for universal subclause $\bigvee_{\ell \in C_{i,U}} \ell$
v_i^*	Variable	$\max_{<_\Pi} \text{vars}(C_{i,U})$	Innermost universal variable of C_i in Π
$\text{PG}(\neg\Phi) = \Pi'.\phi'$	QBF	$U_{\text{PG}(\neg\Phi)} = E_\Phi, E_{\text{PG}(\neg\Phi)} = U_\Phi \cup T$	Definitional encoding of $\neg\Phi$
$(t_i \vee \neg\ell)$	Clause	$\ell \in C_{i,U}, t_i \in T$	Definition clause encoding $\neg t_i \rightarrow \bigwedge_{\ell \in C_{i,U}} \neg\ell$
R^σ	Clause	$\bigvee_{C_i \in \phi^\sigma} \neg t_i^\sigma$	Reference clause emitted on branch σ
ψ^*	Substitution	$[t_i / \bigvee_{\ell \in C_{i,U}} \ell]$	Definition substitution eliminating auxiliary variables
I_i^C	Boolean circuit	Formula over $D_\Pi(u_i)$	Partial Craig interpolant label for clause C and variable u_i
$G_i(\mu)$	Guard condition	$H_\mu^{i-1} \wedge (\mu(u_i) \leftrightarrow 0)$	Prefix guard matching opposing assignment μ

2. Bloem, R., Braud-Santoni, N., Hadžić, V., Egly, U., Lonsing, F., Seidl, M.: Expansion-based QBF solving without recursion. In: 2018 Formal Methods in Computer Aided Design (FMCAD). pp. 1–10. IEEE (2018). <https://doi.org/10.23919/FMCAD.2018.8603004>
3. Hadžić, V., Bloem, R., Shukla, A., Seidl, M.: FERPMODELS: A certification framework for expansion-based QBF solving. In: 2022 24th International Symposium on Symbolic and Numeric Algorithms for Scientific Computing (SYNASC). pp. 80–83. IEEE (2022). <https://doi.org/10.1109/SYNASC57785.2022.00022>
4. Janota, M., Klieber, W., Marques-Silva, J., Clarke, E.M.: Solving QBF with counterexample guided refinement. *Artificial Intelligence* **234**, 1–25 (2016). <https://doi.org/10.1016/j.artint.2016.01.004>
5. Janota, M., Marques-Silva, J.: Expansion-based QBF solving versus Q-resolution. *Theoretical Computer Science* **577**, 25–42 (2015). <https://doi.org/10.1016/j.tcs.2015.01.048>
6. Plaisted, D.A., Greenbaum, S.: A structure-preserving clause form translation. *Journal of Symbolic Computation* **2**(3), 293–304 (1986). [https://doi.org/10.1016/S0747-7171\(86\)80028-1](https://doi.org/10.1016/S0747-7171(86)80028-1)
7. Schlaipfer, M., Slivovsky, F., Weissenbacher, G., Zuleger, F.: Multi-linear strategy extraction for QBF expansion proofs via local soundness. In: Theory and Applications of Satisfiability Testing – SAT 2020. Lecture Notes in Computer Science, vol. 12178, pp. 429–446. Springer (2020). https://doi.org/10.1007/978-3-030-51825-7_30
8. Simader, M., Rebola-Pardo, A., Seidl, M.: FERAT: A new expansion-based certification framework for quantified boolean formulas. In: Proceedings of the 40th ACM/SIGAPP Symposium on Applied Computing (SAC). pp. 1043–1050. ACM (2025). <https://doi.org/10.1145/3672608.3707863>
9. Slivovsky, F.: Strategy extraction by interpolation. In: Chakraborty, S., Jiang, J.H.R. (eds.) 27th International Conference on Theory and Applications of Satisfiability Testing (SAT 2024). Leibniz International Proceedings in Informatics (LIPIcs), vol. 305, pp. 28:1–28:20. Schloss Dagstuhl – Leibniz-Zentrum für Informatik (2024). <https://doi.org/10.4230/LIPIcs.SAT.2024.28>