The Grid Is the Alpha: Measuring Effective Multiplicity and Permutation Nulls in LLM Event-Driven Trading

Simarjot Khanna
Independent Researcher
Canada
simarkhanna76@gmail.com

Abstract

Papers that report trading performance for large language models describe one pipeline: one prompt, one way of reading the model's answer, one holding period, one entry rule. Behind that one number is a search whose size is rarely reported. We measure the effective multiplicity of one such search and benchmark it against a permutation null that any paper can run on the grid it has already computed. Over 2,978 SEC Form 8-K filings from 2025-08-01 to 2026-07-30, a window opening more than ten months after the most recent model in our grid was released, we build one event-driven equity pipeline over three open-weight models under 8 billion parameters and evaluate a pre-registered grid of 7,776 configurations differing only in choices papers rarely report. Annualised Sharpe runs from -3.85 to 2.46, standard deviation 1.01; with model, prompt and truncation all fixed, the 432 configurations reachable *after* the model has spoken still span 4.89 on average. No family of choices is the culprit: on a descriptive partition, 83.3% of the variance sits in interactions rather than in any main effect. The configurations are highly correlated, so the effective number of independent trials is 20 by the cheapest estimator and 160 by measurement, against a nominal 7,776, and the deflated Sharpe ratio of the best configuration moves from 0.995 through 0.390 to 0.072 depending on which count is assumed. We replace that assumption with a measurement: a within-session permutation benchmark, run over the identical grid, gives a best-of-grid Sharpe of 2.72 when the model's scores are permuted among the filings of each session, against 2.46 for the real pipeline ($p = 0.746$). In this study, the grid run on permuted scores reaches a higher best-of-grid Sharpe, on average, than the real pipeline. We close with a reporting protocol built on the same two instruments.


CCS Concepts

• **Applied computing** → **Economics**; • **Computing methodologies** → *Machine learning*.

Keywords

large language models, backtest overfitting, multiple testing, deflated Sharpe ratio, event-driven trading, reproducibility

ACM Reference Format:
Simarjot Khanna. 2026. The Grid Is the Alpha: Measuring Effective Multiplicity and Permutation Nulls in LLM Event-Driven Trading. In *7th ACM International Conference on AI in Finance (ICAIF '26), November 14–17, 2026, Milan, AA, Italy*. ACM, New York, NY, USA, 9 pages. https://doi.org/10.1145/3858063.3858869



This work is licensed under a Creative Commons Attribution 4.0 International License.
ICAIF '26, Milan, AA, Italy
© 2026 Copyright held by the owner/author(s).
ACM ISBN 979-8-4007-3087-0/2026/11
https://doi.org/10.1145/3858063.3858869

1 Introduction

A large and fast-growing literature reports that language models can trade. The reported artifact is almost always a single number attached to a single pipeline: this prompt, this model, this rule for turning the model's text into a position, this holding period. The pipeline has many more moving parts than that, and most of them are never described.

This paper measures what those parts are worth. We build one event-driven equity pipeline over SEC Form 8-K filings, and instead of reporting its Sharpe ratio we report the distribution of Sharpe ratios over a pre-registered grid of 7,776 configurations that differ only in choices that published pipelines leave unstated. The grid is deliberately not a search for alpha. It is an enumeration of the freedom a researcher has after deciding to do the study at all.

The concern is not new in finance. Bailey and López de Prado [3] argue that a backtest whose author has not controlled for the extent of the search is uninformative regardless of how good it looks, and give the deflated Sharpe ratio to correct for it. Harvey, Liu and Zhu [5] raise the significance bar for factor discovery for the same reason. Menkveld et al. [13] let 164 teams test the same hypotheses on the same data and find the resulting dispersion sizeable, and underestimated by the researchers themselves. In machine learning the same fragility is documented for prompts: formatting alone moves benchmark accuracy by up to 76 accuracy points on one model [16], and the order of few-shot examples separates near state of the art from random guessing [12].

What has not been done is to measure the two together in a trading pipeline. A position paper by Ye et al. [20] argues that public evidence cannot yet separate robust predictive ability from confounders such as short-window Sharpe uncertainty and narrative fitting, proposes a minimum reporting protocol, and reports no experiments. This paper supplies measurement where that position supplies standards, and the number needed to apply the existing correction: the effective number of trials.

Contributions.

(1) **An effective trial count and a permutation benchmark.** The grid is nowhere near 7,776 independent trials, and the estimator matters: the cheap participation ratio gives 20, the Li and Ji count gives 244, and the permutation benchmark says the grid behaves like 160. Permuting the model's outputs among the filings of the same session and re-running the identical grid gives the distribution of best-of-grid Sharpe

when those outputs carry no within-session information, and the real pipeline does not exceed it (Section 5.3).

(2) **The correction depends on a number papers rarely report.** We evaluate the expected-maximum formula behind the deflated Sharpe ratio at four assumed trial counts and at the count the permutation implies, and on this grid the spectral count that is easiest to compute is the one that under-corrects most (Section 5.3).

(3) **A measured dispersion.** Over one fixed event set, one universe and one window, annualised Sharpe ranges from -3.85 to 2.46 across 7,776 configurations that a reader of any single paper could not tell apart. With the model, prompt and truncation held fixed, the post-LLM choices alone span 4.89 (Section 5.1).

(4) **No scapegoat, and the reason.** The pre-registered comparison holds, narrowly: the seven post-LLM choices account for 8.7% of the variance against 7.0% for the model, which is the largest *single* main effect, while 83.3% of the variance sits in interactions, so neither family can be blamed on this evidence (Section 5.2).

(5) **A protocol and an estimator** that a paper can run on any grid it has already computed, with the artifact released (Section 6).

The grid, the sample, the primary statistics and the falsification condition were pre-registered before any return was computed, and the pre-registration ships with the artifact alongside a declared count of 7 amendments. The robustness arms in Section 5.5 are not covered by that claim: they were added after the pre-registered analysis was complete, in response to review, and they are declared as such rather than presented as planned.

2 Related work

Backtest overfitting and multiple testing. Selection over trials inflates the selected Sharpe ratio, and the inflation grows with the number of trials [1]. The deflated Sharpe ratio [3] corrects for this given the number of independent trials N, the dispersion of the trial Sharpe ratios, and the higher moments of the selected strategy's returns; the probabilistic Sharpe ratio [2] is its single-trial ancestor. White's reality check [18] bootstraps the distribution of the maximum statistic across strategies. All of this machinery was built for parameter grids over price-based rules. We apply it where the trials are not strategies but implementation choices, most of which the researcher does not think of as choices.

Undisclosed flexibility. Simmons et al. [17] showed that flexibility in analysis, undisclosed, is sufficient to make almost anything significant. Menkveld et al. [13] measured the finance version across 164 teams. Their design cannot attribute the dispersion to a particular decision, because the teams differ in every decision at once. Ours can, because the decisions are enumerated rather than delegated.

LLMs that trade. Lopez-Lira and Tang [11] score news headlines and report daily long-short returns. A line of agentic systems followed [14, 19, 21–23]. Li et al. [9] audit this literature by varying the market: longer horizons and different regimes, with the pipeline held fixed. We do the orthogonal audit, holding the market fixed and varying the pipeline. Glasserman and Lin [4] study look-ahead contamination and find that masking company identifiers changes measured performance, which is why we place our entire sample after the release of every model in the pre-registered grid rather than argue about it, and why we also run an entity-masked arm.

Table 1: What 8 recent LLM trading pipelines report. ✓ means a sentence stating the item was located in the paper's full text; a blank means it was not. *Sensitivity* means a robustness analysis over implementation choices; † marks a paper that ablates *components* instead, which is a different thing and is why the text says no paper we could code reports the former.

	prompt text	holding period	entry timing	sensi-tivity	costs
Lopez-Lira and Tang [11]	✓	✓	✓		✓
FinMem [21]	*full text not machine-readable*				
FinAgent [23]				†	
FinCon [22]		✓		†	
TradingAgents [19]					
FINSABER [9]					✓
ATLAS [14]		✓			
Huang et al. [6]		✓	✓		✓

Reporting practice. Table 1 records what a reader can recover from 8 recent pipelines, 7 coded from machine-readable full text. It is a convenience sample coded by one author: it illustrates practice, it does not survey it. The point is not carelessness, since Lopez-Lira and Tang [11] give their prompt, their rebalancing rule, their exact entry rule and four cost levels. It is that the union of what the sample reports is small, and none of the 7 we could code reports a sensitivity analysis over implementation choices rather than components or the market.

3 The pipeline

3.1 Data

The universe is the **S&P 500** constituent list on Wikipedia, retrieved on 2026-07-31, the day after the last session. The page was then at revision 1365256480, dated 2026-07-21. It lists 503 constituents. One row, for Cboe Global Markets, uses a different ticker format and was not parsed, so the universe holds 502 names. The event pool is every Form 8-K filed in the window by one of those names, 6,076 filings after collapsing dual-class duplicates; 8-K filings are the SEC's current-report mechanism and are known to move prices [7]. We score a seed-fixed random subsample of 3,000, 49% of the pool, because the full factorial did not fit the available compute; this is a declared amendment and the draw ships in the artifact. Of those, 2,978 filings leave room for the longest holding period, and 2,976 of these have every price a position needs; no configuration takes a position in the other two. For each filing we retrieve the primary document and its EX-99 exhibits from EDGAR and strip the markup. Prices are daily open, close and split- and dividend-adjusted close; the benchmark is SPY.

Two properties of this source matter. First, every filing carries an exact acceptance timestamp, so whether a configuration could have traded on it is a fact rather than an assumption. Second, the window opens more than ten months after the most recent of the three scoring models in the grid was publicly released. A model

Table 2: The pre-registered factor grid: $18 \times 432 = 7{,}776$ configurations, each evaluated on the identical events, prices and window.

factor	levels	$\lvert\cdot\rvert$
LLM-side (one inference pass per combination of levels)		
model	Qwen2.5-7B, Mistral-7B-v0.2, Phi-3-mini	3
prompt	analyst probability; label with confidence; JSON with a no-view option	3
truncation	1200, 4000 characters	2
post-LLM (no new inference per level: the same raw output is re-read)		
parsing	strict (drop non-conforming answers), lenient (salvage, else neutral)	2
signal	level, cross-sectional rank, expanding per-ticker demeaning	3
threshold	0.00, 0.10, 0.20 deadband	3
holding	1, 3, 5 sessions	3
entry	next open, next close	2
weighting	equal, proportional to |signal|	2
neutralisation	none, subtract net exposure × SPY	2

cannot have been trained on text published after its own release, so this is a hard bound whether or not a cutoff is documented; the one model of the three whose card states a training-data cutoff gives October 2023. No configuration *in the grid* can therefore owe its performance to a memorised outcome, which is a stronger position than the usual argument about contamination [4] and it costs nothing, because the data source is current. The bound does not extend to the two post hoc scale arms added in Section 5.5, whose models were released mid-window; that exception is stated where the arms are reported and again in Threats.

3.2 Fixed elements

Four things are held fixed, so that none of them is a *factor* in the grid. They are not therefore inert: a constant applied to configurations that differ in turnover, exposure or holding period can still change the spread between them, and Section 5.5 measures exactly that for the cost assumption. (i) An event is tradable only in the first regular session that opens strictly after its acceptance timestamp, converted to Eastern time. (ii) Transaction costs are 5 basis points per side on traded notional, in the range used by comparable studies [6, 11]. (iii) Decoding is greedy with a fixed seed, so the reported dispersion is design, not sampling noise. (iv) Filing text is assembled as item codes, then exhibits, then the primary document, chosen so truncation does not hand every model an earnings 8-K's cover page pointing at Exhibit 99.1. We did not measure alternative orderings.

3.3 The grid

The factors are listed in Table 2. Three are LLM-side, and each combination of their levels costs a separate inference pass; seven are post-LLM and re-use the same raw model output, which is why a grid of this size is affordable at all. We call these choices *undisclosed* rather than meaningless. A five-day hold is not a one-day hold. The claim is narrower and checkable: no theory in this literature determines any of these levels, and Table 1 shows that most of them go unreported.

Table 3: Percentage of filings for which the model answered in the format the prompt asked for, so that a strict parser accepts it. A cell at or near zero means that under a strict parser that model-prompt combination has almost no tradable events. Whether it trades is therefore joint: the same output is usable under a lenient parser and unusable under a strict one.

	P1 probability	P2 label	P3 JSON
Qwen2.5-7B	100.00	99.98	99.98
Mistral-7B-v0.2	0.00	0.00	74.01
Phi-3-mini	0.15	92.11	4.35

4 Statistical framework

Effective trials. The configurations are not independent: they share events, prices and, in most cases, scores. Let Z be the $N \times T$ matrix of standardised daily configuration returns and $C = ZZ^{\top}/T$ its correlation matrix, whose eigenvalues λ_i sum to N. We take the participation ratio

$$N_{\text{eff}} = \Big(\sum_i \lambda_i\Big)^2 \Big/ \sum_i \lambda_i^2 = N^2 \Big/ \sum_{ij} C_{ij}^2, \tag{1}$$

which needs no eigendecomposition, and report the eigenvalue count of Li and Ji [8] as a second estimate. Because $\operatorname{rank}(Z) \le T$, all nonzero eigenvalues are obtained from a $T \times T$ matrix.

Deflated Sharpe. With $\widehat{SR}$ the per-observation Sharpe of the selected configuration, V the variance of the trial Sharpe ratios, γ the Euler-Mascheroni constant and $Z(\cdot)$ the standard normal CDF, Bailey and López de Prado's expected maximum over N independent trials is

$$\mathbb{E}\big[\max \widehat{SR}\big] \approx \sqrt{V}\Big((1-\gamma)Z^{-1}\big[1-\tfrac{1}{N}\big] + \gamma Z^{-1}\big[1-\tfrac{1}{Ne}\big]\Big), \tag{2}$$

and the deflated Sharpe ratio is the probability that the selected Sharpe exceeds that threshold, adjusted for skewness and kurtosis [3]. The open question in any application is what to use for N.

A permutation benchmark. We replace that assumption with a measurement. In each of 1000 replications the assignment of model outputs to filings is permuted within each entry session, destroying the link between a filing and its score while preserving the daily score distribution, the number of positions per day and the correlation structure across configurations. The full grid is re-evaluated each replication.

Being precise about what this tests matters more than the arithmetic. The null it enforces is that the model's outputs are exchangeable *within a session*, that is, that they carry no information about which of that session's filings they belong to. It is not the general claim that the model contributes nothing: because session-level score distributions are preserved, any market-timing content survives permutation untested, and model outputs could still vary systematically with issuer or filing type. Nor is it exact in the combinatorial sense; with 1000 sampled reassignments it is a Monte Carlo permutation distribution. What it does give is a benchmark computed on the same events, the same prices and the same grid, and it is the negative half of a two-sided control for the harness, whose positive half is the oracle sweep in Section 5.3: a pipeline that reports a high number here is measuring its own grid.

Intervals. Confidence intervals on individual configurations use a stationary bootstrap [15] with mean block length five sessions. To separate the spread across configurations from the sampling error of any one of them, sessions are resampled once per replication and every configuration is re-evaluated on the same resampled sessions, so the sampling error they share cancels and what remains is the error of the differences between them.

Configurations that never trade. A configuration can be well defined and still hold nothing: a strict parser rejecting every answer from a model-prompt cell leaves it with no positions and a Sharpe of 0/0. We record those at zero, the limit of a strategy that holds nothing, keep them because a researcher choosing that configuration would face exactly this outcome, and report how many.

5 Results

5.1 Dispersion

Across 7,776 configurations of a single pipeline, evaluated on identical events and prices, annualised Sharpe runs from -3.85 to 2.46, with a standard deviation of 1.01 and an interquartile range of 1.22 (Figure 1). Most configurations lose money: 29% are profitable before any deflation and 9% clear a Sharpe of one, so a researcher drawing settings independently until one did would expect to succeed in about 11 attempts. That count assumes independent draws, which Section 5.3 shows the grid does not supply; it is the number a researcher who believed the settings were independent would predict. 14.8% of the grid never trades, because a strict parser can reject every answer a given model gives to a given prompt (Table 3); those are recorded at zero, which is above the grid median, so every percentile here is over the whole grid and shifts if they are dropped. Excluding the never-trading configurations the median is -0.51 and the default sits at the 45th percentile rather than the 38th; the spread widens to 1.08 from 1.01, and the range, the best configuration and its permutation p-value are unchanged, because both extremes are configurations that trade.

The three configurations in Table 4 are the ones a paper might report: our default returns -0.65 at the 38th percentile, the grid median -0.24, the best 2.46. The default is our own choice of a plausible unexamined setting, not a measured modal practice: Table 1 records what papers *disclose*, which is not enough to identify what they chose. The bootstrap intervals overlap, which is the point: these are not three strategies with different merits, they are three trading configurations built from one event set and one archive of model outputs, and nothing in any of the coded papers would let a reader tell which one was used.

The sharpest form needs no comparison between models. Holding the model, prompt and truncation fixed and letting only the 432 post-LLM configurations vary, the Sharpe ratios inside one such cell have a standard deviation of 0.94 and span 4.89 on average, up to 6.31 in the widest. Every number in that range describes the same model reading the same filings.

The natural objection is that a Sharpe ratio over 250 sessions is noisy enough to produce this spread on its own. Resampling sessions and re-evaluating every configuration on the same resample leaves a between-configuration spread of 1.30 against a within-configuration sampling standard deviation of 0.81, a ratio of 1.6: sampling error is a real component of what any single reported




Figure 1: Every configuration is the same pipeline on the same events, prices and window. The red distribution is the best-of-grid Sharpe when the model's outputs are permuted among the filings of the same session, so that they carry no within-session information.

Table 4: Three ways of reporting the same pipeline, and what the grid produces on permuted scores. The last row is the benchmark, not a fourth way of reporting: the mean best-of-grid annualised Sharpe when scores are permuted among filings of the same session, and it is *higher* than the grid maximum above it. The intervals are stationary-bootstrap intervals for each configuration on its own, unadjusted for the search that selected it; the permutation p-values in Section 5.3 account for that search.

what is reported	Sharpe	95% CI
our default configuration	-0.65	[-2.38, 1.04]
the grid median	-0.24	[-2.24, 1.86]
the grid maximum	2.46	[0.64, 4.31]
best of grid, scores permuted	2.72	

Sharpe ratio means, and it is the smaller one. The gap between the best and the median configuration averages 2.69 (sd 0.97) across resamples, and the best stays above the median in 100% of them.

5.2 Where the variance comes from

A balanced sum-of-squares partition splits the variance of Sharpe across the grid into marginal main effects. The configurations share events, prices and scores, so these shares are descriptive accounting rather than a causal decomposition over independent cells, and they are computed over the whole grid, including the never-trading configurations at zero; excluding those leaves the ordering intact at 9.5% against 7.6%. The pre-registered comparison holds: the seven post-LLM choices account for 8.7% of the variance and the language model for 7.0%. That is seven marginal shares against one, with most of the variance in neither, so it settles less than it appears to. The largest *single* main effect is model, which moves mean Sharpe across its levels by 0.59, and the runner-up is signal at 0.50. Stated without the analysis of variance, whose observations are not independent draws: swapping the language model with every other choice held fixed moves Sharpe by 0.87 on average, and re-deciding the pipeline around a fixed model moves it by 0.97, a ratio of only 1.1.

The conclusion is not that one family of choices is to blame. It is that 83.3% of the variance sits in interactions rather than in any main effect, so on this evidence no family can be. Table 3 makes one such interaction concrete, though it does not establish that this one is the largest. Qwen2.5-7B answers all three prompts in the requested format on essentially every filing; the two smaller models each comply with a *different* single prompt and are at or near zero on the other two. Under a strict parser, "which model" and "how strictly do you parse the answer" are therefore not two questions but one, and most papers disclose neither. A one-factor-at-a-time sensitivity analysis, which is what a reviewer would normally ask for, cannot see this at all.

One qualification the decomposition itself supplies. Run the same partition on the two components of the Sharpe ratio separately: the post-LLM choices carry 8.5% of the variance of mean daily return but 33.3% of the variance of daily volatility. Much of what they do is rescale risk rather than change the return earned, which is a real effect on a reported statistic and a smaller effect on a portfolio someone volatility-targets first.

Two checks that the ranking is not an artifact of how we drew the grid. Dropping the most aggressive level of the two factors a reviewer would name first, the 0.20 deadband and the five-day hold, leaves the post-LLM share at 11.8% against 5.9%, a wider margin than in the full grid. And because the models are optimistic on average, a configuration that neither demeans nor neutralises is partly holding the market; inside the market-neutral half alone the spread is still 0.89 and the post-LLM share 7.9% against 5.7%.

5.3 Multiplicity

The 7,776 configurations are not 7,776 trials. Their daily returns have a mean pairwise correlation of 0.12 and a root-mean-square correlation of 0.22, the quantity equation (1) responds to since it squares C_{ij} and is blind to sign; the leading eigenvalue carries 17% of the total, and equation (1) gives $N_{\text{eff}} = 20$, which is 0.3% of the nominal grid; the Li and Ji count gives 244. A researcher who treats the reported configuration as a single trial and one who applies a Bonferroni count over the whole grid are wrong in opposite directions, the Bonferroni count by more than two orders of magnitude and the single-trial count by more than one.

Table 5 shows what that choice is worth. The deflated Sharpe ratio of the best configuration is 0.995 if the grid is ignored, 0.713 at N_{eff}, 0.335 at the Li and Ji count and 0.072 at the nominal grid size. The same backtest is overwhelming evidence or none at all, depending on a number papers rarely report. Equation (2) is evaluated throughout at a mean trial Sharpe of zero, the null the deflated Sharpe ratio is defined against, so the $N = 1$ row is zero by construction.

The permutation null settles it without any of those assumptions. Over 1000 replications permuting the model's outputs among filings of the same session, the best-of-grid Sharpe averages 2.72 (sd 0.40, 95th percentile 3.45) against 2.46 for the real pipeline, a p-value of 0.746; the default configuration gives >0.99. The median session carries 11 events and 99.9% sit in sessions with at least one other, so the reassignment is far from degenerate and the null is conservative only to the small extent that it is not. The null grid is also slightly wider, 1.10 against 1.01, which raises its maximum: standardising each grid by its own spread narrows the gap from 0.26 to 0.06, so part of what the benchmark shows is dispersion rather than level.

A benchmark that rejects nothing proves nothing. A permutation test is a negative control, and on its own it cannot separate "these models carry no within-session information" from "this pipeline could not have detected information if it were there". So we built the positive half. A synthetic score of known directional accuracy, costing no model inference, is pushed through the identical grid and the identical benchmark, here at 200 replications rather than the 1000 used above, so its p-values are bounded below by $1/(200 + 1)$. A single synthetic dataset would establish only that some alternative is detectable, which is a sensitivity check and not an estimate of power, so we draw 10 independent oracles at each accuracy and report the share of them the benchmark rejects at the 5% level. At 50% it rejects 0% of draws (median best 0.40, median $p = 0.600$), which is the negative control behaving correctly, and at 52% it rejects 10%. At 55% it rejects 40% of draws with a median p of 0.065: an edge of that size is found less often than not, and a single draw at that accuracy can produce a significant result or an insignificant one. At 60% it rejects 100% of draws and at 70% 100%, with median p-values at the floor that replication count allows. So 60% is the lowest level we tested that was rejected in all 10 draws, and 55% is a level detected inconsistently, in 40% of draws, rather than a detection. Every dispersion figure we report is otherwise measured on scores with no detectable signal, so the oracle also settles whether the spread survives when signal is present. It widens: the same 10 oracles pushed through the identical post-LLM grid give 1.79 at 60% accuracy against 0.97 on real scores, a factor of 1.84, and 1.00 and 3.30 at 55% and 70%. Implementation choices move a genuine edge by more than they move noise. The empirical null above is consequently not explained by a pipeline that could not see directional information at all. It remains a statement about this oracle, which is favourable in two respects: its confidence is constant, so every synthetic position clears the widest deadband in the grid, and it is built against the same one-session horizon the entry rule trades. A signal with realistic confidence variation, or one aimed at a different horizon, may require a stronger edge than 60%, and 10 draws at five levels do not estimate where that threshold falls.

An independent check at the score level agrees and needs none of the grid. The rank correlation between a configuration's scores and the forward return, which is nearly invariant to threshold, weighting, neutralisation and entry timing, runs from -0.040 to +0.009 across the 18 LLM configurations, with a mean of -0.012 and 1 of 18 reaching 5% significance, in the wrong direction. In this sample, none of the 18 LLM configurations has scores with a positive rank correlation with the forward return that reaches 5% significance.

Two independent things follow. First, the observed best-of-grid Sharpe is unexceptional here: the identical pipeline with scores carrying no within-session information reaches the same performance. That is a statement about these three open-weight models on 8-K filings under one benchmark, not a demonstration that the models contribute nothing. It is nonetheless the comparison a paper reporting only its best configuration never makes, and without it that configuration's 2.46 looks like skill.

Table 5: What the deflated Sharpe ratio of the best configuration depends on. In the last row $\mathbb{E}[\max SR]$ is measured over 1000 permutation replications and $N = 160$ is the count *calibrated* to reproduce it, so that pairing is fitted rather than predicted; the deflated Sharpe beside it is what the fitted count implies.

trials assumed	$\mathbb{E}[\max SR]$	deflated Sharpe
$N = 1$ (a single trial)	0.00	0.995
$N = N_{\text{eff}} = 20$	1.93	0.713
$N = N_{\text{Li-Ji}} = 244$	2.86	0.335
N = full grid = 7,776	3.84	0.072
measured by permutation, $N = 160$	2.72	0.390

Second, the best-of-grid statistic is sensitive to the trial count whatever the signal. Equation (2) predicts 1.93, 2.86 and 3.84 at N_{eff}, the Li and Ji count and the nominal grid, against the measured 2.72; solving for the count that reproduces the measurement gives $N = 160$, between the two spectral estimates and far below the nominal grid. That count is calibrated to the permutation, not validated against it, so the 0.390 it implies is not independent evidence; it is useful because it sits between the 0.713 the cheapest estimator allows and the 0.072 Bonferroni imposes, and clears no conventional threshold, the verdict the permutation reaches directly at $p = 0.746$. The cheapest estimator under-corrects most here. One calibration does not make the participation ratio a lower bound in general and we do not claim it is; it says a paper which could afford the grid can afford the permutation instead of guessing.

5.4 The ranking is unstable across a split

The multiplicity argument says a selected configuration is inflated, and a split of the window shows how little of the ranking survives. Ranked on the first 125 sessions and re-ranked on the second, all 7,776 configurations show a rank correlation of 0.15. The best on the first half, at 3.73, records 0.53 on the second. It is not worthless: that still puts it at the 72nd percentile, and the ten best first-half configurations have a median second-half Sharpe of 0.40 against a grid median of 0.00. But roughly six sevenths of its apparent performance is gone. The test does not disentangle selection inflation from half-sample noise or genuine instability over time; it establishes that the ordering which produced the selection barely holds.

5.5 Arms that could have broken the design

The scale, masking and decoding arms below re-score the same events and run them through the same 432 post-LLM configurations, each with its own within-session permutation null over 300 replications. The last two add no model inference and have no null of their own: one re-slices the grid already computed, the other re-evaluates it at three further cost levels. The reference arm is the single LLM-side setting a paper would report: Qwen2.5-7B, prompt P1, 4000 characters. Its best-of-grid Sharpe is 2.26 against a null of 1.82, $p = 0.14$, which does not reject its own benchmark either. Throughout this subsection a large p-value is the expected outcome and a small one would be the surprise, the reverse of the oracle sweep above.

Would a larger model change the conclusion? This is the objection the paper most needs to answer, because small open-weight models finding nothing is not evidence that nothing is there. We re-scored every event twice more, at 36B and at 550B, on the identical prompt, truncation and decode cap. The 36B arm is Qwen3.6-35B-A3B, run locally through Ollama under the tag qwen3.6:latest as the build with digest `07d35212591f`. Ollama's library lists that build as qwen3.6:35b-a3b-q4_K_M, and 36B is the parameter count Ollama reports for it. The 550B arm is NVIDIA Nemotron 3 Ultra, called as nvidia/nemotron-3-ultra-550b-a55b: free through OpenRouter's free tier in August 2026; which upstream provider served each call was not recorded. Both arms ran at temperature 0 with reasoning disabled (Ollama's `think` option and OpenRouter's `reasoning.enabled` flag set to false), for the reason given in Section 7. Format compliance is 100% and 99.6% against 100% for the reference arm, so neither larger model is the better instrument on that axis and the largest is marginally the worst. Neither changes the conclusion. Their best-of-grid Sharpe ratios are 2.05 and 1.97 against their own nulls of 2.06 and 2.02 ($p = 0.48$ and $p = 0.52$), so no arm rejects its own benchmark, and the p-value rises with scale from 0.14 to 0.48 and 0.52; the reference arm exceeds its null in level but not significantly. Post-LLM dispersion does not disappear either, at 1.12 and 0.95 against 0.97. The larger models showed no better compliance than the reference arm and no detectable signal against their own nulls. Both were released inside the sample window, so neither inherits the release-date bound the grid enjoys; Threats says what that costs, and why replacing one model with another does not isolate parameter count.

Is the model reading the filing, or recognising the issuer? If the masking effect of Glasserman and Lin [4] applies here, a pipeline is partly trading on what the model remembers about a firm rather than on the filing in front of it. We re-scored every event with the issuer's name and ticker redacted from the prompt and the filing text. The scores move, correlating 0.68 with the unmasked ones and shifting 0.054 on average; the outcomes do not. Over the same 432 configurations the masked arm has median -0.76 against -0.88, maximum 2.35 against 2.26, and spread 0.94 against 0.97. Redaction removes memorised issuer knowledge and legitimate context together, so this does not isolate recognition; it shows the dispersion does not depend on the issuer being nameable.

Is the dispersion design or sampling noise in the decoder? The main grid is greedy-decoded with a fixed seed, so a reviewer is entitled to ask what stochastic decoding would add. Re-scoring the reference arm's configuration 3 times at temperature 0.7 with different seeds moves the median Sharpe of its post-LLM grid by 0.19, against a between-configuration spread of 0.97 in that same cell. In this probe cell the sampler moves the result far less than the design does.

Is the range an artifact of extreme settings? Restrict the grid to the conservative reading of the four factors that invite that objection, keeping only market-neutralised configurations with a demeaned or rank signal, a hold of one or three sessions and a lenient parser. That leaves 864 configurations spanning -3.29 to 2.46. The upper end is the grid maximum again rather than an independent one: the best configuration's model-prompt cell

complies with the strict parser every time, so its strict and lenient readings coincide and the restriction does not exclude it. The range is 5.75 with a standard deviation of 0.95. The spread is not in the corners of the grid.

Would realistic frictions remove it? They widen it. Re-running the whole grid at 0, 10 and 25 basis points per side against our fixed 5 gives best-of-grid Sharpe 3.81, 2.04 and 1.58 against 2.46, and standard deviations 0.96, 1.24 and 2.34 against 1.01. Dispersion rises with the cost level: charging more for trading stretches the grid rather than compressing it.

6 A reporting protocol

None of what follows requires a new statistic. Items R2 to R5 below need no new model inference. For R1, every combination of LLM-side levels (model, prompt and truncation) needs its own inference pass over the events; this grid needed 18 such passes.

R1. Enumerate the choices, then report a distribution. List every pipeline choice, and for those the paper cannot justify from theory, report the headline statistic across their levels rather than at one setting. The post-LLM half re-uses the raw model output, so a level costs a matrix product. Fix the grid before computing any return, and declare every later amendment to the design; this study has 7 declared amendments.

R2. Report the median configuration alongside the selected one. The gap between them is the selection premium, and it is a property of the search, not of the strategy.

R3. Estimate N_{eff} from your own grid, and report more than one. Equation (1) needs the daily return series of each configuration and nothing else:

```
live = R.std(1) > 0  # keep the ones that actually trade
Z = R[live] - R[live].mean(1, keepdims=True)
Z = Z / Z.std(1, keepdims=True)
C = Z @ Z.T / T
n_eff = C.shape[0]**2 / (C**2).sum()
```

The first line is not decoration: 1,152 of our own configurations hold nothing, so their return series is constant and the unguarded snippet returns `NaN` on the very grid it was written for. Report N_{eff} over the live configurations and say how many there were, since the multiplicity being corrected is over the whole grid. Reporting a deflated Sharpe ratio at $N = 1$ is not a correction, and reporting it at the nominal grid size errs the other way; on our grid the participation ratio under-corrected and the Li and Ji count [8] came closer to the measured benchmark. One calibration does not rank these estimators in general, which is the argument for reporting both and pairing them with R4.

R4. Run a permutation benchmark, and state what it holds fixed. Permuting the model's outputs among events of the same session and re-evaluating the grid gives the distribution of best-of-grid performance when those outputs carry no within-session information. It re-uses the scores already computed, so each replication costs one re-evaluation of the grid and no new model inference. Say which null it enforces: ours leaves session-level and market-timing content untested.

R5. State the entry rule against the information timestamp. Not the rebalancing frequency, which most papers do give, but the answer to "at what price could this have been traded, given when the information became public".

7 Threats to validity

The result is about dispersion, not about anybody's alpha. This paper does not show that any published LLM trading result is spurious. It shows that a single reported number from a pipeline of this kind is not identified without the disclosures in Section 6.

One market, one instrument, one window. US large-cap equities, 8-K events, twelve months, one regime. Li et al. [9] show that varying the regime alone changes conclusions about LLM strategies; we hold the regime fixed by construction, so our dispersion is a lower bound on what a reader faces across both sources of variation at once.

Model class. The three grid models are open-weight, from three different families, all under 8 billion parameters, chosen because they can be run tens of thousands of times for free and because all three predate the sample window. The 36B and 550B arms in Section 5.5 take two further steps up that axis and find the conclusion unchanged. Both are mixture-of-experts models whose active parameters per token are far below their totals, so the ladder is not a clean dense-scale sweep, and neither model is a proprietary frontier system, so our evidence cannot establish whether one would beat its own benchmark. Read the scale arms as contrasts in which a larger alternative did not remove the downstream dispersion, not as an isolated effect of parameter count. Decoding is capped at 64 tokens for every model alike, and per-model compliance is reported rather than hidden inside the parsing factor. The cap is itself a design choice and the non-complying cells are verbose enough to reach it, so we ablated it: re-scoring 6 cells on 300 filings at 256 tokens, four times the shipped cap, moves no failing cell by more than 1.8 percentage points, and the two cells that already complied still comply (75.6% to 77.7% and 98.5% to 96.3%), so no cell crosses from complying to not or back. The non-complying answers are refusals, not truncations, and compliance is a property of the model-prompt pair rather than of the cap. A paper about undisclosed choices should not leave its own undisclosed. The grid models and the 36B arm are 4-bit quantised local builds whose digests the artifact records, because a compliance rate is a property of the weights and a tag can be repointed. The 550B arm differs in two ways: a hosted free-tier endpoint serves it at a precision that was not recorded, and it is the one arm whose re-scoring needs an API key. Both larger models ran with their reasoning channel disabled, so that the 64-token decode cap could be the same for every model. That setting is a model-specific intervention. In trial calls with reasoning on, each of the two models spent the whole token budget, mainly in its reasoning channel, and returned an empty answer. The pipeline would have recorded such an answer as a compliance failure of the model.

The release-date bound covers the grid, not the scale arms. It applies to the three pre-registered scoring models. Both post hoc arms were released inside our 2025-08-01 to 2026-07-30 window, the 36B model on 2026-04-16 and the 550B model on 2026-06-04, so filings from the portion of the sample preceding each release may have been available to its training process and neither arm can exclude contamination. We claim no direction for that possible bias, because none is established: exposure could sharpen the association between a filing and its outcome or degrade it. What can be said is that neither arm beat its own benchmark.

Survivorship and index membership. The universe reflects index membership at the end of the window, so it misstates membership during the window in two directions. We counted both post hoc, from the same page revision. Inside the window, 21 listed names joined the index. Of the 2,978 filings analysed, 48 (1.6%, from 17 firms) predate the firm's listed addition date, and the pipeline treats them as filings of a constituent. The same revision lists 22 names removed from the index inside the window. Their filings, and those of Cboe Global Markets (Section 3), were never collected and enter no figure. Every configuration receives the same universe, so membership is not a factor in the grid. It can still affect configurations unequally, since they differ in which names they hold and for how long. The permutation benchmark draws on the same filings, so membership also enters the comparison between the pipeline and its null. No direction is established for either effect. A point-in-time universe would need the removed names' filings, which were never collected, so we did not re-run the grid. Dropping only the pre-addition filings would change the pre-registered event set after the results were known.

Frictions and portfolio mechanics. Costs are a flat 5 basis points per side, and there is no market impact, no borrow cost, and short sales are assumed feasible. Multi-day holds are carried at constant target weight, so intra-hold drift and its rebalancing are not charged, and prices are back-adjusted total-return series, so a pre-dividend level reflects a later distribution. All three simplifications are applied identically to every configuration and so are not factors in the grid, which does not make them neutral: a friction assumption interacts with turnover, and the cost sweep in Section 5.5 shows dispersion widening as costs rise. The spread is at least not an artifact of a lenient cost assumption. Sharpe ratios are annualised by the usual independent-observations factor, which multi-day holds violate by construction, and holding period is a factor in the grid, so that factor is wrong by an amount that differs across configurations. We measured it rather than conceding it. Re-annualising every configuration by Lo's serial-correlation-corrected factor [10] at 5 lags leaves the ordering essentially intact (rank correlation 0.99) and *widens* the spread, from 1.01 to 1.13, and this survives trimming to the 1st and 99th percentiles (0.95 against 1.04) and holds in the interquartile range (1.22 against 1.31), so it is not the work of a few strongly autocorrelated cells. We report the uncorrected figure throughout: it is what the literature reports and it is the conservative one.

The grid is ours, and it is smaller than the real one. A different enumeration would give a different N_{eff} and a different benchmark, which is the point of R1 rather than a defect: the multiplicity of a pipeline is a property of the search that produced it. What matters is the direction of the omission. Four consequential choices sit *outside* the grid, because fixing them is what lets every configuration see identical events and be scored on one scale: which 8-K item codes count and whether amendments are separate; where the score's origin lies, since 0.5 serves at once as abstention, as a balanced read and as the sign boundary; the normalisation of daily gross exposure, which makes a one-filing session a single-name bet weighted like a forty-filing one; and recording an undefined 0/0 Sharpe as zero. Each is a choice a real author makes early and reports late, so every dispersion figure here is conditional on one event definition and one accounting convention.

N_{eff} is a heuristic, and we treat it as one. Equation (2) is derived for independent Gaussian trials. A spectral participation ratio summarises dependence, not the maximum of a correlated, heavy-tailed vector, and the best configuration's returns are not Gaussian (skewness 0.93, kurtosis 6.87). It is computed over the 6,624 configurations that trade while the multiplicity corrected is over all 7,776; we report both denominators. That is why the paper measures the benchmark instead of assuming it, and why R3 is paired with R4.

8 Conclusion

Report the search: the grid, its effective size, the median as well as the maximum, and what the grid alone produces once the model's answers are permuted among the filings of each session. Neither instrument needs a new statistic or a better model, and both run on a grid a paper has already computed. On this grid, 83.3% of the variance of annualised Sharpe sits in interactions between choices. The largest single choice, the language model, accounts for 7.0% of the total.

Artifact. The collection code, the scoring runner, the grid evaluator, the frozen pre-registration with its declared 7 amendments, the decision ledger and the standalone audit module are released at https://github.com/s1mar/grid-is-the-alpha. They regenerate every number in this paper from public sources and the stored model outputs, with no paid data feed and no API key. Re-scoring the 550B arm needs a free-tier key for its hosted endpoint, and a new run may differ because the serving provider and its precision were not recorded.

Generative AI disclosure. Large language models are the object of study here: three open-weight models produced the 53,604 filing scores that the pipeline consumes, as described in Section 3. A general-purpose language model was also used as an assistant during implementation and drafting. All experimental design, all analysis code, all numbers and all claims were checked by the author, who takes responsibility for them.

References

[1] David H. Bailey, Jonathan M. Borwein, Marcos López de Prado, and Qiji Jim Zhu. 2014. Pseudo-Mathematics and Financial Charlatanism: The Effects of Backtest Overfitting on Out-of-Sample Performance. *Notices of the American Mathematical Society* 61, 5 (2014), 458–471.

[2] David H. Bailey and Marcos López de Prado. 2012. The Sharpe Ratio Efficient Frontier. *Journal of Risk* 15, 2 (2012), 3–44.

[3] David H. Bailey and Marcos López de Prado. 2014. The Deflated Sharpe Ratio: Correcting for Selection Bias, Backtest Overfitting, and Non-Normality. *The Journal of Portfolio Management* 40, 5 (2014), 94–107.

[4] Paul Glasserman and Caden Lin. 2023. Assessing Look-Ahead Bias in Stock Return Predictions Generated by GPT Sentiment Analysis. arXiv:2309.17322.

[5] Campbell R. Harvey, Yan Liu, and Heqing Zhu. 2016. … and the Cross-Section of Expected Returns. *The Review of Financial Studies* 29, 1 (2016), 5–68.

[6] Yikuan Huang, Zheqi Fan, Kaiqi Hu, and Yifan Ye. 2026. From Hypotheses to Factors: Constrained LLM Agents in Cryptocurrency Markets. arXiv:2604.26747.

[7] Alina Lerman and Joshua Livnat. 2010. The New Form 8-K Disclosures. *Review of Accounting Studies* 15, 4 (2010), 752–778.

[8] Jian Li and Lei Ji. 2005. Adjusting Multiple Testing in Multilocus Analyses Using the Eigenvalues of a Correlation Matrix. *Heredity* 95, 3 (2005), 221–227.

[9] Weixian Waylon Li, Hyeonjun Kim, Mihai Cucuringu, and Tiejun Ma. 2025. Can LLM-Based Financial Investing Strategies Outperform the Market in Long Run? arXiv:2505.07078.

[10] Andrew W. Lo. 2002. The Statistics of Sharpe Ratios. *Financial Analysts Journal* 58, 4 (2002), 36–52. doi:10.2469/faj.v58.n4.2453

[11] Alejandro Lopez-Lira and Yuehua Tang. 2023. Can ChatGPT Forecast Stock Price Movements? Return Predictability and Large Language Models. arXiv:2304.07619.

[12] Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. 2022. Fantastically Ordered Prompts and Where to Find Them: Overcoming Few-Shot Prompt Order Sensitivity. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*.

[13] Albert J. Menkveld, Anna Dreber, Felix Holzmeister, Jürgen Huber, Magnus Johannesson, Michael Kirchler, Michael Razen, Utz Weitzel, et al. 2024. Nonstandard Errors. *The Journal of Finance* 79, 3 (2024), 2339–2390.

[14] Charidimos Papadakis, Angeliki Dimitriou, Giorgos Filandrianos, Maria Lymperaiou, Konstantinos Thomas, and Giorgos Stamou. 2025. ATLAS: Adaptive Trading with LLM Agents Through Dynamic Prompt Optimization and Multi-Agent Coordination. arXiv:2510.15949.

[15] Dimitris N. Politis and Joseph P. Romano. 1994. The Stationary Bootstrap. *J. Amer. Statist. Assoc.* 89, 428 (1994), 1303–1313.

[16] Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. Quantifying Language Models' Sensitivity to Spurious Features in Prompt Design or: How I Learned to Start Worrying About Prompt Formatting. In *International Conference on Learning Representations (ICLR)*.

[17] Joseph P. Simmons, Leif D. Nelson, and Uri Simonsohn. 2011. False-Positive Psychology: Undisclosed Flexibility in Data Collection and Analysis Allows Presenting Anything as Significant. *Psychological Science* 22, 11 (2011), 1359–1366.

[18] Halbert White. 2000. A Reality Check for Data Snooping. *Econometrica* 68, 5 (2000), 1097–1126.

[19] Yijia Xiao, Edward Sun, Di Luo, and Wei Wang. 2024. TradingAgents: Multi-Agents LLM Financial Trading Framework. arXiv:2412.20138.

[20] Yuxuan Ye, Jun Han, Ao Hu, Juncheng Bu, Yiyi Chen, Liangjian Wen, Danilo Mandic, Danny Dongning Sun, Xu Yinghui, and Zenglin Xu. 2026. The Alpha Illusion: Reported Alpha from LLM Trading Agents Should Not Be Treated as Deployment Evidence. arXiv:2605.16895.

[21] Yangyang Yu, Haohang Li, Zhi Chen, Yuechen Jiang, Yang Li, Denghui Zhang, Rong Liu, Jordan W. Suchow, and Khaldoun Khashanah. 2023. FinMem: A Performance-Enhanced LLM Trading Agent with Layered Memory and Character Design. arXiv:2311.13743.

[22] Yangyang Yu, Zhiyuan Yao, Haohang Li, Zhiyang Deng, Yupeng Cao, et al. 2024. FinCon: A Synthesized LLM Multi-Agent System with Conceptual Verbal Reinforcement for Enhanced Financial Decision Making. arXiv:2407.06567.

[23] Wentao Zhang, Lingxuan Zhao, Haochong Xia, Shuo Sun, Jiaze Sun, et al. 2024. A Multimodal Foundation Agent for Financial Trading: Tool-Augmented, Diversified, and Generalist. arXiv:2402.18485.