

Lab database structure data/lab.sqlite3

svoe-vino-lab · SQLite · 13 tables, all STRICT · schema version 17 = pipeline/schema/001 to 017 · state of 2026-09-25

PK primary-key column FK foreign-key column TEXT? MAY be NULL; all other columns are NOT NULL
≈ a wine slug that no foreign key checks → foreign key → the key that it references

CATALOGUE · key wine_slug

wine_code		
GTINs, barcodes, and QR URLs. A wine MAY have many values. A value MAY belong to many wines.		
PK FK	wine_slug	TEXT → wine_catalog
PK	kind	TEXT gtin barcode qr_url
PK	value	TEXT gtin: 14 digits · barcode: ≤ 128 chars · qr_url: http(s) URL, ≤ 4096 chars
index wine_code_value (kind, value)		

wine_atlas_binding		
The Drink Atlas Core product of a wine. The manual row wins over the automatic row.		
PK FK	wine_slug	TEXT → wine_catalog
PK	source	TEXT automatic manual
	product_uuid	TEXT lower-case UUID, 36 chars
index wine_atlas_binding_product (product_uuid)		

wine_comment		
Comments on a wine. A comment has no edit. A remove names the id.		
PK	id	INTEGER the rowid
FK	wine_slug	TEXT → wine_catalog
	created_at	TEXT UTC time of the write
	source	TEXT user script
	text	TEXT 1 to 4000 chars, with line breaks
index wine_comment_wine (wine_slug, created_at, id)		

wine_favorite		
A wine is a favorite while it has a row.		
PK FK	wine_slug	TEXT → wine_catalog
	created_at	TEXT UTC time of the mark

wine_catalog		
One row per wine card. Sources: the Strapi CSV of the organizers, the website import of vino-svove.ru, and the form Add wine.		
PK	wine_slug	TEXT the key of each wine link
	name	TEXT CSV: Название вина
	producer	TEXT CSV: Винодельня
	category	TEXT CSV: Категория
	color	TEXT CSV: Цвет
	region	TEXT CSV: Регион
	grapes	TEXT? CSV: Сорт винограда
	description	TEXT? CSV: Описание; NULL since 014
	csv_photo_name	TEXT CSV: Название фото
	state	TEXT default Active Active Disabled Removed
	removed_by	TEXT? import person; only for Removed
	website_modified_at	TEXT? lastmod in winesitemap.xml
	modified_at	TEXT? UTC time of the last change
state Active: in the last CSV · Removed: not in the last CSV, or removed by a person · Disabled: out of use; only a person sets it check (state = 'Removed') = (removed_by IS NOT NULL) triggers wine_catalog_insert_time, wine_catalog_update_time set modified_at		

website_refusal		
The choices of a person in the merge dialog of the website import. A later import skips a refused change while its situation stays.		
PK	wine_slug	TEXT ≈ no FK: a refused new wine is not in wine_catalog
PK	kind	TEXT text image new missing back main
PK	field	TEXT the field name for text; else '' (the default)
	website_value	TEXT? text: the website value · image, main: SHA-256 of the file · else NULL
	created_at	TEXT UTC time of the choice
check (kind = 'text') = (field <> '')		

IMAGE STORE · key sha256

wine_image		
Links a wine and an image type to an original file. A file that several wines share has one row for each wine.		
PK FK	wine_slug	TEXT → wine_catalog
PK	image_type	TEXT main main_patched full_front label_front full_back label_back
PK FK	sha256	TEXT → image
	source_name	TEXT the file name at the source
	match_method	TEXT how the file was found, e.g. name-unique, manual
unique index wine_image_one_main (wine_slug, image_type) WHERE image_type IN ('main', 'main_patched')		

image		
One row per stored file: an original or a cut. The file is images/<folder>/<sha256>.<extension>.		
PK	sha256	TEXT 64 lower-case hex digits
	folder	TEXT main patched additional cropped testset
	extension	TEXT lower-case [0-9a-z], e.g. webp
	width	INTEGER? pixels, > 0; NULL: not measured yet
	height	INTEGER? pixels, > 0
check (width IS NULL) = (height IS NULL)		

image_derivative		
The cut of an original file. The box is in the pixels of the original after its EXIF orientation.		
PK FK	source_sha256	TEXT → image: the original
PK	kind	TEXT package label
	method	TEXT crop seg
	settings	TEXT cut settings as text
FK	sha256	TEXT → image: the cut file
	box_left	INTEGER ≥ 0
	box_top	INTEGER ≥ 0
	box_right	INTEGER > box_left
	box_bottom	INTEGER > box_top
kind package (the default): the whole package, crop or seg · label: the label, seg · one cut per original and kind		

TEST SETS · key set_name

test_set		
A photo set of a directory dataset/<set>/.		
PK	set_name	TEXT [0-9a-z-], e.g. my
	source_dir	TEXT the directory of the last import

test_photo		
One photo file of one set: <source_dir>/photo/<place>/<file_name>. The place __null__ holds photos with no card. The same bytes MAY have another label in another set.		
PK FK	set_name	TEXT → test_set
PK	place	TEXT ≈ wine slug, or __null__
PK	file_name	TEXT the file name
FK	sha256	TEXT → image
	label	TEXT? NULL: no label yet
	positive negative unusable variant	
	marked_delete	INTEGER 0 1: the label field delete

test_excluded		
An excluded slug of one set. Its photos are out of the benchmark. Source: excluded-slugs.json.		
PK FK	set_name	TEXT → test_set
PK	wine_slug	TEXT ≈ wine slug
	reason	TEXT? free text from the file
	ts	TEXT? the time as the file gives it

test_variant		
The variant group of a slug in one set. Source: variant-groups.json. The metric near_duplicate_confusion reads it.		
PK FK	set_name	TEXT → test_set
PK	wine_slug	TEXT ≈ wine slug
	group_no	INTEGER ≥ 0: the position of the group in the file

Migrations

pipeline/labdb.py applies each file
pipeline/schema/NNN_<name>.sql one time, in number order, with one transaction for each file.
PRAGMA user_version holds the number of the last applied file. The code refuses a gap in the numbers. A change is a new file with the next number. Do not edit an applied file.

Rebuilds

To change a constraint or to remove a column, a file builds the table again: a new table, a copy of the rows, DROP, RENAME. Files 004, 007, 010, 012, 014, 016, and 017 do this. labdb.migrate runs each file with the foreign keys off, and PRAGMA foreign_key_check checks each link before the COMMIT. A rebuild of wine_catalog drops its two triggers, so the file MUST create them again.

Images

The store is images/ in the directory of the database file. The same bytes are stored one time, in the folder of the type that stored them first: main, patched (main_patched), additional (full_*, label_*), testset. A new cut goes to cropped. A reader MUST use main_patched instead of main when a wine has both.

Values

The columns created_at and modified_at hold UTC text YYYY-MM-DDTHH:MM:SSZ; a GLOB check keeps the form. A TEXT column refuses ' ' through a CHECK or its foreign key. Exceptions: website_refusal.field, website_refusal.website_value, test_excluded.reason, test_excluded.ts. The code does not delete a row of wine_catalog: Removed and Disabled are states.

Test sets

The labels stay in git, in dataset/<set>/review-labels.json. pipeline/import_testset.py copies them here, read-only. Each import makes the rows of a set equal to the files again. The slugs of the test-set tables and of website_refusal have no foreign key (≈).

Schema files 001 wine_catalog · 002 wine_slug · 003 wine_state · 004 removed_by · 005 wine_image · 006 image_size · 007 image_table · 008 wine_code · 009 atlas_binding · 010 additional_types · 011 wine_comment · 012 type_names_kind_first · 013 wine_favorite · 014 description_optional · 015 website_import · 016 testset · 017 derivative_kind