



MAD

(BE031000081)

LABORATORY MANUAL

B.E. Semester-III

**Prepared By:-
CE/IT Department
Vadodara Institute of Engineering (080)
Kotambi, Vadodara – 391510
Academic Year : 2025-2026**



Vadodara Institute of Engineering (080)
Mobile Application Development(3170726)

Index

Sr No	Practicals
1	Write android program to display "Welcome to android".
2	Write android program to demonstrate usage of string.
3	Write android program to demonstrate activity life cycle.
4	Write android program to change the background of activity.
5	Write android program to perform all operation in calculator.
6	Write android program to create multiple activities within an application.
7	Write android program to demonstrate action button by implementing ONCLICKLISTENER.
8	Write android program to demonstrate sound button application.
9	Write an Android application to convert into different currencies for example, Rupees to dollar.
10	Write an android application to count library overdue.
11	Write an android application to convert a ball from size of radius 2(colour red) to radius 4(colour blue) to radius 6 (colour green). The ball must rotate in circle for 1 minute before changing size and colour.
12	Write an application to mark the daily route of travel in map.
13	Write an application to record video and audio on topic "Intent" and play the audio and video
14	Write android program to set the wallpaper of your device using bitmap class.

Vadodara Institute of Engineering (080)
Mobile Application Development(3170726)

Software Requirements

Sr No	Software Requirement	Hardware Requirement
1	Android Studio	64-bit OS
		RAM-16 GB
		Processor (Intel i5/i7, AMD Ryzen, etc.)
		Hard Disk- 512 GB



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 1

AIM: Write Android program to display "Welcome to android".

```
<!-- res/layout/activity_main.xml -->
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:gravity="center"
    android:orientation="vertical">
    <TextView
        android:id="@+id/textView"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Welcome to android"
        android:textSize="24sp"
        android:textStyle="bold"/>
</LinearLayout>
```

Application:

1. Which method is called when an activity is created?

2. Which XML tag is used to display text in Android?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 2

AIM: Write android program to demonstrate usage of string.

Program:

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp"
    android:background="#FFFFFF">

    <TextView
        android:id="@+id/textViewResult"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="String Example"
        android:textSize="22sp"
        android:textColor="#000000" />
</LinearLayout>
```

Main Activity.java

```
package com.example.stringdemo;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.widget.TextView;

public class MainActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
TextView textView = findViewById(R.id.textViewResult);
```

```
// String usage demonstration  
String firstName = "Android";  
String lastName = "Programming";
```

```
// Concatenation  
String fullName = firstName + " " + lastName;
```

```
// Display result  
textView.setText("Concatenated String: " + fullName);
```

```
}
```

```
}
```

Application:

1. Which operator is used to concatenate strings in Java?

2. Which class is used to store text in Java?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 3

AIM: Write android program to demonstrate activity life cycle.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:background="#FFFFFF"
    android:padding="20dp">

    <TextView
        android:id="@+id/textViewLifeCycle"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Activity Life Cycle Demo"
        android:textSize="20sp"
        android:textColor="#000000"/>
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.lifecycleapp;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.widget.TextView;

public class MainActivity extends AppCompatActivity {

    private static final String TAG = "ActivityLifeCycle";
    TextView textView;

    @Override
```


Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
protected void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);  
    setContentView(R.layout.activity_main);
```

```
    textView = findViewById(R.id.textViewLifecycle);  
    textView.setText("onCreate() called");  
    Log.d(TAG, "onCreate() called");  
}
```

```
@Override  
protected void onStart() {  
    super.onStart();  
    Log.d(TAG, "onStart() called");  
}
```

```
@Override  
protected void onResume() {  
    super.onResume();  
    Log.d(TAG, "onResume() called");  
}
```

```
@Override  
protected void onPause() {  
    super.onPause();  
    Log.d(TAG, "onPause() called");  
}
```

```
@Override  
protected void onStop() {  
    super.onStop();  
    Log.d(TAG, "onStop() called");  
}
```

```
@Override  
protected void onRestart() {  
    super.onRestart();  
    Log.d(TAG, "onRestart() called");  
}
```

```
@Override  
protected void onDestroy() {  
    super.onDestroy();  
    Log.d(TAG, "onDestroy() called");  
}
```

```
}
```


Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Application:

1. Which method is called when the activity is first created?

2. Which method is called before an activity is destroyed?



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 4

AIM: Write android program to change the background of activity.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp"
    android:id="@+id/mainLayout">

    <Button
        android:id="@+id/btnChangeColor"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Change Background" />

</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.backgrounddemo;
import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.graphics.Color;
import android.view.View;
import android.widget.Button;
import android.widget.LinearLayout;

public class MainActivity extends AppCompatActivity {

    LinearLayout mainLayout;
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Button btnChange;

@Override

```
protected void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);  
    setContentView(R.layout.activity_main);
```

```
    mainLayout = findViewById(R.id.mainLayout);  
    btnChange = findViewById(R.id.btnChangeColor);
```

```
    btnChange.setOnClickListener(new View.OnClickListener() {
```

```
        @Override
```

```
        public void onClick(View v) {
```

```
            // Change background color on button click
```

```
            mainLayout.setBackgroundColor(Color.CYAN);
```

```
        }
```

```
    });
```

```
}
```

```
}
```

Output :



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Application:

1. Which method is used to set background color in Android?

2. Which class provides predefined color constants in Android?



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 5

AIM: Write android program to perform all operation in calculator.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:padding="20dp"
    android:gravity="center"
    android:id="@+id/mainLayout">

    <EditText
        android:id="@+id/etNum1"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:hint="Enter First Number"
        android:inputType="numberDecimal"
        android:layout_marginBottom="10dp"/>

    <EditText
        android:id="@+id/etNum2"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:hint="Enter Second Number"
        android:inputType="numberDecimal"
        android:layout_marginBottom="20dp"/>

    <LinearLayout
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:orientation="horizontal"
        android:gravity="center"
        android:layout_marginBottom="20dp">

        <Button
            android:id="@+id/btnAdd"
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:text="+" />
```

```
<Button
    android:id="@+id/btnSub"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="-"
    android:layout_marginLeft="10dp"/>
```

```
<Button
    android:id="@+id/btnMul"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="×"
    android:layout_marginLeft="10dp"/>
```

```
<Button
    android:id="@+id/btnDiv"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="÷"
    android:layout_marginLeft="10dp"/>
```

```
</LinearLayout>
```

```
<TextView
    android:id="@+id/tvResult"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Result will be shown here"
    android:textSize="20sp"
    android:textColor="#000000"/>
```

```
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.calculatordemo;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.TextView;
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
import android.widget.Toast;

public class MainActivity extends AppCompatActivity {

    EditText etNum1, etNum2;
    Button btnAdd, btnSub, btnMul, btnDiv;
    TextView tvResult;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        etNum1 = findViewById(R.id.etNum1);
        etNum2 = findViewById(R.id.etNum2);
        btnAdd = findViewById(R.id.btnAdd);
        btnSub = findViewById(R.id.btnSub);
        btnMul = findViewById(R.id.btnMul);
        btnDiv = findViewById(R.id.btnDiv);
        tvResult = findViewById(R.id.tvResult);

        btnAdd.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                calculate('+');
            }
        });

        btnSub.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                calculate('-');
            }
        });

        btnMul.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                calculate('*');
            }
        });

        btnDiv.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
```


Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
        calculate('/');
    }
});
}

private void calculate(char operator) {
    String num1Str = etNum1.getText().toString();
    String num2Str = etNum2.getText().toString();

    if (num1Str.isEmpty() || num2Str.isEmpty()) {
        Toast.makeText(this, "Please enter both numbers", Toast.LENGTH_SHORT).show();
        return;
    }

    double num1 = Double.parseDouble(num1Str);
    double num2 = Double.parseDouble(num2Str);
    double result = 0;

    switch (operator) {
        case '+':
            result = num1 + num2;
            break;
        case '-':
            result = num1 - num2;
            break;
        case '*':
            result = num1 * num2;
            break;
        case '/':
            if (num2 != 0) {
                result = num1 / num2;
            } else {
                Toast.makeText(this, "Cannot divide by zero", Toast.LENGTH_SHORT).show();
                return;
            }
            break;
    }

    tvResult.setText("Result: " + result);
}
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Output :

Application:

1. Which method is used to handle button click events in Android?

2. How do you convert a string input to a number in Java?



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 6

AIM: Write android program to create multiple activities within an application.

Program:

XML Layout for MainActivity (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <Button
        android:id="@+id/btnNext"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Go to Second Activity" />

</LinearLayout>
```

XML Layout for SecondActivity (activity_second.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <TextView
        android:id="@+id/tvMessage"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Welcome to Second Activity"
        android:textSize="20sp"
        android:textColor="#000000"/>

</LinearLayout>
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Java Code for MainActivity.java

```
package com.example.multipleactivities;

import androidx.appcompat.app.AppCompatActivity;
import android.content.Intent;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

public class MainActivity extends AppCompatActivity {

    Button btnNext;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        btnNext = findViewById(R.id.btnNext);

        btnNext.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                // Intent to open SecondActivity
                Intent intent = new Intent(MainActivity.this, SecondActivity.class);
                startActivity(intent);
            }
        });
    }
}
```

Java Code for SecondActivity.java

```
package com.example.multipleactivities;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;

public class SecondActivity extends AppCompatActivity {
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_second);
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

AndroidManifest.xml (Add Second Activity)

```
<application
    android:allowBackup="true"
    android:icon="@mipmap/ic_launcher"
    android:label="@string/app_name"
    android:supportsRtl="true"
    android:theme="@style/Theme.AppCompat.Light.NoActionBar">

    <activity android:name=".SecondActivity"></activity>
    <activity android:name=".MainActivity">
        <intent-filter>
            <action android:name="android.intent.action.MAIN" />
            <category android:name="android.intent.category.LAUNCHER" />
        </intent-filter>
    </activity>
</application>
```

Output :

Application:

1. Which class is used to navigate from one activity to another?

2. Which file must be updated to declare a new activity in Android?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 7

AIM: Write android program to demonstrate action button by implementing ONCLICKLISTENER.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <Button
        android:id="@+id/btnClickMe"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Click Me" />

    <TextView
        android:id="@+id/tvResult"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Result will appear here"
        android:textSize="20sp"
        android:layout_marginTop="20dp"/>
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.onclickdemo;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.TextView;
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
public class MainActivity extends AppCompatActivity implements View.OnClickListener {
```

```
    Button btnClickMe;  
    TextView tvResult;
```

```
    @Override
```

```
    protected void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        setContentView(R.layout.activity_main);
```

```
        btnClickMe = findViewById(R.id.btnClickMe);  
        tvResult = findViewById(R.id.tvResult);
```

```
        // Set OnClickListener  
        btnClickMe.setOnClickListener(this);  
    }
```

```
    @Override
```

```
    public void onClick(View v) {  
        if (v.getId() == R.id.btnClickMe) {  
            tvResult.setText("Button Clicked Successfully!");  
        }  
    }
```

Output :

Application:

1. Which interface is used to handle button clicks in Android?

2. Which method is called when a button is clicked?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

ate:

Practical 8

AIM: Write android program to demonstrate sound button application.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <Button
        android:id="@+id/btnPlaySound"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Play Sound" />
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.soundbuttonapp;

import androidx.appcompat.app.AppCompatActivity;
import android.media.MediaPlayer;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

public class MainActivity extends AppCompatActivity {

    Button btnPlaySound;
    MediaPlayer mediaPlayer;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)


```
btnPlaySound = findViewById(R.id.btnPlaySound);

// Initialize MediaPlayer with sound file from res/raw
mediaPlayer = MediaPlayer.create(this, R.raw.clicksound);

btnPlaySound.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {
        // Play sound when button clicked
        if (mediaPlayer != null) {
            mediaPlayer.start();
        }
    }
});
}

@Override
protected void onDestroy() {
    super.onDestroy();
    if (mediaPlayer != null) {
        mediaPlayer.release();
        mediaPlayer = null;
    }
}
}
```

Output :



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Application:

1. Which Android class is used to play sound files?

2. In which folder should you store raw media files in Android?



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 9

AIM: Write an Android application to convert into different currencies for example, Rupees to dollar.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <EditText
        android:id="@+id/etRupees"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:hint="Enter amount in Rupees"
        android:inputType="numberDecimal"
        android:layout_marginBottom="15dp"/>

    <Button
        android:id="@+id/btnConvert"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Convert to Dollar" />

    <TextView
        android:id="@+id/tvResult"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Result will appear here"
        android:textSize="20sp"
        android:layout_marginTop="20dp"/>
</LinearLayout>
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Java Code (MainActivity.java)

```
package com.example.currencyconverter;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.TextView;
import android.widget.Toast;

public class MainActivity extends AppCompatActivity {

    EditText etRupees;
    Button btnConvert;
    TextView tvResult;

    // Conversion rate (Example: 1 Rupee = 0.012 USD)
    final double DOLLAR_RATE = 0.012;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        etRupees = findViewById(R.id.etRupees);
        btnConvert = findViewById(R.id.btnConvert);
        tvResult = findViewById(R.id.tvResult);

        btnConvert.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                String rupeesStr = etRupees.getText().toString();

                if (rupeesStr.isEmpty()) {
                    Toast.makeText(MainActivity.this, "Please enter amount in Rupees",
Toast.LENGTH_SHORT).show();
                    return;
                }

                double rupees = Double.parseDouble(rupeesStr);
                double dollars = rupees * DOLLAR_RATE;
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
        tvResult.setText("USD: $" + String.format("%.2f", dollars));  
    }  
});  
}  
}
```

Output :

Application:

1. Which widget is used to accept numeric input in Android?

2. How do you convert a string value from EditText into a number?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 10

AIM: Write an android application to count library overdue.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:padding="20dp">

    <EditText
        android:id="@+id/etDays"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:hint="Enter number of overdue days"
        android:inputType="number"
        android:layout_marginBottom="15dp"/>

    <Button
        android:id="@+id/btnCalculate"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Calculate Fine" />

    <TextView
        android:id="@+id/tvResult"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Fine will appear here"
        android:textSize="20sp"
        android:layout_marginTop="20dp"/>
</LinearLayout>
```


Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Java Code (MainActivity.java)

```
package com.example.libraryfine;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.TextView;
import android.widget.Toast;

public class MainActivity extends AppCompatActivity {

    EditText etDays;
    Button btnCalculate;
    TextView tvResult;

    // Fine rate per day
    final int FINE_RATE = 2;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        etDays = findViewById(R.id.etDays);
        btnCalculate = findViewById(R.id.btnCalculate);
        tvResult = findViewById(R.id.tvResult);

        btnCalculate.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                String daysStr = etDays.getText().toString();

                if (daysStr.isEmpty()) {
                    Toast.makeText(MainActivity.this, "Please enter overdue days",
                        Toast.LENGTH_SHORT).show();
                    return;
                }

                int days = Integer.parseInt(daysStr);
                int fine = days * FINE_RATE;

                tvResult.setText("Total Fine: ₹" + fine);
            }
        });
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
}  
});  
}  
}
```

Output :

Application:

1. Which widget is best to display calculated result in Android?

2. How do you display short popup messages in Android?

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 11

AIM: Write an application to mark the daily route of travel in map.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<fragment xmlns:android="http://schemas.android.com/apk/res/android"
    android:id="@+id/map"
    android:name="com.google.android.gms.maps.SupportMapFragment"
    android:layout_width="match_parent"
    android:layout_height="match_parent"/>
```

Java Code (MainActivity.java)

```
package com.example.dailyroute;

import androidx.fragment.app.FragmentActivity;
import android.os.Bundle;

import com.google.android.gms.maps.CameraUpdateFactory;
import com.google.android.gms.maps.GoogleMap;
import com.google.android.gms.maps.OnMapReadyCallback;
import com.google.android.gms.maps.SupportMapFragment;
import com.google.android.gms.maps.model.LatLng;
import com.google.android.gms.maps.model.MarkerOptions;
import com.google.android.gms.maps.model.PolylineOptions;

public class MainActivity extends FragmentActivity implements OnMapReadyCallback {

    private GoogleMap mMap;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        SupportMapFragment mapFragment = (SupportMapFragment) getSupportFragmentManager()
            .findFragmentById(R.id.map);
        if (mapFragment != null) {
            mapFragment.getMapAsync(this);
        }
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
}  
}  
  
@Override  
public void onMapReady(GoogleMap googleMap) {  
    mMap = googleMap;  
  
    // Example route: Home -> Bus Stop -> Office  
    LatLng home = new LatLng(28.6139, 77.2090);    // Delhi example  
    LatLng busStop = new LatLng(28.6200, 77.2100);  
    LatLng office = new LatLng(28.6250, 77.2150);  
  
    // Add markers  
    mMap.addMarker(new MarkerOptions().position(home).title("Home"));  
    mMap.addMarker(new MarkerOptions().position(busStop).title("Bus Stop"));  
    mMap.addMarker(new MarkerOptions().position(office).title("Office"));  
  
    // Draw route with Polyline  
    mMap.addPolyline(new PolylineOptions()  
        .add(home, busStop, office)  
        .width(8)  
        .color(0xFF2196F3)); // Blue  
  
    // Move camera to Home  
    mMap.moveCamera(CameraUpdateFactory.newLatLngZoom(home, 14));  
}  
}
```

Output :

Application:

1. Which Android component is used to integrate Google Maps? _____

2. Which class is used to draw lines on the map? _____

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 13

AIM: Write an application to record video and audio on topic "Intent" and play the audio and video.

Program:

AndroidManifest.xml

```
<uses-permission android:name="android.permission.CAMERA"/>
<uses-permission android:name="android.permission.RECORD_AUDIO"/>
<uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"/>
<uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"/>

<application
    ...>
    <activity android:name=".MainActivity">
        <intent-filter>
            <action android:name="android.intent.action.MAIN"/>
            <category android:name="android.intent.category.LAUNCHER"/>
        </intent-filter>
    </activity>
</application>
```

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:orientation="vertical"
    android:gravity="center"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:padding="20dp">

    <Button
        android:id="@+id/btnRecordAudio"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Record Audio"/>

    <Button
        android:id="@+id/btnRecordVideo"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Record Video">
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
        android:layout_marginTop="15dp"/>

<Button
    android:id="@+id/btnPlayAudio"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Play Audio"
    android:layout_marginTop="15dp"/>

<Button
    android:id="@+id/btnPlayVideo"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Play Video"
    android:layout_marginTop="15dp"/>
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.intentmediaapp;

import androidx.appcompat.app.AppCompatActivity;
import android.content.Intent;
import android.net.Uri;
import android.os.Bundle;
import android.provider.MediaStore;
import android.view.View;
import android.widget.Button;
import android.widget.Toast;

public class MainActivity extends AppCompatActivity {

    Button btnRecordAudio, btnRecordVideo, btnPlayAudio, btnPlayVideo;
    Uri audioUri, videoUri;
    final int AUDIO_REQUEST = 1;
    final int VIDEO_REQUEST = 2;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        btnRecordAudio = findViewById(R.id.btnRecordAudio);
        btnRecordVideo = findViewById(R.id.btnRecordVideo);
        btnPlayAudio = findViewById(R.id.btnPlayAudio);
    }
}
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
btnPlayVideo = findViewById(R.id.btnPlayVideo);

// Record Audio
btnRecordAudio.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {

        Intent audioIntent = new Intent(MediaStore.Audio.Media.RECORD_SOUND_ACTION);
        try {
            startActivityForResult(audioIntent, AUDIO_REQUEST);
        } catch (Exception e) {
            Toast.makeText(MainActivity.this, "No app found to record audio",
Toast.LENGTH_SHORT).show();
        }
    }
});

// Record Video
btnRecordVideo.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {

        Intent videoIntent = new Intent(MediaStore.ACTION_VIDEO_CAPTURE);
        try {
            startActivityForResult(videoIntent, VIDEO_REQUEST);
        } catch (Exception e) {
            Toast.makeText(MainActivity.this, "No app found to record video",
Toast.LENGTH_SHORT).show();
        }
    }
});

// Play Audio
btnPlayAudio.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {
        if (audioUri != null) {
            Intent playAudio = new Intent(Intent.ACTION_VIEW);
            playAudio.setDataAndType(audioUri, "audio/*");
            startActivity(playAudio);
        } else {
            Toast.makeText(MainActivity.this, "No audio recorded", Toast.LENGTH_SHORT).show();
        }
    }
});
```


Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
// Play Video
btnPlayVideo.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {
        if (videoUri != null) {
            Intent playVideo = new Intent(Intent.ACTION_VIEW);
            playVideo.setDataAndType(videoUri, "video/*");
            startActivity(playVideo);
        } else {
            Toast.makeText(MainActivity.this, "No video recorded", Toast.LENGTH_SHORT).show();
        }
    }
});
}

@Override
protected void onActivityResult(int requestCode, int resultCode, Intent data) {
    super.onActivityResult(requestCode, resultCode, data);
    if (resultCode == RESULT_OK) {
        if (requestCode == AUDIO_REQUEST) {
            audioUri = data.getData();
        } else if (requestCode == VIDEO_REQUEST) {
            videoUri = data.getData();
        }
    }
}
}
```

Output :

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Application:

1. Which Intent action is used to record audio?

2. Which Intent action is used to record video?



Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Date:

Practical 14

AIM: Write android program to set the wallpaper of your device using bitmap class.

Program:

XML Layout (activity_main.xml)

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:orientation="vertical"
    android:gravity="center"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:padding="20dp">

    <Button
        android:id="@+id/btnSetWallpaper"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Set Wallpaper"/>
</LinearLayout>
```

Java Code (MainActivity.java)

```
package com.example.wallpaperapp;

import androidx.appcompat.app.AppCompatActivity;
import android.app.WallpaperManager;
import android.graphics.Bitmap;
import android.graphics.BitmapFactory;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.Toast;
import java.io.IOException;

public class MainActivity extends AppCompatActivity {

    Button btnSetWallpaper;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
```

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

```
setContentView(R.layout.activity_main);

btnSetWallpaper = findViewById(R.id.btnSetWallpaper);

btnSetWallpaper.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {

        // Load bitmap from drawable
        Bitmap bitmap = BitmapFactory.decodeResource(getResources(),
R.drawable.wallpaper_image);

        // Set wallpaper using WallpaperManager
        WallpaperManager wallpaperManager =
WallpaperManager.getInstance(getApplicationContext());
        try {
            wallpaperManager.setBitmap(bitmap);
            Toast.makeText(MainActivity.this, "Wallpaper Set Successfully",
Toast.LENGTH_SHORT).show();
        } catch (IOException e) {
            e.printStackTrace();
            Toast.makeText(MainActivity.this, "Failed to Set Wallpaper",
Toast.LENGTH_SHORT).show();
        }
    }
});
}
```

Output :

Vadodara Institute of Engineering (080)

Mobile Application Development(3170726)

Application:

1. Which class is used to set device wallpaper in Android?

2. How do you load an image resource as a bitmap?

