

DATA2410-1 22V Datanettverk og Skytjenester
GROUP Portfolio Assignment 2 - Docker and Zabbix Real Use-Case

Ulrik Bakken Singsaas | s351917
Adrian Bakstad | s341507
Thea | s351879
Andrea Bjørge | s344175

April 25, 2022

Contents

1. VM1: Docker containers setup 10%	2
VM Setup	2
Quad Container Setup	2
mysql	3
zabbix-server	3
zabbix-web	3
zabbix-agent	3
2. VM2 and VM3: Install zabbix-agent and zabbix-proxy 10%	3
Accessing zabbix web with lynx	4
VM 3	4
3. VM2: Nginx proxy 10%	4
4. VM1: Zabbix frontend	4

1. VM1: Docker containers setup 10%

VM Setup

We Started by deleting the 3 default VMs, because these had a different ubuntu version than what was recommended in the assignment description.

We used these commands to make new containers with the focal fossa version, whilst also allowing for docker containers within docker containers.

Making the images to run containers from

```
# making vm 1 image
docker build -f vm1-dockerfile -t vm-image1

# making vm 2 image
docker build -f vm2-dockerfile -t vm-image2

# making vm 3 image
docker build -f vm3-dockerfile -t vm-image3

# running vm1 container
sudo docker container run --privileged -v /var/run/docker.sock:/var/run/docker.sock -d vm_image
# running vm2 container
sudo docker container run -d -t vm2-dockerfile
```

The image, vm_image, was made from this Dockerfile:

```
TODO
- [ ] get from configs/Dockerfile
```

Quad Container Setup

After setting up the VMs we used the file `docker compose.yml`, found in the configs folder, to set up the four containers with required the required config instructions for the assignment.

```
TODO
- [ ] Paste finalized version of this file
```

The assignment does not specify volumes. Therefore, in order to keep the maintenance simple, we used four files from this directory as the volumes for each of the four containers. At first we ran the docker containers without the volume statements to auto generate the configs, then we edited the configs and pasted them back in to a new

compose file to automate our statements. The final files we used can be found below (alt. The changes we made to the files can be found below).

mysql

zabbix-server

zabbix-web

zabbix-agent

2. VM2 and VM3: Install zabbix-agent and zabbix-proxy 10%

We start by fetching this: `wget https://repo.zabbix.com/zabbix/6.1/ubuntu/pool/main/z/zabbix-release/zabbix-release_6.1-1%2Bubuntu20.04_all.deb` So that we can install the zabbix-agent

Installing zabbix-proxy on VM2:

```
root@47b33e945b34:/# apt-get install wget
Reading package lists... Done
...
root@47b33e945b34:/# wget https://repo.zabbix.com/zabbix/6.1/ubuntu/pool/main/z/zabbix-release/zabbix-release_6.1-1%2Bubuntu20.04_all.deb

root@47b33e945b34:/# dpkg -i zabbix-release_6.1-1+ubuntu20.04_all.deb
Selecting previously unselected package zabbix-release.
(Reading database ... 4623 files and directories currently installed.)
Preparing to unpack zabbix-release_6.1-1+ubuntu20.04_all.deb ...
Unpacking zabbix-release (1:6.1-1+ubuntu20.04) ...
Setting up zabbix-release (1:6.1-1+ubuntu20.04) ...
root@47b33e945b34:/# apt-get install -f

root@47b33e945b34:/# apt-get install zabbix-proxy-mysql
Reading package lists... Done
..

root@47b33e945b34:/# apt-get install zabbix-sql-scripts
```

Installing MariaDB inside VM2:

```
root@47b33e945b34:/# curl -LsS -O https://downloads.mariadb.com/MariaDB/mariadb_repo_setup
root@47b33e945b34:/# bash mariadb_repo_setup --mariadb-server-version=10.6
root@47b33e945b34:/# apt -y install mariadb-common mariadb-server-10.6 mariadb-client-10.6
```

Setting new **root password** = 123

```
root@47b33e945b34:/# mysql_secure_installation

Enter current password for root (enter for none):

Switch to unix_socket authentication [Y/n] y

Change the root password? [Y/n] y

Remove anonymous users? [Y/n] y

Disallow root login remotely? [Y/n] y

Remove test database and access to it? [Y/n] y

Reload privilege tables now? [Y/n] y
```

```
Thanks for using MariaDB!
```

```
root@47b33e945b34:/# mysql -uroot -p'123' -e "create database zabbix_proxy character set utf8mb4 collate utf8mb4_bin"
root@47b33e945b34:/# mysql -uroot -p'123' -e "grant all privileges on zabbix_proxy.* to zabbix@localhost identified by '123' with grant option;"
```

Accessing zabbix web with lynx

Accessing the zabbix-web

```
# if lynx is not installed
g13@net513:~$ lynx localhost
```

```
g13@net513:~$ lynx localhost
```

this gives you a cli web browser

VM 3

Installing zabbix-agent on VM3:

Run the following script as root on the vm3 container to install the zabbix agent:

```
wget https://repo.zabbix.com/zabbix/6.1/ubuntu/pool/main/z/zabbix-release/zabbix-release_6.1-1%2Bubuntu20.04_all.deb

dpkg -i zabbix-release_6.1-1+ubuntu20.04_all.deb

apt-get install -f

apt-get install zabbix-agent
```

Creating psk encryption key:

```
root@4d08e816a5a3:/# openssl rand -hex 32 > zabbix_agent.psk
root@4d08e816a5a3:/# cat zabbix_agent.psk
f62ae210eb7e91ab7908cbad2f2e8e0189f57b54e9d4de9be636e17ad362e7f7
```

Moving it to /opt/zabbix folder:

```
chmod 777 /opt/zabbix
mv ./zabbix_agent.psk /opt/zabbix/zabbix_agent.psk
```

Updating zabbix-agent.conf:

```
TLSCConnect=psk
TLSCAccept=psk
TLSPSKIdentity=cbt_psk_01,
TLSPSKFile=/opt/zabbix_agent.psk
```

Since we are running this in a docker container and not a straight vm, then we do not have systemd available, therefore we cannot *enable* the service, only start it, and have it as a run command in a dockerfile and make sure that the service is started every time the contained based on the dockerfile is run

3. VM2: Nginx proxy 10%

4. VM1: Zabbix frontend