

GROUP MATRIX

	1	2	3	4	5	6	7	8
1	+0	-inf	-inf	-inf	-inf	-inf	-inf	-inf
2	-inf	+0	-inf	-inf	-inf	-inf	-inf	-inf
3	-inf	-inf	+0	-inf	-inf	-inf	-inf	-inf
4	-inf	-inf	-inf	+0	-inf	-inf	-inf	-inf
5	-inf	-inf	-inf	-inf	+0	-inf	-inf	-inf
6	-inf	-inf	-inf	-inf	-inf	+0	-inf	-inf
7	-inf	-inf	-inf	-inf	-inf	-inf	+0	-inf
8	-inf	-inf	-inf	-inf	-inf	-inf	-inf	+0


DEVIATION  50%

PATTERN PREVIEW



MOTN 0: static matrix

OUTPUT


OUT  0 dB

PATTERN


GROUP

 8CH v

SHAPE

 FLOW v


MODE

 FREE v

DEPTH

 0%

SPREAD

 0%

VORTEX

 +0.00


MOTION

 0%


RATE

 15%

DIVISION

 16

PHASE

 0%

SMOOTHING

 35 ms

- PATTERN TERMS

CEIL	manual cell is the max/permission for a route	DPTH	generated pattern depth	MODE	FREE runs internally; SYNC follows transport
-INF	closed cell: motion cannot pass	SPRD	widens allowed route distribution	RATE	free-running cycle speed
MOTN	movement depth; 0 = normal matrix	VORT	rotates the generated motion shape	DIV	synced cycle length in beats
PHAS	offsets the visible/audio motion cycle	SMTH	gain smoothing for route changes	SHAPE	generated gain pattern