

NODE FIELD

TOP

SIDE

3/4

-

+

4 NODES / 8 OUT / 128CH

NODE GAIN / POST CURSOR

N01		50%	N05		0%	N09		0%	N13		0%
N02		50%	N06		0%	N10		0%	N14		0%
N03		50%	N07		0%	N11		0%	N15		0%
N04		50%	N08		0%	N12		0%	N16		0%

PEAK METER / POST CURSOR

OUT

-120

N01		-120	N05		-120	N09		-120	N13		-120
N02		-120	N06		-120	N10		-120	N14		-120
N03		-120	N07		-120	N11		-120	N15		-120
N04		-120	N08		-120	N12		-120	N16		-120

OUTPUT

OUT

0 dB

BUS / CURSOR

BED

OCT0

v

CHANNELS

8

NODES

4

INFLUENCE

100%

CURSOR X

+0.00

CURSOR Y

+0.00

CURSOR Z

LOCKED

RADIUS

1.00

FOCUS

1.00

GATE

0.02

LOCK Z

ON

NODE 01

ACTIVE

ON

SOURCE

OCT0

v

BUS

001-008

LEVEL

0 dB

X

+0.00

Y

+0.00

Z

LOCKED

SCALE

1.00

FOCUS

1.00

ROT AZ

+0°

ROT EL

+0°