Tab 1

Memory Architecture & Dynamic Allocation

Executive Summary

In programming systems, primary memory (RAM) is logically partitioned into distinct segments based on program usage rather than physical hardware boundaries. Understanding the behavioral contrast between **Stack Memory** (automatic, named, scoped) and **Heap Memory** (manual, anonymous, dynamic) is fundamental to mastering pointers, dynamic memory management, and avoiding resource leaks.

---

1. Introductory Logic Exercise: Clock Simulation

Before diving into memory management, consider a standard logic-building warm-up:

. **Exercise**: Implementing a digital ticking clock that updates every second (e.g., 10:07:23 ➔ 10:07:24 ➔ 10:07:25).

. **Objective**: Reinforces sequential logic execution, nested looping constructs, and state mutation over time.

---

2. Memory Organization & The "College Ground" Analogy

RAM represents a continuous open address space allocated to your program by the Operating System.

The College Ground Metaphor

Metaphor Element	Real-World Campus Analogy	Memory Architecture Equivalent
Open Ground	An open campus quadrangle assigned to clubs.	Total available RAM assigned to the program process.
Temporary Zones	Dividing space into stage, food stalls, and seating.	Partitioning memory into Stack, Heap, Data, and Code segments.
Event Execution	Activities take place within designated zones.	Program executes; variables and buffers are populated.
Teardown & Reset	Dismantling booths and returning	Program exits; memory is freed and

Metaphor Element	Real-World Campus Analogy	Memory Architecture Equivalent
	the field to neutral.	recycled by the OS.

Key Principle: Memory segments (Stack and Heap) are **logical abstractions** defined by runtime conventions and usage, not hardwired physical barriers on the RAM chip.

---

3. Comparison: Stack vs. Heap at a Glance

Feature	Stack Memory	Heap Memory
Allocation Mechanism	Automatic / Compile-time / Scoped	Explicit / Dynamic / Runtime
Naming	**Named locations** (int x, float y)	**Nameless / Anonymous locations**
Deallocation	Automatically destroyed at end of scope/function	Explicitly freed by programmer (delete)
Access Route	Direct identifier lookup or Stack pointer	Pointer dereferencing (*ptr)
Lifetime	Tied strictly to function stack frame	Persists until explicitly deleted or process terminates
Primary Danger	Stack Overflow (exhaustion via deep recursion)	Memory Leaks (unreleased orphan allocations)

4. Stack Memory & Named Variables

Mechanism

When a variable is declared using standard syntax:

```
int x = 10;
```

1. The compiler allocates space on the **Stack frame** for integer x.
2. The symbol x acts as a human-readable **name** for that memory address.
3. When the surrounding function returns, the stack frame unwinds and x is immediately destroyed.

Pointers on the Stack

```
int x = 10;
int* p = &x;
```

. Variable x lives on the Stack (e.g., at address 0x200) storing value 10.

. Pointer variable p **also resides on the Stack** (e.g., at address 0x400), holding the value 0x200.

---

5. Heap Memory & Dynamic Allocation (new)


In many algorithms, data structures (linked lists, trees, graphs) require creating storage **on the fly without predefined variable names**.

The new Operator

```
int* p = new int;
*p = 20;
```

Architectural Breakdown:

1. **The Request**: new int requests a nameless block of 4 bytes from the **Heap**.
2. **The Address**: The memory manager returns an arbitrary address (e.g., 0x800).
3. **The Bridge**: The pointer p (located on the **Stack**) stores the Heap address 0x800.
4. **Dereferenced Access**: The program writes to the nameless Heap block using *p = 20.



Crucial Insight: Whenever you work with dynamic pointers, there are **two distinct entities**:

1. **The Pointer Location**: Resides on the Stack, has an identifier name (p).
2. **The Pointed-To Location**: Resides on the Heap, anonymous, accessed only via reference.

---

6. Manual Lifecycle & Memory Management (delete)

The Lifecycle Disconnect

- **Stack variables**: Lifecycle is strictly tied to function scope.
- **Heap allocations**: **Do NOT die** when the function exits. The memory manager retains the block as reserved until explicitly told otherwise.

The delete Operator

```
delete p;      // Deallocates heap space at address stored in p
p = nullptr;   // Best practice: clear dangling reference
```

☠ The Cost of Neglect: Memory Leaks

- If a function exits without calling delete p, the local pointer p on the Stack is destroyed, but the block on the Heap **remains allocated and orphaned**.
- The program loses the reference address forever while the Heap space stays locked, resulting in a **Memory Leak**.

---

7. Review & Key Takeaways Checklist

RAM is logically divided into functional zones (Stack and Heap).
Stack variables are named, fast, and automatically cleaned up upon scope exit.
Heap allocations via new provide nameless, flexible memory that outlives stack frames.
Every dynamic allocation with new requires a corresponding delete to prevent memory leaks.

Tab 2

Pointers, Matrices & The Hourglass Problem

Comprehensive Notes • SAHIL SAKALABHAKTHULA

Comprehensive reference guide covering memory indirection, pointer-array-string interrelationships, multi-dimensional array operations, and matrix sub-grid traversal algorithms.

---

1. Pointers & Double Pointers

Pointers are fundamental variables that store memory addresses rather than direct values. Understanding memory layout and dereferencing semantics is essential for low-level data manipulation.

Memory Indirection Map

Pointer Variable	Identifier	Value Stored
Base Variable	`x`	`10`
Single Pointer	`p`	`200`
Double Pointer	`q`	`400`

Single Pointer Mechanics

- A standard integer variable `x` stores a direct value in memory (e.g., `x = 10` located at address `200`).
- A pointer `p` stores the address of variable `x` (`p = &x`).
- Variable `p` holds the value `200` and resides at its own distinct memory address (e.g., `400`).
- Key evaluations:
  - `x = 10`
  - `&x = 200`
  - `p = 200`
  - `&p = 400`
  - `*p = 10` (dereferencing address `200` yields the underlying value `10`)

Double Pointer Mechanics

- A double pointer (pointer-to-pointer) holds the memory address of another pointer variable.
- Declared as `int **q;` and assigned via `q = &p;`.
- Variable `q` resides at its own address (e.g., `800`) and stores the value `400` (the address of `p`).
- Key evaluations:
    - `q = 400`
    - `&q = 800`
    - `*q = 200` (accesses the value at address `400`, which is `&x`)
    - `**q = 10` (dereferences twice to access the value of `x` at address `200`)

2. Interconnection: Arrays, Pointers, and Strings

Arrays, pointers, and strings share an intrinsic memory architecture in low-level systems programming.

The Foundation Triad

- **Arrays & Pointers**: Array names act as constant pointers pointing directly to the contiguous memory block's initial element (`array == &array[0]`). Pointer arithmetic allows efficient traversal without standard index subscripting.
- **Arrays & Strings**: Text is handled sequentially as character arrays, utilizing zero-indexed offset logic for direct memory access.

Mechanics of Strings

- A string is a contiguous sequence of character elements terminated by a mandatory null character (`'\0'`).
- **Memory Traversal**: String operations scan elements sequentially until encountering the `'\0'` terminator byte.
- **Element Access**: Direct indexing (`s[i]`) and dereferenced pointer arithmetic (`*(s + i)`) yield identical, constant-time `O(1)` memory lookups.

3. Matrices (2D Arrays)

A matrix is a two-dimensional visual grid organized into m rows and n columns ($m \times n$). In C++, multi-dimensional arrays are stored in contiguous row-major order.

Core Operations Matrix

Operation	C++ Conceptual Logic	Description
Reading Input	`cin >> mat[i][j]`	Populates matrix elements row-by-row through nested iteration.
Displaying Output	`cout << mat[i][j]`	Renders elements formatted in row-column visual alignment.
Matrix Transposition	`swap(mat[i][j], mat[j][i])`	Flips matrix across its main diagonal (swaps rows with columns).
Element Addition	`C[i][j] = A[i][j] + B[i][j]`	Performs component-wise sum of two identical-dimension matrices.

4. The 2D Array Hourglass Problem (6x6 Matrix)

Hourglass Structure Definition

Within any 3×3 sub-grid of a larger matrix, an hourglass shape consists of exactly 7 elements configured in a distinct layout.

Visual Template:a b c

d

e f g

- **Top Row**: 3 contiguous elements at row `i`, spanning columns `j`, `j+1`, `j+2`.
- **Middle Row**: 1 center element at row `i+1`, column `j+1`.
- **Bottom Row**: 3 contiguous elements at row `i+2`, spanning columns `j`, `j+1`, `j+2`.

Sub-grid Analysis for a 6x6 Matrix

- **Horizontal Bounds**: In a 6-column matrix, a 3-column sub-window can start at column indices `0`, `1`, `2`, or `3` (4 unique horizontal start positions).
- **Vertical Bounds**: In a 6-row matrix, a 3-row sub-window can start at row indices `0`, `1`, `2`, or `3` (4 unique vertical start positions).
- **Total Hourglasses**: $4 \text{ rows} \times 4 \text{ columns} = 16$ distinct overlapping hourglass patterns.

Algorithm Workflow

Initialize max_sum = INT_MIN

For row index i from 0 to 3:

    For column index j from 0 to 3:

        sum = mat[i][j]   + mat[i][j+1]   + mat[i][j+2]
                          + mat[i+1][j+1]
              + mat[i+2][j] + mat[i+2][j+1] + mat[i+2][j+2]

        max_sum = max(max_sum, sum)

Return max_sum

Algorithmic Execution Steps

1. **Initialize Parameters**: Set `max_sum` to the smallest possible integer (`INT_MIN`) to correctly support grids containing negative values.
2. **Boundary-Constrained Traversal**: Restrict loop indices (`i`, `j`) to range from `0` through `3`, preventing out-of-bounds array access beyond the 6x6 grid.
3. **Pattern Computation**: Sum the 7 designated hourglass indices during each iteration.
4. **State Update**: Perform an atomic maximum comparison, updating `max_sum` whenever the current pattern total exceeds all previously processed sums.
5. **Final Output**: Return `max_sum` as the maximal sub-grid sum upon loop completion.

Hourglass Sum Problem and climits :

1. Using `<climits>` for Min/Max Limits

- **Header File:** Include `<climits>` to access macro constants for integer limits (required alongside `#include <iostream>` and namespace setup).
- **Key Constants:**
  - `INT_MIN`: Represents the minimum possible integer value supported by the compiler. Must be written in all uppercase (`INT_MIN`).
  - `INT_MAX`: Represents the maximum possible integer value.
- **Purpose in Max-Finding Logic:**
  - When searching for the maximum sum across a set of numbers (especially with negative values), initialize the tracker to `INT_MIN`.
  - Any valid number encountered will be greater than or equal to `INT_MIN`, ensuring negative sums (e.g., `-10`, `-2`) correctly overwrite the initial value.

2. Hourglass Sum Problem in a 2D Array

Structure of an Hourglass

In a 6x6 2D matrix (indexed 0 to 5), each hourglass fits inside a 3x3 bounding box starting at top-left coordinate `(i, j)`:

- **Top row** (3 elements): `(i, j)`, `(i, j+1)`, `(i, j+2)`
- **Middle element** (1 element): `(i+1, j+1)`
- **Bottom row** (3 elements): `(i+2, j)`, `(i+2, j+1)`, `(i+2, j+2)`
- **Total elements per hourglass:** 7

Loop Constraints

- Because an hourglass requires a 3x3 span, the starting index `i` (row) and `j` (column) can only range from `0` to `3` (a 4x4 grid of possible starting positions).

- **Total possible hourglasses in a 6x6 matrix:** 4 x 4 = 16.

Hourglass Sum Formula

For a given top-left corner `(i, j)`:

Sum = `arr[i][j] + arr[i][j+1] + arr[i][j+2] + arr[i+1][j+1] + arr[i+2][j] + arr[i+2][j+1] + arr[i+2][j+2]`

3. Implementation Algorithm (C++)

```
#include < bits/stdc++.h>
  using namespace std;

int findMaxHourglassSum(const vector<vector>& arr) {
int max_sum = INT_MIN; // Initialize with lowest possible int//
Iterate through all valid starting coordinates (0 to 3)

for (int i = 0; i <= 3; i++) {

    for (int j = 0; j <= 3; j++) {

        // Calculate current hourglass sum

        int current_sum = arr[i][j]     + arr[i][j+1]     + arr[i]
[j+2]

                                        + arr[i+1][j+1]

                        + arr[i+2][j]   + arr[i+2][j+1]   + arr[i+2]
[j+2];

        // Update maximum sum found so far

        if (current_sum > max_sum) {

            max_sum = current_sum;
```

```
        }
    }
}
return max_sum;
}
```

4. Key Problem-Solving Takeaways

* **Deconstruct Problem Complexity:** Large or complex problem statements often look intimidating at first glance, but reducing them to coordinates and clear sub-structures simplifies the solution.

* **Trace Inputs to Outputs:** Identify the exact bounds, test edge cases (such as all-negative values), and establish standard patterns through practice.

Memory Architecture & Dynamic Allocation

Executive Summary

In programming systems, primary memory (RAM) is logically partitioned into distinct segments based on program usage rather than physical hardware boundaries. Understanding the behavioral contrast between **Stack Memory** (automatic, named, scoped) and **Heap Memory** (manual, anonymous, dynamic) is fundamental to mastering pointers, dynamic memory management, and avoiding resource leaks.

---

1. Introductory Logic Exercise: Clock Simulation

Before diving into memory management, consider a standard logic-building warm-up:

. **Exercise**: Implementing a digital ticking clock that updates every second (e.g., 10:07:23 ➔ 10:07:24 ➔ 10:07:25).

. **Objective**: Reinforces sequential logic execution, nested looping constructs, and state mutation over time.

---

2. Memory Organization & The "College Ground" Analogy

RAM represents a continuous open address space allocated to your program by the Operating System.

The College Ground Metaphor

Metaphor Element	Real-World Campus Analogy	Memory Architecture Equivalent
Open Ground	An open campus quadrangle assigned to clubs.	Total available RAM assigned to the program process.
Temporary Zones	Dividing space into stage, food stalls, and seating.	Partitioning memory into Stack, Heap, Data, and Code segments.
Event Execution	Activities take place within designated zones.	Program executes; variables and buffers are populated.
Teardown & Reset	Dismantling booths and returning the field to neutral.	Program exits; memory is freed and recycled by the OS.

Key Principle: Memory segments (Stack and Heap) are **logical abstractions** defined by runtime conventions and usage, not hardwired physical barriers on the RAM chip.

---

3. Comparison: Stack vs. Heap at a Glance

Feature	Stack Memory	Heap Memory
Allocation Mechanism	Automatic / Compile-time / Scoped	Explicit / Dynamic / Runtime
Naming	**Named locations** (int x, float y)	**Nameless / Anonymous locations**
Deallocation	Automatically destroyed at end of scope/function	Explicitly freed by programmer (delete)
Access Route	Direct identifier lookup or Stack pointer	Pointer dereferencing (*ptr)
Lifetime	Tied strictly to function stack frame	Persists until explicitly deleted or

Feature	Stack Memory	Heap Memory
		process terminates
Primary Danger	Stack Overflow (exhaustion via deep recursion)	Memory Leaks (unreleased orphan allocations)

4. Stack Memory & Named Variables

Mechanism

When a variable is declared using standard syntax:

```
int x = 10;
```

1. The compiler allocates space on the **Stack frame** for integer `x`.
2. The symbol `x` acts as a human-readable **name** for that memory address.
3. When the surrounding function returns, the stack frame unwinds and `x` is immediately destroyed.

Pointers on the Stack

```
int x = 10;
int* p = &x;
```

. Variable `x` lives on the Stack (e.g., at address `0x200`) storing value `10`.

. Pointer variable `p` **also resides on the Stack** (e.g., at address `0x400`), holding the value `0x200`.

---

5. Heap Memory & Dynamic Allocation (`new`)

In many algorithms, data structures (linked lists, trees, graphs) require creating storage **on the fly without predefined variable names**.

The `new` Operator

```
int* p = new int;
*p = 20;
```

Architectural Breakdown:

1. **The Request**: `new int` requests a nameless block of 4 bytes from the **Heap**.
2. **The Address**: The memory manager returns an arbitrary address (e.g., `0x800`).

3. **The Bridge**: The pointer `p` (located on the **Stack**) stores the Heap address `0x800`.
4. **Dereferenced Access**: The program writes to the nameless Heap block using `*p = 20`.

```
ㄲ[ STACK MEMORY ]                          [ HEAP MEMORY ]
+--------------------+                    +--------------------+
| Pointer p          |                    | Nameless Block     |
| (Addr: 0x600)      |                    | (Addr: 0x800)      |
| Value: 0x800  ======|==================>| Value: 20          |
+--------------------+                    +--------------------+
```

ㅎ **Crucial Insight**: Whenever you work with dynamic pointers, there are **two distinct entities**:

1. **The Pointer Location**: Resides on the Stack, has an identifier name (`p`).
2. **The Pointed-To Location**: Resides on the Heap, anonymous, accessed only via reference.

---

6. Manual Lifecycle & Memory Management (`delete`)

The Lifecycle Disconnect

. **Stack variables**: Lifecycle is strictly tied to function scope.
. **Heap allocations**: **Do NOT die** when the function exits. The memory manager retains the block as reserved until explicitly told otherwise.

The `delete` Operator

```
ㄲdelete p;      // Deallocates heap space at address stored in p
p = nullptr;   // Best practice: clear dangling reference
```

ㅆ The Cost of Neglect: Memory Leaks

. If a function exits without calling `delete p`, the local pointer `p` on the Stack is destroyed, but the block on the Heap **remains allocated and orphaned**.
. The program loses the reference address forever while the Heap space stays locked, resulting in a **Memory Leak**.

---

7. Review & Key Takeaways Checklist

RAM is logically divided into functional zones (Stack and Heap).

Stack variables are named, fast, and automatically cleaned up upon scope exit.

Heap allocations via `new` provide nameless, flexible memory that outlives stack frames.

Every dynamic allocation with `new` requires a corresponding `delete` to prevent memory leaks.

Tab 3

Hourglass Sum Problem and climits :

1. Using `<climits>` for Min/Max Limits

- **Header File:** Include `<climits>` to access macro constants for integer limits (required alongside `#include <iostream>` and namespace setup).
- **Key Constants:**
  - `INT_MIN`: Represents the minimum possible integer value supported by the compiler. Must be written in all uppercase (`INT_MIN`).
  - `INT_MAX`: Represents the maximum possible integer value.
- **Purpose in Max-Finding Logic:**
  - When searching for the maximum sum across a set of numbers (especially with negative values), initialize the tracker to `INT_MIN`.
  - Any valid number encountered will be greater than or equal to `INT_MIN`, ensuring negative sums (e.g., `-10`, `-2`) correctly overwrite the initial value.

2. Hourglass Sum Problem in a 2D Array

Structure of an Hourglass

In a 6x6 2D matrix (indexed 0 to 5), each hourglass fits inside a 3x3 bounding box starting at top-left coordinate `(i, j)`:

- **Top row** (3 elements): `(i, j)`, `(i, j+1)`, `(i, j+2)`
- **Middle element** (1 element): `(i+1, j+1)`
- **Bottom row** (3 elements): `(i+2, j)`, `(i+2, j+1)`, `(i+2, j+2)`
- **Total elements per hourglass:** 7

Loop Constraints

- Because an hourglass requires a 3x3 span, the starting index `i` (row) and `j` (column) can only range from `0` to `3` (a 4x4 grid of possible starting positions).
- **Total possible hourglasses in a 6x6 matrix:** 4 x 4 = 16.

Hourglass Sum Formula

For a given top-left corner `(i, j)`:
Sum = `arr[i][j] + arr[i][j+1] + arr[i][j+2] + arr[i+1][j+1] + arr[i+2][j] + arr[i+2][j+1] + arr[i+2][j+2]`

3. Implementation Algorithm (C++)

```
#include < bits/stdc++.h>
  using namespace std;

int findMaxHourglassSum(const vector<vector>& arr) {
int max_sum = INT_MIN; // Initialize with lowest possible int//
Iterate through all valid starting coordinates (0 to 3)

for (int i = 0; i <= 3; i++) {

    for (int j = 0; j <= 3; j++) {

        // Calculate current hourglass sum

        int current_sum = arr[i][j]     + arr[i][j+1]     + arr[i]
[j+2]

                                        + arr[i+1][j+1]

                        + arr[i+2][j]   + arr[i+2][j+1]   + arr[i+2]
[j+2];

        // Update maximum sum found so far
```

```
        if (current_sum > max_sum) {
            max_sum = current_sum;
        }
    }
}
return max_sum;
}
```

4. Key Problem-Solving Takeaways

* **Deconstruct Problem Complexity:** Large or complex problem statements often look intimidating at first glance, but reducing them to coordinates and clear sub-structures simplifies the solution.

* **Trace Inputs to Outputs:** Identify the exact bounds, test edge cases (such as all-negative values), and establish standard patterns through practice.

Tab 4

💻 DSA Notes: Searching Algorithms & Matrix Operations

An Executive Developer Guide to Sequential Scan, Divide-and-Conquer Search, and Multi-Dimensional Memory Layouts

---

💡 At a Glance: Core Paradigms & Mental Models

- **Sequential Traversal (Linear Search):** Straightforward check through each element. Zero constraints on data ordering. Runs in **O(N)** time.
- **Search Space Halving (Binary Search):** Cuts the search space in half with each iteration. Requires strictly sorted data. Runs in lightning-fast **O(log N)** time.
- **Matrix Flattening & Hardware Locality:** Maps 2D (rows x columns) matrices into contiguous 1D memory. Row-Major layout maximizes CPU cache hit rates.

---

1. 🔍 Linear Search (Sequential Scan)

🏗️ Core Concept & Mechanism

Linear Search is the simplest searching technique. It starts at index 0 and inspects each element one by one until it finds the target or reaches the end of the array:

`arr[i] == target`

- **Prerequisites / Constraints: None**. The array can be completely unsorted, sorted, or contain duplicates.
- **Early Exit:** The search stops immediately as soon as the target element is encountered.

🚶 Step-by-Step Walkthrough

Given array: **arr = [14, 7, 25, 9, 3]** and **target = 9**

1. **Index 0:** arr[0] is 14 (not equal to 9) → move forward.
2. **Index 1:** arr[1] is 7 (not equal to 9) → move forward.
3. **Index 2:** arr[2] is 25 (not equal to 9) → move forward.
4. **Index 3:** arr[3] is 9 (equal to 9) → **Target found at index 3!** Traversal stops.

🖥️ C++ Implementation (VS Code Style)

```
ㄱㄱ//
================================================================================
========
// File:    LinearSearch.cpp
// Topic:   Sequential 1D Array Search
//
================================================================================
========

#include <iostream>
#include <vector>

// --- 1. Linear Search Function Definition ---
int linearSearch(const std::vector<int>& arr, int target) {
    for (int i = 0; i < static_cast<int>(arr.size()); ++i) {
        if (arr[i] == target) {
            return i;  // Target found: return zero-based index
        }
    }
    return -1;         // Target not present in array
}

// --- 2. Main Execution Routine ---
int main() {
    std::vector<int> numbers = {14, 7, 25, 9, 3};
    int target = 9;

    int resultIndex = linearSearch(numbers, target);

    if (resultIndex != -1) {
        std::cout << "Status: Success | Target found at index: " <<
resultIndex << '\n';
    } else {
        std::cout << "Status: Failure | Target not found in array.
\n";
    }
```

```
    return 0;
}
```

⏱️ Complexity Analysis

- **Best-Case Time Complexity: O(1)** (Target is located right at index 0).
- **Worst-Case Time Complexity: O(N)** (Target is at the very last index or not present at all).
- **Average-Case Time Complexity: O(N)**.
- **Auxiliary Space Complexity: O(1)** (Uses constant extra memory).

---

2. ⚡ Binary Search (Divide and Conquer)

🏗️ Core Concept & Prerequisite

Binary Search is a high-performance algorithm based on the **Divide and Conquer** strategy.

- **Strict Prerequisite:** The array **must be sorted** (ascending or descending order).
- **Mechanism:** Evaluates the middle element and discards **50% of the remaining search space** in every single iteration.

📐 Safe Midpoint Calculation & Logic

Two pointers track the search boundary: **left = 0** and **right = N - 1**.
To safely calculate the middle index without causing integer overflow (which happens in C++ if left + right exceeds integer limits):

```
mid = left + (right - left) / 2
```

(Note: This gives the exact same result as (left + right) / 2, but is completely safe from overflow.)

Decision Steps:

1. **Match Found:** If **arr[mid] == target**, return **mid**.
2. **Target in Right Half:** If **target > arr[mid]**, eliminate the left half: **left = mid + 1**.
3. **Target in Left Half:** If **target < arr[mid]**, eliminate the right half: **right = mid - 1**.

🚶 Lecture Walkthrough Example

Given sorted array: **arr = [1, 2, 3, 4, 5, 6]** and **target = 6**

- **Iteration 1:**
  - Bounds: left = 0, right = 5
  - Midpoint: mid = 0 + (5 - 0) / 2 = 2 → arr[2] is 3
  - Comparison: 6 > 3 → Discard left half [1, 2, 3]. Update **left = mid + 1 = 3**.
- **Iteration 2:**
  - Bounds: left = 3, right = 5
  - Midpoint: mid = 3 + (5 - 3) / 2 = 4 → arr[4] is 5
  - Comparison: 6 > 5 → Discard left half. Update **left = mid + 1 = 5**.
- **Iteration 3:**
  - Bounds: left = 5, right = 5
  - Midpoint: mid = 5 + (5 - 5) / 2 = 5 → arr[5] is 6
  - Comparison: arr[5] == 6 → **Target found at index 5!**

🖥️ C++ Implementation (VS Code Style)

```
┌─//
// ============================================================================
// File:    BinarySearch.cpp
// Topic:   Iterative 1D Binary Search (Divide and Conquer)
//
// ============================================================================

#include <iostream>
#include <vector>

// --- 1. Binary Search Function Definition ---
int binarySearch(const std::vector<int>& arr, int target) {
    int left  = 0;
    int right = static_cast<int>(arr.size()) - 1;

    while (left <= right) {
        // Safe midpoint calculation avoiding integer overflow
        int mid = left + (right - left) / 2;

        if (arr[mid] == target) {
            return mid;       // Target identified: return zero-
based index
        } else if (target > arr[mid]) {
```

```
            left = mid + 1;   // Narrow search scope to right sub-
array
        } else {
            right = mid - 1;  // Narrow search scope to left sub-
array
        }
    }

    return -1;                // Target not found
}

// --- 2. Main Execution Routine ---
int main() {
    std::vector<int> sortedArray = {1, 2, 3, 4, 5, 6};
    int target = 6;

    int resultIndex = binarySearch(sortedArray, target);

    if (resultIndex != -1) {
        std::cout << "Status: Success | Target found at index: " <<
resultIndex << '\n';
    } else {
        std::cout << "Status: Failure | Target not found in array.
\n";
    }

    return 0;
}
```

□⏱️ Complexity Analysis & Logarithmic Intuition

- **Time Complexity: O(log N)**
- **Intuition:** Because the search space is cut in half every time (N → N/2 → N/4 → ... → 1), for 1,000,000 elements, binary search takes at most ~20 comparisons!
- **Space Complexity: O(1)** for the iterative approach.

---

3. ⚖️ Comparative Reference: Linear vs. Binary Search

Feature / Metric	Linear Search	Binary Search
Data Requirement	Unsorted or Sorted	**Strictly Sorted**
Algorithmic Strategy	Sequential check	Divide and Conquer
Search Space Reduction	Reduces by 1 element per step	Reduces by 50% per step
Best-Case Time	O(1)	O(1)
Worst-Case Time	O(N)	O(log N)
Average-Case Time	O(N)	O(log N)
Space Complexity	O(1)	O(1)
Operations for N = 1,000,000	Up to 1,000,000 checks	At most ~20 checks
Primary Use Case	Small lists, unsorted data streams	Large datasets, repeated lookups

4. 🗄️ Multi-Dimensional Searching: 2D Matrices

A. 2D Linear Search (Time Complexity: O(rows * cols))

Uses nested loops to inspect every row (r) and column (c) until it finds **matrix[r][c] == target**.

```
//
================================================================
========
// File:    LinearSearch2D.cpp
// Topic:   Exhaustive 2D Matrix Traversal
//
================================================================
========

#include <iostream>
#include <vector>
#include <utility>

std::pair<int, int> linearSearch2D(const
std::vector<std::vector<int>>& mat, int target) {
    for (int r = 0; r < static_cast<int>(mat.size()); ++r) {
        for (int c = 0; c < static_cast<int>(mat[r].size()); ++c) {
            if (mat[r][c] == target) {
                return {r, c};  // Returns {row_index, col_index}
            }
        }
    }
    return {-1, -1};           // Coordinates when target is absent
}
```

B. 2D Binary Search on a Sorted Matrix (Time Complexity: O(log(rows * cols)))

If each row is sorted, and the first number of each row is greater than the last number of the previous row, the entire 2D matrix can be treated as one flat 1D sorted array.

Coordinate Mapping Formulas:

`row = mid / cols`

`col = mid % cols`

```
//
================================================================
========
// File:    BinarySearch2D.cpp
// Topic:   Optimal 2D Matrix Binary Search
//
================================================================
========

#include <iostream>
#include <vector>
```

```cpp
// --- 1. Matrix Binary Search Function ---
bool binarySearch2D(const std::vector<std::vector<int>>& matrix, int
target) {
    if (matrix.empty() || matrix[0].empty()) return false;

    int rows  = static_cast<int>(matrix.size());
    int cols  = static_cast<int>(matrix[0].size());
    int left  = 0;
    int right = (rows * cols) - 1;

    while (left <= right) {
        int mid = left + (right - left) / 2;
        int r   = mid / cols;  // Map 1D index to Row coordinate
        int c   = mid % cols;  // Map 1D index to Column coordinate

        if (matrix[r][c] == target) {
            return true;
        } else if (target > matrix[r][c]) {
            left = mid + 1;
        } else {
            right = mid - 1;
        }
    }

    return false;
}

// --- 2. Main Execution Routine ---
int main() {
    std::vector<std::vector<int>> matrix = {
        {1,  3,  5},
        {7,  9,  11},
        {13, 15, 17}
    };
    int target = 9;

    bool found = binarySearch2D(matrix, target);
    std::cout << "Search Status: " << (found ? "Target Found" : "Not
Found") << '\n';

    return 0;
}
```

从

---

5. ➕ Matrix Operations: Addition of Two 2D Matrices

🏗️ Rules & Dimensions

- **Dimension Rule:** Two matrices can only be added if they have the **exact same dimensions** (same number of rows and columns).
- **Formula:** Addition happens element by element: **Result[i][j] = A[i][j] + B[i][j]**

Visual Example:

```
Matrix A:      Matrix B:      Sum Matrix:
[1 3]   +   [5 1]   =   [1+5 3+1] = [6 4]
[4 2]       [2 6]       [4+2 2+6]   [6 8]
```

🖥️ C++ Implementation (VS Code Style)

-

```
דד//
================================================================================
// File:    MatrixAddition.cpp
// Topic:   Element-wise Addition of Two Matrices
//
================================================================================

#include <iostream>
#include <vector>

std::vector<std::vector<int>> addMatrices(
    const std::vector<std::vector<int>>& A,
    const std::vector<std::vector<int>>& B
) {
    int rows = static_cast<int>(A.size());
    int cols = static_cast<int>(A[0].size());

    std::vector<std::vector<int>> result(rows,
std::vector<int>(cols, 0));

    for (int i = 0; i < rows; ++i) {
        for (int j = 0; j < cols; ++j) {
            result[i][j] = A[i][j] + B[i][j];
        }
    }
```

```
    return result;
}

int main() {
    std::vector<std::vector<int>> A = {{1, 3}, {4, 2}};
    std::vector<std::vector<int>> B = {{5, 1}, {2, 6}};

    auto sumMatrix = addMatrices(A, B);

    std::cout << "Sum Matrix Output:\n";
    for (const auto& row : sumMatrix) {
        for (int val : row) {
            std::cout << val << " ";
        }
        std::cout << '\n';
    }

    return 0;
}
```

- ⏲️**Time Complexity: O(rows * cols)** (visits each cell once).
- **Space Complexity: O(rows * cols)** to store the resulting matrix.

---

6. 📐 Memory Layouts, Cache Locality & Transposition

🧠 Memory Layout: Row-Major vs. Column-Major

Computer RAM is a continuous 1D strip of memory. A 2D matrix must be flattened into 1D when stored in RAM.

Layout Format	Memory Serialization	Primary Languages	1D Index Formula
Row-Major Order	Stored row by row continuously (Row 0, then Row 1, ...)	C, C++, Python, Java	Index = (row * cols) + col
Column-Major	Stored column by	Fortran, MATLAB, R	Index = (col * rows) +

Layout Format	Memory Serialization	Primary Languages	1D Index Formula
Order	column continuously (Col 0, then Col 1, ...)		row

🏎️ Hardware Engineering: Cache Locality in C++

- **Why it matters:** When the CPU reads memory, it fetches an entire cache line (usually 64 bytes) at once into high-speed cache.
- **Row-Wise Traversal (Fast):** Looping over rows first, then columns accesses adjacent memory spots in sequence → **High Cache Hits**.
- **Column-Wise Traversal (Slow):** Looping over columns first, then rows jumps across memory by an entire row size → **Frequent Cache Misses**.

🔄 Matrix Transposition

Transposing a matrix swaps rows with columns. An **m x n** matrix becomes an **n x m** matrix:

```
Transposed[col][row] = Original[row][col]
```

```
Original Matrix (2 x 3):      Transposed Matrix (3 x 2):
[1 2 3]                       [1 4]
[4 5 6]              →        [2 5]
                              [3 6]
```

```
ㄱㄷ//
================================================================================
// File:    MatrixTranspose.cpp
// Topic:   Matrix Transposition (Dimensions m x n to n x m)
//
================================================================================

#include <iostream>
#include <vector>
```

```
std::vector<std::vector<int>> transposeMatrix(const
std::vector<std::vector<int>>& mat) {
    int rows = static_cast<int>(mat.size());
    int cols = static_cast<int>(mat[0].size());

    // Transposed matrix has swapped dimensions: cols x rows
    std::vector<std::vector<int>> transposed(cols,
std::vector<int>(rows));

    for (int i = 0; i < rows; ++i) {
        for (int j = 0; j < cols; ++j) {
            transposed[j][i] = mat[i][j];
        }
    }

    return transposed;
}
```

□

📝 Quick Exam Checklist & High-Yield Takeaways

1. **Prerequisite Check:** Can you run Binary Search? Only if the array is **already sorted**!
2. **Midpoint Formula:** Always use **left + (right - left) / 2** to prevent integer overflow.
3. **Complexity Rules of Thumb:**
    - Halving the search space each step → **O(log N)**
    - Checking every item sequentially → **O(N)**
    - Checking all cells in a matrix → **O(rows * cols)**
4. **Matrix Addition Rule:** Both matrices **must** have identical dimensions.
5. **C++ Cache Tip:** Loop through rows on the outer loop and columns on the inner loop for best CPU cache performance.

Tab 5

💻 Memory Management & Dynamic Pointers in C++

Study Notes Guide

💡 At a Glance: Executive Summary

Core Principle: RAM serves as the system's volatile execution workspace—essential for runtime calculations and intermediate execution states. While modern workloads (such as AI model training and inference) have dramatically increased memory demands, hardware memory must be strictly managed at the code level between the automatic lifecycle of the Stack and the manual lifecycle of the Heap.The Dual-Location Rule: A pointer always occupies its own slot on the **Stack** while storing the memory address of a target location (which can reside on the **Stack** or the **Heap**). Forgetting to free heap memory before reassigning a pointer creates a permanent **Memory Leak**.

1. 🏗️ Foundations: RAM & The Memory Hierarchy

- **Volatile Execution Workspace**: RAM is temporary working memory required to evaluate expressions, execute functions, and buffer active data. Without RAM, execution is impossible.
- **The AI Memory Explosion**: Modern AI models perform continuous intermediate tensor calculations and dynamic caching, drastically driving up demand, consumption, and market pricing for high-speed RAM.
- **App Lifecycle & Loading Latency**:
    - **Storage (Persistent)**: Downloading an application writes binary files to secondary storage (SSD/flash/ROM).

    - **Memory (Volatile Execution)**: When an app is launched, its binary code, runtime assets, and execution stack are loaded into RAM. The startup delay is the time required to copy assets into RAM.
- **Cognitive Analogy (Brain Memory Model)**:
    - *Short-Term / Ephemeral Memory*: Holds daily transient facts (e.g., what you had for breakfast this morning). Once the cycle ends or you sleep, it is cleared without consequence.
    - *Long-Term Memory*: Repeatedly reinforced stimuli (e.g., repeatedly hearing an instructor's name across many sessions) consolidate into permanent neural storage.

2. ⚖️ Architecture: Stack Memory vs. Heap Memory

Dynamic programming requires understanding the boundary between automatic stack frames and manual heap pools:

Architectural Metric	Stack Memory 📚	Heap Memory 🌐
Locality & Scope	Strictly local to the defining function / block scope.	Global access across the entire program via memory address/pointer.
Management Model	Automatic (managed directly by CPU architecture).	Manual (explicitly allocated and released by developer).
Data Stored	Function parameters, local primitives, and pointer variables.	Dynamically allocated objects, runtime-sized buffers, shared pools.
Lifetime	Tied to function stack frame; automatically freed upon return.	Persists indefinitely until explicitly deallocated or process exits.
C++ Operators	Standard variable declaration (e.g., `int x;`).	Managed via `new` (allocation) and `delete` (deallocation).
Primary Danger	Stack Overflow (exhaustion via deep recursion).	Memory Leaks (orphaned heap blocks) & Dangling Pointers.

Real-World Conceptual Analogies

- **Personal Budget vs. Shared Treasury**: An individual function's stack memory is like personal pocket money—spent and discarded when that person leaves. The heap is like a shared club treasury—funds pooled across functions that require someone to balance and close out the account.
- **The Hotel Room Checkout**: Allocating heap memory (`new`) is checking into a hotel room. When you leave, calling `delete` is checking out at the front desk. If you leave without checking out, the hotel manager cannot assign that room to anyone else, leaving rooms permanently blocked.

3. ⚠ Critical Pitfall: Memory Leaks & Resource Management

- **The Anatomy of a Memory Leak**: A memory leak occurs when memory allocated on the heap loses all active pointer references before being deallocated via `delete`.
- **The Reassignment Trap**:
    - Suppose pointer `q` holds the address of a dynamically allocated heap block (`q = new int;`).
    - If you reassign `q` directly to another address (e.g., `q = &x;` or `q = new int;` again) without first executing `delete q;`, the original heap location becomes an orphaned block.
    - C++ does not provide a built-in reverse lookup for heap addresses; once lost, that heap memory cannot be reclaimed until program termination.
- **System Impact**:
    - Accumulation of orphaned heap allocations continuously increases memory footprint.
    - As free RAM diminishes, page swapping and latency escalate, eventually starving system processes and forcing application crashes or machine restarts.
- **The Golden Rule**: Every dynamic allocation (`new`) must have a guaranteed corresponding destruction path (`delete`).

4. 🎯 Pointers in Practice: Capabilities, Dual Locations & Syntax

Pointers as Capabilities

A pointer declaration (e.g., `int* p;`) represents a **capability**—the ability to hold and navigate to a target memory address.

- Just as having a license to ride a motorcycle gives you the skill/capability, you cannot demonstrate riding without an actual motorcycle vehicle.
- Similarly, an uninitialized pointer possesses the capability to address memory, but until it is bound to a valid address (stack address `&x` or heap address `new int`), it remains a wild/null pointer.

The Dual-Location Rule

Whenever dealing with a pointer, always distinguish between its two physical locations:

1. **The Pointer's Storage Location**: The pointer variable itself, located on the **Stack** (e.g., at address `0x600`).
2. **The Target Pointed Location**: The address stored inside the pointer pointing to actual data (e.g., stack address `&x` or heap address `0x800`).

5. 📊 Comparative Reference: Arrays vs. Pointers

Dimension	Array (int arr[N];)	Pointer (int* ptr;)
Nature	A contiguous sequence of allocated elements.	A variable holding a single memory address.
Address Mutability	**Constant Pointer**; array base identifier cannot be rebound (`arr = ...` is invalid).	**Mutable Reference**; pointer can be redirected freely to new targets (`ptr = &y;`).

Dimension	Array (int arr[N];)	Pointer (int* ptr;)
Subscript Syntax	`arr[i]` accesses element at offset `i`.	`ptr[i]` or `*(ptr + i)` navigates pointer arithmetic identically.
Memory Allocation	Typically fixed compile-time stack allocation (or static).	Dynamic runtime allocation on heap (`new int[N]`) or reference to stack.

6. 💻 Production Implementation: VS Code-Style Demo

```
//
============================================================
==============

// File: memory_management_demo.cpp

// Topic: Stack vs. Heap Allocation, Pointer Manipulation & Safe Deallocation

// Standard: C++17 / C++20

//
============================================================
==============

#include <iostream>

using namespace std;

// --- 1. Main Execution & Pointer Demonstration ---

int main() {

    // [Stack Allocation]
```

```
// Primitive variable on the stack frame

int x = 10;



// Pointer variable 'p' on the stack, referencing stack address of 'x'

int* p = &x;



cout << "=== Stack Variables ===" << endl;

cout << "Value of x:              " << x << endl;

cout << "Address of x (&x):       " << &x << endl;

cout << "Pointer p value (holds): " << p << endl;

cout << "Dereferenced *p:         " << *p << endl << endl;

// --- 2. Dynamic Heap Allocation ---

// Pointer 'q' exists on the Stack, but receives a new memory address on the Heap

int* q = new int;



// Assigning data to the heap block

*q = 89;

cout << "=== Dynamic Heap Allocation ===" << endl;

cout << "Heap address allocated to q: " << q << endl;

cout << "Value stored at heap (*q):   " << *q << endl;

// Overwriting heap value in-place
```

```
    *q = 90;

    cout << "Updated value at heap (*q):   " << *q << endl << endl;

    // --- 3. Preventing Memory Leaks (Safe Deallocation) ---

    // CRITICAL: Before reassigning 'q', deallocate existing heap storage!

    delete q;

    q = nullptr; // Clear dangling reference

    cout << "=== Deallocation Complete ===" << endl;

    cout << "Heap block freed. Pointer safely set to nullptr." << endl << endl;

    // --- 4. Rebinding Pointer to Stack Address ---

    q = &x; // Now safely points to stack variable 'x' without leaking heap memory

    cout << "=== Rebound Pointer ===" << endl;

    cout << "Pointer q now points to x:   " << q << " with value: " << *q << endl;

    return 0;

}
```

7. 📝 Quick Exam Checklist

- **RAM as Temporary Storage**: RAM is volatile workspace for actively executing code and temporary data.
- **Stack vs. Heap Dichotomy**: Stack memory is local, fast, and auto-managed; Heap memory is global, dynamic, and manually managed.
- **Pointer Mechanics**: Always distinguish the pointer's own address on the stack from the target address it points to.
- **Dynamic Syntax**: Use `new` to request heap memory and `delete` to free it.

Memory Leak Prevention: Reassigning a pointer before calling `delete` permanently isolates heap memory.

Arrays vs. Pointers: Array names act as constant pointers that cannot be rebound; pointer variables can be reassigned.

guide to memory allocations , C++ pointer , dynamic heap allocation and leak prevention.

At a Glance: Executive Takeaways

The Core Intuition:

- **RAM as the Staging Ground:** Every executable binary, running process, and active dataset must be copied into volatile RAM before the CPU can execute instructions.
- **Stack (Automatic & Local):** Operates like private pocket cash—allocated instantly when entering a function, automatically reclaimed upon return.
- **Heap (Dynamic & Shared):** Operates like an open hotel room or communal fund—available globally across the application, but requiring explicit check-in (`new`) and check-out (`delete`).
- **Pointers as Capabilities:** Declaring a pointer creates a navigational capability (holding an address). The pointer itself is not the data; it merely directs execution flow to a target referent.

1. Hardware Foundations: RAM & Volatile Runtime Memory

- **The Execution Lifecycle:**
  When software is downloaded (e.g., from an app store or package repository), it resides at rest on non-volatile, persistent storage (SSD/HDD). Launching the application initiates a buffering phase where machine code, assets, and runtime state are paged directly into **Random Access Memory (RAM)**. Without residency in RAM, CPU execution cannot occur.
- **The Modern Demand Driver (AI & Data Footprint):**
  Emerging artificial intelligence models, matrix transformations, and multi-tenant workloads perform enormous volumes of intermediate scratchpad computations. This explosive demand for temporary data buffers directly impacts hardware scaling, memory bandwidth constraints, and module pricing.
- **Cognitive Analogy (Temporary vs. Permanent Memory):**
  - **Short-Term Buffer:** Everyday ephemeral details (such as what was consumed for breakfast) occupy temporary memory registers and are systematically cleared out once obsolete.
  - **Reinforced Long-Term Storage:** Repeatedly encountered identifiers, continuous exposure, and deliberate storage calls consolidate transient signals into persistent long-term structures.

2. The Dual Storage : Stack vs. Heap

In compiled environments like C++, virtual runtime memory is bifurcated into two primary segments governed by contrasting operational contracts:

Architectural Comparison: Stack vs. Heap

Attribute	Stack Memory 📦	Heap Memory 🌐
Locality & Scope	Bound strictly to the local scope / stack frame of the	Global / program-wide access via referenced memory

Attribute	Stack Memory 📦	Heap Memory 🌐
	executing function.	addresses.
Allocation Mechanism	Sequential push/pop handled automatically by compiler stack pointer offsets.	Dynamic allocation managed via runtime system calls (`new` / `malloc`).
Deallocation & Lifetime	Destroyed deterministically the exact instant the enclosing function returns.	Persists indefinitely until explicitly freed via `delete` / `free`.
Access Speed	Blazing fast (contiguous cache hits, zero fragmentation).	Slower (metadata tracking, dynamic lookup, potential page fragmentation).
Management Responsibility	Fully automated by the compiler / runtime call stack.	Manual developer responsibility (risk of leaks or dangling pointers).
Failure Modes	**Stack Overflow** (excessive recursion, overly large local arrays).	**Memory Leak** (orphaned allocations) or Heap Fragmentation.

Architectural Metaphors:

- **Private Cash vs. Communal Union Pool:**
  If several contributors maintain individual wallets, each person spends and depletes their private stash independently within their own context (local stack variables). If they pool assets into a single joint account (heap block), that pooled resource exists independently of any single member's individual presence and must be explicitly audited and closed when dissolved.
- **Hotel Room Reservation:**
  Allocating heap space is analogous to reserving a hotel room. As long as you possess the keycard (the pointer address), you have legitimate access. However, once you check out, the room manager can reassign the space. Failing to formally check out locks the room perpetually against future guests.

3. Memory Leaks & Allocation Lifecycles

- **Anatomy of a Memory Leak:**
  A **memory leak** occurs when dynamic memory is allocated on the heap, but all pointer references to that allocated block are overwritten, reassigned, or lost without first executing an explicit `delete` instruction.
- **Mechanics of Loss:**

1. A pointer `q` is allocated heap space via `new int`.
2. The address location (e.g., `0x800`) is stored within `q`.
3. Later, the code assigns `q = &x;` (redirecting `q` to a local stack address).

4. The heap memory block at `0x800` remains marked as active in the operating system's heap manager, but the program has permanently lost the pointer handle required to address or reclaim it.

- **System Impact:**
  Over prolonged execution cycles, accumulated leaked allocations fragment available memory pools, increase paging pressure, degrade overall execution throughput, and eventually cause host processes or systems to stall or crash.
- **The Core Rule:**
  Every dynamic initialization (`new`) must guarantee a corresponding, unambiguous deallocation path (`delete`) before reference mutation.

4. Pointers: Capabilities vs. Referents

- **The Dual-Location Reality:**
  Working with pointers invariably requires tracking **two distinct spatial entities**:

1. **The Pointer Location:** The physical stack address where the pointer variable itself lives.
2. **The Pointed Location (Referent):** The memory address (stack or heap) stored as the pointer's value.

- **Pointers as Capabilities:**
  A pointer declaration (e.g., `int* q;`) is an uncommitted capability—much like having the licensed ability to operate a motorcycle. Without an actual vehicle assigned or present, the capability cannot produce work. Before initialization, a pointer is unassigned/null and must not be dereferenced.
- **Arrays vs. Pointers:**
  - An **Array identifier** is a **constant pointer** locked permanently to the base address of a contiguous memory buffer.
  - A **Standard Pointer** is a dynamic variable that can traverse, point to, and be reassigned across arbitrary locations throughout the memory space.

Arrays vs. Pointers Reference Table

Dimension	Array (int arr[N])	Pointer (int* ptr)
Address Mutability	**Constant**: Bound immutably to the allocated block.	**Mutable**: Can point to any arbitrary valid memory block.
Storage Allocation	Allocates space for *N* × `sizeof(Type)` bytes sequentially.	Allocates space solely for the memory address (4 or 8 bytes).
Subscript Syntax	`arr[i]` accesses element directly via base offset.	`ptr[i]` calculates offset dynamically via arithmetic (`*(ptr + i)`).
Reassignment	`arr = newAddress;` ❌ Compile Error.	`ptr = newAddress;` ✅ Permitted.

5. Implementation: Modern C++ Memory Architecture

```
//
================================================================
============

// File: memory_architecture.cpp

// Topic: Stack vs. Heap Allocation, Pointer Manipulation, and Leak Prevention

//
================================================================
============

#include <iostream>

int main() {

    // ------------------------------------------------------------------------

    // 1. Stack Allocation & Pointer Capability Declaration

    // ------------------------------------------------------------------------

    int  x        = 10;         // Stack variable holding integer literal 10

    int* p        = &x;         // Pointer 'p' on stack storing the address of 'x'

    int* q        = nullptr;    // Pointer 'q' initialized safely without referent

    std::cout << "[Stack] Address of x: " << &x << " | Value: " << x  << std::endl;

    std::cout << "[Stack] Pointer p holds: " << p  << " | Deref: " << *p << std::endl;

    // ------------------------------------------------------------------------

    // 2. Dynamic Heap Allocation & Value Overwriting

    // ------------------------------------------------------------------------

    q = new int(89);            // Allocates unnamed integer on heap; stores 89

    std::cout << "\n[Heap] Allocated address: " << q  << " | Initial value: " << *q <<
std::endl;
```

```
    *q = 90;                  // Overwrites heap contents via dereferenced handle

    std::cout << "[Heap] Overwritten value:  " << *q << " at address:    " << q << std::endl;

    // ------------------------------------------------------------------------

    // 3. Proper Lifecycle Cleanup (Preventing Memory Leaks)

    // ------------------------------------------------------------------------

    // Critical: Free the allocated heap block BEFORE redirecting the pointer!

    delete q;                 // Check out / release heap memory back to system

    q = nullptr;              // Prevent dangling pointer vulnerabilities

    // ------------------------------------------------------------------------

    // 4. Pointer Redirection to Stack Target

    // ------------------------------------------------------------------------

    q = &x;                   // Safely rebind 'q' to stack variable 'x'

    std::cout << "\n[Stack Rebind] Pointer q now holds: " << q << " | Value: " << *q <<
std::endl;

    return 0;

}
```

6. Quick Exam Checklist & Diagnostic Summary

- **Volatile Memory:** Do you recall why application programs must load from non-volatile storage into RAM before CPU execution?
- **Stack Scope:** Are you able to explain why local stack variables disappear immediately when a function exits?
- **Heap Persistence:** Can you articulate why heap allocations survive function returns until explicit `delete` calls are made?
- **Memory Leak Anatomy:** Can you diagram how reassigning `q = &x` without `delete q` causes an untraceable orphaned heap block?
- **Dual Memory Coordinates:** For any pointer operation, can you identify both where the pointer resides (stack) and where it points (target address)?
- **Array Identity:** Do you understand why array names act as immutable constant pointers whereas standard pointers are mutable?

Dereferencing Mechanics: Can you distinguish between altering a pointer's target address (`q = new_addr`) versus mutating its pointed value (`*q = new_val`)?[