

Logo 1

Logo2

Universität Bayreuth
Fakultät für Informatik

Bachelorarbeit

im Studiengang Informatik

zur Erlangung des akademischen Grades
Bachelor / Master of Science

Thema: Integration of JPA-conform ORM-Implementations in Hibernate Search

Autor: Martin Braun <martinbraun123@aol.com>
Matrikel-Nr. 1249080

Version vom: August 6, 2015

1. Betreuer: Dr. Bernhard Volz
2. Betreuer: Prof. Dr. Bernhard Westfechtel

Zusammenfassung

Abstract

Contents

1	Preface	5
2	Overview of technologies	8
2.1	Object Relational Mappers	8
2.2	JPA	9
2.3	Fulltext search engines	10
2.3.1	Lucene	11
2.3.1.1	Concepts	11
2.3.1.2	Usage	12
2.3.1.3	Features	12
2.3.2	Solr	13
2.3.3	ElasticSearch	13
2.3.4	Hibernate Search	13
2.3.5	Conclusion: Why a generic Hibernate Search?	13
2.4	Versions used in this Thesis	13
3	Challenges	14
3.1	The example project	14
3.2	Indexing & searching	16
3.3	Automatic index updating	17
4	Building a JPA integration on top of Hibernate Search	18
4.1	Setting up the example project	18
4.2	Using Hibernate Search's engine	21
4.2.1	Starting the engine	21
4.2.2	Indexing, updating and deleting objects from the index	22
4.2.3	Querying the index	23
4.3	Standalone version of Hibernate Search	25
4.3.1	Starting the standalone	26
4.3.2	Indexing, updating and deleting objects from the index	26
4.3.3	Querying the index	27
4.4	Standalone integration with JPA interfaces	28
4.4.1	Architecture of Hibernate Search ORM	28
4.4.1.1	Starting	28
4.4.1.2	Indexing, updating and deleting objects from the index	29
4.4.1.3	Querying the index	29
4.4.1.4	Index rebuilds	30
4.4.2	Architecture of the generic version	31
4.4.2.1	Starting	31
4.4.2.2	Indexing, updating and deleting objects from the index	32
4.4.2.3	Querying the index	34
4.4.2.4	Index rebuilds	35
4.5	The automatic index updating feature	36
4.5.1	Overview of possible implementations	36
4.5.1.1	Synchronous approaches	36
4.5.1.2	Asynchronous approaches	36
4.5.2	Native event integration with JPA providers	36

4.5.3 Generic approach	36
References	37
Listings	38
Tables	49
Eidesstattliche Erklärung	49

1 Preface

In the software world, or more specific, the Java enterprise world, developers tend to abstract access to data in a way that components are interchangeable. A perfect example for such an abstraction is the usage of Object Relational Mappers (ORM). The database specifics are mostly irrelevant to the average developer and the need for native SQL is brought down to a minimum. This makes the switch to a different relational database system (RDBMS) easier in the later stages of a product's life cycle.

The Java Persistence API (JPA) went even further by standardising ORMs. First conceived in 2006 ¹, it is now the de-facto standard for Object Relational Mappers in Java. The developer doesn't need to know which specific ORM is used in the application, as all the database queries are written against a standardized query API and therefore portable. This means that not only the database is interchangeable, but even the specific ORM, it is accessed by, is as well.

However, this does not mean that all JPA implementations come with the same features. While all of them are JPA compliant (apart from minor bugs), some ship with additional modules to enhance their capabilities. A perfect example for this is the Hibernate Search API aimed at Hibernate ORM users.^{2 3}

Nowadays, even small applications like online shops need enhanced search capabilities to let the user find more results for a given input. This is not something a regular RDBMS excels at and Hibernate Search comes into use: It works atop the Hibernate ORM/JPA system and enables the developer to index the domain model for searching. It's not only a mapper from JPA entities to a search index, but also keeps the index up-to-date if something in the database changes.

¹Wikipedia on Java Persistence API, see [1]

²Hibernate ORM project homepage, see [10]

³Hibernate Search project homepage, see [2]




Figure 1: Hibernate Search with Hibernate ORM

Hibernate Search, which is based on the powerful Lucene search toolbox, is a separate project in the Hibernate family and aims to provide a JPA "feeling" in its API as it also incorporates a lot of JPA interfaces in its codebase. However, this does not mean that it is compatible with other JPA providers than Hibernate ORM (apart from Hibernate OGM, the NoSQL JPA mapper of the family).




Figure 2: Hibernate Search's incompatibility with other JPA implementations

While using Hibernate Search obviously is beneficial for Hibernate ORM applications, not all developers can bind themselves to a specific JPA implementation in their application. For some, the ability to change implementations might be of strategic importance, for others it could just be sheer preference to use a different JPA implementation.

Currently, developers that do not want to bind themselves to Hibernate ORM have to resort to using different full text search systems like native Lucene⁴, ElasticSearch⁵ or Solr⁶. While this is always a viable option, for some applications Hibernate Search

⁴official Lucene website, see [19]

⁵ElasticSearch Java API, see [5]

⁶Solr Java API, see [6]

would be a much better suit because of its design with an entity structure in mind and the automatic index updating feature, if it just were compatible with generic JPA.

When investigating Hibernate Search's project structure ⁷, we can see that the only module apart from some server-integration modules that depends on any ORM logic is "hibernate-search-orm". The modules that contain the indexing engine, the replication logic, alternative backends, etc. are completely independent from any ORM logic. This means, that most of the codebase could be reused for a generic version of Hibernate Search.

Creating this would be a better approach for a search API on top of JPA rather than rewriting everything from scratch. Hibernate Search could then act as the standard for fulltext search in the JPA world instead of having a competing API that would just do the same thing in a different style.




Figure 3: xkcd.com on competing standards ⁸

This is why in this thesis we will show how such a generic version can be built. First, we will look at how Hibernate Search's engine can be reused. Then, we will write a standalone version of this engine and finally integrate it with generic JPA.

⁷Hibernate Search GitHub repository, see [14]

⁸xkcd comic #927, see [17]

2 Overview of technologies

Before we start going into detail about how to work with Hibernate Search in a generic environment, we will give a short overview of relevant technologies first. We will explain why ORMs in general and the JPA specification in particular are beneficial. Then, we will explain what fulltext search engines are used for and give a short overview about the available solutions for Java. We will see that generalizing Hibernate Search for any JPA implementation is a good approach and that it has benefits over using the different search solutions available.

2.1 Object Relational Mappers

Nowadays, many popular languages like Java, C#, etc. are object-oriented⁹. While SQL solutions for querying relational databases exist for these languages (JDBC for Java¹⁰, OleDb for C#¹¹), the user either has to work with the rowsets manually or convert them into custom data transfer objects (DTO) to gain at least some "real" objects to work with. Both approaches don't suit the object oriented paradigm well as SQL "flattens" the data into rows with when querying while a well designed class model would work with multiple classes in a hierarchy.

```
1 SELECT author.id, author.name, book.id, book.name
2 FROM author_book, author, author
3 WHERE author_book.bookid = book.id
4 AND author_book.authorid = author.id
```

Listing 1: sql query "flattening" the author and book table into rows

This is where Object Relational Mappers (ORM) come into use. They map tables to entity-classes and enable users to write queries against these classes instead of tables. The returned objects are part of a complex object hierarchy and are easier to use from a object oriented point of view.

```
1 List<Author> data = orm.query("SELECT a FROM Author a " +
2     "LEFT OUTER JOIN a.books");
3 for (Author author : data) {
4     System.out.println("name: " + author.getName() +
5         ", books: " + author.getBooks());
6 }
```

Listing 2: ORM query example

⁹Wikipedia on Object Oriented Programming (OOP), see [7]

¹⁰Oracle JDBC overview, see [15]

¹¹OleDb usage page, see [16]

This is especially useful if used in big software products as not all programmers have to know the exact details of the underlying database. The database system could even be completely replaced for another (provided the ORM supports the specific RDBMS), while the business logic would not changing a bit.

2.2 JPA

The first version of the JPA standard was released in May 2006. From then on it rose to being probably the most commonly used persistence API for Java and is considered the "industry standard approach for Object Relational Mapping"¹². While mostly known for standardizing relational database mappers (ORM), it also supports other concepts like NoSQL^{13 14} or XML storage¹⁵. However, when talking about JPA in this thesis, we will be focusing on the relational aspects of it. Currently, the newest version of this standard is 2.1.¹⁶

Some popular relational implementations are:

- Hibernate ORM (JBoss)¹⁷
- EclipseLink (Eclipse foundation)¹⁸
- OpenJPA (Apache foundation)¹⁹

Using the standardized JPA API over any native ORM API has one really interesting benefit: The specific JPA implementation can be swapped out as it comes with standards for many common use cases.

This is particularly important if you are working in a Java EE environment. Java EE itself is a specification for platforms, mostly Web-servers (JPA is part of the Java EE spec).²⁰ Many Java EE Web-servers ship with a bundled JPA implementation that they are optimized for (Wildfly with Hibernate ORM, GlassFish with EclipseLink, ...). This means that if the server is switched, it could also be a reasonable idea to swap out the JPA implementor. If everything in the application is written in a JPA compliant way, the user will then generally not run into many problems related to this switch.

¹²Wikibooks on Java Persistence, see [8]

¹³Hibernate OGM project homepage, see [9]

¹⁴EclipseLink project homepage, see [13]

¹⁵EclipseLink project homepage, see [13]

¹⁶Wikipedia on Java Persistence API, see [1]

¹⁷Hibernate ORM project homepage, see [10]

¹⁸EclipseLink project homepage, see [13]

¹⁹OpenJPA project homepage, see [11]

²⁰Wikipedia on Java EE, see [18]

2.3 Fulltext search engines

Conventional relational databases are good at retrieving and querying structured data. But if one wants to build a search engine atop a domain model, most RDBMS will only support the SQL-LIKE operator ²¹:

```
1 SELECT book.id , book.name FROM book WHERE book.name LIKE %name%;
```

Listing 3: SQL LIKE operator in use

While this might be enough for some applications, this wildcard query doesn't support features a good search engine would need, for example:

- fuzzy queries (variations of the original string will get matched, too)
- phrase queries (search for a specified phrase)
- regular expression queries (matches are determined by a regular expression)

There may exist some RDBMS that support similar query-types, but in the context of using a ORM we would then lose the ability to switch databases since, we would use vendor-specific features not every RDBMS supports.

Fulltext search engines can be used to complement databases in this regard. They are generally not intended to be replacing the database, but add additional functionality by indexing the data that is to be searched in a more sophisticated way. We will now take a look at some of the most popular available options for Java developers (including Hibernate Search) focusing on their usage and features. After that we will give the reasoning behind why a **generic** Hibernate Search is a good idea.

²¹w3schools on SQL LIKE, see [12]

2.3.1 Lucene

mention current version for each of these?

Apache Lucene™ is a high-performance, full-featured text search engine library written entirely in Java. It is a technology suitable for nearly any application that requires full-text search, especially cross-platform.²²

Lucene serves as the basis for many fulltext search engines written in Java. It has many different utilities and modules aimed at search engine developers. However, it can be used on its own as well.

2.3.1.1 Concepts As Lucene's focus is not on storing relational data, it comes with its own set of concepts. Following is a short overview over the most important ones. These are not only the basis for Lucene, but also for the other search engines we will discuss next, as they are based on Lucene's rich set of features.

Index structure Lucene uses an **inverted index** to store data. This means that instead of storing texts mapped to the words contained in them, it works the other way around. All different words (terms) are mapped to the texts they occur in²³, so it can be compared to a *Map < String, List < Text >>* in Java. Before anything can be searched using Lucene, it has to be added to the the index (indexed) first.

Documents Documents are the data-structure Lucene stores and retrieves from the index. An index can contain zero or more Documents.

Fields A Document consists of at least one field. Fields are basically tuples of key and value. They can be stored (retrievable from the index) and/or indexed (used for searches, generate hits).

Analyzers Before documents get indexed, their fields are analyzed with one of the many Analyzers first. Analysis is the process of modifying the input in a manner such that it can be searched upon (stemming, tokenization, ...).

²²official Lucene website, see [19]

²³Lucene basic concepts, see [20]

Sowas hier drinlassen? Wenn ja, dann aber auch für Searching

Quelle: <http://acupof.blogspot.de/2011/02/lucene-and-hibernate-search-small.html>




Figure 4: The indexing "pipeline" ²⁴

2.3.1.2 Usage Using Lucene as a standalone engine requires the programmer to design the engine from the bottom up. The developer has to write all the logic, starting with the actual indexing code through to the code managing access to the index. The conversion from Java objects to Documents (for indexing) and back (for searching) have to be implemented as well. This whole process requires a lot of code to be written and the API only helps by providing the necessary tools. This has one additional problem: The Lucene API tends to change a lot between versions and the code has to be kept up-to-date. It's not uncommon that whole features that were state-of-the-art in one version, are deprecated (potentially unstable, marked to be removed in the future) in the next release, resulting in big code changes being potentially necessary.

2.3.1.3 Features Lucene probably is the most complete toolbox to build a search-engine from. It has pre-built analyzers for many languages, a queryparser to support generating queries out of user input, a phonetic module, a faceting module, and many other features. While mostly known for its fulltext capabilities, it also has modules used for other purposes, for example the spatial module that enables geo-location query support.

²⁴Footnote für Bild

2.3.2 Solr

Solr is the popular, blazing-fast, open source enterprise search platform built on Apache Lucene™.

2.3.3 ElasticSearch

2.3.4 Hibernate Search

Hibernate Search transparently indexes your objects and offers fast regular, full-text and geolocation search. Ease of use and easy clustering are core.²⁵

some kind of conclusion with a table of features. -> Hibernate Search, aber mit dem Problem von Kompatibilität mit Non Hibernate ORM, mention Compass?

2.3.5 Conclusion: Why a generic Hibernate Search?

2.4 Versions used in this Thesis

Hier die Versionen, die benutzt werden auflisten für Hibernate Search, Hibernate ORM, EclipseLink, OpenJPA

²⁵Hibernate Search project homepage, see [2]

3 Challenges

While building the generic version of Hibernate Search, we will encounter some challenges. We will now discuss the biggest ones and introduce a small example project. This project will be used to showcase some problems and usages later on in this thesis as well.

3.1 The example project

Consider a software built with JPA that is used to manage the inventory of a bookstore. It stores information about the available books (ISBN, title, genre, short summary of the contents) and the corresponding authors (surrogate id, first & last name, country) in a relational database. Each author is related to zero or more Books and each Book is written by one or more Authors. The entity relationship model diagram defining the database looks like this:




Figure 5: the bookstore entity relationship model

Using a mapping table for the M:N relationship of Author and Book, the database contains three tables: Author, Book and Author_Book. The JPA annotated classes for these entities are defined as following:

```

1 @Entity
2 @Table(name = "Book")
3 public class Book {
4
5     @Id
6     @Column(name = "isbn")
7     private String isbn;
8
9     @Column(name = "title")
10    private String title;
11
12    @Column(name = "genre")
13    private String genre;
  
```

```
14
15     @Lob
16     @Column(name = "summary")
17     private String summary;
18
19     @ManyToMany(mappedBy = "books", cascade = {
20         CascadeType.MERGE,
21         CascadeType.DETACH,
22         CascadeType.PERSIST,
23         CascadeType.REFRESH
24     })
25     private Set<Author> authors;
26
27     //getters & setters ...
28 }
```

Listing 4: Book.java

```
1 @Entity
2 @Table(name = "Author")
3 public class Author {
4
5     @Id
6     @GeneratedValue(strategy = GenerationType.AUTO)
7     @Column(name = "authorId")
8     private Long authorId;
9
10    @Column(name = "firstName")
11    private String firstName;
12
13    @Column(name = "lastName")
14    private String lastName;
15
16    @Column(name = "country")
17    private String country;
18
19    @ManyToMany(cascade = {
20        CascadeType.MERGE,
21        CascadeType.DETACH,
22        CascadeType.PERSIST,
23        CascadeType.REFRESH
24    })
25    @JoinTable(name = "Author_Book",
26        joinColumns =
27            @JoinColumn(name = "authorFk",
28                referencedColumnName = "authorId"),
29        inverseJoinColumns =
30            @JoinColumn(name = "bookFk",
31                referencedColumnName = "isbn"))
```

```

32     private Set<Book> books;
33
34     //getters & setters ...
35 }

```

Listing 5: Author.java

For the sake of simplicity and since every JPA provider is able to derive a default DDL script from the annotations, we don't supply any information about how to create the schema here. However, for real world applications defining a hand-written DDL script might be a better idea since the generated code might not be optimal and differs between the different JPA implementations and RDBMSs used.

3.2 Indexing & searching

Hibernate Search's engine wasn't designed to be used directly by application developers. Its main purpose is to serve as an integration point for other APIs that need to leverage its power to index object graphs and query the index for hits. This is why we have to write our own standalone module based on the "hibernate-search-engine" to ease its general usage. After the standalone is finished, we will build an integration of it with JPA to have a user experience as similar to Hibernate Search ORM as possible. By incorporating the same engine that the original does, we will support the same indexing behaviour and even stay compatible with entities designed for the original.




Figure 6: Complete Architecture of Hibernate Search GenericJPA

3.3 Automatic index updating

The most important feature to be re-built, is automatic index updating. In Hibernate Search ORM, every change in the database is automatically reflected in the index. It is important to have this feature, because otherwise developers would have to manually make sure the index is always up-to-date. With bigger project sizes it gets increasingly harder to keep track of all the locations in the code that change index relevant data and inconsistencies in the indexing logic become nearly unavoidable. While this problem might be mitigated by hiding all the database access logic behind a service layer, even such a solution would be hard to keep error-free as for big applications this layer will probably have multiple critical indexing relevant spots as well.

The original Hibernate Search ORM is achieving an up-to-date index by listening to specific Hibernate ORM events for all of the C_UD (CREATE, UPDATE DELETE) actions. These events also cover entity relationship collections (for example represented by mapping tables like Author_Book). As our goal is to create a generic Hibernate Search engine that works with any JPA implementation, we cannot rely on any vendor specific event system. Thus, a generic solution has to be found.

4 Building a JPA integration on top of Hibernate Search

In this section we will start by discussing how Hibernate Search's engine (in the form of the module "hibernate-search-engine") can be used in general. Then we will work out a standalone version of this engine that is easier to work with and lastly we will show how we integrate this standalone version with JPA.

4.1 Setting up the example project

Before we explain how we do things in particular, we set up the example entities described in 3.1 as if the original Hibernate Search would have been used. We do so by adding additional annotations to our entity-classes:

1. **@Indexed**: marks the entity as an index root-type.
2. **@DocumentId**: marks the field as the id of this entity. this is only needed if no JPA @Id can be found, but can be used to override settings.
3. **@Field**: describes how the annotated field should be indexed. The fieldname defaults to the property name.
4. **@IndexedEmbedded**: marks properties that point to other classes which should be included in the index. By default, all fields contained in these entities are prefixed with the property name this is placed on.
5. **@ContainedIn**: used in entities that are embedded in other indexes. this is set on the properties that point back to the index-owning entity.

The resulting entities look like this:

```
1 @Entity
2 @Table(name = "Book")
3 @Indexed
4 public class Book {
5
6     @Id
7     @Column(name = "isbn")
8     @DocumentId
9     private String isbn;
10
11     @Column(name = "title")
12     @Field(store = Store.YES, index = Index.YES)
13     private String title;
14 }
```

```

15     @Column(name = "genre")
16     @Field(store = Store.YES, index = Index.YES)
17     private String genre;
18
19     @Lob
20     @Column(name = "summary")
21     @Field(store = Store.NO, index = Index.YES)
22     private String summary;
23
24     @ManyToMany(mappedBy = "books", cascade = {
25         CascadeType.MERGE,
26         CascadeType.DETACH,
27         CascadeType.PERSIST,
28         CascadeType.REFRESH
29     })
30     @IndexedEmbedded(includeEmbeddedObjectId = true)
31     private Set<Author> authors;
32
33     //getters & setters ...
34 }

```

Listing 6: Book.java with Hibernate Search annotations

```

1  @Entity
2  @Table(name = "Author")
3  public class Author {
4
5      @Id
6      @GeneratedValue(strategy = GenerationType.AUTO)
7      @Column(name = "authorId")
8      @DocumentId
9      private Long authorId;
10
11     @Column(name = "firstName")
12     @Field(store = Store.YES, index = Index.YES)
13     private String firstName;
14
15     @Column(name = "lastName")
16     @Field(store = Store.YES, index = Index.YES)
17     private String lastName;
18
19     @Column(name = "country")
20     @Field(store = Store.YES, index = Index.YES)
21     private String country;
22
23     @ManyToMany(cascade = {
24         CascadeType.MERGE,
25         CascadeType.DETACH,
26         CascadeType.PERSIST,

```

```
27         CascadeType.REFRESH
28     })
29     @JoinTable(name = "Author_Book",
30         joinColumns =
31             @JoinColumn(name = "authorFk",
32                 referencedColumnName = "authorId"),
33         inverseJoinColumns =
34             @JoinColumn(name = "bookFk",
35                 referencedColumnName = "isbn"))
36     @ContainedIn
37     private Set<Book> books;
38
39     //getters & setters ...
40 }
```

Listing 7: Author.java with Hibernate Search annotations

As these annotations are defined in `hibernate-search-engine`, we can rely on all of them while designing the standalone version of Hibernate Search and all other modules depending on it.

4.2 Using Hibernate Search's engine

As already described earlier (3.2), hibernate-search-engine is not intended to be used by application developers, but for other APIs to integrate with. Therefore there is no real public documentation available on how to use it and all following information had to be retrieved from tests in the hibernate-search-engine and hibernate-search-orm integration module source code.

4.2.1 Starting the engine

A Hibernate Search engine instance is represented by a **SearchIntegrator**. In order to obtain it, we first have to write a special configuration class that implements **org.hibernate.search.cfg.spi.SearchConfiguration**. An object of this class has then to be created and filled with all the configuration properties Hibernate Search requires. The minimum that has to be set for this to work map are the following properties:

1. **hibernate.search.default.directory_provider**: The two most common cases here are either "ram" or "filesystem". This decides where the index will be stored. A ram directory is only present in the system memory while the SearchIntegrator exists. A "filesystem" directory is persisted on the hard disk. For "filesystem" the additional property "hibernate.search.default.indexBase" has to be set to an appropriate path.
2. **hibernate.search.lucene_version**: This decides which Lucene version has to be used internally. The currently latest supported version is "4.10.4".

A complete list of the available settings can be found in the Hibernate Search documentation²⁶ (only some Hibernate ORM specific settings cannot be used). Our **StandaloneSearchConfiguration** (appendix listing 32) defaults to "ram" and "4.10.4".

Having this class in place, a **SearchIntegrator** can be obtained by a **SearchIntegratorBuilder** like this:

```

1 List<Class<?>> indexClasses = Arrays.asList(Book.class, Author.class);
2
3 SearchConfiguration searchConfiguration =
4     new StandaloneSearchConfiguration();
5 indexClasses.forEach( searchConfiguration::addClass );
6
7 //bootstrapping class for Hibernate Search
8 SearchIntegratorBuilder builder = new SearchIntegratorBuilder();

```

²⁶Hibernate Search documentation, see [3]

```
9
10 //we have to build an integrator here (the builder needs a
11 // "base integrator" first before we can add index classes)
12 builder.configuration( searchConfiguration ).buildSearchIntegrator();
13
14 indexClasses.forEach( builder::addClass );
15
16 //starts the engine with all configuration properties set
17 SearchIntegrator searchIntegrator = builder.buildSearchIntegrator();
18
19 //use the integrator ...
20
21 //close it
22 searchIntegrator.close();
```

Listing 8: Starting up the engine

4.2.2 Indexing, updating and deleting objects from the index

Now that we know how a `SearchIntegrator` can be built, we can take a look at how we can control the index using the engine's features.

The engine does a lot of optimizations in the backend. This is the reason the specifics are hidden behind a **Worker** pattern. Such a worker batches operations by synchronizing upon the `org.hibernate.search.backend.TransactionContext` interface. Our implementation of this is simply called **Transaction** (appendix listing 31). The different index operations are represented by **Work** objects that contain the `WorkType` (INDEX, UPDATE, PURGE, etc.) and all necessary data to execute the individual task.

Indexing objects with **WorkType.INDEX**:

```
1 Book book = ...;
2 Transaction tx = new Transaction();
3 Worker worker = searchIntegrator.getWorker();
4 worker.performWork( new Work( book, WorkType.INDEX ), tx );
5 tx.commit();
```

Listing 9: Indexing an object with the engine

Updating objects with **WorkType.UPDATE**:

```
1 Book book = ...;
2 Transaction tx = new Transaction();
3 Worker worker = searchIntegrator.getWorker();
```

```

4 worker.performWork( new Work( book, WorkType.UPDATE ), tx );
5 tx.commit();

```

Listing 10: Updating an object with the engine

Deleting objects with **WorkType.PURGE**:

```

1 String isbn = ...;
2 Transaction tx = new Transaction();
3 Worker worker = searchIntegrator.getWorker();
4 worker.performWork( new Work( Book.class, isbn, WorkType.PURGE ), tx );
5 tx.commit();

```

Listing 11: Deleting an object by id with the engine

This API doesn't have any "convenience" methods that wrap around the Transaction management if no batching is needed, nor does it have any wrapper utility for the Work object generation.

4.2.3 Querying the index

Querying the index is already acceptable to some extent when it comes to building the actual query. This is mainly due to the fact the query class **HSQuery** supports method chaining and that the same query builder DSL used in Hibernate Search ORM is available (the Builder returns a Lucene query. Any basic Lucene query could be used as well, but if these are used the Analyzers have to be manually used. The Query from the builder has that already integrated).

```

1 SearchIntegrator searchIntegrator = ...;
2
3 HSQuery query = searchIntegrator.createHSQuery();
4
5 //find information about all the entities matching a given title
6 List<EntityInfo> entityInfos =
7     query.luceneQuery(
8         //query DSL:
9         searchIntegrator.buildQueryBuilder()
10             .forEntity( Book.class )
11             .get()
12             .keyword()
13             .onField( "title" )
14             .matching( "searchString" )
15             .createQuery()
16     ).targetedEntities(

```

```
17         Collections.singletonList(  
18             Book.class  
19         )  
20     ).projection(  
21         ProjectionConstants.ID  
22     ).queryEntityInfos();
```

Listing 12: Querying the index with the engine

However, the queries don't return anything resembling the original Java objects, as this depends on what we project in the `projection(...)` call and is wrapped in an **EntityInfo** object. In the example above we only return the ids of the Books matching our query. We do this because when using a search index, we don't generally want to work with the actual data found in the index after the hits have been found. We want objects retrieved from the database.

```
1  //a JPA EntityManager  
2  EntityManager em = ...;  
3  
4  //extract info from the entityInfos  
5  for(EntityInfo entityInfo : entityInfos) {  
6      String isbn = (String) entityInfo.getProjection()[0];  
7      //retrieve an object from the database  
8      Book book = em.find(Book.class, isbn);  
9      //handle this information ...  
10 }
```

Listing 13: Extracting info from the results

4.3 Standalone version of Hibernate Search

In 4.2 we described how the engine can be used natively without any notion of JPA. While using the engine this way is possible, it is not feasible because some of the code is quite complicated. This is the reason, we will now discuss a standalone abstraction of this code.

As we have seen in the examples earlier, the main class used for index control and querying are **SearchIntegrator** and **HSQuery**. In order to abstract some of the complicated logic, we now introduce two new interfaces:

- **StandaloneSearchFactory**: This interface is responsible for all index changes. Code using this abstraction doesn't have to cope with the Worker pattern, at all. This is hidden behind index/delete/update methods.
- **HSearchQuery**: While still having the same chaining methods as **HSQuery**, we retrieve results from the index in a different manner now. Instead of manually having to extract the ID out of the **EntityInfos**, this interface retrieves the actual data needed by the calling code with the help of the **EntityProvider** interface which wraps the access to the database. The specifics of the **EntityProvider** are still use-case specific as the examples later in this chapter will show.

The following diagram shows the rough architecture of our new standalone. Note that we are using a specialization of **SearchIntegrator** - namely **ExtendedSearchIntegrator** - which allows us to have more sophisticated features.




Figure 7: Rough architecture of the standalone (important parts)

4.3.1 Starting the standalone

The startup process of the standalone doesn't differ much from manually using the engine in terms of configuration as we still have to use the `SearchConfiguration` interface. The only different thing is how we build the `StandaloneSearchFactory`. This is done with a **`StandaloneSearchFactoryFactory`**, so the code using it doesn't have to handle the creation of an the actual implementation object.

```
1 List<Class<?>> indexClasses = Arrays.asList(Book.class, Author.class);
2
3 SearchConfiguration searchConfiguration =
4     new StandaloneSearchConfiguration();
5 indexClasses.forEach( searchConfiguration::addClass );
6
7 StandaloneSearchFactory searchFactory =
8     StandaloneSearchFactoryFactory.
9         createSearchFactory(
10             searchConfiguration,
11             indexClasses
12         );
13
14 //use the searchfactory ...
15
16 //close it
17 searchFactory.close();
```

Listing 14: Starting up the standalone

4.3.2 Indexing, updating and deleting objects from the index

With our standalone version, basic index control becomes more streamlined as we don't have to work with `SearchIntegrator`'s `Worker` pattern anymore.

```
1 Book book = ...;
2 Transaction tx = new Transaction();
3 searchFactory.index(book, tx);
4 tx.commit();
```

Listing 15: Indexing an object with the standalone

```
1 Book book = ...;
2 Transaction tx = new Transaction();
3 searchFactory.update(book, tx);
4 tx.commit();
```

Listing 16: Updating an object with the standalone

```
1 Transaction tx = new Transaction();
2 String isbn = ...;
3 searchFactory.delete(Book.class, isbn, tx);
4 tx.commit();
```

Listing 17: Deleting an object by id with the standalone

4.3.3 Querying the index

The biggest change in the standalone version is probably how the index is queried. We don't have to work with EntityInfos anymore as we introduce the **EntityProvider** interface. This interface hosts one method that is to be used for batch fetching (Fetch.BATCH) and one for single fetching (FETCH.FIND_BY_ID).

A good default implementation delegating the database access to a JPA EntityManager is our **BasicEntityProvider** (33). Besides taking a EntityManager in its constructor, the class also needs a Map<Class<?>, String> containing the id properties of the entities. While we leave the construction of this map out in the following example for the sake of simplicity, the code for this can be found in the listings (34). After its creation this map can then be stored in a central place and be reused.

```
1 StandaloneSearchFactory searchFactory = ...;
2
3 EntityManager em = ...;
4 Map<Class<?>, String> idProperties = ...;
5
6 EntityProvider entityProvider = new BasicEntityProvider(em, idProperties);
7
8 List<Book> = searchFactory.createQuery(searchFactory.buildQueryBuilder()
9                                     .forEntity(Book.class)
10                                    .get()
11                                    .keyword()
12                                    .onField("title")
13                                    .matching("searchString")
14                                    .createQuery(), Book.class
15                                ).query(
16                                entityProvider,
17                                Fetch.BATCH
18                                );
```

Listing 18: Querying the index with the standalone

4.4 Standalone integration with JPA interfaces

After simplifying the access to Hibernate Search's engine we will work out an integration with JPA interfaces next. Since we started with the premise of not wanting to "reinvent the wheel" by writing everything from scratch - which was one of the reasons why we chose to use Hibernate Search's engine in the first place - we will try to build an integration as similar to the JPA interfaces of Hibernate Search ORM as possible.

Before we can go into detail about how we build our integration, we have to discuss the general architecture first. We will go over how the Hibernate Search ORM integration with JPA interfaces behaves from a user point and then take a look at what has to be changed in order to be compatible with any JPA implementor.

4.4.1 Architecture of Hibernate Search ORM

Hibernate Search ORM integrates with the JPA API by extending the interfaces `javax.persistence.EntityManager` and `javax.persistence.Query` and adding new functionality to the fulltext search versions of these interfaces: **FullTextEntityManager** and **FullTextQuery**. The following figure shows a rough overview of this. Note that this only contains only the methods relevant for the following inspections.




Figure 8: The main JPA interfaces of Hibernate Search ORM

4.4.1.1 Starting As Hibernate Search ORM is tightly coupled with Hibernate ORM it is automatically started if found on the classpath and the persistence.xml contains the following:

```

1 ...
2 <property name="hibernate.search.default.directory_provider"
3 value="filesystem"/>
4 <property name="hibernate.search.default.indexBase"
5 value="/path/to/indexes"/>

```

6 ...

Listing 19: Additions to persistence.xml with Hibernate Search ORM

This means that there exists no real code entry point as Hibernate Search is fully integrated into the Hibernate ORM/OGM lifecycle. FullTextEntityManagers can therefore be obtained with:

```
1 EntityManager em = ...;
2 FullTextEntityManager fem = Search.getFullTextEntityManager(em);
```

Listing 20: Obtaining a FullTextEntityManager with Hibernate Search ORM

All of FullTextEntityManager's operations are controlled by the same transactions the original Hibernate EntityManager is using. This is the reason we will not have any search Transaction related code in the following paragraphs.

4.4.1.2 Indexing, updating and deleting objects from the index The index operations are all straightforward and are similar to what we designed our Standalone integration in 4.3 to work like apart from minor naming differences.

Hibernate Search ORM doesn't differentiate between indexing and updating.

```
1 FullTextEntityManager fem = ...;
2 Book book = ...;
3 fem.index(book);
```

Listing 21: Indexing/Updating an object with Hibernate Search ORM

Deleting objects from the index is called purging. This is probably due to not wanting to confuse it with JPA's delete(...).

```
1 FullTextEntityManager fem = ...;
2 String isbn = ...;
3 fem.purge(Book.class, isbn);
```

Listing 22: Deleting an object by id with Hibernate Search ORM

4.4.1.3 Querying the index Hibernate Search ORM integrates even better with JPA for queries than our Standalone version as the FullTextQuery interfaces extends the JPA Query interface and uses getResultList() to return its results.

```
1 EntityManager em = ...;
2 FullTextEntityManager fem = Search.getFullTextEntityManager(em);
```

```
3
4 FullTextQuery fullTextQuery = fem.createFullTextQuery (
5     searchFactory.buildQueryBuilder ()
6         .forEntity (Book.class)
7         .get ()
8         .keyword ()
9         .onField ("title")
10        .matching ("searchString")
11        .createQuery () ,
12    Book.class );
13
14 List<Book> books = (List<Book>) fullTextQuery.getResultList ();
```

Listing 23: Querying with Hibernate Search ORM

4.4.1.4 Index rebuilds A noteworthy feature of Hibernate Search is its `MassIndexer`. It can be used whenever the way the entities are indexed is changed (e.g. in the `@Field` annotations). It uses multiple threads working in parallel to scroll results from the database and then indexes these efficiently. This is by far faster than the naive approach working in only one thread. It also incorporates a lot of internal improvements a normal developer wouldn't have access to as the specifics are hidden in the implementation packages of Hibernate Search which are not intended to be used outside of its own code.

A full index rebuild for our `Book` entity would look like this:

```
1 EntityManager em = ...;
2 FullTextEntityManager fem = Search.getFullTextEntityManager(em);
3
4 fem.createIndexer( Book.class )
5     .batchSizeToLoadObjects( 25 )
6     .threadsToLoadObjects( 12 )
7     .idFetchSize( 150 )
8     .transactionTimeout( 1800 )
9     .startAndWait ();
```

Listing 24: `MassIndexer` usage with Hibernate Search ORM

"This will rebuild the index of all `[Book]` instances (and subtypes), and will create 12 parallel threads to load the `User` instances using batches of 25 objects per query; these same 12 threads will also need to process indexed embedded relations and custom `FieldBridges` or `ClassBridges`, to finally output a Lucene document."²⁷

²⁷Hibernate Search documentation (`MassIndexer`, v5.4), see [4]

4.4.2 Architecture of the generic version

As good as Hibernate Search ORM's API integration with JPA's EntityManager and Query interface is, its additional interfaces still contain some Hibernate ORM related features and logic that a generic version (we call it Hibernate Search GenericJPA) can not support and therefore have to be changed, emulated or removed all together.




Figure 9: Required fixes for a generic version

In the figure above, we marked all the methods needing fixing in the FullTextEntityManager and FullTextQuery interfaces. Besides these, some other aspects need changing as well. We will discuss all of the needed changes & additions in the following paragraphs.

4.4.2.1 Starting In our generic version we can't tightly integrate with the EntityManagerFactory of the JPA provider. This is the reason we introduce a separate interface called **JPAsearchFactoryController**.




Figure 10: JPAsearchFactoryController

Having this separate interface means that its lifecycle has to be controlled on its own. We start it with our bootstrapping class **Setup** like this:

```

1 EntityManagerFactory emf = ...;
2 Properties properties = new Properties();

```

```

3
4 properties.setProperty(
5     "hibernate.search.searchfactory.type",
6     "manual-updates"
7 );
8
9 JPASearchFactoryController searchFactoryController =
10     Setup.createSearchFactoryController( emf, properties );
11
12 //use it...
13
14 searchFactoryController.close();

```

Listing 25: MassIndexer usage with Hibernate Search ORM

For this example we are using "manual-updates", as we haven't discussed how the index is kept up-to-date. After we worked that out, "manual-updates" will just be a fallback setting for developers not wanting to have the index automatically updated. Also note that there are many more properties that can be set and vanilla Hibernate Search settings are passed this way as well. A complete list of the available generic jpa configuration properties can be found in table 1 in the appendix.

Unlike the static way a `FullTextEntityManager` is obtained in Hibernate Search ORM via the `Search` class, in our generic version, we obtain it with the **`getFullTextEntityManager(EntityManager entityManager)`** method. This means that an instance of the `JPASearchFactoryController` has to be available at all times access to the index is required.

Using a non-static approach here has one benefit, though: We can pass null to this method and get a search only `FullTextEntityManager` that can be used to work on the index when no database access is needed. This is particularly useful if we want to index POJOs which are not associated with JPA (see table 1 for the property to work with these additional entities).

4.4.2.2 Indexing, updating and deleting objects from the index In Hibernate Search ORM, all manual index manipulation is synchronized with the `EntityManager` transaction lifecycle. In our generic approach we cannot do this as JPA doesn't have an extension point for this kind of usage. This is the reason we introduce the **`[begin/-commit/rollback]SearchTransaction()`** methods in `FullTextEntityManager`. These have to be used to control the transaction lifecycle of all the index manipulation methods.

```

1 EntityManager em = ...;

```



```

2 JPASearchFactoryController searchFactoryController = ...;
3
4 FullTextEntityManager fem =
5     searchFactoryController.getFullTextEntityManager(em);
6
7 fem.beginSearchTransaction();
8 try {
9     //index or purge here
10    fem.commitSearchTransaction();
11 } catch (Exception e) {
12    fem.rollbackSearchTransaction();
13    throw e;
14 }

```

Listing 26: Index control with Hibernate Search GenericJPA

One additional problem with supporting indexing generic JPA entities is that some JPA providers don't return objects of the original entity class. For example, EclipseLink returns an object of an anonymous subclass of the original in which it hides away some utility logic needed for lazy loading, etc.. But the engine needs to know which class to get the index description metamodel from.

This is the reason in Hibernate Search GenericJPA we implement logic to feed the right entity class into the engine via user input. Entity classes have to be marked with **@InIndex** on the type level so we can start from any object's class and then go up in the class hierarchy until we find one that is annotated with this annotation.

```

1 // get the first class in the hierarchy that is actually in the index
2 Class<T> clazz = (Class<T>) entity.getClass();
3 while ( (clazz = (Class<T>) clazz.getSuperclass()) != null ) {
4     if ( clazz.isAnnotationPresent( InIndex.class ) ) {
5         break;
6     }
7 }
8 if ( clazz != null ) {
9     return clazz;
10 }
11 //no @InIndex found, try this class
12 return entity.getClass();

```

Listing 27: Algorithm to determine the actual indexed type

Note that this has to be done for every entity that is part of the index, even the ones that are just embedded. With this in mind our entities Book and Author now look like this:

```
1 @Entity
2 @InIndex
3 @Table(name = "Book")
4 public class Book {
5
6     //rest is unchanged
7
8 }
```

Listing 28: Book.java with @InIndex

```
1 @Entity
2 @InIndex
3 @Table(name = "Author")
4 public class Author {
5
6     //rest is unchanged
7
8 }
```

Listing 29: Author.java with @InIndex

4.4.2.3 Querying the index While we didn't mention this in 4.4.1.3, Hibernate Search ORM supports modifying the resulting objects of a query with these two methods:

- **setCriteriaQuery(Criteria criteria)**: This method lets the user define a custom Hibernate Criteria query (no JPA criteria query) that has to be used to retrieve the results from the database. This can be used to make sure all necessary data is loaded after it is returned by `getResultList()`. These custom queries are particularly in cases where no session is available when the data is actually used: If the data is requested, an error would occur.
- **setResultTransformer(ResultTransformer resultTransformer)**: A ResultTransformer can be used to transform the results (useful for projections) into POJOs (Plain Old Java Object).

There is a problem with these two methods, though. They are using the Hibernate ORM API to accomplish their behaviour, and therefore we cannot support them.

By adding a new method **entityProvider(EntityProvider entityProvider)** with the same EntityProvider interface as in 4.3.3 to the method, we can at least support custom queries.

As the main use case scenario for the ResultTransformer is probably just the transformation from a projection of the queried documents to a POJO, we just completely remove this feature. In the future, we can add such a feature back to the generic version, if needed. But as this method cannot be kept as-is anyways, Hibernate Search ORM developers wanting to use Hibernate Search GenericJPA that use this feature have to change some of their code either way.

4.4.2.4 Index rebuilds The MassIndexer utility is a really important feature of Hibernate Search ORM. As it uses Hibernate ORM logic under the hood (and in its interface), we have to write our own version of it. We don't build a API compatible version for Hibernate Search GenericJPA as the MassIndexer will not be used in that many places in the code anyways. Additionally this way we can give different configuration properties for better performance as our approach differs in some implementation details.

The basic ideas are the same though: Each entity type has its ids scrolled from the database by one thread (there can be multiple threads doing this, but for other entities) and then a configurable amount of indexing threads handles these ids batch by batch in a Hibernate Search index-writing backend optimized for this task (this is part of Hibernate Search's engine and therefore can be reused).

In Hibernate Search GenericJPA our Book entities are massindexed like this:

```
1 EntityManager em = ...;
2 FullTextEntityManager fem = Search.getFullTextEntityManager(em);
3
4 fem.createIndexer( Book.class )
5     .batchSizeToLoadObjects( 25 )
6     .threadsToLoadObjects( 12 )
7     .batchSizeToLoadIds( 150 )
8     .idProducerTransactionTimeout( 1800 )
9     .startAndWait();
```

Listing 30: MassIndexer usage with Hibernate Search ORM

4.5 The automatic index updating feature

4.5.1 Overview of possible implementations

4.5.1.1 Synchronous approaches

JPA events

Native integrations with JPA providers

4.5.1.2 Asynchronous approaches

Triggers `includeEmbeddedObjectId = true` ist Pflicht!

4.5.2 Native event integration with JPA providers

4.5.3 Generic approach

References

- [1] Wikipedia https://en.wikipedia.org/wiki/Java_Persistence_API, 07/16/2015
- [2] Hibernate Search project homepage <http://hibernate.org/search/>, 07/26/2015
- [3] Hibernate Search documentation <http://hibernate.org/search/documentation/>, 07/31/2015
- [4] Hibernate Search documentation (MassIndexer, v5.4) https://docs.jboss.org/hibernate/search/5.4/reference/en-US/html_single/#search-batchindex-massindexer, 08/05/2015
- [5] Elasticsearch Java API [<https://www.elastic.co/guide/en/elasticsearch/client/java-api/current/index.html>], 07/27/2015
- [6] Solr Java API <https://wiki.apache.org/solr/Solrj>, 07/27/2015
- [7] Wikipedia on Object Oriented Programming (OOP) https://en.wikipedia.org/wiki/Object-oriented_programming, 07/27/2015
- [8] Wikibooks on Java Persistence https://en.wikibooks.org/wiki/Java_Persistence/What_is_JPA%3F, 07/27/2015
- [9] Hibernate OGM project homepage <http://hibernate.org/ogm/>, 07/27/2015
- [10] Hibernate ORM project homepage <http://hibernate.org/orm/>, 07/27/2015
- [11] OpenJPA project homepage <http://openjpa.apache.org/>, 07/27/2015
- [12] w3schools on SQL LIKE http://www.w3schools.com/sql/sql_like.asp, 07/27/2015
- [13] EclipseLink project homepage <http://www.eclipse.org/eclipselink/>, 07/27/2015
- [14] Hibernate Search GitHub repository <https://github.com/hibernate/hibernate-search>, 07/26/2015
- [15] Oracle JDBC overview <http://www.oracle.com/technetwork/java/javase/jdbc/index.html>, 07/27/2015
- [16] Documentation on how to use OleDb with .NET [https://msdn.microsoft.com/en-us/library/5ybdbtte\(v=vs.71\).aspx](https://msdn.microsoft.com/en-us/library/5ybdbtte(v=vs.71).aspx), 07/27/2015
- [17] xkcd #927 on competing standards <https://xkcd.com/927/>, 07/26/2015
- [18] Java Platform, Enterprise Edition Wikipedia https://en.wikipedia.org/wiki/Java_Platform,_Enterprise_Edition, 07/16/2015
- [19] Lucene Website <https://lucene.apache.org/core/>, 07/16/2015
- [20] Lucene Tutorial <http://www.lucenetutorial.com/basic-concepts.html>, 07/20/2015

Listings

```
1 public class Transaction implements TransactionContext {
2
3     private boolean progress = true;
4     private List<Synchronization> syncs = new ArrayList<>();
5
6     @Override
7     public boolean isTransactionInProgress() {
8         return this.progress;
9     }
10
11    @Override
12    public Object getTransactionIdentifier() {
13        return this;
14    }
15
16    @Override
17    public void registerSynchronization(
18        Synchronization synchronization ) {
19        this.syncs.add( synchronization );
20    }
21
22    /**
23     * @throws IllegalStateException if already committed/rolledback
24     */
25    public void commit() {
26        if ( !this.progress ) {
27            throw new IllegalStateException(
28                "can't commit - " +
29                "No Search Transaction is in Progress!" );
30        }
31        this.progress = false;
32        this.syncs.forEach( Synchronization::beforeCompletion );
33
34        for ( Synchronization sync : this.syncs ) {
35            sync.afterCompletion( Status.STATUS_COMMITTED );
36        }
37    }
38
39    /**
40     * @throws IllegalStateException if already committed/rolledback
41     */
42    public void rollback() {
43        if ( !this.progress ) {
44            throw new IllegalStateException(
45                "can't rollback - " +
46                "No Search Transaction is in Progress!" );
```

```

47         }
48         this.progress = false;
49         this.syncs.forEach( Synchronization::beforeCompletion );
50
51         for ( Synchronization sync : this.syncs ) {
52             sync.afterCompletion( Status.STATUS_ROLLEDBACK );
53         }
54     }
55
56 }

```

Listing 31: the simple Transaction contract

```

1  /**
2   * Manually defines the configuration.
3   * Classes and properties are the only implemented options at the moment.
4   *
5   * @author Martin Braun (adaption), Emmanuel Bernard
6   */
7  public class StandaloneSearchConfiguration
8      extends SearchConfigurationBase
9      implements SearchConfiguration {
10
11      private final Logger LOGGER =
12          Logger.getLogger(
13              StandaloneSearchConfiguration.class.getName()
14          );
15
16      private final Map<String, Class<?>> classes;
17      private final Properties properties;
18      private final HashMap<Class<? extends Service>, Object>
19          providedServices;
20      private final InstanceInitializer initializer;
21      private SearchMapping programmaticMapping;
22      private boolean transactionsExpected = true;
23      private boolean indexMetadataComplete = true;
24      private boolean idProvidedImplicit = false;
25      private ClassLoaderService classLoaderService;
26      private ReflectionManager reflectionManager;
27
28      public StandaloneSearchConfiguration() {
29          this( new Properties() );
30      }
31
32      public StandaloneSearchConfiguration(Properties properties) {
33          this(
34              SubClassSupportInstanceInitializer.INSTANCE,
35              properties
36          );

```

```

37     }
38
39     public StandaloneSearchConfiguration(InstanceInitializer init) {
40         this( new Properties() );
41     }
42
43     public StandaloneSearchConfiguration(InstanceInitializer init ,
44         Properties properties) {
45         this.initializer = init;
46         this.classes = new HashMap<>();
47         this.properties = properties;
48         // default values if nothing was explicitly set
49         this.properties.computeIfAbsent(
50             "hibernate.search.default.directory_provider",
51             (key) -> {
52                 LOGGER.info(
53                     "defaulting to RAM directory-provider"
54                 );
55                 return "ram";
56             });
57         this.properties.computeIfAbsent(
58             "hibernate.search.lucene_version",
59             (key) -> {
60                 LOGGER.info(
61                     "defaulting to Lucene Version: "
62                     + Version.LUCENE_4_10_4.toString()
63                 );
64                 return Version.LUCENE_4_10_4.toString();
65             });
66         this.reflectionManager = new JavaReflectionManager();
67         this.providedServices = new HashMap<>();
68         this.classLoaderService = new DefaultClassLoaderService();
69     }
70
71     public StandaloneSearchConfiguration addProperty(String key ,
72         String value) {
73         properties.setProperty( key , value );
74         return this;
75     }
76
77     public StandaloneSearchConfiguration addClass(Class<?> indexed) {
78         classes.put( indexed.getName(), indexed );
79         return this;
80     }
81
82     @Override
83     public Iterator<Class<?>> getClassMappings() {
84         return classes.values().iterator();

```



```
85     }
86
87     @Override
88     public Class<?> getClassMapping(String name) {
89         return classes.get( name );
90     }
91
92     @Override
93     public String getProperty(String propertyName) {
94         return properties.getProperty( propertyName );
95     }
96
97     @Override
98     public Properties getProperties() {
99         return properties;
100    }
101
102    @Override
103    public ReflectionManager getReflectionManager() {
104        return this.reflectionManager;
105    }
106
107    @Override
108    public SearchMapping getProgrammaticMapping() {
109        return programmaticMapping;
110    }
111
112    public StandaloneSearchConfiguration setProgrammaticMapping(
113        SearchMapping programmaticMapping
114    ) {
115        this.programmaticMapping = programmaticMapping;
116        return this;
117    }
118
119    @Override
120    public Map<Class<? extends Service>, Object>
121        getProvidedServices() {
122        return providedServices;
123    }
124
125    public void addProvidedService(
126        Class<? extends Service> serviceRole ,
127        Object service
128    ) {
129        providedServices.put( serviceRole , service );
130    }
131
132    @Override
```

```
133     public boolean isTransactionManagerExpected() {
134         return this.transactionsExpected;
135     }
136
137     public void setTransactionsExpected(
138         boolean transactionsExpected) {
139         this.transactionsExpected = transactionsExpected;
140     }
141
142     @Override
143     public InstanceInitializer getInstanceInitializer() {
144         return initializer;
145     }
146
147     @Override
148     public boolean isIndexMetadataComplete() {
149         return indexMetadataComplete;
150     }
151
152     public void setIndexMetadataComplete(
153         boolean indexMetadataComplete) {
154         this.indexMetadataComplete = indexMetadataComplete;
155     }
156
157     @Override
158     public boolean isIdProvidedImplicit() {
159         return idProvidedImplicit;
160     }
161
162     public StandaloneSearchConfiguration
163         setIdProvidedImplicit(boolean idProvidedImplicit) {
164         this.idProvidedImplicit = idProvidedImplicit;
165         return this;
166     }
167
168     @Override
169     public ClassLoaderService getClassLoaderService() {
170         return classLoaderService;
171     }
172
173     public void setClassLoaderService(
174         ClassLoaderService ) {
175         this.classLoaderService = classLoaderService;
176     }
177
178 }
```

Listing 32: StandaloneSearchConfiguration.java

```
1 public class BasicEntityProvider implements EntityProvider {
2
3     private static final String QUERY_FORMAT =
4         "SELECT obj FROM %s obj " +
5         "WHERE obj.%s IN :ids";
6     private final EntityManager em;
7     private final Map<Class<?>, String> idProperties;
8
9     public BasicEntityProvider(EntityManager em,
10        Map<Class<?>, String> idProperties) {
11         this.em = em;
12         this.idProperties = idProperties;
13     }
14
15     @Override
16     public void close() throws IOException {
17         this.em.close();
18     }
19
20     @Override
21     public Object get(Class<?> entityClass, Object id,
22        Map<String, String> hints) {
23         return this.em.find( entityClass, id );
24     }
25
26     @SuppressWarnings({"rawtypes", "unchecked"})
27     @Override
28     public List getBatch(Class<?> entityClass, List<Object> ids,
29        Map<String, String> hints) {
30         List<Object> ret = new ArrayList<>( ids.size() );
31         if ( ids.size() > 0 ) {
32             String idProperty =
33                 this.idProperties.get( entityClass );
34             String queryString =
35                 String.format(
36                     QUERY_FORMAT,
37                     this.em.getMetamodel()
38                         .entity( entityClass )
39                         .getName(),
40                     idProperty
41                 );
42             Query query = this.em.createQuery( queryString );
43             query.setParameter( "ids", ids );
44             ret.addAll( query.getResultList() );
45         }
46         return ret;
47     }
48 }
```

```

48
49     public void clearEm() {
50         this.em.clear();
51     }
52
53     public EntityManager getEm() {
54         return this.em;
55     }
56
57 }

```

Listing 33: BasicEntityProvider.java

```

1 SearchConfiguration config = ...;
2
3 MetadataProvider metadataProvider =
4     MetadataUtil.getDummyMetadataProvider( config );
5 MetadataRehasher rehasher = new MetadataRehasher();
6
7 List<RehashedTypeMetadata> rehashedTypeMetadatas = new ArrayList<>();
8 for ( Class<?> indexRootType : this.getIndexRootTypes() ) {
9     RehashedTypeMetadata rehashed =
10         rehasher.rehash(
11             metadataProvider
12                 .getTypeMetadataFor( indexRootType )
13         );
14     rehashedTypeMetadatas.add( rehashed );
15 }
16
17 Map<Class<?>, String> idProperties =
18     MetadataUtil.calculateIdProperties( rehashedTypeMetadatas );

```

Listing 34: Obtaining idProperties

```

1 /**
2  * @author Emmanuel Bernard
3  * @author Martin Braun
4  */
5 public interface FullTextEntityManager extends EntityManager {
6
7     /**
8      * Create a fulltext query on top of a native Lucene
9      * query returning the matching objects of columnTypes
10     * <code>entities</code> and their respective subclasses.
11     *
12     * @param luceneQuery The native Lucene query to be
13     *                     run against the Lucene index.
14     * @param entities List of classes for columnTypes filtering.
15     *                 The query result will only return entities

```

```

16      *           of the specified types and their respective
17      *           subtype.
18      *           If no class is specified no columnTypes filtering
19      *           will take place.
20      *
21      * @return A <code>FullTextQuery</code> wrapping around the
22      *           native Lucene query.
23      *
24      * @throws IllegalArgumentException if entityType is
25      * <code>null</code> or not a class or superclass annotated with
26      * <code>@Indexed</code>.
27      */
28      FullTextQuery createFullTextQuery(
29          org.apache.lucene.search.Query luceneQuery,
30          Class<?>... entities);
31
32      /**
33      * Force the (re)indexing of a given <b>managed</b> object.
34      * Indexation is batched per search-transaction: if a
35      * transaction is active, the operation will not affect
36      * the index at least until commit.
37      *
38      * @param entity The entity to index
39      *      - must not be <code>null</code>.
40      *
41      * @throws IllegalArgumentException
42      *      if entity is null or not an @Indexed entity
43      * @throws IllegalStateException
44      *      if no search-transaction is in progress
45      */
46      <T> void index(T entity);
47
48      /**
49      * @return the <code>SearchFactory</code> instance.
50      */
51      SearchFactory getSearchFactory();
52
53      /**
54      * Remove the entity with the columnTypes
55      * <code>entityType</code> and the identifier
56      * <code>id</code> from the index. If
57      * <code>id == null</code> all indexed entities
58      * of this columnTypes and its indexed subclasses
59      * are deleted. In this case
60      * this method behaves like {@link #purgeAll(Class)}.
61      *
62      * @param entityType The columnTypes of the
63      *      entity to delete.

```

```

64      * @param id The id of the entity to delete.
65      *
66      * @throws IllegalArgumentException if entityType is
67      * <code>null</code> or not a class or superclass
68      * annotated with <code>@Indexed</code>.
69      * @throws IllegalStateException if no
70      * search-transaction is in progress
71      */
72      <T> void purge(Class<T> entityType, Serializable id);
73
74      /**
75       * Remove all entities from of particular class
76       * and all its subclasses from the index.
77       *
78       * @param entityType The class of the entities to remove.
79       *
80       * @throws IllegalArgumentException if entityType is
81       *      <code>null</code> or not a class or superclass
82       * annotated with <code>@Indexed</code>.
83       * @throws IllegalStateException if no search-transaction
84       * is in progress
85       */
86      <T> void purgeAll(Class<T> entityType);
87
88      <T> void purgeByTerm(Class<T> entityType,
89                          String field,
90                          Integer val);
91
92      <T> void purgeByTerm(Class<T> entityType,
93                          String field,
94                          Long val);
95
96      <T> void purgeByTerm(Class<T> entityType,
97                          String field,
98                          Float val);
99
100     <T> void purgeByTerm(Class<T> entityType,
101                          String field,
102                          Double val);
103
104     <T> void purgeByTerm(Class<T> entityType,
105                          String field,
106                          String val);
107
108     /**
109      * Flush all index changes forcing Hibernate Search to apply all
110      * changes to the index not waiting for the batch limit.
111      *

```

```
112      * @throws IllegalStateException
113      *          if no search-transaction is in progress
114      */
115      void flushToIndexes();
116
117      /**
118       * <b>different from the original Hibernate Search!</b> <br>
119       * <br>
120       * this has to be called when you want to
121       * change the index manually!
122       *
123       * @throws IllegalStateException
124       *          if a search-transaction is already in progress
125       */
126      void beginSearchTransaction();
127
128      /**
129       * <b>different from the original Hibernate Search!</b> <br>
130       * <br>
131       * this has to be called when you want to
132       * change the index manually!
133       *
134       * @throws IllegalStateException
135       *          if no search-transaction is in progress
136       */
137      void rollbackSearchTransaction();
138
139      /**
140       * <b>different from the original Hibernate Search!</b> <br>
141       * <br>
142       * this has to be called when you want to
143       * change the index manually!
144       *
145       * @throws IllegalStateException
146       *          if no search-transaction is in progress
147       */
148      void commitSearchTransaction();
149
150      boolean isSearchTransactionInProgress();
151
152      /**
153       * @throws IllegalStateException
154       *          if search-transaction is still in progress.
155       *          underlying EntityManager is still closed.
156       */
157      void close();
158
159      /**
```

```
160      * Creates a MassIndexer to rebuild the indexes of some
161      * or all indexed entity types. Instances cannot be reused. Any
162      * {@link org.hibernate.search.indexes.interceptor
163      * .EntityIndexingInterceptor} registered on the entity
164      * types are applied: each instance will trigger an
165      * {@link org.hibernate.search.indexes.interceptor
166      * .EntityIndexingInterceptor#onAdd(Object)} event from where you can
167      * customize the indexing operation.
168      *
169      *
170      * @param types optionally restrict the operation to
171      * selected types
172      *
173      * @return a new MassIndexer
174      */
175      MassIndexer createIndexer(Class<?>... types);
176
177 }
```

Listing 35: generic JPA FullTextEntityManager

Tables

hibernate.search.useJTATransactions	false true
hibernate.search.searchfactory.type	sql manual-updates eclipselink hibernate openjpa
hibernate.search.trigger.batchSizeForUpdates	5
hibernate.search.trigger.batchSizeForUpdateQueries	20
hibernate.search.trigger.updateDelay	200
hibernate.search.trigger.source	<class>
hibernate.search.additionalIndexedTypes	<class>
hibernate.search.transactionManagerProvider	org.hibernate. search.generic jpa.trans action.impl JNDILookup Transaction ManagerProvider
hibernate.search.transactionManagerProvider.jndi	<jndi-string>
hibernate.search.trigger.createstrategy	create create-drop dont-create

Table 1: Basic JPASearchFactoryController configuration properties (**default**)

Eidesstattliche Erklärung

Eidesstattliche Erklärung zur <-Arbeit>

Ich versichere, die von mir vorgelegte Arbeit selbstständig verfasst zu haben. Alle Stellen, die wörtlich oder sinngemäß aus veröffentlichten oder nicht veröffentlichten Arbeiten anderer entnommen sind, habe ich als entnommen kenntlich gemacht. Sämtliche Quellen und Hilfsmittel, die ich für die Arbeit benutzt habe, sind angegeben. Die Arbeit hat mit gleichem Inhalt bzw. in wesentlichen Teilen noch keiner anderen Prüfungsbehörde vorgelegen.

Unterschrift :

Ort, Datum :

