TadusIQ demo testing guide

Use this guide to present six synthetic verification packages. Three intact packages should be accepted; three deliberately faulty packages should be quarantined. The demonstration checks file origin and integrity, and records the receiver's decision and audit events.

Prepare the demonstration

1. **Extract the ZIP.** On Windows, right-click TadusIQ_Demo_Kit.zip and choose Extract All. Open the TadusIQ_Demo_Kit folder.
2. **Open the hosted app.** Visit https://rapidready-verify.tadusiq.workers.dev/ and confirm Receiver ready. The archive contains test files and instructions; it does not start the app.
3. **Use the prepared receiver.** These files match the public demo signing key registered in the hosted demo receiver. A different receiver, needs its maintainer to independently confirm and register that public key. Uploading a package never grants trust.

Run the first valid package

1. Choose simulated **Lab B** and open **Verify package**. Select **Upload package**.
2. Click **Select package files**. From **01-valid-human**, select exactly these three files together: **01-valid-human.txt**, **manifest.json** and **signature.txt**. Do not select the ZIP or an entire folder.
3. Review the three distinct assignments: Synthetic file, Manifest and Signature. Click **Use these files**. All three should show Loaded and the summary should say Ready to submit.
4. Click **Verify package**. Expect **Accepted**, reason **VALID**, and seven passed checks. Ready to submit alone is only a local attachment check.
5. Review the recorded checks and Suggested next step. Open **View audit trail** to see this record's events. Record the verification ID if you need to identify the run later.

Keep the files intact. Preserve each payload filename, every manifest byte and the signature. Do not mix folders, reformat JSON or add whitespace. Only the three files inside a numbered folder belong in an upload.

Expected results for all six demos

Return to Verify package and load the next numbered folder using the same three-file workflow. Submit each package manually. The app displays human-readable reason labels; the codes below identify the same recorded reasons.

Folder	Decision	Reason	What it demonstrates
01-valid-human	ACCEPTED	VALID	Intact human-health TXT example.
02-valid-animal	ACCEPTED	VALID	Intact animal-health CSV example.
03-valid-environment	ACCEPTED	VALID	Intact environmental JSON example.
04-modified-file	QUARANTINED	HASH_MISMATCH	One payload byte changed after signing; size stays the same.
05-invalid-signature	QUARANTINED	INVALID_SIGNATURE	The detached signature was deliberately altered.
06-missing-metadata	QUARANTINED	INVALID_METADATA	The required synthetic sample ID is missing.

Explain the three quarantine cases

Modified file: The sender's manifest is signed, but the received file no longer matches its SHA-256 digest. Request the original file and its matching signed package.

Invalid signature: The signature does not match the manifest bytes. Obtain a matching manifest and signature from the sender.

Missing metadata: Required metadata is absent. Request a corrected, newly signed package. Do not repair the signed text in the receiver.

Show review and audit

Select simulated **Lab C** to open History. Find the newest test record and click its Inspect action. Explain the passed, failed and skipped checks, then open View audit trail. The selected view fetches events for that verification ID; Show all events returns to the latest 100-event overview. Selected audits show up to 200 events and disclose that limit when reached.

The three sector examples contain fictional development data. Lab A is the signing sender for every package; the CSV and JSON examples do not turn Labs B or C into senders.

Troubleshooting and completion

If the result differs from the guide

Unknown or revoked key or sender mismatch: Confirm you are using the prepared receiver. Ask its maintainer to check the authorized signing identity using public-key.json. This file is setup information, not an attachment to upload, and must not be trusted automatically.

A valid example is quarantined: Reload all three untouched files from the same extracted folder. Check the payload filename. Do not resave the manifest, modify line endings, or combine files from different folders. If the identity is not recognized, follow the registry check above.

Receiver unavailable or verification not confirmed: Restore the local connection, then refresh History before retrying. A request may have reached the receiver even when its response was lost. An operational error is never an accepted decision.

Package not ready or assignment error: Select exactly three files and assign a different file to each role. Review the inline message. ZIP and folder imports are excluded; extract the ZIP first.

Optional interface checks

1. **Validation notification:** With an empty draft, click Verify package. Expect a specific error pop-up and inline messages; the synthetic file input receives focus. No accepted result should be created.
2. **Duplicate assignment:** Select a full package, then assign the same file to two roles and click Use these files. Expect an error. Correct the assignments and load the package again; nothing submits automatically.
3. **Cancel preserves the draft:** Load a valid package. Start another three-file selection, then Cancel the assignment review. The previously loaded draft should remain.
4. **Theme and navigation:** With a loaded draft, change Dark mode and navigate to History and back. The draft should remain loaded. Use the pop-up close button to dismiss a notification, or focus it and press Escape.

Finish the demonstration

Confirm all six submitted cases produced the expected decisions and that a selected result has matching audit events. Note the receiver used, date, actual outcomes and verification IDs if you are recording evidence. Repeated submissions create new records; do not expect IDs or timestamps to match a previous run.

Scope: All data and roles are synthetic. Role selection is a simulation, not authentication. These checks do not establish biological validity. Quarantine is logical and the local audit is not tamper-proof. The kit contains public signing information and detached signatures, never private signing keys.