

TWINBRAIN

Mobile Brain/Body Imaging (MoBI) Workshop

TwinBrain Workshop 1.0:



Berlin Mobile Brain/Body
Imaging Labs

MoBI meets Android: Current Developments and Future Directions

Sarah Blum

Carl von Ossietzky University of Oldenburg

@Berlin Mobile Brain/Body Imaging Lab, TU Berlin, 25-27 May 2021



**UNIVERSITÉ
DE GENÈVE**



**UNIVERSITY
OF TRIESTE**



This project has received funding from
the European Union's Horizon 2020
research and innovation programme
under grant agreement No 952401



```
function training(self, target, iter, trainingSteps)

    % Get the learning rate for this iteration from the schedule,
    % treat the first 60% with first learning and so on
    if iter/trainingSteps < 0.6
        learningRate = self.learningRateSchedule(1);
    elseif iter/trainingSteps < 0.8
        learningRate = self.learningRateSchedule(2);
    else
        learningRate = self.learningRateSchedule(3);
    end

    % Forward pass
    node_output = innerFunction(self);
    % "descend" the error surface. this error can be used
    % to asses the goodness of the network, it is not used
    % for learning purposes
    % error = 0.5*((node_output - self.targets(example))^2);


    % Backward pass.
    % Create d_k
    derivative = node_output*(1-node_output);
    d_k = (derivative) .* (node_output - target);

    % Apply it -> adapt the weights to learn
    self.weights = self.weights + learningRate * (-1) * d_k
    self.bias = self.bias + learningRate * (-1) * d_k;

    %fprintf('Done training!\n');
end

function final_test(self, target)
    %fprintf('\tWeights: \t= \t%.2f\n', self.weights);
    node_output = innerFunction(self);
    % fprintf('For input = %.1f, output = %.2f (target=%i)\n'
    %     self.inputs, node_output, target);
    s = ['Input was ', num2str(self.inputs), ' output = ', num2str(node_output), ' target = ', num2str(target)];
    %fprintf(s);
end


function result = innerFunction(self)
    result = self.sigma(self.weights * self.inputs' + self.bias);
end
```





MoBI meets Android


Sarah Blum, University of Oldenburg. sarah.blum@uol.de



MoBI meets Android



Sarah Blum, University of Oldenburg. sarah.blum@uol.de

Two Topics Today




Artifacts: Signal or Noise?

- outlier
- unwanted signal
- deviant
- context specific




Types of Artifacts in EEG

– biological



– technical



Artifact Subspace Reconstruction (ASR)

- online artifact handling method
- no validation, complicated
- my adaptation: Riemannian ASR

Kothe, Mullen (2013)
Swartz Center for Computational Neuroscience, San Diego, USA
Chang (2018,2019)

ASR toolbox versus ASR algorithm


```
graph LR; A["clean_rawdata<br/>clean_artifacts<br/>clean_flatlines<br/>clean_drifts<br/>[clean_channels]<br/>clean_asr<br/>[clean_windows]"] --> B["calibration<br/>processing"]
```

clean_rawdata
clean_artifacts
clean_flatlines
clean_drifts
[clean_channels]
clean_asr
[clean_windows]

calibration
processing


Correlational Structure over Channels

- consider an eye blink
- covariance matrices
- correlational structure is very regular
- locally captured artifacts break correlation structure
- detection based on asymmetry in correlation




Correlational Structure over Time

- correlation for 2 channels x_1, x_2
- every point is a covariance matrix for one segment in time
- most points form a neighbourhood
- outliers: possible artifact



ASR: Detection of Outliers

- neighbourhood defined during training
- threshold
- for more channels: curved space



Riemannian Methods in EEG Data

- covariance matrices are symmetric positive definite matrices (SPD)
- SPD matrices form curved space
- straight line distance is imprecise
- → ASR might not detect some data points as artifacts!




Figure adapted from Yger et al., 2015

Results: Cap-EEG Sensitivity






Figure adapted from Blum et al., 2019

Results: Cap-EEG Specificity








Figure adapted from Blum et al., 2010

Movement Artifact: ASR vs. ICA

- adapted from
Jacobsen et al., 2020



Artifact footprint




Ferris
Nordin
Wagner
Seeber

ASR - Discussion


- training data make the difference!
- global artifacts
- processing delay
- spatial coverage of channels

Results: rASR Toolbox




Two Topics Today

mobile EEG
&
new Android Apps




artifact handling
&
Riemannian ASR



Mobile EEG and Current Developments

- LSL
- continuous data no markers
 - combining EEG with additional sensors

LabStreamingLayer




Markerless EEG



Real-time audio processing of real-life soundscapes for EEG analysis: The AFEx Android App





Martin Bleichner's Group




RECORD-A and SEND-A

- Android applications
- enable completely mobile **LabStreamingLayer** setups
- SEND-A
 - LSL streams from smartphone sensors
- RECORD-A
 - record all incoming LSL streams to xdf


SEND-A




RECORD-A









Evaluation




Timing



Timing Data



All Timing Events





End

- artifact correction is important
- know your data
- add information to your data
- don't be afraid to go completely mobile



Find me here:



connect
&
download

@s4rify

github.com/s4rify

References

- Blum, S., Debener, S., Emkes, R., Volkenning, N., Fudickar, S., & Bleichner, M. G. M. G. (2017). EEG Recording and Online Signal Processing on Android: A Multiapp Framework for Brain-Computer Interfaces on Smartphone. *BioMed Research International*, 2017, 1–12. <https://doi.org/10.1155/2017/3072870>
- Blum, S., Emkes, R., Minow, F., Anlauff, J., Finke, A., & Debener, S. (2020). Flex-printed forehead EEG sensors (fEEGGrid) for long-term EEG acquisition. *Journal of Neural Engineering*.
- Blum, S., Jacobsen, N. S. J., Bleichner, M. G., & Debener, S. (2019). A Riemannian Modification of Artifact Subspace Reconstruction for EEG Artifact Handling. *Frontiers in Human Neuroscience*, 13, 141. <https://doi.org/10.3389/fnhum.2019.00141>
- Blum, S., Mirkovic, B., & Debener, S. (2019). Evaluation of Riemannian ASR on cEEGGrid data: an artifact correction method for BCIs. In *IEEE International Conference on Systems, Man, and Cybernetics* (p. 5). Bari.
- Lotte, F., Congedo, M., Lécuyer, A., Lamarche, F., Arnaldi, B., Anatole, L., ... Adeli, H. (2018). A review of classification algorithms for EEG-based brain – computer interfaces To cite this version : A Review of Classification Algorithms for EEG-based Brain-Computer Interfaces. *Human Brain Mapping*, 38(11), 270–278. <https://doi.org/10.1002/hbm.23730>
- Blankertz, B., Tangermann, M., Vidaurre, C., Fazli, S., Sannelli, C., Haufe, S., ... Mueller, K. (2010). The Berlin Brain–Computer Interface: Non-Medical Uses of BCI Technology. *Frontiers in Neuroscience*, 4(198). <https://doi.org/10.3389/fnins.2010.00198>


References ctd.

- Choi, I., Rajaram, S., Varghese, L. A., & Shinn-Cunningham, B. G. (2013). Quantifying attentional modulation of auditory-evoked cortical responses from single-trial electroencephalography. *Frontiers in Human Neuroscience*, 7(April), 115. <https://doi.org/10.3389/fnhum.2013.00115>
- Nordin, A.D., Hairston, W.D. & Ferris, D.P. Human electrocortical dynamics while stepping over obstacles. *Sci Rep* 9, 4693 (2019). <https://doi.org/10.1038/s41598-019-41131-2>
- Farwell, L. A., & Donchin, E. (1988). Talking off the top of your head: toward a mental prosthesis utilizing event-related brain potentials. *Electroencephalography and Clinical Neurophysiology*, 70(6), 510–523. [https://doi.org/10.1016/0013-4694\(88\)90149-6](https://doi.org/10.1016/0013-4694(88)90149-6)
- Mullen, T. R., Kothe, C. A. E., Chi, Y. M., Ojeda, A., Kerth, T., Makeig, S., ... Cauwenberghs, G. (2015). Real-time neuroimaging and cognitive monitoring using wearable dry EEG. *IEEE Transactions on Biomedical Engineering*, 62(11), 2553–2567. <https://doi.org/10.1109/TBME.2015.2481482>
- Florian Yger, Maxime Berar, Fabien Lotte. Riemannian approaches in Brain-Computer Interfaces: a review. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, Institute of Electrical and Electronics Engineers, 2017. <hal-01394253>
- Yger, F., Lotte, F., & Sugiyama, M. (2015). Averaging covariance matrices for EEG signal classification based on the CSP: An empirical study. *2015 23rd European Signal Processing Conference, EUSIPCO 2015*, 2721–2725. <https://doi.org/10.1109/EUSIPCO.2015.7362879>


References again

- Congedo, M., Barachant, A., & Bhatia, R. (2017). Riemannian geometry for EEG-based brain-computer interfaces; a primer and a review. *Brain-Computer Interfaces*, 4(3), 155–174. <https://doi.org/10.1080/2326263X.2017.1297192>
- Jacobsen, N. S. J., Blum, S., Witt, K., & Debener, S. (2020). A walk in the park? Characterizing gait-related artifacts in mobile EEG recordings. *European Journal of Neuroscience*, 00, ejn. <https://doi.org/10.1111/ejn.14965>
- Mullen, T., Kothe, C., Chi, Y.M., Ojeda, A., Kerth, T., Makeig, S., Cauwenberghs, G., Jung, T.P.: Real-time modeling and 3D visualization of source dynamics and connectivity using wearable EEG. In: 35th Annual International Conference on Engineering in Medicine and Biology Society (EMBC). IEEE, pp. 2184–2187 (2013)


- flaticon.com
- <https://nachrichten.idw-online.de/2019/11/14/was-unser-gang-verbirgt-die-zukunft-der-hirnstrommessung-am-hanse-wissenschaftskolleg/>



Auditory Oddball



Vibrotactile Oddball



- variance of a time series X:

$$\text{var}(X) = \frac{1}{n} \sum_{i=0}^n (x_i - \mu)^2$$

variance in 1 dimension is a positive real number

- covariance between two time series:

$$\text{cov}(X, Y) = \frac{1}{n} \sum_{i=1}^n (x_i - \mu_x)(y_i - \mu_y)$$

- covariance matrix of two time series:

$$C = \begin{pmatrix} \text{var}(X) & \text{cov}(X, Y) \\ \text{cov}(Y, X) & \text{var}(Y) \end{pmatrix}$$

variance in n dimensions is a positive matrix

- where X and Y can denote epochs in EEG measurement, or data from different channels

(symmetric) positive definite matrices

1) a symmetric $n \times n$ real matrix M is positive definite if

$$z^T M z$$

is strictly positive for every non-zero column vector of z (energy)

2) all eigenvalues λ of SPD matrices are real and positive