




Artifact handling for mobile EEG

Sarah Blum




Neuropsychology Lab Oldenburg,
Germany









biological

technical







Artifact Subspace Reconstruction



adapted
from Mullen et al., 2015




Riemannian Geometry




e.g. Barachant et al., 2012, Yger et al., 2015, Congedo et al. 2017, Kalunga et al., 2015, Barthélemy et al., 2019


uncorrected






ASR





Riemann ASR





Blum et al., 2019



Blum et al., 2019



Blum et al., 2019a



SCALA SETTINGS

Recording Specifications

Filter

SamplingRate

Artefact Detection

Artifact Detection ☒

Training and Templates

Training Trials altogether

Save Templates to File ☐

Enter Subject Name (no spaces)
eg.: subj_01

Communication

Send out generated Templates via TCP ☐

Send out UDP messages on Port 50008 ☐

Channel Selection

Channel 1
Enter Index Channel 1

Channel 2

Blum et al., 2017

connect
&
download

@s4rify

github.com/s4rify

References & Sources

- Mullen T, Christian K, Mike C Y, Alejandro O, Trevor K, Scott M, Gert C, Kothe C, Chi Y M, Ojeda A, Kerth T, Makeig S, Cauwenberghs G and Tzyy-Ping Jung (2013). Real-time modeling and 3D visualization of source dynamics and connectivity using wearable EEG. *2013 35th Annu. Int. Conf. IEEE Eng. Med. Biol. Soc.* 2184–7
- Barachant A, Bonnet S, Congedo M and Jutten C 2012 Multiclass brain-computer interface classification by Riemannian geometry *IEEE Trans. Biomed. Eng.* **59** 920–8
- Yger F, Lotte F and Sugiyama M 2015 Averaging Covariance Matrices For EEG Signal Classification Based on the CSP: an Empirical Study *Proc. Eur. Signal Process. Conf.* 2721–5
- Congedo M, Barachant A and Bhatia R 2017 Riemannian geometry for EEG-based brain-computer interfaces; a primer and a review *Brain-Computer Interfaces* **4** 155–74
- Kalunga E, Chevallier S and Barthélemy Q 2015 Using Riemannian geometry for SSVEP-based Brain Computer Interface
- Barthelemy Q, Mayaud L, Ojeda D and Congedo M 2019 The Riemannian Potato Field: a tool for online Signal Quality Index of EEG *IEEE Trans. Neural Syst. Rehabil. Eng.* 1–1
- clean_rawdata toolbox: [1https://sccn.ucsd.edu/wiki/EEGLAB_Extensions](https://sccn.ucsd.edu/wiki/EEGLAB_Extensions)
- Blum S, Debener S, Emkes R, Volkening N, Fudickar S and Bleichner M G 2017 EEG Recording and Online Signal Processing on Android: A Multiapp Framework for Brain-Computer Interfaces on Smartphone *Biomed Res. Int.* **2017**
- Blum S, Jacobsen N S J, Bleichner M G and Debener S 2019 A Riemannian Modification of Artifact Subspace Reconstruction for EEG Artifact Handling *Front. Hum. Neurosci.* **13**
- Blum S, Mirkovic B, Debener S 2019a, Evaluation of Riemannian ASR on cEEGrid data: an artifact correction method for BCIs. IEEE SMC Proceedings (in press).

