A Simplified Round-by-round Soundness Proof of FRI

Albert Garreta
Nethermind Research

Nicolas Mohnblatt
zkSecurity

Benedikt Wagner
Ethereum Foundation

Theory of Cryptography Conference, 11 Nov. 2026

ZKS

Introduction

Fast Reed–Solomon IOPP (FRI)

FRI [BBHR18] is an interactive oracle proof of proximity (IOPP) for Reed–Solomon codes: the prover convinces the verifier that a function $f_0 : \mathcal{L}_0 \to \mathbb{F}$ is close to the evaluations of a low-degree polynomial.

Introduction

Fast Reed–Solomon IOPP (FRI)

FRI [BBHR18] is an interactive oracle proof of proximity (IOPP) for Reed–Solomon codes: the prover convinces the verifier that a function $f_0 : \mathcal{L}_0 \to \mathbb{F}$ is close to the evaluations of a low-degree polynomial.

- Widely deployed in production.
- Its concrete security is proven...
- ...but the security proofs are notoriously complicated.

Introduction

Fast Reed–Solomon IOPP (FRI)

FRI [BBHR18] is an interactive oracle proof of proximity (IOPP) for Reed–Solomon codes: the prover convinces the verifier that a function $f_0 : \mathcal{L}_0 \to \mathbb{F}$ is close to the evaluations of a low-degree polynomial.

- Widely deployed in production.
- Its concrete security is proven...
- ...but the security proofs are notoriously complicated.

What is FRI? **Can** we come up with a simpler proof? **Why** should we care?

Agenda

Motivation: SNARKs

Background: RS codes and IOPPs

The FRI protocol

Analysis: soundness of FRI

SNARKs

SNARKs


- SNARK: succinct, non-interactive argument of knowledge.
- A short string that certifies that the prover knows a witness to some NP statement.
  - using elliptic curves, ≈ 260 B.
  - using lattices, ≈ 60 KB.
  - using only hash-functions, $\approx$ 100-1000 KB.
- Widely deployed in the blockchain industry, growing adoption from tech giants.

A recipe for hash-based SNARKs


A recipe for hash-based SNARKs

SNARK for $\mathcal{R}$
in the ROM


A recipe for hash-based SNARKs



A recipe for hash-based SNARKs




A recipe for hash-based SNARKs




On simplifying proofs


On simplifying proofs




On simplifying proofs



On simplifying proofs



On simplifying proofs



Agenda

Motivation: SNARKs


Background: RS codes and IOPPs

The FRI protocol

Analysis: soundness of FRI


Reed–Solomon codes

A message of length d is a polynomial $\hat{u} \in \mathbb{F}^{<d}[X]$; its codeword $u \in \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$ is the evaluations of $\hat{u}$ on a domain $\mathcal{L} \subseteq \mathbb{F}$.




Reed–Solomon codes

A message of length d is a polynomial $\hat{u} \in \mathbb{F}^{<d}[X]$; its codeword $u \in \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$ is the evaluations of $\hat{u}$ on a domain $\mathcal{L} \subseteq \mathbb{F}$.




Reed–Solomon codes

A message of length d is a polynomial $\hat{u} \in \mathbb{F}^{<d}[X]$; its codeword $u \in \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$ is the evaluations of $\hat{u}$ on a domain $\mathcal{L} \subseteq \mathbb{F}$.




- Write $\Delta(f, g)$ for the relative Hamming distance.
- The agreement set between f and u is the subset $S \subseteq \mathcal{L}$ where f and u agree.

Interactive oracle proofs (IOPs)




Interactive oracle proofs (IOPs)



- Prover messages are oracles: the verifier reads only the positions it queries.
- Statement split into $\mathbb{x}$ (read in full) and $\mathbb{y}$ (oracle access). The prover knows a witness $\mathbb{w}$.
- Public coin: verifier messages are uniformly random and independent, including the query positions.
- Neither succinct nor non-interactive. To compile to a SNARK, we replace oracles with Merkle roots and interaction with Fiat–Shamir [Kil92, Mic94, BCS16].

Interactive oracle proofs (IOPs)



- Prover messages are oracles: the verifier reads only the positions it queries.
- Statement split into $\mathbb{x}$ (read in full) and $\mathbb{y}$ (oracle access). The prover knows a witness $\mathbb{w}$.
- Public coin: verifier messages are uniformly random and independent, including the query positions.
- Neither succinct nor non-interactive. To compile to a SNARK, we replace oracles with Merkle roots and interaction with Fiat–Shamir [Kil92, Mic94, BCS16].

$\Longrightarrow$ SNARK size depends on the number of queries.

Figure adapted from Chiesa and Yogev, *Building Cryptographic Proofs from Hash Functions*, Fig. 23.1 (CC BY-SA 4.0).

IOP of proximity (IOPP)

IOP of proximity (IOPP)

Definition (IOPP for $\mathcal{C}$, informal)

An IOP for the relation $\mathcal{R}_{\mathcal{C}}$ where soundness is a function of distance.

$$\mathcal{R}_{\mathcal{C}} := \{(\perp, f, w) : f = \mathsf{Encode}_{\mathcal{C}}(w)\}$$


IOP of proximity (IOPP)

Definition (IOPP for $\mathcal{C}$, informal)

An IOP for the relation $\mathcal{R}_{\mathcal{C}}$ where soundness is a function of distance.

$$\mathcal{R}_{\mathcal{C}} := \{(\perp, f, w) : f = \mathsf{Encode}_{\mathcal{C}}(w)\}$$

- **Completeness.** $\forall f \in \mathcal{C} : \Pr\left[\mathbf{V}^f = 1\right] = 1.$
- **Soundness.** $\forall f \notin \mathcal{C} : \Pr\left[\mathbf{V}^f = 1\right] \leq \varepsilon(\delta)$, where $\delta := \Delta(f, \mathcal{C})$.



(a sketch, not a real soundness bound)

IOP of proximity (IOPP)


Definition (IOPP for $\mathcal{C}$, informal)

An IOP for the relation $\mathcal{R}_{\mathcal{C}}$ where soundness is a function of distance.

$$\mathcal{R}_{\mathcal{C}} := \{(\perp, f, w) : f = \mathsf{Encode}_{\mathcal{C}}(w)\}$$

- **Completeness.** $\forall f \in \mathcal{C} : \Pr\left[\mathbf{V}^f = 1\right] = 1.$
- **Soundness.** $\forall f \notin \mathcal{C} : \Pr\left[\mathbf{V}^f = 1\right] \leq \varepsilon(\delta)$, where $\delta := \Delta(f, \mathcal{C})$.
- We say that the IOPP has λ bits of security at distance δ^* if

$$\forall f \text{ s.t. } \Delta(f, \mathcal{C}) \geq \delta^*, \quad \Pr\left[\mathbf{V}^f = 1\right] \leq 2^{-\lambda}$$



(a sketch, not a real soundness bound)

Agenda

Motivation: SNARKs

Background: RS codes and IOPPs


The FRI protocol

Analysis: soundness of FRI


FRI in pictures: folding phase

$f_0 : \mathcal{L}_0 \to \mathbb{F}$ 

FRI in pictures: folding phase



FRI in pictures: folding phase



The Fold function

For every $\alpha \in \mathbb{F}$, $\mathsf{Fold}(\cdot, \alpha)$:


- **maps $\mathcal{C}_0 := \mathbf{RS}[\mathbb{F}, \mathcal{L}_0, d_0]$ to $\mathcal{C}_1 := \mathbf{RS}[\mathbb{F}, \mathcal{L}_1, d_1]$**, where

$$\mathcal{L}_1 := \mathcal{L}_0^2 = \{x^2 : x \in \mathcal{L}_0\} \quad \text{and} \quad d_1 := d_0/2.$$


  Domain size and degree bound are both halved. The rate $\frac{d_1}{|\mathcal{L}_1|} = \frac{d_0}{|\mathcal{L}_0|} = \rho$ is unchanged.

- **is locally computable**. *E.g.*, $\mathsf{Fold}(f_0, \alpha_1)(s^2)$ is computed from $f_0(s)$ and $f_0(-s)$.


FRI in pictures: folding phase




FRI in pictures: folding phase




FRI in pictures: folding phase



FRI in pictures: folding phase




FRI in pictures: query phase




1. **Final function check.** Read f_k in full and check that it is a codeword of $\mathcal{C}_k$.

FRI in pictures: query phase



1. **Final function check.** Read f_k in full and check that it is a codeword of $\mathcal{C}_k$.
2. **Local fold checks.** A query $s \in \mathcal{L}_0$ induces a path s, s^2, s^4, s^8. Walk down it and, at each node, recompute the fold from the two children (solid and dashed) and compare with the node's value.

FRI in pictures: query phase



1. **Final function check.** Read f_k in full and check that it is a codeword of $\mathcal{C}_k$.
2. **Local fold checks.** A query $s \in \mathcal{L}_0$ induces a path s, s^2, s^4, s^8. Walk down it and, at each node, recompute the fold from the two children (solid and dashed) and compare with the node's value.
3. **Repeat.** A second query s' induces a second path.

Agenda

Motivation: SNARKs

Background: RS codes and IOPPs


The FRI protocol

Analysis: soundness of FRI

Overview of proof strategy


Overview of proof strategy

1. Color the graph according to the verifier's check.



Overview of proof strategy


1. Color the graph according to the verifier's check.



Overview of proof strategy

1. Color the graph according to the verifier's check.
2. Accepting probability for single query is

$$\frac{\#\text{ of green nodes in } \mathcal{L}_0}{|\mathcal{L}_0|}$$




Overview of proof strategy

1. Color the graph according to the verifier's check.
2. Accepting probability for single query is

$$\frac{\#\text{ of green nodes in } \mathcal{L}_0}{|\mathcal{L}_0|}$$

3. Relate the # of green nodes in $\mathcal{L}_0$ to $\Delta(f_0, \mathcal{C}_0)$, leveraging properties of Fold.



Proving 3.

Proving 3.

P_θ — agreement propagates upwards

If there is a large enough set of green nodes where f_i agrees with $\mathcal{C}_i$ then, f_{i-1} agrees with $\mathcal{C}_{i-1}$ on green nodes except with negligible probability over the choice of α_i.

Define parameter $\theta \in [0, 1]$ and say that sets of size $(1 - \theta) \cdot |\mathcal{L}_i|$ are large enough.

Proving 3.

P_θ — agreement propagates upwards

If there is a large enough set of green nodes where f_i agrees with $\mathcal{C}_i$ then, f_{i-1} agrees with $\mathcal{C}_{i-1}$ on green nodes except with negligible probability over the choice of α_i.

Define parameter $\theta \in [0, 1]$ and say that sets of size $(1 - \theta) \cdot |\mathcal{L}_i|$ are large enough.

$$\Pr[\mathbf{V} \text{ accepts}] \leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]$$

Proving 3., continued

$$\Pr[\mathbf{V} \text{ accepts}] \leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]$$

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \sum_i \Pr[P_\theta \text{ fails at round } i] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]\end{aligned}$$

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

$\varepsilon^{\mathsf{qry}}$: case analysis.

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

↓ Lemma 5.1

Property of linear combinations of $\mathcal{C}_i$: mutual correlated agreement [ACFY24].

↓

Write $\varepsilon^{\mathsf{mca}}$, give the problem to coding theorists. See the Proximity Prize and [ABF26].

$\varepsilon^{\mathsf{qry}}$: case analysis.

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

↓ Lemma 5.1

Property of linear combinations of $\mathcal{C}_i$: mutual correlated agreement [ACFY24].

↓

Write $\varepsilon^{\mathsf{mca}}$, give the problem to coding theorists. See the Proximity Prize and [ABF26].

$\varepsilon^{\mathsf{qry}}$: case analysis.

Case 1: at least $(1-\theta)$ fraction of green nodes.

Case 2: less than $(1-\theta)$ fraction of green nodes.

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

↓ Lemma 5.1

Property of linear combinations of $\mathcal{C}_i$: mutual correlated agreement [ACFY24].

↓

Write $\varepsilon^{\mathsf{mca}}$, give the problem to coding theorists. See the Proximity Prize and [ABF26].

$\varepsilon^{\mathsf{qry}}$: case analysis.

Case 1: at least $(1-\theta)$ fraction of green nodes.

$\Rightarrow$ since P_θ holds, agreement propagates upwards.

$\Rightarrow$ exists u_0 that agrees with f_0 on green nodes.

$\Rightarrow$ accept probability is bounded by $(1-\delta)^t$.

Case 2: less than $(1-\theta)$ fraction of green nodes.

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

↓ Lemma 5.1

Property of linear combinations of $\mathcal{C}_i$: mutual correlated agreement [ACFY24].

↓

Write $\varepsilon^{\mathsf{mca}}$, give the problem to coding theorists. See the Proximity Prize and [ABF26].

$\varepsilon^{\mathsf{qry}}$: case analysis.

Case 1: at least $(1-\theta)$ fraction of green nodes.

$\Rightarrow$ since P_θ holds, agreement propagates upwards.

$\Rightarrow$ exists u_0 that agrees with f_0 on green nodes.

$\Rightarrow$ accept probability is bounded by $(1-\delta)^t$.

Case 2: less than $(1-\theta)$ fraction of green nodes.

$\Rightarrow$ accept probability is bounded by $(1-\theta)^t$.

Proving 3., continued

$$\begin{aligned}\Pr[\mathbf{V} \text{ accepts}] &\leq \Pr[P_\theta \text{ fails at some round}] + \Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}] \\ &\leq \underbrace{\sum_i \Pr[P_\theta \text{ fails at round } i]}_{\sum_i \varepsilon_i^{\mathsf{fold}}(\delta)} + \underbrace{\Pr[\mathbf{V} \text{ accepts} \mid P_\theta \text{ holds at all rounds}]}_{\varepsilon^{\mathsf{qry}}(\delta)}\end{aligned}$$

$\varepsilon_i^{\mathsf{fold}}$ is a probability over α_i. Property of $\mathcal{C}_{i-1}$, $\mathcal{C}_i$ and **Fold**.

↓ Lemma 5.1

Property of linear combinations of $\mathcal{C}_i$: mutual correlated agreement [ACFY24].

↓

Write $\varepsilon^{\mathsf{mca}}$, give the problem to coding theorists. See the Proximity Prize and [ABF26].

$\varepsilon^{\mathsf{qry}}$: case analysis.

Case 1: at least $(1-\theta)$ fraction of green nodes.

$\Rightarrow$ since P_θ holds, agreement propagates upwards.

$\Rightarrow$ exists u_0 that agrees with f_0 on green nodes.

$\Rightarrow$ accept probability is bounded by $(1-\delta)^t$.

Case 2: less than $(1-\theta)$ fraction of green nodes.

$\Rightarrow$ accept probability is bounded by $(1-\theta)^t$.

Join the cases by taking the $\max$.

The theorem, as it appears in the paper

Theorem (Theorem 5.2)

Consider FRI with parameters as in Construction 4.4 and assume Powers is a proximity generator with mutual correlated agreement (cf. Definition 2.2) with error $\varepsilon^{\mathsf{mca}}$. For every tradeoff parameter $\theta \in [0,1]$, FRI has round-by-round soundness with error functions $\varepsilon_1^{\mathsf{fold}}, \ldots, \varepsilon_k^{\mathsf{fold}}, \varepsilon^{\mathsf{qry}} : (0,1] \to [0,1]$ such that for every initial function $f_0 \notin \mathcal{C}_0$:

- for all $i \in [k]$, $\varepsilon_i^{\mathsf{fold}}(\delta) = \varepsilon^{\mathsf{mca}}(\mathcal{C}_i, m_i, \theta)$,
- $\varepsilon^{\mathsf{qry}}(\delta) = (\max\{1-\theta, 1-\delta\})^t = (1 - \min\{\theta, \delta\})^t$,


where $\delta := \Delta(f_0, \mathcal{C}_0)$.


Understanding the error bounds


Understanding the error bounds

The tradeoff parameter


- Folding round errors: $\varepsilon_i^{\text{fold}}(\delta) = \varepsilon^{\text{mca}}(\mathcal{C}_i, 2, \theta)$ grows with θ — wants θ small.
- Query round error: $\varepsilon^{\text{qry}}(\delta)$ is clamped from below at $(1-\theta)^t$ — wants θ large.







Bonus: extraction from erasure decoding



- If $\Pr[\mathbf{V} \text{ accepts}] \geq (1-\theta)^t$ and $\theta \leq 1-\rho$, case 1 gives a *unique* $u_0 \in \mathcal{C}_0$ agreeing with f_0 on the green top nodes: $\geq \rho\,|\mathcal{L}_0| = d_0$ points.
- Recover u_0 by erasure decoding (interpolation on green nodes), no list decoding. The folding phase is a binding commitment, beyond the unique decoding radius.

Comparison to previous proofs

Our bounds are the same as previous proofs [BCIKS20, ABN23]; ethSTARK [StarkWare21] observed that these are round-by-round bounds. The difference is the guarantee given by a *good* folding challenge:

Comparison to previous proofs

Our bounds are the same as previous proofs [BCIKS20, ABN23]; ethSTARK [StarkWare21] observed that these are round-by-round bounds. The difference is the guarantee given by a *good* folding challenge:

MCA (this work)

If all **green** layers are large enough, agreement propagates upwards through the **green** nodes.

CA (previous proofs)

If all **green** layers are large enough, agreement propagates upwards *at unknown nodes*, possibly not aligned with **green**.

Comparison to previous proofs

Our bounds are the same as previous proofs [BCIKS20, ABN23]; ethSTARK [StarkWare21] observed that these are round-by-round bounds. The difference is the guarantee given by a *good* folding challenge:

MCA (this work)

If all **green** layers are large enough, agreement propagates upwards through the **green** nodes.

CA (previous proofs)

If all **green** layers are large enough, agreement propagates upwards *at unknown nodes*, possibly not aligned with **green**.

- Losing the location forces previous proofs to introduce *weighted* distances and a weighted correlated agreement theorem, with weights tracking the quality of agreement at each node.
- Without keeping track of agreement sets, extraction requires error decoding.

Summary


- FRI is part of the SNARK pipeline.
- We present a simpler proof that provides new insights.
- Proof overview:
  - define and bound a bad event for honest folds.
  - if many dishonest folds, verifier rejects.
  - else, if many honest folds and no bad event, acceptance probability is related to distance δ.
- Paper also includes: formal proof, formal statement of the new insights, comparison to previous works and batched FRI.

Thank you! Questions?

Full paper: ia.cr/2025/1993.

Backup: decoding regimes

How far can f be from $\mathcal{C} = \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$ and still have few codewords nearby? $(\rho = 1/4)$




State-of-the-art before the Proximity Prize:

- Below $\frac{1-\rho}{2}$: at most one codeword within distance δ of f.
- Below $1-\sqrt{\rho}$: polynomially many codewords (Johnson bound).
- Between $1-\sqrt{\rho}$ and $1-\rho$: unknown area.
- Above $1-\rho$: vacuous statement.

Our analysis has a parameter θ that plays the role of "how far we dare to go".

Backup: mutual correlated agreement (MCA)



1. **Commit.** Fix two functions $u, v : \mathcal{L} \to \mathbb{F}$.
2. **Combine.** Sample $r \leftarrow \mathbb{F}$ and form $u + r \cdot v$.
3. **Observe.** $u + rv$ agrees with a codeword of $\mathcal{C} = \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$ on a large set S: $|S| \geq (1 - \gamma) \cdot |\mathcal{L}|$.
4. **Conclude.** What is the probability that u and v do not agree with codewords on S? Define it as $\varepsilon^{\mathsf{mca}}(\mathcal{C}, 2, \gamma)$ and let coding theorists figure that out ☺.

Note. Bounding this error for varying values of γ is at the core of the Proximity Prize.

Backup: mutual correlated agreement, formally

Definition (Proximity generator with mutual correlated agreement)

Let $\mathcal{C} \coloneqq \mathsf{RS}[\mathbb{F}, \mathcal{L}, d]$. A sampler Gen has MCA for $\mathcal{C}$ with error $\varepsilon^{\mathsf{mca}}$ if for every $f_1, \ldots, f_m : \mathcal{L} \to \mathbb{F}$ and every $\gamma \in [0, 1]$:

$$\Pr_{(r_1,\ldots,r_m) \leftarrow \mathsf{Gen}\ (m)} \left[\exists S \subseteq \mathcal{L} \text{ s.t. } \begin{array}{c} |S| \geq (1-\gamma) \cdot |\mathcal{L}| \\ \wedge\, \exists u \in \mathcal{C}, u[S] = \sum_j r_j \cdot f_j[S] \\ \wedge\, \exists j, \forall u' \in \mathcal{C}, u'[S] \neq f_j[S] \end{array} \right] \leq \varepsilon^{\mathsf{mca}}(\mathcal{C}, m, \gamma).$$

- FRI uses the Powers generator: sample $r \leftarrow \mathbb{F}$ and output $(1, r, r^2, \ldots, r^{m-1})$. Folding by 2 is the case $m = 2$.
- For a general folding factor m the key lemma goes through a bivariate polynomial $\hat{Q}(X, Y) = \sum_j \hat{u}_j(X) Y^{j-1}$ and $\hat{u}(X) \coloneqq \hat{Q}(X^m, X)$.

Backup: round-by-round soundness

A state function $\mathsf{State}\ (\mathtt{x}, \mathtt{y}, \mathtt{tr}) \in \{0, 1\}$ on partial transcripts; state 0 means "the prover is about to lose".

- $\mathsf{State}\ (\varnothing) = 1$ iff the statement is true. Prover messages cannot change the state. A complete transcript in state 0 is rejected.
- **Round-by-round soundness with errors $(\varepsilon_1, \ldots, \varepsilon_k)$**: for every partial transcript $\mathtt{tr}$ in state 0, $\Pr_{\alpha_i}[\mathsf{State}\ (\mathtt{tr} \parallel \alpha_i) = 1] \leq \varepsilon_i$.

Why Fiat–Shamir needs it

A grinding prover retries each challenge: Q_i hashes at round i. It succeeds with probability at most $\sum_i Q_i \varepsilon_i$. Plain soundness assumes one challenge per round and says nothing about this prover.

Our state function

State 1 during the folding phase iff some round i had a bad fold: a large-enough $S \subseteq \mathcal{L}_{i-1}$ on which $\mathsf{Fold}(f_{i-1}, \alpha_i)$ agrees with a codeword while f_{i-1} does not. After the query phase: state 1 iff the verifier accepts.