

<

Previous











Next >

Question 2-5

 [Bookmark this page](#)

Here is our data definition for a list of strings:

```
;; ListOfString is one of:  
;; - empty  
;; - (cons String ListOfString)  
;; interp. a list of strings  
  
(define LOS1 empty)  
(define LOS2 (cons "a" empty))  
(define LOS3 (cons "a" (cons "b" empty)))  
  
#;  
(define (fn-for-los los)  
  (cond [(empty? los) (...)]  
        [else  
         (... (first los)  
              (fn-for-los (rest los)))]))
```


Question 2


1/1 point (graded)


Here is the signature and purpose for `arrange-strings`:

```
;; ListOfStrings -> Image  
;; layout strings vertically in alphabetical order
```

Which of the following is a correct test for `arrange-strings`?

- 

(check-expect (arrange-strings (cons "Sally" (cons "Apple" empty))) BLANK)
- 

(check-expect (arrange-strings (cons "Sally" (cons "Apple" empty)))
 (above/align "left"
 (text "Sally" TEXT-SIZE TEXT-COLOR)
 (text "Apple" TEXT-SIZE TEXT-COLOR)
 BLANK))
- 

(check-expect (arrange-strings (cons "Sally" (cons "Apple" empty)))
 (above/align "left"
 (text "Apple" TEXT-SIZE TEXT-COLOR)
 (text "Sally" TEXT-SIZE TEXT-COLOR)
 BLANK))




Explanation

First we need to sort the list alphabetically, and then lay the elements out vertically using the `above/align` and `text` functions.

Submit


 Show Answer


 Answers are displayed within the problem

Question 3

1/1 point (graded)

Do we need to add the following base case test to the `arrange-strings` function design?

- (check-expect (arrange-strings empty) BLANK)
- 

yes
- 

no



Explanation

Because `arrange-strings` is a function composition, the tests only need to ensure that `arrange-strings` is composing the functions properly, so no base case test is needed.

[Submit](#)[Show Answer](#)

Answers are displayed within the problem

Question 4

1/1 point (graded)

Consider the following `check-expect`:

```
(check-expect (arrange-strings (cons "Apple" (cons "Sally" empty))) BLANK)
  (above/align "left"
    (text "Apple" TEXT-SIZE TEXT-COLOR)
    (text "Sally" TEXT-SIZE TEXT-COLOR)
    BLANK))
```

Is it good enough to have only this `check-expect` for `arrange-strings`?

☐ yes

☒ no



Explanation

The list is already sorted alphabetically, so this tests the rendering part, but not the sorting.

[Submit](#)[Show Answer](#)

Answers are displayed within the problem

Question 5

1/1 point (graded)

Since `arrange-strings` needs to perform two tasks, we need to use a function composition. Assume we wished for two functions, `sort-strings` which sorts a list of strings, and `layout-strings` that arranges the strings into a vertical line.

Which of the following is the correct function definition for `arrange strings`?

☒

```
(define (arrange-strings los)
  (layout-strings (sort-strings los)))
```

☐

```
(define (arrange-strings los)
  (sort-strings (layout-strings los)))
```



Explanation

The first task is to sort the strings, and the second is to lay them out. Remember the BSL evaluation rules. Expressions like this evaluate inside to outside. So the sorting evaluates before the laying out, because the call to the sorting function is an operand to the call to the laying out function.

[Submit](#)[Show Answer](#)

Answers are displayed within the problem

[< Previous](#)[Next >](#)

© 2020 edX Inc. All rights reserved.



edX

About
edX for Business

Legal

Terms of Service &
Honor Code
Privacy Policy
Accessibility Policy

Connect

Blog
Contact Us
Help Center



© 2020 edX Inc. All rights reserved.
| 深圳市恒宇博科技有限公司 粤ICP备17044299号-2