

## Questions 5-7

 [Bookmark this page](#)


### Question 5


1/1 point (graded)


Just as we can have self-reference without reference (`ListOfString`), we can also have reference without self-reference. Consider these two partial data definitions:


```
(define-struct bar (a b))  
;; Bar is (make-bar String String)  
  
(define-struct foo (x b))  
;; Foo is (make-foo Integer Bar)
```

What are the correct arrows for this figure?

☒ 

☐ 

☐ 

☐ 



#### Explanation

The reference should go from `bar` in `(make-foo Integer Bar)` to the `bar` before the word `is`.

Submit


 Show Answer


 Answers are displayed within the problem


### Question 6

1/1 point (graded)

What is the correct template for `foo`?

☒ 

☐ 

☐ 



```
(define (fn-for-foo f)
  (... (foo-x f)
    (fn-for-bar (foo-b f))))
```



#### Explanation

(foo-x f) is of type Bar, so it is wrapped in fn-for-bar

Submit

Show Answer

Answers are displayed within the problem

### Question 7

1/1 point (graded)

Drag the template rules to create the correct template rules for foo. Only use as many template rules as are necessary.

```
;; Template Rules Used
;; - compound
;; - reference
;; - atomic
```

◀

;; - foo-02

▶



#### Answer:

#### Explanation

foo is compound. The first field is a simple atomic type, Integer, and the second field is a reference to a non-primitive type.

Submit

Show Answer

Answers are displayed within the problem

◀ Previous    Next ▶

© 1 3 2 Some Rights Reserved



edX

About  
edX for Business

Legal

Terms of Service &  
Honor Code  
Privacy Policy  
Accessibility Policy

Connect

Blog  
Contact Us  
Help Center



© 2020 edX Inc. All rights reserved.  
| 深圳市恒宇博科技有限公司 粤ICP备17044299  
号-2