

< Previous











Next >

Question 4-6

 [Bookmark this page](#)

Question 4

1/1 point (graded)

Choose the part of the template that results from each highlighted part of the Type Comment.

```
;; ListOfNumber is one of:  
;; - empty  
;; (cons Number ListOfNumber  
;; interp. a list of numbers  
  
(define (fn-for-lon lon)  
  (cond [(empty? lon) (...)]  
        [else  
         (... (first lon)  
              (fn-for-lon (rest lon)))]))
```




Explanation

ListOfNumber has two cases, so we need a cond expression. empty is the first case, and it is atomic distinct, so the answer clause is (...).

Submit

 Show Answer

 Answers are displayed within the problem

Question 5

1/1 point (graded)

```
;; ListOfNumber is one of:  
;; - empty  
;; (cons Number ListOfNumber  
;; interp. a list of numbers  
  
(define (fn-for-lon lon)  
  (cond [(empty? lon) (...)]  
        [else  
         (... (first lon)  
              (fn-for-lon (rest lon)))]))
```



Explanation

(cons Number ListOfNumber) is compound, so we separate it into two parts, the first being (first lon).

Submit

 Show Answer

 Answers are displayed within the problem

Question 6

1/1 point (graded)

```
;; ListOfNumber is one of:  
;; - empty  
;; (cons Number ListOfNumber  
;; interp. a list of numbers  
  
(define (fn-for-lon lon)  
  (cond [(empty? lon) (...)]  
        [else  
         (... (first lon)  
              (fn-for-lon rest lon)))]))
```



Explanation

The second part of the compound is (rest lon) which is ListOfNumber. This is a self-reference in the type comment, so (rest lon) is wrapped in a call to fn-for-lon to form a natural recursion.

Submit

 Show Answer

 Answers are displayed within the problem



edX

[About](#)
[edX for Business](#)

Legal

[Terms of Service &
Honor Code](#)
[Privacy Policy](#)
[Accessibility Policy](#)

Connect

[Blog](#)
[Contact Us](#)
[Help Center](#)



© 2020 edX Inc. All rights reserved.
| 深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)