

Introduction to PRE

Partial redundancy elimination

- discovers partially redundant expressions,
- converts to fully redundant, then eliminates redundancy

Tradeoffs with PRE

- data-flow properties are complex and non-intuitive, but . . .
 - dominates classical GCSE and LICM, and does more;
 - it minimizes auxiliary variable lifetimes
 - algorithms give strong guarantees about optimality
- ⇒ *every optimizing compiler should use it*

Introduction to PRE (cont'd)

References:

J. Knoop, O. Rüthing, and B. Steffen, "Lazy Code Motion," In *Proc. ACM Symposium on Programming Language Design and Implementation*, 1992.

- Muchnick, Chapter 13.3 (based on Knoop et al., above).
- Effective Partial Redundancy Elimination, Preston Briggs and Keith Cooper, *PLDI 1994* (improves how distinct expressions are identified to find more redundancies).


Additional Reading:

- Original paper:* E. Morel and C. Renvoise, "Global optimization by suppression of partial redundancies," *CACM* 22(2), February, 1979.
- Numerous Improvements*, e.g.,
 - Dreschler and Stadel, *TOPLAS* 10(4), 1988.
 - Dhamdhere *TOPLAS*, 13 (2), 1991 (practical adaptation).


Partially redundant expressions

An expression is *partially redundant* at p if it is *available* on some, but not all, paths reaching p

Example



PRE inserts code to make $b + c$ fully redundant



Loop invariant expressions

Another example



before

PRE removes loop invariants

- invariant expression is partially redundant (or redundant)
- PRE converts it to full redundancy
- PRE removes redundant expression

What can be moved?

- ideally, both computation and assignment
- of course, computation is easier

High-level view

How does it work?

- Use five distinct data-flow problems
- Computationally optimal placement: *anticipatable*, *earliest*
- Lifetime-optimal placement: *latest* (in 2 steps), *isolated*
- Insert the code and remove the redundant expressions

Scope

PRE works with *lexically identical* expressions:

- expressions
- loads
- constants
- *not* stores, copies, or calls

Strategies to make PRE more effective

Problems

- Associativity, commutativity
- Algebraic identities
- Complex Expressions

Solution: Two pre-passes to make PRE more effective.

Effective Partial Redundancy Elimination, Preston Briggs and Keith Cooper, PLDI 1994.

Global Reassociation

- Reorder expressions to expose constants and loop-invariant terms, and to normalize order

Global Value Numbering

- Use algorithm similar to AWZ to identify “equivalent” variables
- Do *not* perform the GVN optimization: placement may be poor!

Problem: Critical Edges

Definition:

A *critical edge* in a flow graph is an edge from a node with multiple successors to a node with multiple predecessors.

So what's the problem?

Splitting critical edges

Split every edge leading to a node with more than one predecessor.

Note: Not just critical edges

⇒ sufficient to insert computations at node entries only

Overview of PRE Algorithm

Assume each basic block is a single statement.

Informally...

1. **Anticipatable** : *aka “very busy,” “down-safe”*
 e is anticipatable at p if
 ⇒ Computing e at p would be useful along any path from p .
2. **Earliest** :
 e is *earliest* at p if there is some path from s to p on which e cannot be computed “anticipatably” and correctly
 ⇒ p is an earliest point to compute e .

Overview of PRE Algorithm (cont'd)

A computationally optimal placement

Compute expression e at each point p such that e is both *anticipatable* and *earliest* at p .

Problem

May compute expressions very early on some paths
 \Rightarrow significantly increases register pressure

Improved PRE Algorithm - Lazy Code Motion

Informally . . .

3. Latest:
 p is a *latest* point to compute e if placing e at p is computationally optimal *AND*, on every path from p , any later optimal point on the path would be after some use of e .
 \Rightarrow cannot move e later on any path from p
4. Isolated:
 p is an *isolated* point to compute e if it is optimal, and that value of e is only used immediately after p .
 \Rightarrow unnecessary to allocate a new temporary at p

Improved PRE Algorithm - Lazy Code Motion (cont'd)

A lifetime-optimal placement

Compute expression e at each point p such that e is latest at p and not isolated at p .

\Rightarrow *This is computationally optimal and requires the shortest lifetimes for all temporary variables introduced*

Preliminaries

Local properties of basic block b

Used : e is used in b if its value is computed in b

Killed : e is killed in b if any of its operands may be modified in b

transp(b) :

$e \in \text{transp}(b)$ if the operands of e are not modified in block b .
 (We say block b is *transparent* to e).

Preliminaries (cont'd)

$ANTloc(b)$:

$e \in ANTloc(b)$ if e is computed at least once in b and its operands are not modified before its first computation.

(We say e is *locally anticipatable* in block b).

\Rightarrow can move first evaluation to the start of b

Note that $ANTloc(b) = Used(b)$ if b has a single statement.

Example :

```
a ← b + c
d ← a + e
```

the following properties hold

$transp = \{\mathcal{U} - \{\text{expressions using } a \text{ or } d\}\}$

$ANTloc = \{b+c\}$

Anticipatable

$ANT(p)$:

$e \in ANT(p)$ if e is used before being killed on every path from point p to the exit.

e is *globally anticipatable* at point p .

(Also called *down-safe* at p .)

$ANTin(b), ANTout(b)$:

$ANT(p)$ at entry and exit of block b

$$ANTout(b) = \begin{cases} \phi & \text{if } b \text{ is an exit block} \\ \bigcap_{j \in \text{succ}(b)} ANTin(j) & \text{otherwise} \end{cases}$$

$$ANTin(b) = ANTloc(b) \cup (ANTout(b) \cap transp(b))$$

Earliestness

$EARlin(b)$:

$e \in EARlin(b)$ if there is some path q from s to $ENTRY(b)$ where no node prior to b on q both evaluates e and produces the same value as e would produce at $ENTRY(b)$.

We say e is *earliest* at $ENTRY(b)$.

$$EARlin(b) = \begin{cases} \mathcal{U} & \text{if } b = s \\ \bigcup_{j \in \text{pred}(b)} EARlout(j) & \text{otherwise} \end{cases}$$

$$EARlout(b) = \overline{transp(b)} \cup (EARlin(b) \cap \overline{ANTin(b)})$$

Theorem 3.9:

It is **computationally optimal** to compute e at entry to block b if

$e \in ANTin(b) \cap EARlin(b)$

Delayedness

Used to compute *Latest*

$DELAY(p)$:

$e \in DELAY(p)$ if, for every path from s to p , there is a Safe-Earliest computational point of e on the path (may be p itself), say p_{SE} , and there are no subsequent uses of e on that path (i.e., between p_{SE} and p)

Think: e should be *delayed* at least up to point p .

Note: $DELAY(p)$ preserves down-safety, and therefore preserves computational optimality!

Why?

Delayedness (cont'd)

$DELAY_{in}(b)$, $DELAY_{out}(b)$:

$DELAY(p)$ at entry and exit of b respectively.

$$DELAY_{in}(b) = (ANT_{in}(b) \cap EARL_{in}(b)) \cup \begin{cases} \phi & \text{if } b = s \\ \bigcap_{j \in \text{pred}(b)} DELAY_{out}(j) & \text{otherwise} \end{cases}$$

$$DELAY_{out}(b) = DELAY_{in}(b) \cap \overline{ANT_{loc}(b)}$$

Latestness

$LATEST(p)$:

$e \in LATEST(p)$ if p is a *computationally optimal* point for computing e and, for every path q from p to `exit`, any later optimal point on q occurs after a use of e on q .

Say: e is *latest* at point p

$LATEST_{in}(b)$:

$LATEST(p)$ at entry to block b .

$$LATEST_{in}(b) = DELAY_{in}(b) \cap \overline{(ANT_{loc}(b) \cup \bigcap_{j \in \text{succ}(b)} DELAY_{in}(j))}$$

Isolatedness

$ISOL_{out}(b)$:

$e \in ISOL_{out}(b)$ if and only if, on every path from a successor block to `exit`, a use of e is preceded by an optimal computation point of e .

$ISOL_{in}(b)$:

Similar, but think of b itself as being a successor block of the entry point of b .

$$ISOL_{out}(b) = \begin{cases} \phi & \text{if } b \text{ is an exit block} \\ \bigcap_{j \in \text{succ}(b)} ISOL_{in}(j) & \text{otherwise} \end{cases}$$

$$ISOL_{in}(b) = LATEST_{in}(b) \cup (ISOL_{out}(b) \cap \overline{ANT_{loc}(b)})$$

Culmination

The lifetime-optimal points

$$OPT(b) = LATEST_{in}(b) \cap \overline{ISOL_{out}(b)}$$

The redundant expressions

$$REDN(b) = ANT_{loc}(b) \cap \overline{LATEST_{in}(b) \cap ISOL_{out}(b)}$$

The Transformation for an Expression e

- Introduce a new auxiliary variable, h , for e
- Replace e with h in each block b such that $e \in REDN(b)$
- Insert $h = e$ at entry of each node b such that $e \in OPT(b)$

Implementation of Lazy Code Motion

Dataflow Analyses

- Use bit vectors and the iterative algorithm
- Use actual basic blocks, not individual statements
- Again, number the expressions *carefully*
 - Use global reassociation and global value numbering
 - Textually identical expressions → same number

Code generation

- Split critical edges and other edges to blocks with multiple successors
- May need to insert code at entry *or interior* of basic blocks
- *Important*: Check for zero-trip loops when moving computations out of loops