```
Product Table:
```

```
CREATE TABLE product (
  id int NOT NULL AUTO_INCREMENT,
  name varchar(255) NOT NULL,
  price decimal(10,2) NOT NULL,
  PRIMARY KEY (id)
);
Customer Table:
CREATE TABLE customer (
  id int NOT NULL AUTO_INCREMENT,
  name varchar(255) NOT NULL,
  address varchar(255) NOT NULL,
 PRIMARY KEY (id)
);
Manufacturer Table:
CREATE TABLE manufacturer (
 id int NOT NULL AUTO_INCREMENT,
```

```
name varchar(255) NOT NULL,
  PRIMARY KEY (id)
);
<?xml version='1.0' encoding='utf-8'?>
<!DOCTYPE hibernate-configuration PUBLIC</pre>
    "-//Hibernate/Hibernate Configuration DTD 3.0//EN"
    "http://hibernate.sourceforge.net/hibernate-configuration-3.0.dtd">
<hibernate-configuration>
  <session-factory>
    <!-- Database connection settings -->
    property
name="connection.driver_class">com.mysql.jdbc.Driver</property>
    property
name="connection.url">jdbc:mysql://localhost:3306/test</property>
    connection.username">root/property>
    cproperty name="connection.password"></property>
    <!-- JDBC connection pool (use the built-in) -->
```

```
cproperty name="connection.pool_size">1/property>
    <!-- SQL dialect -->
    cproperty name="dialect">org.hibernate.dialect.MySQL5Dialect/property>
    <!-- Disable the second-level cache -->
    property
name="cache.provider_class">org.hibernate.cache.NoCacheProvider</property>
    <!-- Echo all executed SQL to stdout -->
    cproperty name="show sql">true
    <!-- Drop and re-create the database schema on startup -->
    cproperty name="hbm2ddl.auto">create/property>
    <!-- Names the annotated entity class -->
    <mapping class="Product"/>
    <mapping class="Customer"/>
    <mapping class="Manufacturer"/>
  </session-factory>
</hibernate-configuration>
```

i) insert a new record inside product table

```
Session session = sessionFactory.openSession();
Transaction tx = null;
try {
 tx = session.beginTransaction();
 Product product = new Product();
 product.setName("Product 1");
 Customer customer = new Customer();
 customer.setName("Customer 1");
 Manufacturer manufacturer = new Manufacturer();
 manufacturer.setName("Manufacturer 1");
 product.setCustomer(customer);
 product.setManufacturer(manufacturer);
 session.save(product);
 tx.commit();
catch (HibernateException e) {
 if (tx!=null) tx.rollback();
 e.printStackTrace();
}
```

```
finally {
 session.close();
}
ii) update an existing record in product table
Session session = sessionFactory.openSession();
Transaction tx = null;
try {
 tx = session.beginTransaction();
 Product product = (Product)session.get(Product.class, 1);
 product.setName("Updated Product 1");
 session.update(product);
 tx.commit();
}
catch (HibernateException e) {
 if (tx!=null) tx.rollback();
 e.printStackTrace();
}
finally {
 session.close();
}
```

iii) delete an existing record from product table

```
Session session = sessionFactory.openSession();
Transaction tx = null;
try {
 tx = session.beginTransaction();
 Product product = (Product)session.get(Product.class, 1);
 session.delete(product);
 tx.commit();
}
catch (HibernateException e) {
 if (tx!=null) tx.rollback();
 e.printStackTrace();
}
finally {
 session.close();
}
```

iv) execute an query and return the manufacturer list for a given product name.

```
Session session = sessionFactory.openSession();
```

```
Transaction tx = null;
try {
 tx = session.beginTransaction();
 List manufacturers = session.createQuery("FROM Manufacturer m WHERE
m.name = :name").setParameter("name", "Manufacturer 1").list();
 for (Iterator iterator = manufacturers.iterator(); iterator.hasNext();){
   Manufacturer manufacturer = (Manufacturer) iterator.next();
   System.out.println(manufacturer.getName());
 }
 tx.commit();
}
catch (HibernateException e) {
 if (tx!=null) tx.rollback();
 e.printStackTrace();
}
finally {
 session.close();
}
```