

Server Document

(۱) فرمت results به صورت json می باشد و تمامی کلماتی که در "" قرار دارند به عنوان key هستند. در صورتی که value آنها فقط یک کلمه باشد از نوشتن آن خودداری شده، در غیر این صورت فرمت value نوشته شده است.

(۲) در صورتی که client بخواهد تاریخی را به سرور بفرستد باید سال، ماه و روز را جداگانه بفرستد (year,month,day). سرور تاریخ را به صورت یک رشته با این فرمت ("year-month-day") به client می فرستد.

Page name	Address	Info that client sends	Info that server sends back	description
Register	Ip/register	All the fields in register page	Results { "projects" : [{ "projectID" , "projectName" } , [list of user tasks in this project -> "tasks": [{ "taskName" , "taskID" }]] }	<p>The length of list of "projects" can be more than 1(there is more than 1 project for this user)</p> <p>-----</p> <p>If successful="False"- → if error="exist" : username exist</p> <p>-----</p> <p>The value of "projects" is a list including all user's projects and her/his tasks in that project.</p> <p>-----</p> <p>The length of list of "tasks" can be more</p>

				than 1(there is more than 1 task for this user in this project)
Login	lp/login	username and password	Results { "projects" : [{"projectID" , "projectName" } , [list of user tasks in this project -> "tasks": [{ "taskName" , "taskID" }]] }	<p>The length of list of "projects" can be more than 1(there is more than 1 project for this user)</p> <p>-----</p> <p>If successful="False" - → if error="incorrect" : the username or password is incorrect</p> <p>-----</p> <p>The value of "projects" is a list including all user's projects and her/his tasks in that project.</p> <p>-----</p> <p>The length of list of "tasks" can be more than 1(there is more than 1 task for this user in this project)</p>
Profile	lp/view_profile	username	Results { "projects" : [{"projectID" , "projectName" } , [list of user tasks in this project -> "tasks": [{ "taskName" , "taskID" }]] }	<p>The length of list of "projects" can be more than 1(there is more than 1 project for this user)</p> <p>-----</p> <p>The value of "projects" is a list including all user's projects and her/his tasks in that project.</p> <p>-----</p> <p>The length of list of "tasks" can be more than 1(there is more</p>

				than 1 task for this user in this project)
Project info	lp/projectInfo	projectID	Results { "successful", "projectInfo" : [{ "projectID", "projectName", "managerName", "managerUser", "project_info", "progress", "pDeadline" }] }	
Project users	lp/project_users	projectID	Results { "successful", "project_users" : [{ "username", "name", "password" }] }	The length of list of "project_users" can be more than 1
Project tasks	lp/project_tasks	projectID	Results { "successful", "project_tasks" : [{ "taskID", "taskName" }] }	The length of list of "project_tasks" can be more than 1
Task info	lp/taskInfo	taskID	Results { "successful", "taskInfo" : [{ "taskID", "taskName", "task_info", "username", "projectID", "deadline", "status" }] }	Status="1" : doing ----- Status="2" : done by user ----- Status="3" : accepted by manager
Add member	lp/addMember	username,projectID	Results {"successful"}	If successful="False" - → if error='1' : username is already added to this project ----- If error='2' : username doesn't exist.
addTask	lp/addTask	username,projectID,taskName,task_info,deadline	Results{"successful"}	If successful='False' - → if error='1' : username doesn't exist. ----- If error='2' : username isn't added to this project
addProject	lp/addProject	username,projectName,project_info,pDeadline	Results{"successful"}	
Delete a project	lp/deleteProject	projectID	Results{"Successful"}	
Edit project	lp/editProject	projectID,projectName,pro	Results{"successful"}	

		ject_info,pDeadline		
Edit Task	lp/editTask	taskID,username,taskName,task_info,deadline,projectID	Results{"Successful"}	If "successful"="false"- →if "error"='1' : this username is not a member of this project