

www.phoronix-test-suite.com

## unpackvanilla2

Intel Core i7-8850H testing with a Dell 0WCMKT (1.7.3 BIOS) and Intel UHD 630 3GB on Fedora 32 via the Phoronix Test Suite.

# Phoronix Test Suite

#### unpackvanilla2

### **Test Systems:**

#### PM981 NVMe Samsung

Processor: Intel Core i7-8850H @ 4.30GHz (6 Cores / 12 Threads), Motherboard: Dell 0WCMKT (1.7.3 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16384MB, Disk: PM981 NVMe Samsung 512GB, Graphics: Intel UHD 630 3GB (1150MHz), Audio: Realtek ALC3246, Network: Intel I219-LM + Qualcomm Atheros QCA6174 802.11ac

OS: Fedora 32, Kernel: 5.7.7nocamflow0.7.0+ (x86\_64), Desktop: GNOME Shell 3.36.7, Display Server: X Server 1.20.9 + Wayland, Display Driver: modesetting 1.20.9, OpenGL: 4.6 Mesa 20.2.2, Compiler: GCC 10.2.1 20201016 + Clang 10.0.1, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: MFLAGS= MAKEFLAGS= Disk Notes: NONE / relatime.rw.seclabel

Processor Notes: Scaling Governor: intel\_pstate powersave

Security Notes: SELinux + itlb\_multihit: KVM: Mitigation of Split huge pages + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec\_store\_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre\_v1: Mitigation of usercopy/swapgs barriers and \_\_user pointer sanitization + spectre\_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS\_FW STIBP: conditional RSB filling + srbds: Mitigation of Microcode + tsx\_async\_abort: Mitigation of Clear buffers; SMT vulnerable

#### PM981 NVMe Samsung


Unpacking The Linux Kernel - linux-4.15.tar.xz (sec) 5.67

Standard Deviation 0.9%

Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com



## unpackvanilla2



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 11 December 2020 12:17.

Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com