



phpbenchoff1

Intel Core i7-8850H testing with a Dell 0WCMKT (1.7.3 BIOS) and Intel UHD 630 3GB on Fedora 32 via the Phoronix Test Suite.

Test Systems:

Intel Core i7-8850H - Intel UHD 630 3GB - Dell 0WCMKT

Processor: Intel Core i7-8850H @ 4.30GHz (6 Cores / 12 Threads), Motherboard: Dell 0WCMKT (1.7.3 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16384MB, Disk: PM981 NVMe Samsung 512GB, Graphics: Intel UHD 630 3GB, Audio: Realtek ALC3246, Network: Intel I219-LM + Qualcomm Atheros QCA6174 802.11ac

OS: Fedora 32, Kernel: 5.7.7camflow0.7.0+ (x86_64), Desktop: GNOME Shell 3.36.7, Display Server: X Server 1.20.9 + Wayland, Display Driver: modesetting 1.20.9, OpenGL: 4.6 Mesa 20.2.2, Compiler: GCC 10.2.1 20201016 + Clang 10.0.1, File-System: ext4, Screen Resolution: 1920x1080


Processor Notes: Scaling Governor: intel_pstate powersave

Security Notes: SELinux + itlb_multihit: KVM: Mitigation of Split huge pages + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling + srbsds: Vulnerable: No microcode + tsx_async_abort: Mitigation of Clear buffers; SMT vulnerable

Intel Core i7-8850H - Intel UHD
630 3GB - Dell 0WCMKT

PHPBench - P.B.S (Score) 709023

Standard Deviation 0.2%



This file was automatically generated via the Phoronix Test Suite benchmarking software on Monday, 14 December 2020 20:09.