

www.phoronix-test-suite.com

# mcperfprovbpf2

Intel Core i7-8850H testing with a Dell 0WCMKT (1.7.3 BIOS) and Intel CoffeeLake-H GT2 [UHD 630] 2GB on Fedora 34 via the Phoronix Test Suite.

# Phoronix Test Suite

#### mcperfprovbpf2

### **Test Systems:**

#### Intel Core i7-8850H - Intel CoffeeLake-H GT2 [UHD

Processor: Intel Core i7-8850H @ 4.30GHz (6 Cores / 12 Threads), Motherboard: Dell 0WCMKT (1.7.3 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16384MB, Disk: PM981 NVMe Samsung 512GB, Graphics: Intel CoffeeLake-H GT2 [UHD 630] 2GB (1150MHz), Audio: Realtek ALC3246, Network: Intel I219-LM + Qualcomm Atheros QCA6174 802.11ac

OS: Fedora 34, Kernel: 5.11.2provbpf0.1.0+ (x86\_64), Desktop: GNOME Shell 40.0, Display Server: X Server, Compiler: GCC 11.0.1 20210324 + Clang 12.0.0, File-System: btrfs, Screen Resolution: 1920x1080

Compiler Notes: --build=x86\_64-redhat-linux --disable-libunwind-exceptions --enable-\_cxa\_atexit --enable-bootstrap --enable-cet --enable-checking=release --enable-gnu-indirect-function --enable-gnu-unique-object --enable-initfini-array --enable-languages=c,c++,fortran,objc,obj-c++,ada,go,d,lto --enable-multilib --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-arch\_32=i686 --with-gcc-major-version-only --with-linker-hash-style=gnu --with-tune=generic --without-cuda-driver

Processor Notes: Scaling Governor: intel\_pstate powersave


Security Notes: itlb\_multihit: KVM: Mitigation of VMX disabled + I1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec\_store\_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre\_v1: Mitigation of usercopy/swapgs barriers and \_\_user pointer sanitization + spectre\_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS\_FW STIBP: conditional RSB filling + srbds: Mitigation of Microcode + tsx\_async\_abort: Mitigation of Clear buffers; SMT vulnerable


	Intel Core i7-8850H - Intel CoffeeLake-H GT2 [UHD
Memcached mcperf - Add - 64 (Operations/sec)	41359
Standard Deviation	0.5%
Memcached mcperf - Get - 64 (Operations/sec)	62153
Standard Deviation	0.2%
Memcached mcperf - Set - 64 (Operations/sec)	41371
Standard Deviation	0.5%
Memcached mcperf - Append - 64 (Operations/sec)	43166
Standard Deviation	0.1%
Memcached mcperf - Delete - 64 (Operations/sec)	61763
Standard Deviation	0.3%


Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com




#### mcperfprovbpf2










Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com



## mcperfprovbpf2



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 21 May 2021 13:36.

Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com