

www.phoronix-test-suite.com

# mcperfvanilla1

Intel Core i7-8850H testing with a Dell 0WCMKT (1.7.3 BIOS) and Intel CoffeeLake-H GT2 [UHD 630] 3GB on Fedora 34 via the Phoronix Test Suite.

# Phoronix Test Suite

#### mcperfvanilla1

### **Test Systems:**

#### Intel Core i7-8850H - Intel CoffeeLake-H GT2 [UHD

Processor: Intel Core i7-8850H @ 4.30GHz (6 Cores / 12 Threads), Motherboard: Dell 0WCMKT (1.7.3 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16384MB, Disk: PM981 NVMe Samsung 512GB, Graphics: Intel CoffeeLake-H GT2 [UHD 630] 3GB, Audio: Realtek ALC3246, Network: Intel I219-LM + Qualcomm Atheros QCA6174 802.11ac

OS: Fedora 34, Kernel: 5.11.2 (x86\_64), Desktop: GNOME Shell 40.0, Display Server: X Server + Wayland, OpenGL: 4.6 Mesa 21.0.2, Compiler: GCC 11.0.1 20210324, File-System: btrfs, Screen Resolution: 1920x1080

Compiler Notes: --build=x86\_64-redhat-linux --disable-libunwind-exceptions --enable-\_\_cxa\_atexit --enable-bootstrap --enable-cet --enable-checking=release --enable-gnu-indirect-function --enable-gnu-unique-object --enable-initfini-array --enable-languages=c,c++,fortran,objc,obj-c++,ada,go,d,lto --enable-multilib --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-arch\_32=i686 --with-gcc-major-version-only --with-linker-hash-style=gnu --with-tune=generic --without-cuda-driver

Processor Notes: Scaling Governor: intel\_pstate powersave


Security Notes: SELinux + itlb\_multihit: KVM: Mitigation of VMX disabled + I1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec\_store\_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre\_v1: Mitigation of usercopy/swapgs barriers and \_\_user pointer sanitization + spectre\_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS\_FW STIBP: conditional RSB filling + srbds: Mitigation of Microcode + tsx\_async\_abort: Mitigation of Clear buffers; SMT vulnerable

	Intel Core i7-8850H - Intel CoffeeLake-H GT2 [UHD
Memcached mcperf - Add - 64 (Operations/sec)	43909
Standard Deviation	0.6%
Memcached mcperf - Get - 64 (Operations/sec)	67839
Standard Deviation	0.3%
Memcached mcperf - Set - 64 (Operations/sec)	44312
Standard Deviation	0.9%
Memcached mcperf - Append - 64 (Operations/sec)	46785
Standard Deviation	0.3%
Memcached mcperf - Delete - 64 (Operations/sec)	67649
Standard Deviation	0.2%


Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com




#### mcperfvanilla1










Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com



## mcperfvanilla1



This file was automatically generated via the Phoronix Test Suite benchmarking software on Wednesday, 19 May 2021 10:01.

Phoronix Test Suite v9.0.1 www.phoronix-test-suite.com