



## **phpbenchvanilla02**

Intel Core i7-8850H testing with a Dell 0WCMKT (1.7.3 BIOS) and Intel UHD 630 3GB on Fedora 32 via the Phoronix Test Suite.

## Test Systems:

### Intel Core i7-8850H - Intel UHD 630 3GB - Dell 0WCMKT

Processor: Intel Core i7-8850H @ 4.30GHz (6 Cores / 12 Threads), Motherboard: Dell 0WCMKT (1.7.3 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16384MB, Disk: PM981 NVMe Samsung 512GB, Graphics: Intel UHD 630 3GB (1150MHz), Audio: Realtek ALC3246, Network: Intel I219-LM + Qualcomm Atheros QCA6174 802.11ac


OS: Fedora 32, Kernel: 5.9.11nocamflow0.7.1+ (x86\_64), Desktop: GNOME Shell 3.36.7, Display Server: X Server 1.20.9 + Wayland, Display Driver: modesetting 1.20.9, OpenGL: 4.6 Mesa 20.2.2, Compiler: GCC 10.2.1 20201016 + Clang 10.0.1 + LLVM 10.0.1, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: MFLAGS= MAKEFLAGS=

Processor Notes: Scaling Governor: intel\_pstate powersave

Security Notes: SELinux + itlb\_multihit: KVM: Mitigation of VMX disabled + I1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec\_store\_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre\_v1: Mitigation of usercopy/swaps barriers and \_\_user pointer sanitization + spectre\_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS\_FW STIBP: conditional RSB filling + srbsds: Mitigation of Microcode + tsx\_async\_abort: Mitigation of Clear buffers; SMT vulnerable

Intel Core i7-8850H - Intel UHD 630 3GB - Dell 0WCMKT	
PHPBench - P.B.S (Score)	701912
Standard Deviation 0.2%	



*This file was automatically generated via the Phoronix Test Suite benchmarking software on Saturday, 9 January 2021 18:57.*