

# SSH Access & Live Logs — Travel Partner Server

This README explains how SSH access to your DigitalOcean `45.55.78.67` works, how others can securely log in, and how to view live console logs from your Spring Boot service.

---



## 1 . Logging into your droplet

### Your current PowerShell command

```
ssh -i "C:\Users\Ali Computers\.ssh\id_rsa" root@45.55.78.67
```

**Explanation:** `ssh` → initiates a secure shell connection. `-i` specifies the private key file on your PC. `- root@45.55.78.67` → logs in as user `root` to your droplet.

Your **private key** (`id_rsa`) acts as a **digital key**. Only a computer with this exact file can log in. If someone else tries this command without your private key, they'll get:

```
Permission denied (publickey).
```



## 2 . How another person can access the server (securely)

If you want another developer to log in, they must use **their own SSH key pair**.

### Step 1 . They generate an SSH key pair on their system

On macOS, Linux, or Windows (PowerShell):

```
ssh-keygen -t rsa -b 4096 -C "developer@example.com"
```

This generates two files: `~/.ssh/id_rsa` (private key — keep secret) - `~/.ssh/id_rsa.pub` (public key — can be shared)

### Step 2 . They send you their public key

The contents of `id_rsa.pub` will look like:

```
ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQD... developer@example.com
```

### Step 3 . You add their public key to your droplet

SSH into your droplet and run:

```
sudo mkdir -p /root/.ssh  
sudo nano /root/.ssh/authorized_keys
```

Paste their public key at the end of the file (one line per user). Save and exit ( `Ctrl + O`, `Enter`, `Ctrl + X` ).

Then fix permissions:

```
sudo chmod 600 /root/.ssh/authorized_keys  
sudo chown root:root /root/.ssh/authorized_keys
```

### Step 4 . They connect using their own private key

Example command from their PC or Mac:

```
ssh -i ~/.ssh/id_rsa root@45.55.78.67
```

✓ Each developer has a unique key — safe and traceable.

To revoke access, remove their line from `/root/.ssh/authorized_keys`.



## 3 . Security tips

- **Never share** your private key ( `id_rsa` ).
- Use separate keys for each developer.
- Disable password authentication in `/etc/ssh/sshd_config`:

```
PasswordAuthentication no
```

Then restart SSH:

```
sudo systemctl restart ssh
```

- Keep your private key safe (don't email or upload it).



## 4 . Viewing live console logs

Your Spring Boot app runs under `systemd` as a service named `travel-partner.service`.

### View live logs (follow mode)

```
sudo journalctl -u travel-partner.service -f
```

### View last 1 0 0 lines

```
sudo journalctl -u travel-partner.service -n 100
```

### Filter logs for specific terms (e.g., ERROR)

```
sudo journalctl -u travel-partner.service | grep ERROR
```

### Stop viewing logs

Press `Ctrl + C` to stop following.



## 5 . Optional: Log to file

To save logs for future review, add these lines to your service file:

```
StandardOutput=append:/var/log/travel-partner.log  
StandardError=append:/var/log/travel-partner-error.log
```

Then reload and restart:

```
sudo systemctl daemon-reload  
sudo systemctl restart travel-partner.service
```

Tail the file:

```
tail -f /var/log/travel-partner.log
```



## 6 . Summary of key commands

| Purpose                       | Command                                                                   |
|-------------------------------|---------------------------------------------------------------------------|
| SSH into droplet              | <code>ssh -i "C:\Users\Ali Computers\.ssh\id_rsa" root@45.55.78.67</code> |
| Add another user's public key | <code>sudo nano /root/.ssh/authorized_keys</code>                         |
| Restart service               | <code>sudo systemctl restart travel-partner.service</code>                |
| Check service status          | <code>sudo systemctl status travel-partner.service -l</code>              |
| Follow live logs              | <code>sudo journalctl -u travel-partner.service -f</code>                 |
| View logs in file             | <code>tail -f /var/log/travel-partner.log</code>                          |

**End of document — SSH access & live log management guide for Travel Partner server.**