5COSC024W Server-side Web Development Mock ICT02 – Sample Data and PHP Code

Part A PHP Code: for 9 questions on PHP in mock ICT02 (pointing to lines 1 to 85), the following PHP file was created.

somepage.php

```
01  <?php
02  session_start();
03  include("db.php");
04
05  $pagename="Confirmation";
06  echo "<link rel=stylesheet type=text/css href=mystylesheet.css>";
07  echo "<title>My ".$pagename."</title>";
08
09  include("headlayout.html");
10  echo date ('l d F Y H:i:s');
11  include ("detectlogin.php");
12  echo "<p></p>";
13  echo "<h2>".$pagename."</h2>";
14
15  $total=0;
16  $subtotal=0;
17  $currentdatetime=date('Y-m-d H:i:s');
18
19  $SQL1="insert into orders (userId,orderDateTime)
20  values (".$_SESSION['c_userid'].", '".$currentdatetime."')";
21  $exeSQL1=mysql_query($SQL1);
22
23  if (mysql_errno($conn)==0)
24  {
25        $SQL2="select max(orderNo) as maxno from orders
26        where userId=".$_SESSION['c_userid'];
27        $exeSQL2=mysql_query($SQL2) or die(mysql_error());
28        $results2=mysql_fetch_array($exeSQL2);
29        $latestorderNo=$results2['maxno'];
30        echo "<p>Your order has been placed successfully";
31        echo "<b><p>ORDER NO: ".$latestorderNo."</b>";
32
33        echo "<table border=1 cellpadding=5>";
34        echo "<tr>";
35        echo "<th>Name</th>";
36        echo "<th>Price</th>";
37        echo "<th>Quantity</th>";
38        echo "<th>Subtotal</th>";
39        echo "</tr>";
40
41        foreach ($_SESSION['place'] as $indexprodid => $quantityinbasket)
42        {
43              if ($indexprodid>0)
44              {
45                    $SQL3="select prodId, prodName, prodPrice
46                    from product where prodId=".$indexprodid;
47                    $exeSQL3=mysql_query($SQL3) or die(mysql_error());
48                    $results3=mysql_fetch_array($exeSQL3);
49                    $subtotal=$quantityinbasket * $results3['prodPrice'];
50
51                    $SQL4="insert into
52                    order_line (orderNo, prodId, quantityOrdered, subTotal)
53                    values (".$latestorderNo.",".$indexprodid.",
54                    ".$quantityinbasket.",".$subtotal.")";
55                    $exeSQL4=mysql_query($SQL4) or die(mysql_error());
```

somepage.php (continued)

```
56                  echo "<tr>";
57                  echo "<td>".$prodinbasketarray['prodName']."</td>";
58                  echo "<td>GBP".$prodinbasketarray['prodPrice']."</td>";
59                  echo "<td>".$quantityinbasket."</td>";
60                  echo "<td>GBP".number_format($subtotal,2)."</td>";
61                  echo "</tr>";
62                  $total=$total+$subtotal;
63            }
64      }
65      echo "<tr>";
66      echo "<td colspan=3><b>ORDER TOTAL</b></td>";
67      echo "<td><b>GBP".number_format($total,2)."</b></td>";
68      echo "</tr>";
69      echo "</table>";
70
71      $SQL5="UPDATE orders SET orderTotal=".$total."
72      WHERE orderNo=".$latestorderNo;
73      $exeSQL5 = mysql_query($SQL5) or die (mysql_error());
74
75      echo "<br>To leave the system <a href=logout.php>Logout</a>";
76  }
77  else
78  {
79      echo "<p>Sorry there has been an error with your order";
80      echo "Go back to <a href=basket.php>My Basket</a>";
81  }
82
83  include("footlayout.html");
84  ?>
85
```

Sample Data: for 2 questions on PHP in this mock ICT02 (pointing to lines 101 to 122), the following two tables ***Album*** and ***Album_Copy*** were created in the MySQL database.

Album

albumCode	albumTitle	artist	yearOfRelease
912	Abbey Road	The Beatles	1969
354	The Wall	Pink Floyd	1979
770	Wu-Tang Forever	Wu-Tang Clan	1997

Album_Copy

copyCode	albumCode	purchaseDate	conditions
1355	354	2011-02-28	Good
3454	912	2010-09-27	OK
9822	354	2012-01-22	Damaged
7453	770	2011-04-14	Excellent
8903	912	2011-10-03	Damaged

PHP Code: for the same 2 questions on PHP in this mock ICT02 (pointing to line 101 to 122), the following PHP file was created.

initialpage.php

```
101  <?php
102  include("db.php");
103  echo "<html>";
104  echo "<body>";
105  echo "<h1>INITIAL PAGE</h1>";
106
107  $SQL="select * from Album order by albumCode";
108  $exeSQL=mysqli_query($conn, $SQL) or die(mysqli_error($conn));
109
110  while ($results=mysqli_fetch_array($exeSQL))
111  {
112        echo "<br><a href=followingpage.php?u_id=".$results['albumCode'].">";
113        echo $results['albumTitle']."||";
114        echo "</a>";
115        echo $results['artist']."||";
116        echo $results['yearOfRelease']."||";
117  }
118
119  echo "</body>";
120  echo "</html>";
121  ?>
122
```

Part B NODE Code: for 4 questions on Node.js in mock ICT02 (pointing to lines 201 to 240), the following JavaScript file was created.

Index.js

```
201 const express = require("express");
202 const app = express();
203 const dotenv = require("dotenv");
204 const mongoose = require("mongoose");
205 const TodoTask = require("./models/TodoTask");
206
207 dotenv.config();
208 app.use(express.urlencoded({ extended: true }));
209
210 mongoose.connect(process.env.DB_CONNECT)
211       .then(() => {
212             console.log("Connected to db!");
213             app.listen(3000, () => console.log("Server Up and running"));
214       })
215       .catch((err) => { console.error(err); });
216
217 app.set("view engine", "ejs");
218
219 app.get('/', (req, res) => {
220       res.render("todo.ejs");
221 });
222
223 app.post('/', (req, res) => {
224       console.log(req.body);
225 });
226
227 app.post('/', async (req, res) => {
228       const todoTask = new TodoTask({
229             content: req.body.content
230       });
231       try {
232             await todoTask.save();
233             res.redirect("/");
234       } catch (err) {
235             res.send(500, err);
236             res.redirect("/");
237       }
238 });
239
240
```