

CS340 – Advanced Data Structures and Algorithm Design – Fall 2020
Assignment 3 – September 25, 2020

Dr. Sandra Zilles, Department of Computer Science, University of Regina

due October 5, 2020, 10.00 am

- Please submit one single pdf for your solution to all problems, including code printouts and printouts of results from running your code, through URCourses.
- Please submit your C++ code (compilable in Visual Studio or g++) for the solution of the programming part in UR Courses, in addition to the printed version of the code. In UR Courses, please submit everything related to your code in a single zip file.

Problem 1 (3+3+1 marks).

- (a) Show the result of inserting 10, 12, 1, 14, 6, 5, 8, 15, 3, 9, 7, 4, 11, 13, and 2, one at a time, into an initially empty binary heap. Additionally, show the intermediate result after every single insertion. (This is an extension of textbook problem 6.2(a).)
- (b) Show the result of using the linear-time algorithm to build a binary heap using the same input. (This is textbook problem 6.2(b).)
- (c) Show the results of two consecutive `deleteMin` operations on the 3-heap in Figure 6.19 in the textbook.

Problem 2 (2+3 marks).

- (a) Show that, in any heap, the maximum item must be at one of the leaves. (This is textbook problem 6.8(a).)
- (b) Show that any binary heap contains exactly $\lceil N/2 \rceil$ leaves. (This is textbook problem 6.8(b).)

Problem 3 (4+2+2 marks).

- (a) Implement the following algorithm, which is given a duplicate-free array `array` as input, in C++.
`whatDoIDo (array):`
 - 1) Build a heap from `array` (using `buildHeap` as explained in class), where the heap starts at position `array[0]`.
 - 2) Starting from `j = size of array - 1`, as long as `j > 0`:
 - i. Swap the entries `array[0]` and `array[j]`.
 - ii. Percolate down `array[0]`, but only within the subarray `array[0..j-1]`.
 - iii. Decrement `j` by 1.

Provide three input/output examples for duplicate-free arrays of size about 10.

- (b) What does `whatDoIDo` do? Explain your answer.
- (c) What is the worst-case running time of `whatDoIDo`, in dependence of the size N of the given array? Explain your answer.