

Data Mining



HIERARCHICAL CLUSTERING



Prof. Dr. Hikmat Ullah Khan
Department of Information Technology

UNIVERSITY OF SARGODHA, SARGODHA

Lesson from Holy Quran

2

يَا أَيُّهَا النَّاسُ إِنَّا خَلَقْنَاكُمْ مِنْ ذَكَرٍ
وَأُنْثَىٰ وَجَعَلْنَاكُمْ شُعُوبًا وَقَبَائِلَ
لِتَعَارَفُوا إِنَّ أَكْرَمَكُمْ عِنْدَ اللَّهِ أَتَقَاهُمْ
إِنَّ اللَّهَ عَلِيمٌ خَبِيرٌ ﴿١٣﴾

O humanity! Indeed, We created you from a male and a female, and made you into peoples and tribes so that you may 'get to' know one another. Surely the most noble of you in the sight of Allah is the most righteous among you. Allah is truly All-Knowing, All-Aware.¹

Quran
Chapter 49 (Al Hujurat)
Verse 13

Types of Clusterings

3

- Important distinction between **hierarchical** and **partitional** sets of clusters
- Partitional Clustering
 - A division data objects into non-overlapping subsets (clusters) such that each data object is in exactly one subset
- Hierarchical clustering
 - A set of nested clusters organized as a hierarchical tree


Hierarchical Clustering

4


- Two main types of hierarchical clustering
 - ▣ Agglomerative:
 - Start with the points as individual clusters
 - At each step, merge the closest pair of clusters until only one cluster (or k clusters) left
 - ▣ Divisive:
 - Start with one, all-inclusive cluster
 - At each step, split a cluster until each cluster contains a point (or there are k clusters)
- Traditional hierarchical algorithms use a similarity or distance matrix
 - ▣ Merge or split one cluster at a time

Hierarchical Clustering


5




Traditional Hierarchical Clustering



Traditional Dendrogram



Non-traditional Hierarchical Clustering





Non-traditional Dendrogram

Hierarchical Clustering

6

- Produces a set of nested clusters organized as a hierarchical tree
- Can be visualized as a dendrogram
 - ▣ A tree like diagram that records the sequences of merges or splits



Strengths of Hierarchical Clustering

7

- Do not have to assume any particular number of clusters
 - ▣ Any desired number of clusters can be obtained by 'cutting' the dendrogram at the proper level

- They may correspond to meaningful taxonomies
 - ▣ Example in biological sciences (e.g., animal kingdom, ...)

Agglomerative Clustering Algorithm


8

- More popular hierarchical clustering technique
- Basic algorithm is straightforward
 1. Compute the proximity matrix
 2. Let each data point be a cluster
 3. **Repeat**
 4. Merge the two closest clusters
 5. Update the proximity matrix
 6. **Until** only a single cluster remains
- Key operation is the computation of the proximity of two clusters
 - ▣ Different approaches to defining the distance between clusters distinguish the different algorithms

How to Define Inter-Cluster Similarity

9

- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - ▣ Ward's Method uses squared error




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						

Proximity Matrix

How to Define Inter-Cluster Similarity

10

- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - ▣ Ward's Method uses squared error




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						

Proximity Matrix

How to Define Inter-Cluster Similarity

11

- MIN
- **MAX**
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - ▣ Ward's Method uses squared error




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						

Proximity Matrix

How to Define Inter-Cluster Similarity

12

- MIN
- MAX
- **Group Average**
- Distance Between Centroids
- Other methods driven by an objective function
 - ▣ Ward's Method uses squared error




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						

· Proximity Matrix
·

How to Define Inter-Cluster Similarity

13

- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - ▣ Ward's Method uses squared error



	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						


Proximity Matrix

Cluster Similarity: MIN

14

- Similarity of two clusters is based on the two most similar (closest) points in the different clusters
 - Determined by one pair of points, i.e., by one link in the proximity graph.

	I1	I2	I3	I4	I5
I1	1.00	0.90	0.10	0.65	0.20
I2	0.90	1.00	0.70	0.60	0.50
I3	0.10	0.70	1.00	0.40	0.30
I4	0.65	0.60	0.40	1.00	0.80
I5	0.20	0.50	0.30	0.80	1.00



example to create Hierarchical Clustering using MIN

15


Point	X coordinate	Y coordinate
P1	0.40	0.53
P2	0.22	0.38
P3	0.35	0.32
P4	0.26	0.19
P5	0.08	0.41
P6	0.45	0.30

Proximity matrix (Euclidean Distance)


16

	P1	P2	P3	P4	P5	p6
P1	0.00	0.24	0.22	0.37	0.34	0.23
P2	0.24	0.00	0.15	0.20	0.14	0.25
P3	0.22	0.15	0.00	0.15	0.28	0.11
P4	0.37	0.14	0.28	0.00	0.29	0.39
P5	0.34	0.14	0.28	0.29	0.00	0.39
P6	0.23	0.25	0.11	0.22	0.39	0.00

Hierarchical Clustering: MIN



Nested Clusters



Dendrogram

- 1) Min distance of individual in matrix
- 2) For Grouped values, compute combined min
- 3) For instance

$$\begin{aligned}\text{Dist}(\{3,6\},\{2,5\}) &= \min(\text{dist}(3,2), \text{dist}(6,2), \text{dist}(3,5), \text{dist}(6,5)) \\ &= \min(0.15, 0.25, 0.28, 0.39) \\ &= 0.15\end{aligned}$$

Finding Distance of [3,6] from 1 and 4 as well:

$$\begin{aligned}\text{Dist}(\{3,6\},4) &= \min(\text{dist}(3,4), \text{dist}(6,4)) \\ &= \min(0.15, 0.22) \\ &= 0.15\end{aligned}$$


$$\begin{aligned}\text{Dist}(\{3,6\},1) &= \min(\text{dist}(3,1), \text{dist}(6,1)) \\ &= \min(0.22, 0.23) \\ &= 0.22\end{aligned}$$

Cluster Validity


- For supervised classification we have a variety of measures to evaluate how good our model is
 - ▣ Accuracy, precision, recall
- For cluster analysis, the analogous question is how to evaluate the “goodness” of the resulting clusters?
- Then why do we want to evaluate them?
 - ▣ To avoid finding patterns in noise
 - ▣ To compare clustering algorithms
 - ▣ To compare two sets of clusters
 - ▣ To compare two clusters

Clusters found in Random Data


Random
Points




K-means



DBSCAN




Complete Link




Measuring Cluster Validity Via Correlation

- Correlation of incidence and proximity matrices for the K-means clustering of the following two data sets.






Corr = -0.9235



Corr = -0.5810

Hierarchical Clustering: Comparison

23



Internal Measures: Cohesion and Separation

24

- **Cluster Cohesion**: Measures how closely related are objects in a cluster
 - ▣ Example: Sum of Square Error (SSE)
- **Cluster Separation**: Measure how distinct or well-separated a cluster is from other clusters
- Example: Squared Error
 - ▣ Cohesion is measured by the within cluster sum of squares (SSE)

$$WSS = \sum_i \sum_{\mathbf{x} \in C_i} (\mathbf{x} - \mathbf{m}_i)^2$$

- ▣ Separation is measured by the between cluster sum of squares

$$BSS = \sum_i |C_i| (m - m_i)^2$$


- Where $|C_i|$ is the size of cluster i

Internal Measures: Cohesion and Separation

25

□ Example: SSE

▣ BSS + WSS = constant



K=1 cluster:

$$WSS = (1 - 3)^2 + (2 - 3)^2 + (4 - 3)^2 + (5 - 3)^2 = 10$$

$$BSS = 4 \times (3 - 3)^2 = 0$$


$$Total = 10 + 0 = 10$$

Internal Measures: Cohesion and Separation

26

□ Example: SSE

▣ BSS + WSS = constant



K=1 cluster:

$$WSS = (1 - 1.5)^2 + (2 - 1.5)^2 + (4 - 4.5)^2 + (5 - 4.5)^2 = 1$$

$$BSS = 2 \times (3 - 1.5)^2 + 2 \times (4.5 - 3)^2 = 9$$

$$Total = 1 + 9 = 10$$

K=2 clusters:

$$WSS = (1 - 3)^2 + (2 - 3)^2 + (4 - 3)^2 + (5 - 3)^2 = 10$$

$$BSS = 4 \times (3 - 3)^2 = 0$$

$$Total = 10 + 0 = 10$$



OLD WISDOM OUT OF THE CLUSTER OF GATHERING SHADOWS

GEORGE MACKAY BROWN

PICTUREQUOTES.COM



PICTUREQUOTES