

1. Import Libraries

```
In [1]: import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score, classification_report
```

2. Load the Data

```
In [2]: data = pd.read_excel("Building_data.xlsx")
```

3. Data Information and Initial Cleaning

```
In [3]: data.info()

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 60718 entries, 0 to 60717
Data columns (total 4 columns):
 #   Column                                Non-Null Count  Dtype  
---  -
 0   Inund Depth obs. (m)                  60718 non-null  float64
 1   Damage Indices (0-4)                  60718 non-null  int64  
 2   Material (RC, Steel, Wood, Masonry)   60718 non-null  object  
 3   Structure (Building or Infrastructure) 60718 non-null  object  
dtypes: float64(1), int64(1), object(2)
memory usage: 1.9+ MB
```

```
In [4]: data.drop(columns=["Structure (Building or Infrastructure)"], inplace=True)
```

```
In [5]: data.head()
```

```
Out[5]:
```

	Inund Depth obs. (m)	Damage Indices (0-4)	Material (RC, Steel, Wood, Masonry)
0	-0.6	0	Masonry
1	-0.5	0	Wood
2	-0.5	0	Wood
3	-0.4	0	Masonry
4	-0.4	0	Wood

4. Renaming Columns for Clarity

```
In [6]: data.rename(columns={
    'Inund Depth obs. (m)': 'Inund Depth',
    'Damage Indices (0-4)': 'Damage Indices',
    'Material (RC, Steel, Wood, Masonry)': 'Material'
}, inplace=True)

# Print the DataFrame with renamed columns
data.head()
```

```
Out[6]:
```

	Inund Depth	Damage Indices	Material
0	-0.6	0	Masonry
1	-0.5	0	Wood
2	-0.5	0	Wood
3	-0.4	0	Masonry
4	-0.4	0	Wood

```
In [7]: from sklearn.preprocessing import MinMaxScaler

scaler = MinMaxScaler()
data['Inund Depth'] = scaler.fit_transform(data[['Inund Depth']]) # Original column overwrite ho gaya
```

5. Value Counts and Filtering the Data

```
In [8]: data["Damage Indices"].value_counts()
```

```
Out[8]: 2    23636
         4    16991
         3    13366
         1     6386
         0     339
        Name: Damage Indices, dtype: int64
```

```
In [9]: data.drop(data[(data['Damage Indices'] == 2) | (data['Damage Indices'] == 3) | (data['Damage Indices'] == 4)].index, inplace=True)
```

```
In [10]: data["Damage Indices"].value_counts()
```

```
Out[10]: 1     6386
         0     339
        Name: Damage Indices, dtype: int64
```

```
In [11]: data.shape
```

```
Out[11]: (6725, 3)
```

```
In [12]: data.duplicated().sum()
```

```
Out[12]: 6343
```

6. One-Hot Encoding for Categorical Variables

```
In [13]: pd.get_dummies(data, columns=["Damage Indices", "Material"])
```

```
Out[13]:
```

	Inund Depth	Damage Indices_0	Damage Indices_1	Material_Masonry	Material_Reinforced concrete	Material_Steel	Material_Wood
0	0.000000	1	0	1	0	0	0
1	0.004065	1	0	0	0	0	1
2	0.004065	1	0	0	0	0	1
3	0.008130	1	0	1	0	0	0
4	0.008130	1	0	0	0	0	1
...	...	...	...	...	...	...	...
46818	0.219512	0	1	0	0	0	1
54233	0.341463	1	0	0	0	0	1
54330	0.345528	0	1	0	1	0	0
55167	0.389024	0	1	0	0	0	1
56163	0.451220	0	1	0	0	0	1

6725 rows × 7 columns

```
In [14]: data = pd.get_dummies(data, columns=["Damage Indices", "Material"], drop_first=False)
data.head()
```

```
Out[14]:
```

	Inund Depth	Damage Indices_0	Damage Indices_1	Material_Masonry	Material_Reinforced concrete	Material_Steel	Material_Wood
0	0.000000	1	0	1	0	0	0
1	0.004065	1	0	0	0	0	1
2	0.004065	1	0	0	0	0	1
3	0.008130	1	0	1	0	0	0
4	0.008130	1	0	0	0	0	1

```
In [15]: data.shape
```

```
Out[15]: (6725, 7)
```

7. Define Features and Target Variables

```
In [16]: # Define features (X) and target (y)
X = data[['Inund Depth', 'Material_Reinforced concrete', 'Material_Steel', 'Material_Wood']]
y = data[['Damage Indices_0', 'Damage Indices_1']]
```

```
In [17]: y = np.argmax(y.values, axis=1)
```

8. Split the Data into Training, Validation, and Test Sets

```
In [18]: from sklearn.model_selection import train_test_split

# First, split the data into 90% training+validation and 10% testing
X_train_val, X_test, y_train_val, y_test = train_test_split(X, y, test_size=0.2, random_state=0)

# Further split the training+validation set into training (80%) and validation (20%)
X_train, X_val, y_train, y_val = train_test_split(X_train_val, y_train_val, test_size=0.2, random_state=0)
```

9. Initialize and Train the Random Forest Model

```
In [19]: # Step 4: Initialize and Train the Random Forest Model
rf = RandomForestClassifier(n_estimators=100, random_state=0)
rf.fit(X_train, y_train)
```

```
Out[19]: RandomForestClassifier
RandomForestClassifier(random_state=0)
```

(<https://scikit-learn.org/1.6/modules/generated/sklearn.ensemble.RandomForestClassifier.html>)

10. Evaluate the Model on the Test Set

```
In [20]: y_test_pred = rf.predict(X_test)
test_accuracy = accuracy_score(y_test, y_test_pred)
print("Test Accuracy:", test_accuracy)
```

Test Accuracy: 0.9472118959107807

11. Classification Report

```
In [21]: print("Classification Report (Test Set):")
print(classification_report(y_test, y_test_pred))
```

```
Classification Report (Test Set):
              precision    recall  f1-score   support

     0           0.52       0.15      0.24         72
     1           0.95       0.99      0.97       1273

 accuracy              0.95         1345
 macro avg           0.74       0.57      0.60         1345
 weighted avg           0.93       0.95      0.93         1345
```

```

In [22]: import seaborn as sns
import matplotlib.pyplot as plt
from sklearn.metrics import confusion_matrix


cm = confusion_matrix(y_test, y_test_pred)

plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues', xticklabels=[0, 1, 2], yticklabels=[0, 1, 2])

plt.title("Confusion Matrix")
plt.xlabel("Predicted Labels")
plt.ylabel("True Labels")

plt.show()

```



In []: