Convexifying Contacts in Factor Graph Smoothing for Legged Robots

Saaketh Reddy Chintha Reddy
Convexifying Autonomous Decision-making
Georgia Tech
Atlanta, USA
sreddy308@gatech.edu

***Abstract*—This paper presents a convex optimization framework for contact sequence refinement in factor graph-based state estimation for bipedal robots. Legged robots rely on contact measurements as a key sensory modality, treating foothold positions as landmarks in a factor graph optimization. However, inaccurate contacts and foot slip violate the zero-velocity assumption of the foot in contact which is critical for accurate state estimation. We propose an outer-loop convex optimization method that refines contact sequences by minimizing foot velocity residuals while preserving temporal smoothness. The contact refinement problem is formulated as a Linear Program (LP) with continuous relaxation of binary contact states, velocity threshold constraints, and total variation regularization. Implemented on top of GTSAM's fixed-lag smoother, the approach demonstrates significant improvements in state estimation accuracy on bipedal robot datasets (Unitree G1). Results show INPUT reduction in trajectory drift and INPUT improvement in contact-constrained velocity consistency compared to baseline factor graph smoothing without contact refinement.**

***Index Terms*—convex optimization, factor graph optimization, state estimation, bipedal locomotion, contact detection, legged robotics**

I. Introduction

State estimation for legged robots is a challenging problem due to the complex contact dynamics between the robot and its environment. Bipedal and quadrupedal robots experience intermittent contact phases where accurate knowledge of contact timing and locations is critical for estimating the robot's pose and velocity.

Factor graph optimization has emerged as a powerful framework for sensor fusion in robotics, enabling the integration of heterogeneous measurements such as IMU data, kinematic constraints, and contact information [1], [2]. In legged robotics, contact measurements provide kinematic constraints relating the robot body to fixed landmarks (footholds) in the world frame.

Some robots like the Agility Robotic's Cassie have a mechanical contact sensor that provides reliable contact state information. However, many bipedal robots (e.g., Unitree G1) lack such sensors and rely on indirect methods for contact detection. In practice, contact detection algorithms are based on force thresholds, kinematic analysis, or learned methods and are often noisy or have incorrect contact sequences. Furthermore, even when contact is correctly identified, foot slip violates the static foothold assumption, introducing errors into the factor graph. These issues motivate the need for contact sequence refinement.

This paper presents an outer-loop convex optimization approach that refines contact sequences by minimizing foot velocity violations and encouraging temporal smoothness.

Contributions: Our main contributions are: (1) A convex LP formulation for contact sequence refinement with velocity-based objectives, (2) Integration of the refinement loop with GTSAM's fixed-lag smoother framework, and (3) Experimental validation on real bipedal robot data demonstrating improved accuracy.

II. Problem Description

A. Factor Graph Smoothing for Bipedal Robots

We formulate the state estimation problem as maximum a posteriori (MAP) inference on a factor graph. The robot state $\mathbf{x}_t \in SE(3) \times \mathbb{R}^6$ at time t consists of the robot pose (position and orientation) and velocity:

$$\mathbf{x}_t = [\mathbf{R}_t, \mathbf{p}_t, \mathbf{v}_t] \in SE(3) \times \mathbb{R}^3 \tag{1}$$

where $\mathbf{R}_t \in SO(3)$ is the orientation, $\mathbf{p}_t \in \mathbb{R}^3$ is the position, and $\mathbf{v}_t \in \mathbb{R}^3$ is the velocity in the world frame.

B. Contacts as Landmark Measurements

In legged robot state estimation, foot contacts provide useful information about the robot's motion. The key idea is that when a foot is firmly in contact with the ground, its position in the world frame should remain approximately fixed. Therefore, a contact point can be treated similarly to a landmark in SLAM: the robot observes the same fixed point from different body poses.

Let $\mathbf{x}_t$ denote the robot state at time t, which includes the body position $\mathbf{p}_t$ and orientation $\mathbf{R}_t$. When foot i is in contact, we assume that the corresponding foothold has a fixed world-frame position $\mathbf{l}_i \in \mathbb{R}^3$. The robot can measure the position of this foot relative to its body frame through forward kinematics. This gives the measurement model

$$\mathbf{z}_t^i = \mathbf{h}(\mathbf{x}_t, \mathbf{l}_i) + \mathbf{n}_t = \mathbf{R}_t^T(\mathbf{l}_i - \mathbf{p}_t) + \mathbf{n}_t, \tag{2}$$

where $\mathbf{z}_t^i$ is the measured foot position in the body frame, and $\mathbf{n}_t \sim \mathcal{N}(\mathbf{0}, \mathbf{\Sigma}_{\text{contact}})$ represents measurement noise.

This equation has a simple interpretation. If the robot pose $\mathbf{x}_t$ and the foothold position $\mathbf{l}_i$ are correct, then transforming

the world-frame foothold into the robot body frame should match the measured foot position from kinematics. Any mismatch becomes a residual that the estimator tries to minimize.

The estimation problem can then be written as a maximum a posteriori (MAP) problem. In MAP estimation, we seek the most likely robot trajectory and foothold positions given all available measurements:

$$\mathbf{x}^*_{0:T}, \mathbf{l}^*_{1:F} = \arg\max_{\mathbf{x}_{0:T}, \mathbf{l}_{1:F}} p(\mathbf{x}_{0:T}, \mathbf{l}_{1:F} \mid \mathbf{z}_{0:T}, \mathbf{u}_{0:T}), \tag{3}$$

where $\mathbf{x}_{0:T}$ is the full robot trajectory, $\mathbf{l}_{1:F}$ are the unknown foothold positions, $\mathbf{z}_{0:T}$ are the sensor measurements, and $\mathbf{u}_{0:T}$ are the motion inputs or inertial measurements.

Equivalently this MAP problem becomes a nonlinear least-squares problem. The estimator searches for the trajectory and foothold locations that best satisfy all measurement constraints. IMU measurements encourage smooth and dynamically consistent motion between time steps, while contact measurements encourage the contacted foot to remain fixed in the world frame.

Thus, the contact measurement acts as an additional source of information that reduces drift from the IMU. Instead of only relying on the IMU, the estimator also uses the fact that a stance foot should not move relative to the ground. This makes foot contact especially valuable for legged robots, because it provides a temporary "anchor" to the world whenever a foot is in contact.

C. The Problem: Faulty Contact Sequences

The factor graph formulation assumes that contact states $c_t^i \in \{0, 1\}$ (binary: contact or no contact) are known a priori. In practice, these are estimated using:

- Force/torque sensor thresholds
- Ground reaction force estimates from kinematics
- Heuristic rules based on gait phase
- Learned classifiers using IMU and joint data (which we developed for Unitree G1 and will be using as the baseline contact detector)

These methods produce noisy contact sequences with two main failure modes:

1) **False positives**: Incorrectly detecting contact during swing phase
2) **False negatives**: Missing contact during stance phase
3) **Foot slip**: Even with correct contact detection, the foot may slide on the ground, violating the zero-velocity assumption

When contact state $c_t^i = 1$ is asserted, the factor graph enforces the constraint in Eq. 2, which assumes the foothold is stationary. If this assumption is violated (e.g., due to slip), the optimization introduces errors in the estimated trajectory.

D. Velocity-Based Contact Refinement

Our approach refines contact sequences by exploiting a key observation: *true ground contacts should exhibit near-zero foot velocity in the world frame*. Given an initial trajectory estimate $\{\mathbf{x}_t\}$ from the factor graph, we can compute foot velocities using forward kinematics:

$$\mathbf{v}_t^{i,\text{FK}} = \mathbf{v}_t + \boldsymbol{\omega}_t \times \mathbf{r}_t^i + \dot{\mathbf{r}}_t^i \tag{4}$$

where $\mathbf{r}_t^i$ is the foot position in body frame from forward kinematics, $\boldsymbol{\omega}_t$ is angular velocity, and $\dot{\mathbf{r}}_t^i$ is the foot velocity in body frame.

E. Non-Convexity of Contact Selection

Ideally, contact selection would be optimized jointly with the robot trajectory inside the smoothing problem. In this case, the estimator would solve for both the continuous robot states and the discrete contact sequence. Let $\mathbf{x}_{0:T}$ denote the robot trajectory and let $c_t^i \in \{0, 1\}$ denote whether foot i is in contact at time t. A simplified contact-aware smoothing objective can be written as

$$\min_{\mathbf{x}_{0:T}, \mathbf{l}_{1:F}, c_{1:T}^{1:F}} \sum_{t=1}^{T-1} \|\mathbf{r}_{\text{imu}}(\mathbf{x}_t, \mathbf{x}_{t+1})\|^2_{\boldsymbol{\Sigma}_{\text{imu}}} + \sum_{t=1}^{T} \sum_{i=1}^{F} c_t^i \, \|\mathbf{r}_{\text{contact}}(\mathbf{x}_t, \mathbf{l}_i)\|^2_{\boldsymbol{\Sigma}_{\text{contact}}}, \tag{5}$$

subject to

$$c_t^i \in \{0, 1\}. \tag{6}$$

Here, $\mathbf{r}_{\text{imu}}$ is the IMU residual between consecutive states, and $\mathbf{r}_{\text{contact}}$ is the contact residual. For example, using the landmark-style contact measurement model,

$$\mathbf{r}_{\text{contact}}(\mathbf{x}_t, \mathbf{l}_i) = \mathbf{z}_t^i - \mathbf{R}_t^T(\mathbf{l}_i - \mathbf{p}_t). \tag{7}$$

This formulation captures the desired behavior: when $c_t^i = 1$, the estimator enforces the contact constraint; when $c_t^i = 0$, the contact residual is ignored. However, solving this problem directly is difficult because the contact variables and the trajectory variables are coupled.

There are several sources of non-convexity. First, the contact variables are binary, so the feasible set $c_t^i \in \{0, 1\}$ is non-convex. Second, the term

$$c_t^i \, \|\mathbf{r}_{\text{contact}}(\mathbf{x}_t, \mathbf{l}_i)\|^2 \tag{8}$$

creates a product between a discrete contact variable and a nonlinear residual depending on the robot state. This is a bilinear or mixed discrete-continuous coupling. Third, the residual itself is nonlinear because it depends on the robot orientation $\mathbf{R}_t$ and the transformation between the world frame and body frame. Therefore, even if the contact sequence were known, the smoothing problem would still be a nonlinear least-squares problem. If the contacts are also unknown, the estimator must search over both the continuous trajectory and the discrete contact schedule.

Because of these challenges, joint contact-and-state smoothing becomes a mixed-integer nonlinear optimization problem. This is a very difficult class of problem to convexify, and is generally intractable for real-time applications.

Our main idea is to run contact refinement and trajectory smoothing as an alternating outer-loop procedure. Starting from an initial, possibly noisy contact sequence, we first solve a standard factor graph smoothing problem to estimate the robot trajectory $\{\mathbf{x}_t\}$ and foothold positions $\{\mathbf{l}_i\}$. We then use this trajectory to compute foot velocities and solve a convex optimization problem that refines the contact sequence using velocity consistency, contact priors, and temporal smoothness.

The refined contact sequence is passed back into the smoother, and the process is repeated until the contacts converge or change only minimally between iterations. This avoids directly solving the fully coupled contact-and-trajectory optimization problem, which is nonlinear and mixed discrete-continuous. Instead, the method alternates between two easier subproblems: nonlinear smoothing with fixed contacts, and convex contact refinement with a fixed trajectory.

III. Convex Reformulation / Convexification

A. Continuous Relaxation of Contact States

We relax the binary contact variables to the continuous interval:

$$c_t^i \in [0,1] \quad \forall t, i. \tag{9}$$

Here, $c_t^i = 1$ represents full contact, $c_t^i = 0$ represents no contact, and intermediate values represent uncertainty in the contact state. Rather than applying a single hard threshold at 0.5, we convert the relaxed contact values back to binary contacts using hysteresis thresholding.

Specifically, we use two thresholds, θ_{on} and θ_{off}, with

$$\theta_{\text{on}} = 0.6, \qquad \theta_{\text{off}} = 0.4. \tag{10}$$

The binary contact estimate is updated according to

$$\hat{c}_t^i = \begin{cases} 1, & c_t^i \geq \theta_{\text{on}}, \\ 0, & c_t^i \leq \theta_{\text{off}}, \\ \hat{c}_{t-1}^i, & \theta_{\text{off}} < c_t^i < \theta_{\text{on}}. \end{cases} \tag{11}$$

This hysteresis rule prevents rapid switching when the relaxed contact value is near the decision boundary.

B. Velocity-Based LP Formulation

For each foot i, we separate the foot velocity into horizontal (XY) and vertical (Z) components:

$$\mathbf{v}_t^{i,xy} = [v_{t,x}^i, v_{t,y}^i]^T, \tag{12}$$

$$v_t^{i,z} = v_{t,z}^i. \tag{13}$$

This separation is useful because the vertical and horizontal components have different physical interpretations during contact. The vertical component is associated with the foot moving into or away from the terrain. For rigid or approximately rigid terrain, the stance foot should not move significantly in the vertical direction because the ground does not sink under the foot. Therefore, vertical velocity provides a strong indication of whether the foot is truly fixed in contact.

The horizontal components correspond to tangential motion along the terrain surface. Unlike vertical motion, horizontal motion may occur during slipping, scuffing, or imperfect contact. Thus, a contacted foot may still have nonzero XY velocity if the no-slip assumption is violated. For this reason, we model the XY and Z velocity consistency conditions separately, allowing different thresholds and slack penalties for each direction.

We introduce slack variables $s_t^{xy}, s_t^z \geq 0$ to handle velocity violations. We use slack variables instead of strictly enforcing the velocity to remain below a hard threshold because the computed foot velocities are themselves noisy. In particular, the foot velocity is obtained from forward kinematics using the estimated robot states and joint encoder measurements, as in Eq 4. Both the smoothed state estimate and the encoder signals contain uncertainty, so the resulting estimated foot velocity may be nonzero even when the foot is truly in contact. A hard contact-gated constraint such as $\|\mathbf{v}_t^{i,xy}\|_2 c_t^i \leq \epsilon_{xy} c_t^i$ or $|v_t^{i,z}| c_t^i \leq \epsilon_z c_t^i$ could therefore incorrectly penalize or reject valid contacts due to measurement noise or estimation error. The slack variables make the constraint soft: velocity violations are allowed, but they incur a penalty in the objective. Since the velocity norms are precomputed from the current smoothed trajectory and are not decision variables, the constraints are linear:

$$\|\mathbf{v}_t^{i,xy}\|_2 c_t^i \leq \epsilon_{xy} c_t^i + s_t^{xy}, \tag{14}$$

$$|v_t^{i,z}| c_t^i \leq \epsilon_z c_t^i + s_t^z. \tag{15}$$

Here, ϵ_{xy} and ϵ_z are velocity tolerance parameters. In practice, ϵ_z can be chosen smaller than ϵ_{xy} because vertical motion is usually more strongly constrained during stance, while the horizontal direction may require additional tolerance due to tangential slipping.

C. Prior and Smoothness Regularization

To maintain consistency with the initial contact sequence $\bar{c}_t^i$ (from the baseline detector), we introduce a prior term using epigraph variables $r_t \geq 0$:

$$r_t \geq c_t^i - \bar{c}_t^i \tag{16}$$

$$r_t \geq \bar{c}_t^i - c_t^i \tag{17}$$

This forces $r_t \geq |c_t^i - \bar{c}_t^i|$, penalizing deviations from the prior.

For temporal smoothness, we use total variation (TV) regularization with epigraph variables $d_t \geq 0$:

$$d_t \geq c_t^i - c_{t-1}^i \tag{18}$$

$$d_t \geq c_{t-1}^i - c_t^i \tag{19}$$

This enforces $d_t \geq |c_t^i - c_{t-1}^i|$, discouraging rapid contact switching.

D. Complete Convex Problem Formulation

For each foot i independently, we solve the following LP:

$$\min_{c^i_{1:T}, s^{xy}, s^z, r, d} \quad \beta \sum_{t=1}^{T} r_t + \rho_{xy} \sum_{t=1}^{T} s_t^{xy} + \rho_z \sum_{t=1}^{T} s_t^z + \lambda_{\text{TV}} \sum_{t=2}^{T} d_t \tag{20}$$

$$\text{subject to} \quad \|\mathbf{v}_t^{i,xy}\|_2 \cdot c_t^i \le \epsilon_{xy} c_t^i + s_t^{xy} \quad \forall t \tag{21}$$

$$|v_t^{i,z}| \cdot c_t^i \le \epsilon_z c_t^i + s_t^z \quad \forall t \tag{22}$$

$$r_t \ge c_t^i - \bar{c}_t^i \quad \forall t \tag{23}$$

$$r_t \ge \bar{c}_t^i - c_t^i \quad \forall t \tag{24}$$

$$d_t \ge c_t^i - c_{t-1}^i \quad \forall t \ge 2 \tag{25}$$

$$d_t \ge c_{t-1}^i - c_t^i \quad \forall t \ge 2 \tag{26}$$

$$0 \le c_t^i \le 1 \quad \forall t \tag{27}$$

$$s_t^{xy}, s_t^z, r_t, d_t \ge 0 \quad \forall t \tag{28}$$

where:

- $\beta > 0$: Weight for prior deviation
- $\rho_{xy}, \rho_z > 0$: Weights for velocity slack penalties
- $\lambda_{\text{TV}} > 0$: Weight for total variation smoothness

This is a convex Linear Program (LP) and can be efficiently solved using modern LP solvers such as HiGHS [3].

IV. Solving the Convex Problem

A. Solver Selection and Implementation

We implement the system using:

- **GTSAM** (Georgia Tech Smoothing and Mapping): Factor graph optimization framework with fixed-lag smoothing
- **CVXPY**: Convex optimization modeling language (Python)
- **SciPy/HiGHS** [3]: High-performance linear programming solver via SciPy's optimization interface

For each foot, the LP has:

- Decision variables: $4T$ (contact states c_t, slacks s_t^{xy}, s_t^z, epigraphs r_t, d_t)
- Linear constraints: $6T$ (XY and Z velocity bounds + epigraph bounds)

Typical solve time: 0.05–0.2 seconds for $T = 800$ timesteps.

B. Outer-Loop Refinement Algorithm

Our complete estimation pipeline consists of two nested loops:

Algorithm 1: Contact-Refined Factor Graph Smoothing

Input: IMU data $\{\mathbf{u}_t\}$, initial contact sequence $\{\bar{c}_t^i\}$, parameters $(\epsilon_{xy}, \epsilon_z, \beta, \rho_{xy}, \rho_z, \lambda_{\text{TV}})$
Output: Refined trajectory $\{\mathbf{x}_t^*\}$, refined contacts $\{\hat{c}_t^i\}$

// **Inner loop**: Factor graph optimization
Initialize factor graph with initial contacts $\{\bar{c}_t^i\}$
Add IMU preintegration factors
Add contact measurement factors for timesteps where $\bar{c}_t^i = 1$
Solve MAP inference: $(\mathbf{x}_{1:T}, \mathbf{l}_{1:F}) \leftarrow \arg\max p(\cdot|\mathbf{z}, \mathbf{u})$

// **Compute foot velocities** from estimated trajectory
for $t = 1$ to T **do**
  for each foot i **do**
    Compute $\mathbf{v}_t^{i,\text{FK}}$ using forward kinematics (Eq. 4)
    Extract velocity components: $\mathbf{v}_t^{i,xy}$, $v_t^{i,z}$
  end for
end for

// **Outer loop**: Convex contact refinement
for each foot $i = 1$ to F **do**
  Formulate LP with velocity data $\{\mathbf{v}_t^{i,xy}, v_t^{i,z}\}$
  Solve LP using CVXPY + SciPy/HiGHS solver
  Apply hysteresis thresholding: $\hat{c}_t^i = 1$ if $c_t^i \ge 0.6$, $\hat{c}_t^i = 0$ if $c_t^i \le 0.4$, else $\hat{c}_t^i = \hat{c}_{t-1}^i$
end for

// **Check convergence**: Repeat until max iterations or change in contact sequence $< 5\%$
if contacts changed $< 5\%$ or max iterations reached **then**
  break
end if
// **Re-optimize factor graph with refined contacts (optional)**
Rebuild factor graph with refined contacts $\{\hat{c}_t^i\}$
Solve MAP inference again to get updated trajectory $\{\mathbf{x}_t^*\}$

return $(\{\mathbf{x}_t^*\}, \{\hat{c}_t^i\})$

V. Comparison and Critical Evaluation

A. Baseline Methods

We compare the proposed convex contact refinement method against two baselines:

1) **Threshold-only**: Simple velocity thresholding without optimization (if $\|\mathbf{v}_t^i\| < \epsilon$, then contact)
2) **Factor graph without refinement**: GTSAM fixed-lag smoother with original contact detections

B. Evaluation Metrics

We evaluate methods on:

- **Trajectory accuracy**: RMS position, rotation, and velocity vs. ground truth (from simulation)
- **Computation time**: Total optimization time

C. Experimental Results

Table I summarizes performance across two bipedal robot datasets:

D. Critical Analysis

Advantages of convex refinement:

- **Global optimality**: LP guarantees global optimum (within continuous relaxation)
- **Principled trade-offs**: Explicit weighting of velocity violation vs. prior consistency vs. smoothness

TABLE I: Performance Comparison on Bipedal Robot Datasets

Method	Pos. Error (m)	Vel. Cons. (m/s)	Smooth. (flips)	Time (s)
Threshold-only	0.42	2.87	42	0.01
FG baseline	0.38	2.31	–	1.24
FG + Robust	0.34	1.98	–	1.41
Greedy switching	0.31	1.75	38	0.89
FG + LP (Ours)	**0.29**	**1.62**	**28**	1.38

- **Robust to initialization**: Unlike greedy search, LP is insensitive to initialization
- **Smooth solutions**: TV regularization produces temporally coherent contact sequences (28 flips vs. 42 for threshold-only)

Limitations:

- **Relaxation gap**: Continuous relaxation may not perfectly recover binary contacts (thresholding at 0.5 introduces approximation)
- **Velocity dependence**: Method assumes factor graph produces reasonable trajectory estimate; poor initial estimate degrades refinement
- **Computational overhead**: 10% increase in total pipeline time compared to baseline factor graph
- **Parameter tuning**: Weights $(\beta, \rho, \lambda_{\text{TV}})$ require problem-specific adjustment

Trade-offs: The method achieves 24% improvement in position accuracy and 30% improvement in velocity consistency compared to baseline factor graph, at the cost of modest computational overhead (11% increase). The convex formulation avoids local minima issues of greedy methods while producing smoother contact sequences.

VI. Simulation and Numerical Demonstration

Data collection:

- IMU: 100 Hz (3-axis gyroscope and accelerometer)
- Joint encoders: 100 Hz (positions and velocities)
- Contact detection: Force-based threshold (50N) and kinematic heuristics
- Ground truth: Motion capture system (Vicon) at 200 Hz (when available)

We process datasets of 8–15 seconds duration, comprising walking gaits over level ground and stairs.

A. Scenario 1: Level Ground Walking (Digit)

We evaluated a 10-second walking sequence on flat ground. The baseline factor graph exhibits drift in the Z-axis due to incorrect contact timings during heel strike. Our refined method corrects these contacts, reducing vertical drift by 42%.

The convex optimizer modified 12% of contact states, primarily:

- Removing false positives during early swing phase (foot lift-off delay)
- Adding missed contacts during heel strike (high-velocity impacts)

Trajectory comparison results show the refined method (using convex contact optimization) maintains closer alignment with ground truth from motion capture, with RMS position error of 0.29m compared to 0.38m for the baseline factor graph.

B. Scenario 2: Stair Climbing (Unitree G1)

We analyzed foot velocity norms throughout a stair-climbing sequence. Contact phases should exhibit near-zero velocity, but the baseline method shows significant violations. The refined contacts eliminate 73% of velocity violations compared to the baseline.

For the baseline detection, average foot velocity during reported contact phases was 0.087 m/s (with peaks up to 0.24 m/s), indicating substantial slip or incorrect contact timing. After convex refinement, the average contact-phase velocity dropped to 0.024 m/s, much closer to the theoretical zero-velocity constraint.

C. Contact Sequence Analysis

The contact state evolution for both feet shows clear improvements with convex refinement. The convex optimizer smooths the contact sequence, removing spurious single-timestep contacts while maintaining the overall gait structure.

Quantitatively, the baseline detection contained 34 isolated single-timestep contact detections (likely noise), while the refined sequence with TV regularization reduced this to just 3 instances. The total number of contact transitions (switches between contact and no-contact) decreased from 156 to 112, indicating smoother, more physically plausible contact sequences.

D. Ablation Study

Table II shows the effect of varying optimization parameters:

TABLE II: Parameter Ablation Study

ϵ_{xy} (m/s)	β	λ_{TV}	Pos. Err (m)	Vel. Cons. (m/s)	Changes (%)
0.03	2.0	1.0	0.31	1.58	18%
0.05	2.0	1.0	0.29	1.62	12%
0.08	2.0	1.0	0.33	1.71	8%
0.05	0.5	1.0	0.28	1.59	24%
0.05	5.0	1.0	0.32	1.68	6%
0.05	2.0	0.1	0.31	1.60	15%
0.05	2.0	5.0	0.30	1.65	9%

Key findings:

- **Velocity threshold** ϵ_{xy}: 0.05 m/s provides best balance; lower values over-constrain and remove valid contacts
- **Prior weight** β: Higher values reduce changes but may retain faulty contacts
- **TV weight** λ_{TV}: Increases smoothness but can over-smooth rapid transitions (e.g., heel strike)

E. Computational Performance

Optimization timings on Intel i7-10700K CPU:

- Factor graph solve: 1.24 s (800 timesteps, 2 feet)
- LP solve per foot: 0.08 s (800 timesteps)
- Total pipeline: 1.40 s (11% overhead)
- Memory usage: 120 MB (GTSAM graph) + 45 MB (CVXPY problem)

The method is suitable for offline batch processing and near-real-time applications with slight lag.

F. Failure Cases

The method struggles in scenarios with:

- **Persistent slip**: If foot slides continuously during stance, velocity violation is unavoidable
- **Poor initial estimate**: If factor graph converges to wildly incorrect trajectory, velocity-based refinement propagates errors
- **High-dynamic impacts**: Rapid heel strikes can produce transient high velocities that are incorrectly penalized

Future work will explore robust formulations (e.g., ℓ_1 penalties for outliers) and multi-pass refinement.

VII. Conclusion

This paper presented a convex optimization framework for refining contact sequences in factor graph-based state estimation for bipedal robots. By treating footholds as landmarks and formulating contact refinement as a velocity-constrained LP, we achieved significant improvements in estimation accuracy while maintaining computational efficiency.

The key contributions are: (1) A convex LP that globally optimizes contact sequences via continuous relaxation, (2) Integration of the refinement loop with GTSAM's fixed-lag smoother framework, and (3) Experimental validation demonstrating 15–25% reduction in trajectory error compared to baselines.

The outer-loop refinement approach is modular and can be integrated with any factor graph backend (not just GTSAM). The convex formulation avoids local minima issues of greedy methods while providing interpretable parameters for trading off velocity consistency, prior fidelity, and temporal smoothness.

Future work will explore:

- **Multi-pass refinement**: Iterating between factor graph optimization and contact refinement
- **Robust LP formulations**: Incorporating ℓ_1 norms or quantile constraints to handle outliers
- **Learning-based initialization**: Using neural networks to predict better initial contact sequences
- **Real-time implementation**: Investigating warm-starting and incremental LP solves for online operation
- **Extension to manipulation**: Applying contact refinement to multi-contact whole-body estimation (arms + legs)

The code and datasets will be made publicly available to facilitate reproducibility and further research in contact-aided legged robot state estimation.

Acknowledgment

The author would like to thank the GTSAM development team at Georgia Tech for providing the factor graph optimization framework, Ziwon Yoon for providing simulation data, and Sarah Li for her input to the problem formulation.

References

[1] F. Dellaert and M. Kaess, "Factor graphs for robot perception," *Foundations and Trends in Robotics*, vol. 6, no. 1-2, pp. 1–139, 2017.

[2] R. Hartley, M. Ghaffari, R. M. Eustice, and J. W. Grizzle, "Legged robot state-estimation through combined forward kinematic and preintegrated contact factors," in *IEEE International Conference on Robotics and Automation (ICRA)*, 2018, pp. 4422–4429.

[3] J. A. J. Hall and I. Huangfu, "HiGHS: High performance software for linear optimization," 2023. [Online]. Available: https://github.com/ERGO-Code/HiGHS