RAJALAKSHMI ENGINEERING COLLEGE

P Saam 251801276-2025-AIDS

P2

Started on	Thursday, 27 August 2026, 8:51 AM
State	Finished
Completed on	Thursday, 27 August 2026, 8:56 AM
Time taken	5 mins 36 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int V;

    // Read the value from standard input
    if (scanf("%d", &V) != 1) {
        return 1;
    }

    // Standard Indian currency denominations in descending order
    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = sizeof(denominations) / sizeof(denominations[0]);

    int count = 0;

    // Iterate through each denomination
    for (int i = 0; i < n; i++) {
        if (V == 0) {
            break;
        }
        // Add the number of notes/coins of the current denomination
        count += V / denominations[i];

        // Update the remaining amount
        V %= denominations[i];
    }

    // Print the total minimum number of notes/coins
    printf("%d\n", count);

    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course