RAJALAKSHMI ENGINEERING COLLEGE

P Saam 251801276-2025-AIDS

P2

Started on	Thursday, 27 August 2026, 8:59 AM
State	Finished
Completed on	Thursday, 27 August 2026, 9:00 AM
Time taken	41 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparison function for qsort to sort in ascending order
int compareAscending(const void *a, const void *b) {
    int int_a = *((int *)a);
    int int_b = *((int *)b);
    return int_a - int_b;
}

int main() {
    int n;
    // Read the number of elements
    if (scanf("%d", &n) != 1) return 0;

    // Allocate memory for the array elements
    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Sort the array in ascending order (Greedy approach)
    qsort(arr, n, sizeof(int), compareAscending);

    long long max_sum = 0;

    // Calculate the sum of arr[i] * i
    for (int i = 0; i < n; i++) {
        max_sum += (long long)arr[i] * i;
    }

    // Print the maximum array sum
    printf("%lld\n", max_sum);

    // Free allocated memory
    free(arr);

    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course