

Topic 1: Basic Linux Commands

1. Pwd ~ Display the current working directory

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ pwd  
/home/saanvi_kompelli
```

2. Clear ~ clear the terminal screen

```
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

3. History ~ displays previously executed commands

```
88  pwd  
89  clear  
90  history  
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

4. Whoami ~ display the current logged-in username

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ whoami  
saanvi_kompelli
```

5. Date ~ display the current system date and time

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ date  
Tue Aug 11 04:08:40 UTC 2026
```

6. Hostname ~ Display the system hostname

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ hostname  
DESKTOP-2U40RG7
```

7. Uname -a ~ Display operating system operation

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ uname -a  
Linux DESKTOP-2U40RG7 6.18.33.2-microsoft-standard-WSL2 #1 SMP PREEMPT_DYNAMIC Thu Jun 18 21:54:43 UTC 2026 x86_64 GNU/Linux
```

8. Exit ~ exit the terminal

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ exit
```

TOPIC 2 ~ DIRECTORY MANAGEMENT

1. Ls ~ list files and directories

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ls
EighthProgramme  FirstProgramme  NinthProgramme  SecondProgramme  SixthProgramme.c  hello
EighthProgramme.c  FirstProgramme.c  NinthProgramme.c  SecondProgramme.c  ThirdProgramme
FifthProgramme    FourthProgramme  ReadUser.c.save  SeventhProgramme  ThirdProgramme.c
FifthProgramme.c  FourthProgramme.c  S2Commands       SeventhProgramme.c  a.out
FirstFile         Hello.c          SAANVI           SixthProgramme     example.txt
```

2. Ls -a ~ display detailed file information

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ls -a
.          .config      FifthProgramme  FourthProgramme.c  SAANVI          SixthProgramme.c
..         .local       FifthProgramme.c  Hello.c            SecondProgramme  ThirdProgramme
.bash_history  .motd_shown  FirstFile       NinthProgramme     SecondProgramme.c  ThirdProgramme.c
.bash_logout  .profile     FirstProgramme  NinthProgramme.c  SeventhProgramme  a.out
.bashrc       EighthProgramme  FirstProgramme.c  ReadUser.c.save  SeventhProgramme.c  example.txt
.cache        EighthProgramme.c  FourthProgramme  S2Commands        SixthProgramme     hello
```

3. Cd ~ change the current directory

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ cd
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

4. Cd .. ~ move to parent directory

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ cd ..
saanvi_kompelli@DESKTOP-2U40RG7:/home$
```

5. mkdir ~ create a new directory

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ mkdir OSSPLAB
```

6. rmdir ~ remove a directory

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ rmdir OSSPLAB
```

7. find FileName.c ~ search for files and directories

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ find Hello.c
Hello.c
```

8. locate ~ Quickly locate files

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ locate Hello.c
```

3.FILE MANAGEMENT

1.touch ~ Create new empty file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ touch KL.c
```

2. cat ~ display file contents

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ cat Hello.c
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
```

3. cp ~ copy files or directories

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ cp Hello.c FirstProgramme.c
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

4. mv ~ move or rename files

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ mv Hello.c hello.c
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

5. rm ~ remove file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ rm hello.c
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

6. head ~ display first lines of a file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ head FirstProgramme.c
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
```

7. tail ~ display last lines of the file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ tail FirstProgramme.c
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
```

8.more ~ view a file page by page

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ more FirstProgramme.c
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
```

9.less ~ Scroll through a file

```
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
FirstProgramme.c (END)
```

10.wc ~ count lines, words and characters

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ wc FirstProgramme.c
 6 10 69 FirstProgramme.c
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

11.diff ~ compare two files

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ diff FirstProgramme.c FourthProgramme.c
1c1,3
< #include <stdio.h>
---
> #include<stdio.h>
> #include<unistd.h>
>
4,5c6,10
< printf("Hello Linux\n");
< return 0;
---
>     fork();
>
>     printf("Hello\n");
>
>     return 0;
6a12
>
```

12.sort ~ sort file contents

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ sort FirstProgramme.c
#include <stdio.h>
int main()
printf("Hello Linux\n");
return 0;
{
}
```

13.uniq ~ remove duplicate files

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ uniq FirstProgramme.c
#include <stdio.h>
int main()
{
printf("Hello Linux\n");
return 0;
}
```

14.grep ~ search for text inside a file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ grep main FirstProgramme.c
int main()
```

4. TOPIC ~ FILE EDITING

1.nano ~ create or edit a file

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ nano Hello.c
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

2. vi ~ edit a file using vim editor

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    pid_t pid;

    pid=fork();

    if(pid==0)
    {
        printf("I am Child Process\n");
    }
    else
    {
        printf("I am Parent Process\n");
    }

    return 0;
}

~
~
~
~
~
~
~
```

"FifthProgramme.c" 21L, 231B

5. C PROGRAM COMPILATION AND EXECUTION

1. gcc ~ compile a C program

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ gcc FirstProgramme.c -o file
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

2. ./program ~ Execute the compiled program

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ./file
Hello Linux
```

3. which ~ Locate the executable of a command

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ which gcc
/usr/bin/gcc
```

4. whereis ~ Locate binary, source and manual pages

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ whereis gcc
gcc: /usr/bin/gcc /usr/lib/gcc /usr/libexec/gcc /usr/share/gcc /usr/share/man/man1/gcc.1.gz
```

5. man ~ display manual pages

```
GCC(1)                                GNU                                GCC(1)

NAME
    gcc - GNU project C and C++ compiler

SYNOPSIS
    gcc [-c|-S|-E] [-std=standard]
        [-g] [-pg] [-Olevel]
        [-Wwarn...] [-Wpedantic]
        [-Idir...] [-Ldir...]
        [-Dmacro[=defn]...] [-Umacro]
        [-foption...] [-mmachine-option...]
        [-o outfile] [@file] infile...

    Only the most useful options are listed here; see below for the remainder.  g++ accepts mostly the same options
    as gcc.

DESCRIPTION
    When you invoke GCC, it normally does preprocessing, compilation, assembly and linking.  The "overall options"
    allow you to stop this process at an intermediate stage.  For example, the -c option says not to run the linker.
    Then the output consists of object files output by the assembler.

    Other options are passed on to one or more stages of processing.  Some options control the preprocessor and
    others the compiler itself.  Yet other options control the assembler and linker; most of these are not
    documented here, since you rarely need to use any of them.

    Most of the command-line options that you can use with GCC are useful for C programs; when an option is only
    useful with another language (usually C++), the explanation says so explicitly.  If the description for a
    particular option does not mention a source language, you can use that option with all supported languages.

    The usual way to run GCC is to run the executable called gcc, or machine-gcc when cross-compiling, or
    machine-gcc-version to run a specific version of GCC.  When you compile C++ programs, you should invoke GCC as
    g++ instead.

    The gcc program accepts options and file names as operands.  Many options have multi-letter names; therefore
    multiple single-letter options may not be grouped: -dv is very different from -d -v.

    You can mix options and other arguments.  For the most part, the order you use doesn't matter.  Order does
    matter when you use several options of the same kind; for example, if you specify -L more than once, the
    directories are searched in the order specified.  Also, the placement of the -l option is significant.

    Manual page gcc(1) line 1 (press h for help or q to quit)
```

6.PROCESS MANAGEMENT

1. ps ~ display running processes

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ps
  PID TTY          TIME CMD
 1376 pts/0        00:00:00 bash
 1407 pts/0        00:00:00 ps
```

2. ps -ef ~ display all running processes

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ps -ef
UID          PID    PPID  C STIME TTY          TIME CMD
root           1        0  0  04:45 ?        00:00:01 /sbin/init
root           2        1  0  04:45 hvcc0   00:00:00 /init
root           8        2  0  04:45 hvcc0   00:00:00 plan9 --control-socket 7 --log-level 4 --server-fd 8 --pipe-fd 10 --root          51      1  0 04:45 ?        00:00:00
/usr/lib/systemd/systemd-journald
systemd+       72        1  0  04:45 ?        00:00:00 /usr/lib/systemd/systemd-resolved
root          93        1  0  04:45 ?        00:00:02 /usr/lib/systemd/systemd-udevd
root         115        1  0  04:45 ?        00:00:00 /bin/sh /usr/lib/systemd/scripts/chronyd-starter.sh -n -F 1
root         116        1  0  04:45 ?        00:00:00 /usr/sbin/cron -f -P
message+      117        1  0  04:45 ?        00:00:00 @dbus-daemon --system --address=systemd: --nofork --nopidfile --systroot          122      1  0 04:45 ?        00:00:00
/usr/bin/python3 /usr/bin/networkd-dispatcher --run-startup-triggersroot          127      1  0 04:45 ?        00:00:00 /usr/lib/systemd/systemd-logind
syslog        180        1  0  04:45 ?        00:00:00 /usr/sbin/rsyslogd -n -iNONE
root         186        1  0  04:45 tty1    00:00:00 /usr/sbin/agetty --noreset --noclear --issue-file=/etc/issue:/etc/is_chrony          217     115  0 04:45 ?        00:00:00
/usr/sbin/chronyd -n -F 1 -x
root         223        1  0  04:45 ?        00:00:00 /usr/bin/python3 /usr/share/unattended-upgrades/unattended-upgrade-s_chrony          236     217  0 04:45 ?        00:00:00
/usr/sbin/chronyd -n -F 1 -x
root         356        2  0  04:45 ?        00:00:00 login -- saanvi_kompelli
saanvi_+      405        1  0  04:45 ?        00:00:00 /usr/lib/systemd/systemd --user
saanvi_+      407        405  0  04:45 ?        00:00:00 (sd-pam)
saanvi_+      436        356  0  04:45 pts/1    00:00:00 -bash
root        1373        2  0  05:38 ?        00:00:00 /init
root        1374      1373  0  05:38 ?        00:00:00 /init
saanvi_+     1376      1374  0  05:38 pts/0    00:00:00 -bash
saanvi_+     1425     1376  0  05:38 pts/0    00:00:00 ps -ef
```

3. top ~ monitor running processes

```
top - 05:40:15 up 55 min, 1 user, load average: 0.01, 0.03, 0.00
Tasks: 24 total, 1 running, 23 sleeping, 0 stopped, 0 zombie
%Cpu(s): 0.0 us, 0.0 sy, 0.0 ni, 99.9 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
MiB Mem : 3851.6 total, 3328.0 free, 527.1 used, 128.9 buff/cache
MiB Swap: 1024.0 total, 1024.0 free, 0.0 used, 3324.5 avail Mem
```

PID	USER	PR	NI	VIRT	RES	SHR	S	%CPU	%MEM	TIME+	COMMAND
1	root	20	0	24576	15532	11564	S	0.0	0.4	0:01.74	systemd
2	root	20	0	3180	2208	2072	S	0.0	0.1	0:00.05	init-systemd(Ub
8	root	20	0	3180	2048	1940	S	0.0	0.1	0:00.00	init
51	root	19	-1	50392	16844	15540	S	0.0	0.4	0:00.51	systemd-journal
72	systemd+	20	0	22540	14640	12020	S	0.0	0.4	0:00.21	systemd-resolve
93	root	20	0	35276	12244	9252	S	0.0	0.3	0:02.22	systemd-udev
115	root	20	0	2888	1948	1820	S	0.0	0.0	0:00.16	chronyd-starter
116	root	20	0	4472	3092	2844	S	0.0	0.1	0:00.02	cron
117	message+	20	0	8820	5400	4732	S	0.0	0.1	0:00.23	dbus-daemon
122	root	20	0	44092	29764	14624	S	0.0	0.8	0:00.50	networkd-dispat
127	root	20	0	18452	9448	8184	S	0.0	0.2	0:00.27	systemd-logind
180	syslog	20	0	220548	5924	4632	S	0.0	0.2	0:00.27	rsyslogd
186	root	20	0	5492	2768	2588	S	0.0	0.1	0:00.02	agetty
217	_chrony	20	0	20420	6368	5592	S	0.0	0.2	0:00.16	chronyd
223	root	20	0	123456	32656	18048	S	0.0	0.8	0:00.38	unattended-upgr
236	_chrony	20	0	12092	2452	1808	S	0.0	0.1	0:00.00	chronyd
356	root	20	0	8644	5508	4668	S	0.0	0.1	0:00.02	login
405	saanvi_+	20	0	22748	13392	10932	S	0.0	0.3	0:00.39	systemd
407	saanvi_+	20	0	22908	4092	2092	S	0.0	0.1	0:00.00	(sd-pam)
436	saanvi_+	20	0	6136	5408	3856	S	0.0	0.1	0:00.10	bash
1373	root	20	0	3184	1120	980	S	0.0	0.0	0:00.00	SessionLeader
1374	root	20	0	3200	1260	1108	S	0.0	0.0	0:00.01	Relay(1376)
1376	saanvi_+	20	0	6268	5532	3860	S	0.0	0.1	0:00.22	bash
1435	saanvi_+	20	0	8172	6052	3944	R	0.0	0.2	0:00.09	top

4. kill ~ terminate a process

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ kill 1234
-bash: kill: (1234) - No such process
```

5. kill -9 ~ Forcefully terminate a process

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ kill -9
kill: usage: kill [-s sigspec | -n signum | -sigspec] pid | jobspec ... or kill -l [sigspec]
```

7. JOB CONTROL

1. jobs ~ Display background jobs

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ jobs
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

2. bg ~ Resume a job in the background

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ bg %2
-bash: bg: %2: no such job
```


3.fg ~ Bring a job to the foreground

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ fg %2
-bash: fg: %2: no such job
```

4.& - Run a process in the background

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ./FirstProgramme
Hello Linux
```

8.FILE PERMISSIONS AND LINKS

1. chmod ~ Change file permissions

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ chmod +x script.sh
```

2. chmod 755 ~ Set read, write and execute permissions

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ chmod 755
```

3.ln ~ create a hard link

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ln FirstProgramme.c Hello.c
```

4.ln -s ~ create a symbolic link

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ ln -s FirstProgramme shortcut
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

9. DISK AND MEMORY INFORMATION

1. df -h ~ display disk space usage

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ df -h
Filesystem      Size  Used Avail Use% Mounted on
none            1.9G   0 1.9G   0% /usr/lib/modules/6.18.33.2-microsoft-standar
d-WSL2
none            1.9G  4.0K  1.9G   1% /mnt/wsl
drivers          151G  134G   17G  89% /usr/lib/wsl/drivers
/dev/sdd        1007G   1.6G  955G   1% /
none            1.9G   56K  1.9G   1% /mnt/wslg
none            1.9G   0 1.9G   0% /usr/lib/wsl/lib
rootfs          1.9G   2.8M  1.9G   1% /init
none            1.9G  500K  1.9G   1% /run
none            1.9G   0 1.9G   0% /run/lock
none            1.9G   0 1.9G   0% /run/shm
none            1.9G   80K  1.9G   1% /mnt/wslg/versions.txt
none            1.9G   80K  1.9G   1% /mnt/wslg/doc
C:\             151G  134G   17G  89% /mnt/c
D:\             163G   34G  130G  21% /mnt/d
E:\             163G  21G  142G  13% /mnt/e
none            1.0M   0 1.0M   0% /run/credentials/systemd-journald.service
tmpfs           1.9G   0 1.9G   0% /tmp
none            1.0M   0 1.0M   0% /run/credentials/systemd-resolved.service
none            1.0M   0 1.0M   0% /run/credentials/getty@tty1.service
tmpfs           386M  12K  386M   1% /run/user/1000
```

2. du -sh ~ display directory size

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ du -sh
376K .
```

3. free -h ~ display memory usage (Linux)

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ free -h
```

	total	used	free	shared	buff/cache	available
Mem:	3.8Gi	517Mi	3.2Gi	3.5Mi	197Mi	3.3Gi
Swap:	1.0Gi	0B	1.0Gi			

10.USER AND ENVIRONMENT MANAGEMENT

1.id ~ display user and group IDs

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ id
uid=1000(saanvi_kompelli) gid=1000(saanvi_kompelli) groups=1000(saanvi_kompelli),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),100(users)
```

2.env ~ display environment variables

```
SHELL=/bin/bash
XSL2_GUI_APPS_ENABLED=1
XSL_DISTRO_NAME=Ubuntu
NAME=DESKTOP-2U40RG7
PWD=/home/saanvi_kompelli
LOGNAME=saanvi_kompelli
HOME=/home/saanvi_kompelli
LANG=C.UTF-8
XSL_INTEROP=/run/XSL/1445_interop
LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33:cd=40;33:or=40;31:mi=00:su=37;41:sg=30;43:ca=00:tw=30;42:ow=34;42:st=37;44:ex=01;32:*.t
r=01;31:*.tgz=01;31:*.arce=01;31:*.anj=01;31:*.taz=01;31:*.lha=01;31:*.lzd=01;31:*.lzh=01;31:*.lзма=01;31:*.tlz=01;31:*.txz=01;31:*.tzw=01;31:*.zip=01;31:*.z=01;
31:*.dz=01;31:*.gz=01;31:*.lrz=01;31:*.lz=01;31:*.lzo=01;31:*.xz=01;31:*.zst=01;31:*.tzt=01;31:*.bz2=01;31:*.bz=01;31:*.tbz2=01;31:*.tbz=01;31:*.tzt=01;31:*.deb=01;31:*.rpm
=01;31:*.jar=01;31:*.war=01;31:*.ear=01;31:*.sar=01;31:*.rar=01;31:*.alz=01;31:*.ace=01;31:*.zoo=01;31:*.cpio=01;31:*.7z=01;31:*.rz=01;31:*.cab=01;31:*.xwm=01;31:*.swm=01;3
1:*.dwm=01;31:*.esd=01;31:*.avi=01;35:*.jpg=01;35:*.jpeg=01;35:*.mjpg=01;35:*.mjpeg=01;35:*.gif=01;35:*.bmp=01;35:*.pbm=01;35:*.pgm=01;35:*.ppm=01;35:*.tga=01;35:*.xbm=01;
35:*.xpm=01;35:*.tif=01;35:*.tiff=01;35:*.png=01;35:*.svg=01;35:*.svgz=01;35:*.mng=01;35:*.pck=01;35:*.mov=01;35:*.mpeg=01;35:*.mpega=01;35:*.m2v=01;35:*.mkv=01;35:*.webm=01;
35:*.webp=01;35:*.ogm=01;35:*.mp4=01;35:*.m4v=01;35:*.mp4v=01;35:*.vob=01;35:*.qt=01;35:*.nuv=01;35:*.wmv=01;35:*.asf=01;35:*.rm=01;35:*.rmvb=01;35:*.flc=01;35:*.avi=01;35:
*.fli=01;35:*.flv=01;35:*.gl=01;35:*.dl=01;35:*.xcf=01;35:*.xwd=01;35:*.yuv=01;35:*.cgm=01;35:*.emf=01;35:*.ogv=01;35:*.ogx=01;35:*.aac=00;36:*.au=00;36:*.flac=00;36:*.m4a
=00;36:*.mid=00;36:*.midi=00;36:*.mka=00;36:*.mp3=00;36:*.mpc=00;36:*.ogg=00;36:*.ra=00;36:*.wav=00;36:*.oga=00;36:*.opus=00;36:*.spx=00;36:*.xspf=00;36:*.a=00;90:*.n=00;90:*.
bak=00;90:*.old=00;90:*.orig=00;90:*.part=00;90:*.rej=00;90:*.swp=00;90:*.tmp=00;90:*.dpkg-dist=00;90:*.dpkg-old=00;90:*.ucf-dist=00;90:*.ucf-new=00;90:*.ucf-old=00;90:*.rp
mnew=00;90:*.rpmorig=00;90:*.rpmave=00;90:
WAYLAND_DISPLAY=wayland-0
LESSCLOSE=/usr/bin/lesspipe %s %s
TERM=xterm-256color
LESSOPEN=| /usr/bin/lesspipe %s
USER=saanvi_kompelli
DISPLAY=:0
SHLVL=1
XDG_RUNTIME_DIR=/run/user/1000
XSLENV=
XDG_DATA_DIRS=/usr/local/share:/usr/share:/var/lib/snap/desktop
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/usr/lib/xsl/lib:/mnt/c/Program Files/WindowsApps/MicrosoftCorporationII.Windo
wsSubsystemForLinux.2.7.11.0_x64_8wekyb3d8bbwe:/mnt/c/Program Files/Common Files/Oracle/Java/javapath:/mnt/c/Program Files (x86)/Common Files/Oracle/Java/javapath:/mnt/c/
Program Files (x86)/Common Files/Oracle/Java/javapath:/mnt/c/Windows/system32:/mnt/c/Windows:/mnt/c/Windows/System32/Wbem:/mnt/c/Windows/System32/WindowsPowerShell/v1.0:/m
nt/c/Windows/System32/OpenSSH:/mnt/c/Program Files/dotnet:/mnt/c/Program Files/nodejs:/mnt/c/Program Files/MySQL/MySQL Shell 8.0/bin:/mnt/c/Users/dell/AppData/Local/Pro
grams/Python/Python34/Scripts:/mnt/c/Users/dell/AppData/Local/Programs/Python/Python34:/mnt/c/Users/dell/AppData/Local/Programs/Python/Launcher:/mnt/c/Users/dell/AppData
ta/Local/Microsoft/WindowsApps:/mnt/c/Users/dell/AppData/Local/Programs/Microsoft VS Code/bin:/mnt/c/Users/dell/AppData/Roaming/npm:/mnt/c/Users/dell/AppData/Local/Python/t
bin:/snap/bin
DBUS_SESSION_BUS_ADDRESS=unix:path=/run/user/1000/bus
HOSTTYPE=x86_64
PULSE_SERVER=unix:/mnt/wslg/PulseServer
=/usr/bin/env
```

3.export ~ Set an environment variable

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ export PATH=$PATH
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

4. alias ~ Create a command shortcut

```
saanvi_kompelli@DESKTOP-2U40RG7:~$ alias ll='ls -l'
saanvi_kompelli@DESKTOP-2U40RG7:~$
```

