

Target Aim Trainer

09/30/2026 23:58:25

<https://chatgpt.com/c/6abc7ea1-68cc-83ee-9b07-f92fcae5e65f>

target aim trainer.zip I am completing Lab 4: Vibe Coding for PES...

I'll inspect the ZIP directly, map the README requirements to the actual...

Okay, let's implement **Task 1: collision detection** first. Based on the...

Yes — Task 1 only needs a very small change. 1. Current code that is...

I made the change and tested Task 1. The game runs correctly, and the...

Great. For Task 2, we should build on the existing game_over flag rather...

Yes, re-check the actual README and current `game/game\_engine.py`,...

Thinking ● Searched 7 websites ● Investigated File Search tool schema...

okay task 2 is working now. let's move to the next README requirement...

Thinking ● Searched 5 websites 🌐 Inspecting ZIP archive contents ●...

Task 3 is working now. Let's implement the next README requirement .

I'll check the README's next requirement against the repository...



target aim trainer.zip

I am completing Lab 4: Vibe Coding for PES University.
My assigned repository is 47_target-aim-trainer.

I have uploaded the original README and source files
from my repository.

Please analyze the actual files before suggesting any
changes.

First:

1. Explain the overall program flow, including the game loop, target spawning, shrinking, mouse clicks, timer, score and accuracy.
2. Identify the exact functions responsible for each feature and explain how the files interact.
3. Compare the current implementation with every requirement in the README.
4. Identify which requirements are already implemented, broken, or missing.
5. Explain the root cause of each problem using the actual code.

Give me a concise technical analysis and a numbered
implementation plan.

****Do not modify or rewrite the code yet.**** I want to
understand the existing implementation before making
changes.

9/30/2026, 8:46:41 AM



I'll inspect the ZIP directly, map the README requirements to the actual source, then trace the runtime flow function-by-function. I won't change any files.

The repository is small: the actual application is just `main.py`, `game/game_engine.py`, and `game/target.py`; the ZIP also contains a `.venv`, which is not part of the game logic.

Thinking



Inspecting aim trainer archive contents

- Inspected aim trainer archive and game project source files

✓ Worked for 25s

1. Overall program flow

The program is a **Pygame real-time loop** with `GameEngine` coordinating the game and `Target` representing the current target.

Startup

`main.py`:

1. Calls `pygame.init()`.
2. Creates a `700 × 500` window.
3. Creates a `pygame.time.Clock()` capped at **60 FPS**.
4. Creates one `GameEngine`:

```
engine = GameEngine(WIDTH, HEIGHT)
```

That immediately creates the first target.

Main game loop

`main()` repeatedly does:

```
Fill background
↓
Read Pygame events
↓
Handle mouse clicks / quit
```

↓
Handle continuous input
↓
Update timer + target
↓
Draw target + HUD
↓
Display frame
↓
Wait for 60 FPS

The relevant code is:

```
while running:
    SCREEN.fill(DARK_GRAY)

    for event in pygame.event.get():
        ...
        engine.handle_event(event)

    engine.handle_input()
    engine.update()
    engine.render(SCREEN)

    pygame.display.flip()
    clock.tick(FPS)
```

2. Feature-by-feature implementation

A. Target spawning

Function: `GameEngine._spawn_target()`

File:

`game/game_engine.py`

```
def _spawn_target(self):
    x = random.randint(self.margin, self.width - self.margin)
    y = random.randint(self.margin + self.hud_height, self.height -
```

```
self.margin)
    return Target(x, y)
```

It randomly chooses the target center and creates:

```
Target(x, y)
```

The default `Target` values are:

```
base_radius=40
min_radius=12
lifespan_frames=90
```

So every target:

- starts at radius **40**
- shrinks to radius **12**
- lives for **90 frames**
- at 60 FPS, approximately **1.5 seconds**

Targets are spawned initially in `GameEngine.__init__()`:

```
self.target = self._spawn_target()
```

They are subsequently respawned after:

- a successful click
- a timeout

B. Target shrinking

Functions: `Target.update()`, `Target.visual_radius()`

File:

```
game/target.py
```

Every update:

```
def update(self):  
    self.age += 1
```

Then the visible radius is calculated:

```
def visual_radius(self):  
    t = min(1.0, self.age / self.lifespan_frames)  
    return self.base_radius - (self.base_radius - self.min_radius) * t
```

So conceptually:

Age 0	→ radius 40
Age 45	→ radius ~26
Age 90	→ radius 12

The game draws that calculated radius in:

```
r = int(self.target.visual_radius())  
pygame.draw.circle(..., r)
```

Important bug

The **drawing uses the shrinking radius**, but collision detection does not.

That is the main Task 1 bug.

3. Mouse clicks and scoring

Event handling

Function: `GameEngine.handle_event()`

```
def handle_event(self, event):  
    if self.game_over:  
        return  
  
    if event.type == pygame.MOUSEBUTTONDOWN:  
        self._handle_click(event.pos)
```

So mouse clicks are forwarded to `_handle_click()`.

Click handling

Function: `GameEngine._handle_click()`

```
def _handle_click(self, pos):  
    x, y = pos  
  
    if self.target.contains_point(x, y):  
        self.hits += 1  
        self.score += 1  
        self.target = self._spawn_target()  
    else:  
        self.misses += 1
```

Therefore:

Successful click

```
click target  
→ Target.contains_point()  
→ hits += 1  
→ score += 1  
→ spawn new target
```

Missed click

```
click outside target  
→ Target.contains_point() == False  
→ misses += 1
```

There is no penalty to the score for a miss.

4. Collision detection

Function: `Target.contains_point()`

Current implementation:

```
def contains_point(self, x, y):
```

```
return math.hypot(self.x - x, self.y - y) <= self.base_radius
```

This calculates the distance between the mouse and target center.

The problem is that it compares the distance against:

```
self.base_radius
```

which is **always 40**.

But the rendered circle uses:

```
self.visual_radius()
```

which can be as small as **12**.

Therefore:

```
Visible target = radius 12  
Clickable target = radius 40
```

near the end of its lifespan.

That directly explains the README's reported bug:

Late clicks well outside the small, shrunken target circle can still register as a hit.

5. Timer

Functions: `GameEngine.__init__()` and `GameEngine.update()`

The round starts at:

```
self.round_seconds = 30  
self.time_left_frames = self.round_seconds * 60
```

So:

```
30 seconds × 60 FPS = 1800 frames
```

Every frame:

```
self.time_left_frames -= 1
```

Once it reaches zero:

```
if self.time_left_frames <= 0:  
    self.game_over = True  
    return
```

The HUD displays:

```
seconds_left = max(0, self.time_left_frames // 60)
```

and:

```
Time: Xs
```

One implementation detail

The timer is frame-based rather than using elapsed real time. The game is intended to run at 60 FPS because of:

```
clock.tick(FPS)
```

so under normal conditions it behaves like a 30-second timer.

6. Target timeout / automatic miss

This is also handled by `GameEngine.update()`:

```
self.target.update()  
  
if self.target.expired():  
    self.misses += 1  
    self.target = self._spawn_target()
```

`Target.expired()` is:

```
def expired(self):
```

```
return self.age >= self.lifespan_frames
```

Therefore:

```
target reaches 90 frames  
→ expired()  
→ misses += 1  
→ new target spawned
```

This part **is already implemented correctly** according to the README.

7. Accuracy

Function: `GameEngine.accuracy()`

```
def accuracy(self):  
    total = self.hits + self.misses  
  
    if total == 0:  
        return 0.0  
  
    return round(100 * self.hits / total, 1)
```

So:

$$\text{Accuracy} = \text{hits} / (\text{hits} + \text{misses}) \times 100$$

Both kinds of misses count:

- clicking outside the target
- allowing the target to expire

For example:

```
Hits = 8  
Misses = 2  
  
Accuracy = 8 / 10 × 100  
          = 80%
```

This is displayed continuously by `render()`.

8. Rendering / HUD

Function: `GameEngine.render()`

It draws:

Target

```
pygame.draw.circle(...)
```

Score

```
Score: {self.score}
```

Timer

```
Time: {seconds_left}s
```

Accuracy

```
Accuracy: {self.accuracy()}%
```

So the required live HUD is already present.

9. Game-over behavior

The timer correctly sets:

```
self.game_over = True
```

However, the implementation of the actual game-over screen is **missing**.

The only special behavior currently is inside `render()`:

```

if self.game_over and not getattr(self, "_game_over_logged", False):
    print(f"Time's up! Final score: {self.score} Accuracy:
{self.accuracy()}%")
    self._game_over_logged = True

```

This prints the result to the **terminal**, not the Pygame window.

Also, `handle_event()` immediately returns once `game_over` is true:

```

if self.game_over:
    return

```

So there is currently no way for the player to interact with a game-over screen.

10. File interaction

The architecture is:

```

main.py
  |
  | creates
  ▼
GameEngine
  |
  | creates / replaces
  ▼
Target

```

`main.py`

Responsible for:

- Pygame initialization
- window
- FPS clock
- top-level game loop
- quitting Pygame

`game_engine.py`

Responsible for:

- game state
- target spawning
- clicks
- score
- hits/misses
- timer
- accuracy
- updating
- rendering
- current game-over flag

`target.py`

Responsible only for the target itself:

- position
- size
- age
- lifespan
- shrinking
- collision detection
- expiration

This is a reasonably clean separation: `GameEngine` manages the game, while `Target` manages target-specific behavior.

11. README requirements vs current implementation

README requirement	Status	Actual implementation
Single target appears randomly	✅ Implemented	<code>_spawn_target()</code>
Target shrinks over time	✅ Implemented	<code>Target.update()</code> + <code>visual_radius()</code>
Clicking target scores hit	⚠️ Implemented but buggy	<code>_handle_click()</code> + incorrect collision radius
Successful hit immediately spawns another target	✅ Implemented	<code>_handle_click()</code>
Clicking elsewhere counts as miss	✅ Implemented	<code>_handle_click()</code>
Target timeout counts as miss	✅ Implemented	<code>update()</code>
Countdown timer	✅ Implemented	<code>time_left_frames</code>
Score display	✅ Implemented	<code>render()</code>
Accuracy display	✅ Implemented	<code>accuracy()</code> + <code>render()</code>
Round ends at zero	✅ Implemented	<code>update()</code>
Task 1: collision matches visual target	❌ Broken	<code>contains_point()</code> uses <code>base_radius</code>
Task 2: graphical Game Over screen	❌ Missing	Only <code>print()</code> exists
Task 2: final score/accuracy on screen	❌ Missing	Only terminal output
Task 2: gracefully waits for input	❌ Missing	Game simply freezes in game-over state
Task 3: replay	❌ Missing	No reset/restart mechanism
Task 3: Easy/Medium/Hard	❌ Missing	No difficulty state
Task 3: difficulty changes lifespan/size	❌ Missing	<code>Target()</code> always uses defaults

README requirement	Status	Actual implementation
Task 3: exit option	⚠️ Partial	Window close still works, but no game-over menu/exit choice
Task 4: successful-hit sound	❌ Missing	No audio code
Task 4: miss sound	❌ Missing	No audio code
Task 4: timeout/miss sound	❌ Missing	No audio code
Task 4: round-ending sound	❌ Missing	No audio code

12. Root cause of each problem

Problem 1 — Collision detection is too large

Root cause: `Target.contains_point()` uses:

```
self.base_radius
```

instead of the target's current rendered radius.

Meanwhile `render()` uses:

```
self.target.visual_radius()
```

Therefore the logical hitbox and visual target diverge as the target shrinks.

Affected file: `game/target.py`

Problem 2 — No graphical Game Over screen

The game does correctly detect the end:

```
self.game_over = True
```

But there is no game-over rendering branch that draws a message or final statistics.

Instead, `render()` executes:

```
print(...)
```

which sends the information to the terminal.

Affected file: `game/game_engine.py`

Problem 3 — No Game Over input handling

At game over:

```
if self.game_over:
    return
```

appears at the beginning of `handle_event()`.

That means **all events are ignored** after the round ends.

Consequently there is no mechanism for:

```
Game Over
  ↓
Press key / click
  ↓
Replay / exit
```

Affected file: `game/game_engine.py`

Problem 4 — No replay/reset mechanism

There is no function that resets:

```
hits
misses
score
time_left_frames
game_over
target
```

to their initial values.

The only target creation mechanism is `_spawn_target()`, which creates a target but doesn't reset the rest of the round.

So simply spawning another target would not constitute a replay.

Affected file: `game/game_engine.py`

Problem 5 — No difficulty system

GameEngine always does:

```
Target(x, y)
```

with no difficulty argument.

And Target defaults permanently to:

```
base_radius=40  
min_radius=12  
lifespan_frames=90
```

There is consequently no state representing:

```
Easy  
Medium  
Hard
```

and no way for difficulty selection to alter target lifespan/size.

Affected files: game/game_engine.py , game/target.py

Problem 6 — No sound system

There is:

```
pygame.init()
```

but no:

```
pygame.mixer
```

usage and no sound files/resources.

None of these events currently trigger audio:

- hit
- manual miss
- timeout

- game over

Affected files: currently no audio implementation exists.

Also, `requirements.txt` contains only:

```
pygame
```

which is sufficient for Pygame audio itself, but the repository has no actual sound assets.

13. One subtle issue worth knowing

The target's lifecycle is:

```
spawn
  ↓
age increases every frame
  ↓
visual radius decreases
  ↓
age reaches 90
  ↓
miss++
  ↓
new target
```

The game updates **after processing mouse events**:

```
handle_event()
handle_input()
update()
render()
```

So a click is tested against the target's state from before that frame's `update()`.

That's not inherently wrong, but it matters when fixing Task 1: collision detection should correspond to the radius that is actually being displayed for the current target state.

14. Concise implementation plan

I would implement the lab in this order:

1. Fix collision detection

Modify `Target.contains_point()` so the hit-test uses the **current visual radius**, not `base_radius`.

Goal:

```
drawn circle radius == clickable radius
```

2. Create a proper Game Over state/screen

Keep `game_over` as the state flag, but make `render()` display:

```
GAME OVER

Final Score: X
Accuracy: X%

[Replay]
[Exit]
```

instead of relying on `print()`.

3. Add Game Over input handling

Allow input while `game_over == True`.

The input should transition to either:

```
Replay → difficulty selection
Exit   → quit
```

rather than being discarded by:

```
if self.game_over:
    return
```

4. Add difficulty selection

Introduce three difficulty configurations:

```
Easy  
Medium  
Hard
```

Each should define target characteristics such as:

- lifespan
- starting radius
- minimum radius

Then pass those values when creating a `Target`.

5. Add a clean round-reset/replay mechanism

Create a dedicated reset/start-round operation that resets:

```
target  
timer  
hits  
misses  
score  
game_over
```

while preserving the selected difficulty.

This prevents old score/accuracy from carrying into a replay.

6. Add sound feedback

Add four sound events:

```
successful hit → hit sound  
manual miss   → miss sound  
timeout       → miss/timeout sound  
game over     → round-ending sound
```

The sounds should be triggered exactly where those game events occur rather than from the rendering code.

7. Test against the README's expected behavior

Test specifically:

1. Target shrinking.
2. Clicking the visible edge of a small target.
3. Clicking outside it.
4. Waiting for timeout.
5. Timer reaching zero.
6. Final score/accuracy.
7. Replay.
8. Each difficulty.
9. Exit.
10. All four sound events.

Bottom line: the base game is already substantially implemented. The main existing functional defect is **collision detection using a fixed 40-pixel hitbox while the target visually shrinks to 12 pixels**. Tasks 2-4 are largely unimplemented rather than subtly broken: the necessary game-state architecture for those features does not yet exist.

9/30/2026, 8:46:37 AM · gpt-5-6



Okay, let's implement **Task 1: collision detection** first.

Based on the code you analyzed, explain the smallest change needed in `Target.contains_point()` so that collision detection matches the target's current visible radius as it shrinks.

Please:

1. Show me the current code that is wrong.
2. Show me only the code I need to change.
3. Explain why the change fixes the bug.
4. Tell me exactly which file to edit in VS Code.
5. Give me a simple way to test the fix manually.

9/30/2026, 8:49:10 AM



Yes — Task 1 only needs a **very small change**.

1. Current code that is wrong

In `game/target.py`, `Target.contains_point()` currently uses the fixed `base_radius`:

```
def contains_point(self, x, y):  
    return math.hypot(self.x - x, self.y - y) <= self.base_radius
```

The problem is that `base_radius` stays at **40**, even after the target visually shrinks.

2. Change only this code

Replace the function with:

```
def contains_point(self, x, y):  
    return math.hypot(self.x - x, self.y - y) <= self.visual_radius()
```

That's the **only code change needed for Task 1**.

3. Why this fixes it

Your target is drawn using:

```
self.target.visual_radius()
```

and `visual_radius()` decreases as the target ages:

```
Start → radius 40
      ↓
      ↓ shrinking
      ↓
End   → radius 12
```

Previously, collision detection always checked against:

```
radius = 40
```

So you could click **outside the visible small circle** and still get a hit.

After the change, both use the same radius:

```
Rendering:
visible radius → visual_radius()

Collision:
hit radius → visual_radius()
```

So the **clickable area exactly matches the visible target**.

4. File to edit in VS Code

Open:

```
47_target-aim-trainer/
├── game/
│   └── target.py ← EDIT THIS
```

Find:

```
def contains_point(self, x, y):
```

and replace only that function.

Do not modify `game_engine.py` **or** `main.py` **for this task.**

5. Simple manual test

Run the game normally.

Test 1 — beginning of target life

1. Immediately click near the edge of the large target.
2. A click inside the visible circle should register as a hit.

Test 2 — after it has shrunk

1. Wait until the target becomes noticeably small.
2. Click **just outside the visible circle but well within the original 40-pixel radius**.
3. It should now register as a **miss**, not a hit.
4. Click inside the small visible circle.
5. It should register as a **hit**.

The easiest way to verify the fix is specifically:

Wait until the target is tiny → click around the old 40px boundary but outside the visible circle → make sure it does NOT spawn a new target.

That's exactly the bug Task 1 is asking you to fix.

9/30/2026, 8:49:08 AM · gpt-5-6



I made the change and tested Task 1. The game runs correctly, and the collision detection now matches the visible shrinking target. Let's move to Task 2.

9/30/2026, 8:54:18 AM



Great. For **Task 2**, we should build on the existing `game_over` flag rather than restructure the game.

The task is essentially:

1. When the timer reaches 0 → enter Game Over state.
2. Show a **graphical Game Over screen**.
3. Display the **final score and accuracy**.
4. Let the player choose **Replay** or **Exit**.

The existing timer logic already handles step 1. The missing pieces are the graphical screen and Game Over input handling.

Task 2 implementation plan

We'll make changes only in `game/game_engine.py`:

1. Add a `reset_game()` /replay mechanism for starting another round.
2. Change `handle_event()` so clicks/keys are still processed when `game_over` is `True`.
3. Add Game Over rendering inside `render()`.
4. Keep the existing final score and accuracy calculation.
5. Make sure the normal gameplay logic stops while the Game Over screen is displayed.

One thing I'd recommend before editing: since your README may specify exactly what the Game Over screen should contain/interact with, I can re-check the actual

README and give you the **smallest possible Task 2 patch**, just like we did for Task 1.

9/30/2026, 8:54:14 AM · gpt-5-6



Yes, re-check the actual README and current `game/game\_engine.py`, then give me the smallest Task 2 implementation.

9/30/2026, 8:54:55 AM



Thinking

- Searched 7 websites
- Investigated File Search tool schema errors
- Listing ZIP archive contents
- Inspecting Aim Trainer Zip Contents

✓ Worked for 22s

I re-checked the **actual README and current** `game/game_engine.py` **from your uploaded ZIP**. Task 2 is narrower than Task 3: **do not add replay or difficulty yet**. The README only asks for a Game Over screen showing final score/accuracy and waiting for input. ([GitHub](#))

The smallest clean implementation is therefore **only in** `game/game_engine.py`.

1. What already works

The timer already ends the round:

```
if self.time_left_frames <= 0:  
    self.game_over = True  
    return
```

So we **do not need to change** `update()`.

Currently, however, `render()` only prints:

```
print(f"Time's up! Final score: {self.score} Accuracy: {self.accuracy()}%")
```

And `handle_event()` immediately ignores everything after Game Over:

```
if self.game_over:
    return
```

Those are the two things Task 2 needs fixed.

2. Smallest Task 2 implementation

File to edit

```
game/game_engine.py
```

Change 1 - Game Over input

Replace the current `handle_event()`:

```
def handle_event(self, event):
    if self.game_over:
        return
    if event.type == pygame.MOUSEBUTTONDOWN:
        self._handle_click(event.pos)
```

with:

```
def handle_event(self, event):
    if self.game_over:
        if event.type == pygame.KEYDOWN:
            pygame.quit()
            raise SystemExit
        return

    if event.type == pygame.MOUSEBUTTONDOWN:
        self._handle_click(event.pos)
```

This makes the game **wait for a key press** after Game Over instead of continuing to process gameplay clicks.

For Task 2, a key press exits. **Replay will be Task 3**, so we don't add it yet.

Change 2 - Draw the Game Over screen

Replace the current `render()` function with this:

```
def render(self, screen):
    if self.game_over:
        game_over_text = self.font.render("GAME OVER", True, WHITE)
        score_text = self.font.render(
            f"Final Score: {self.score}", True, WHITE
        )
        acc_text = self.font.render(
            f"Accuracy: {self.accuracy()}%", True, WHITE
        )
        instruction_text = self.font.render(
            "Press any key to exit", True, WHITE
        )

        screen.blit(
            game_over_text,
            (self.width // 2 - game_over_text.get_width() // 2, 150)
        )
        screen.blit(
            score_text,
            (self.width // 2 - score_text.get_width() // 2, 210)
        )
        screen.blit(
            acc_text,
            (self.width // 2 - acc_text.get_width() // 2, 250)
        )
        screen.blit(
            instruction_text,
            (self.width // 2 - instruction_text.get_width() // 2, 320)
        )
        return

    r = int(self.target.visual_radius())
    pygame.draw.circle(screen, RED, (self.target.x, self.target.y), r)
    pygame.draw.circle(screen, WHITE, (self.target.x, self.target.y), r, 2)

    score_text = self.font.render(f"Score: {self.score}", True, WHITE)
    screen.blit(score_text, (10, 10))
```

```
seconds_left = max(0, self.time_left_frames // 60)
timer_text = self.font.render(f"Time: {seconds_left}s", True, WHITE)
screen.blit(timer_text, (self.width - 140, 10))

acc_text = self.font.render(f"Accuracy: {self.accuracy()}%", True, WHITE)
screen.blit(acc_text, (self.width // 2 - 90, 10))
```

Why the `return` matters

Once:

```
self.game_over == True
```

the function draws the Game Over screen and immediately returns.

Therefore it **doesn't draw the target or normal gameplay HUD underneath it.**

3. One thing to remove

The old console-printing code at the bottom of `render()`:

```
if self.game_over and not getattr(self, "_game_over_logged", False):
    print(f"Time's up! Final score: {self.score} Accuracy: {self.accuracy()}%")
    self._game_over_logged = True
```

is removed entirely.

The result is now displayed **inside the Pygame window**, which is exactly what Task 2 asks for.

4. What the resulting flow becomes

```
30-second round
    ↓
Timer reaches 0
    ↓
game_over = True
    ↓
```

```
Normal gameplay stops
↓
Game Over screen appears
↓
Final Score displayed
Accuracy displayed
↓
"Press any key to exit"
↓
Key pressed
↓
Game exits
```

This deliberately **doesn't implement Replay or difficulty selection yet**. Those belong to Task 3.

5. Test it

Run:

```
python main.py
```

Then either:

- play normally until the 30 seconds expire, **or**
- temporarily wait for the timer to reach zero.

You should see something like:

```
GAME OVER

Final Score: 8
Accuracy: 72.7%

Press any key to exit
```

Then press any keyboard key.

Verify these three things

1. **No terminal message is required** - the result appears in the game window.

2. **The target no longer appears/moves** after Game Over.
3. **A key press exits the game.**

Once this works, Task 2 is complete without prematurely mixing in Task 3's replay/difficulty functionality.

Sources

[GitHub - yoyozaemon/CC-UE20CS351: A repository containing the source code for the Cloud Computing Laboratory, Assignment and Project Course \(UE20CS351\) at PES University · GitHub](#) [github.com](#)

9/30/2026, 8:54:50 AM · gpt-5-6



okay task 2 is working now. let's move to the next README requirement: add difficulty levels (Easy/Medium/Hard) and replay functionality. please first inspect the current code and explain what needs to change, then give me the changes step by step without changing unrelated parts.

9/30/2026, 10:43:24 PM



Thinking

- Searched 5 websites
- Inspecting ZIP archive contents
- Inspected ZIP archive and extracted project files

✓ Worked for 20s

Yep. I re-checked the **actual README requirement** and the source in the uploaded repository. One important note: the ZIP you uploaded is the **original repository**, so its `game_engine.py` still shows the pre-Task-2 code. I'm therefore using the Task 2 changes you just confirmed working as the current state.

The README's Task 3 requirement is specifically:

"After Game Over, allow the user to play again by choosing a difficulty (Easy, Medium, or Hard target lifespan/size), or exit."

So we can implement this **without touching** `main.py` **or** `target.py`. `Target` already accepts `base_radius`, `min_radius`, and `lifespan_frames`, so the engine can supply different values for each difficulty.

What needs to change

There are 3 pieces:

1. Store the selected difficulty

Currently there is no difficulty state.

We'll add something like:

```
self.difficulty = "Medium"
```

and a difficulty configuration:

```
self.difficulties = {  
    "Easy": (45, 14, 120),  
    "Medium": (40, 12, 90),  
    "Hard": (35, 10, 60)  
}
```

These mean:

Difficulty	Starting size	Minimum size	Lifespan
Easy	45	14	120 frames $\approx$ 2 sec
Medium	40	12	90 frames $\approx$ 1.5 sec
Hard	35	10	60 frames $\approx$ 1 sec

The README doesn't prescribe exact numbers, so these are sensible values that make the difficulty visibly meaningful.

2. Make `_spawn_target()` use the selected difficulty

Currently it does:

```
return Target(x, y)
```

That means every target always gets the default:

```
40 radius → 12 radius → 90 frames
```

We'll instead retrieve the settings for the selected difficulty and pass them into `Target`.

This works because `Target.__init__()` already supports:

```
Target(x, y, base_radius, min_radius, lifespan_frames)
```

Therefore `target.py` **does not need to change.**

3. Replace the current Game Over exit behavior with a difficulty menu

Your Task 2 version currently does roughly:

```
Game Over
Final Score
Accuracy
Press any key to exit
```

Task 3 changes that to:

```
GAME OVER

Final Score: 8
Accuracy: 72.7%

Choose difficulty:
[E] Easy
[M] Medium
[H] Hard

[X] Exit
```

Then:

```
E → reset game → Easy round
M → reset game → Medium round
H → reset game → Hard round
X → exit
```

Pygame's event system provides `KEYDOWN` events with the pressed key in `event.key`, so this fits directly into the event handling you already have. ([Pygame](#))

Step-by-step changes

We'll keep this deliberately contained to:

```
game/game_engine.py
```

No changes to `main.py`.

No changes to `target.py`.

Step 1 - Add difficulty configuration

Inside `GameEngine.__init__()`, after your existing setup, add:

```
self.difficulties = {
    "Easy": (45, 14, 120),
    "Medium": (40, 12, 90),
    "Hard": (35, 10, 60)
}

self.difficulty = "Medium"
```

So your engine now knows which difficulty is active.

Step 2 - Change `_spawn_target()`

Your current function is:

```
def _spawn_target(self):
    x = random.randint(self.margin, self.width - self.margin)
    y = random.randint(self.margin + self.hud_height, self.height -
self.margin)
    return Target(x, y)
```

Change **only the last part**:

```
def _spawn_target(self):
    x = random.randint(self.margin, self.width - self.margin)
    y = random.randint(self.margin + self.hud_height, self.height -
self.margin)

    base_radius, min_radius, lifespan_frames =
```

```
self.difficulties[self.difficulty]

    return Target(x, y, base_radius, min_radius, lifespan_frames)
```

Now every newly spawned target automatically uses the current difficulty.

For example, Hard produces a smaller/faster target:

```
base radius = 35
minimum radius = 10
lifespan = 60 frames
```

Step 3 - Add a reset function

Add this method to `GameEngine` :

```
def reset_game(self):
    self.time_left_frames = self.round_seconds * 60
    self.hits = 0
    self.misses = 0
    self.score = 0
    self.game_over = False
    self.target = self._spawn_target()
```

This is important because **replay must start a completely fresh round**.

Without it, the previous score/hits/misses would carry over.

Notice that it does **not** reset:

```
self.difficulty
```

because we want the difficulty the player just selected to be used for the new round.

Step 4 - Change Game Over input handling

Your Task 2 version currently has something similar to:

```
if self.game_over:
    if event.type == pygame.KEYDOWN:
        pygame.quit()
```

```
        raise SystemExit
    return
```

Replace just that Game Over section with:

```
if self.game_over:
    if event.type == pygame.KEYDOWN:
        if event.key == pygame.K_e:
            self.difficulty = "Easy"
            self.reset_game()
        elif event.key == pygame.K_m:
            self.difficulty = "Medium"
            self.reset_game()
        elif event.key == pygame.K_h:
            self.difficulty = "Hard"
            self.reset_game()
        elif event.key == pygame.K_x:
            pygame.quit()
            raise SystemExit
    return
```

Keep your normal gameplay click handling underneath it:

```
if event.type == pygame.MOUSEBUTTONDOWN:
    self._handle_click(event.pos)
```

So the overall function becomes:

```
def handle_event(self, event):
    if self.game_over:
        if event.type == pygame.KEYDOWN:
            if event.key == pygame.K_e:
                self.difficulty = "Easy"
                self.reset_game()
            elif event.key == pygame.K_m:
                self.difficulty = "Medium"
                self.reset_game()
            elif event.key == pygame.K_h:
                self.difficulty = "Hard"
                self.reset_game()
            elif event.key == pygame.K_x:
```

```

        pygame.quit()
        raise SystemExit
    return

if event.type == pygame.MOUSEBUTTONDOWN:
    self._handle_click(event.pos)

```

Step 5 - Change only the Game Over part of `render()`

Your current Task 2 Game Over section displays the final score and accuracy.

Change the instruction text from:

```
Press any key to exit
```

to:

```
[E] Easy    [M] Medium    [H] Hard
[X] Exit
```

For example:

```

instruction_text = self.font.render(
    "[E] Easy    [M] Medium    [H] Hard", True, WHITE
)

exit_text = self.font.render(
    "[X] Exit", True, WHITE
)

```

Then draw both.

The Game Over portion should conceptually look like:

```

if self.game_over:
    game_over_text = self.font.render("GAME OVER", True, WHITE)
    score_text = self.font.render(
        f"Final Score: {self.score}", True, WHITE
    )
    acc_text = self.font.render(
        f"Accuracy: {self.accuracy()}%", True, WHITE
    )

```

```

)
instruction_text = self.font.render(
    "[E] Easy    [M] Medium    [H] Hard", True, WHITE
)
exit_text = self.font.render(
    "[X] Exit", True, WHITE
)

screen.blit(
    game_over_text,
    (self.width // 2 - game_over_text.get_width() // 2, 150)
)
screen.blit(
    score_text,
    (self.width // 2 - score_text.get_width() // 2, 210)
)
screen.blit(
    acc_text,
    (self.width // 2 - acc_text.get_width() // 2, 250)
)
screen.blit(
    instruction_text,
    (self.width // 2 - instruction_text.get_width() // 2, 320)
)
screen.blit(
    exit_text,
    (self.width // 2 - exit_text.get_width() // 2, 360)
)
return

```

Keep the `return`.


That prevents the normal target from being rendered behind the menu.

Resulting flow

After these changes:

GAME RUNNING





Or:

GAME OVER → X → Exit

What we are not changing

To keep this isolated to Task 3:

- ✗ `main.py` - unchanged
- ✗ `target.py` - unchanged
- ✗ collision detection - unchanged from your Task 1 fix
- ✗ timer logic - unchanged
- ✗ scoring - unchanged
- ✗ accuracy calculation - unchanged
- ✗ sound - **Task 4**
- ✗ gameplay loop - unchanged

The only file you need to edit is:

```
47_target-aim-trainer/  
└─ game/  
    └─ game_engine.py    ← only file
```

Recommended implementation order

Do **one step at a time** and run after each:

1. Add `difficulties` + `difficulty`.
2. Modify `_spawn_target()`.
3. Add `reset_game()`.
4. Change Game Over keyboard handling.
5. Change the Game Over display.
6. Test Easy → Medium → Hard → Exit.

That way, if something breaks, we know exactly which small change caused it.

Sources

[pygame.event](#) — [pygame v2.6.0 documentation](#) [pygame.org](#)

9/30/2026, 10:43:19 PM · gpt-5-6



Task 3 is working now. Let's implement the next README requirement .

9/30/2026, 11:24:43 PM



I'll check the README's next requirement against the repository structure, then keep the implementation limited to that requirement—no unrelated refactoring.

Thinking



Inspecting ZIP README requirements

- Inspected ZIP requirements and current game engine code

✓ Worked for 20s

Yep — the **next README requirement is Task 4: Sound Feedback.**

The README specifically requires three sound cases:

1. **Successful hit**
2. **Miss**, including a target that times out
3. **Round ending**

Since your Task 3 is already working, we should add sound **without changing your difficulty/replay logic.**

What needs to change

The cleanest minimal approach is:

```
game/  
├─ game_engine.py  
├─ target.py  
└─ sounds/  
    └─ hit.wav
```

```
|— miss.wav  
|— game_over.wav
```

And only `game_engine.py` needs code changes.

`target.py` should stay untouched.

Where each sound belongs

Your existing logic already has the exact locations where these events happen:

Successful hit:

```
if self.target.contains_point(x, y):  
    self.hits += 1  
    self.score += 1  
    self.target = self._spawn_target()
```

→ play `hit.wav` here.

Manual miss:

```
else:  
    self.misses += 1
```

→ play `miss.wav` here.

Timed-out target:

```
if self.target.expired():  
    self.misses += 1  
    self.target = self._spawn_target()
```

→ play `miss.wav` here too.

Round ending:

```
if self.time_left_frames <= 0:  
    self.game_over = True  
    return
```

→ play `game_over.wav` here.

Step 1 — Add the sound files

Create this folder inside your project:

```
47_target-aim-trainer/  
├── game/  
│   ├── game_engine.py  
│   ├── target.py  
│   └── sounds/  
│       ├── hit.wav  
│       ├── miss.wav  
│       └── game_over.wav
```

You need actual `.wav` files.

They can be very short — for example:

- `hit.wav` → short click/pop
- `miss.wav` → short error/buzz
- `game_over.wav` → short end-of-round sound

Don't change `requirements.txt`. Pygame already includes the mixer functionality needed for this.

Step 2 — Initialize the mixer

At the beginning of `GameEngine.__init__()`, after the existing setup, add:

```
pygame.mixer.init()  
  
self.hit_sound = pygame.mixer.Sound("game/sounds/hit.wav")  
self.miss_sound = pygame.mixer.Sound("game/sounds/miss.wav")  
self.game_over_sound = pygame.mixer.Sound("game/sounds/game_over.wav")
```

So the engine loads the sounds once when the game starts.

Don't load the sound inside `_handle_click()` **or** `update()`. Those functions run repeatedly, so loading files there would be unnecessary.

Step 3 — Add the hit sound

In `_handle_click()`, change:

```
if self.target.contains_point(x, y):
    self.hits += 1
    self.score += 1
    self.target = self._spawn_target()
```

to:

```
if self.target.contains_point(x, y):
    self.hits += 1
    self.score += 1
    self.hit_sound.play()
    self.target = self._spawn_target()
```

That's it.

Step 4 — Add the manual miss sound

Change:

```
else:
    self.misses += 1
```

to:

```
else:
    self.misses += 1
    self.miss_sound.play()
```

Now clicking outside the target produces the miss sound.

Step 5 — Add the timeout miss sound

Your existing timeout code is:

```
if self.target.expired():
    self.misses += 1
    self.target = self._spawn_target()
```

Change it to:

```
if self.target.expired():
    self.misses += 1
    self.miss_sound.play()
    self.target = self._spawn_target()
```

This satisfies the README's requirement that a **timed-out target is also a miss** with feedback.

Step 6 — Add the Game Over sound

Your timer code currently does:

```
if self.time_left_frames <= 0:
    self.game_over = True
    return
```

Change it to:

```
if self.time_left_frames <= 0:
    self.game_over = True
    self.game_over_sound.play()
    return
```

The sound plays exactly once because after `game_over` becomes `True`, the beginning of `update()` prevents the code from running again:

```
if self.game_over:
    return
```

So **don't add any extra flag for the Game Over sound**.

That's all the code changes

Your Task 4 changes are therefore limited to:

`game/game_engine.py`

- Initialize 3 sounds

- Play hit sound on successful hit
- Play miss sound on manual miss
- Play miss sound on timeout
- Play game-over sound when timer reaches zero

New files

```
game/sounds/hit.wav  
game/sounds/miss.wav  
game/sounds/game_over.wav
```

Don't touch

```
main.py      ✗  
target.py    ✗  
requirements.txt ✗
```

One important path detail

Because you're running:

```
python main.py
```

from the **repository root**, this:

```
"game/sounds/hit.wav"
```

is the simplest path for your current project structure.

Testing order

After adding the sounds:

Test 1 — Hit

Click directly on a target → 🎧 hit sound.

Test 2 — Manual miss

Click somewhere away from the target → 🎧 miss sound.

Test 3 — Timeout

Don't click the target → when it disappears → 🎧 miss sound.

Test 4 — Game Over

Let the 30-second timer reach zero → 🎧 game-over sound → your Task 3 Game Over screen appears.

If all four work, **Task 4 is complete.**

9/30/2026, 11:24:38 PM · gpt-5-6