

Ace2 PCR results, Culex pipiens complex

Norah Saarman

2024-02-27

R build: Geospatial 4.4.0

Import species/hybrid counts per site

```
counts <- read.csv("../data/ThisStudy.txt", sep = "\t")
countsSp <- SpatialPoints(coords = cbind(counts$long, counts$lat))
```

Genotypes in p/q notation: Cx. pipiens = pp Cx. quinquefasciatus = qq

Create a dataframe of counts

```
# start data frame and name fields
countsDf <- as.data.frame(counts[,c(2,1,4,5,6,9,10,7,8)])
names(countsDf) <- c("locality", "site", "pp", "pq", "qq", "latitude", "longitude", "year", "h-index")

# name rows
rownames(countsDf) <- countsDf$site
```

Pie charts on a map

Convert counts to proportions (frequency):

```
freqsDf <- as.data.frame(countsDf[,c("pp", "pq", "qq")])
freqsDf <- as.matrix.data.frame(t(apply(freqsDf, 1, function(row) row / sum(row))))
```


One pie chart at a time, to check code

Plot points on map to check data:

```
# Set xpd to NA to allow for plotting in the margins
par(xpd = NA)

#create and plot coord = long, lat
coord <- as.data.frame(countsDf[,c("longitude", "latitude")])

#plot coordinates onto map
map("usa")
map(add = T, col = "grey90", fill = TRUE)
points(coord, col="black", cex=1)
```




Add pies to map following: “<http://membres-timc.imag.fr/Olivier.Francois/Conversion.R>”

```
# Set xpd to NA to allow for plotting in the margins
par(xpd = NA)
```

```
# Determine plot order by descending h-index
plot_order <- rev(order(countsDf$h-index`))
```

```
# plot pies onto map
map("usa")
map(add = T, col = "grey90", fill = TRUE)
for (i in plot_order){
  add.pie(z = freqsDf[i,],
    x = coord[i,1],
    y = coord[i,2],
    clockwise=TRUE,
    labels = "",
    col = c("black","grey","white"),
    cex = 1, radius = 1 )
}
```



Create a jitter data frame by hand:

```
# Create a jitter df
jitterDf <- data.frame(x_jitter = rep(0,25), y_jitter = rep(0,25))
rownames(jitterDf) <- rownames(countsDf)
jitterDf[3,] <- c(0,1)
jitterDf[5,] <- c(1,-1)
jitterDf[6,] <- c(-2,0)
jitterDf[8,] <- c(2,-3)
jitterDf[9,] <- c(3,-1)
jitterDf[14,] <- c(3,1.5)
jitterDf[16,] <- c(2,-1.5)
jitterDf[19,] <- c(1,1)
jitterDf[20,] <- c(1,-1)
```

Add jitter with a line from true origin:

```
# Set xpd to NA to allow for plotting in the margins
par(xpd = NA)

# Plot base map
map("usa")
map(add = TRUE, col = "grey90", fill = TRUE)

for (i in plot_order) {
  # Jittered coordinates
  jittered_x <- coord[i, 1] + (jitterDf[i, 1])
```

```

jittered_y <- coord[i, 2] + (jitterDf[i, 2])

# Draw line from true location to jittered pie
segments(x0 = coord[i, 1],
         y0 = coord[i, 2],
         x1 = jittered_x,
         y1 = jittered_y,
         col = "black", lty = 1, lwd = 1)

# Plot pie chart at jittered location
add.pie(z = freqsDf[i,],
       x = jittered_x,
       y = jittered_y,
       clockwise = TRUE,
       labels = "",
       col = c("black", "grey", "white"),
       cex = 1.2, radius = 1.2)
}

```

