```sql
SELECT
  AVG(total)
FROM
  fastkitchen.orders;

SELECT
  order_type,
  AVG(total) AS ato,
  AVG(subtotal) AS asu,
  AVG(tip) AS ati
FROM
  fastkitchen.orders
GROUP BY
  order_type;

SELECT
  COUNT(order_id)
FROM
  fastkitchen.orders
WHERE
  user_id is NOT NULL;

SELECT
  user_id,
  COUNT(order_id)
FROM
  fastkitchen.orders
WHERE
  user_id is NULL
GROUP BY
  user_id;

SELECT
  COUNT(user_id),
  city
FROM
  fastkitchen.users
GROUP BY
  city
ORDER BY
  count DESC;

SELECT
  COUNT(user_id),
```

```sql
  city,
  zip
FROM
  fastkitchen.users
GROUP BY
  city,
  zip
ORDER BY
  count DESC;

SELECT
  o.*,
  u.*
FROM
  fastkitchen.users AS u FULL
  OUTER JOIN fastkitchen.orders AS o ON u.user_id = o.user_id;

SELECT
  u.zip,
  MAX(total)
FROM
  fastkitchen.users AS u FULL
  OUTER JOIN fastkitchen.orders AS o ON u.user_id = o.user_id
GROUP BY
  zip;

SELECT
  u.zip,
  AVG(total)
FROM
  fastkitchen.users AS u FULL
  OUTER JOIN fastkitchen.orders AS o ON u.user_id = o.user_id
GROUP BY
  zip;
```