VIT-AP UNIVERSITY, ANDHRA PRADESH

Lab Sheet 7: MongoDB with Basic Commands

Branch/ Class: B.Tech/M.Tech
Faculty Name: Prof. S.Gopikrishnan
Student name: Duddu Sabareesh

Date: 11-03-2026
School: SCOPE
Reg. no.: 23BCE9055

---

1. Use MongoDB to implement the following DB operations

1. Create a database called 'vehicles' and *write* a MongoDB query to select database as "vehicles".

```
>_MONGOSH
> use vehicles
< switched to db vehicles
```

2. Write a MongoDB query to display all the databases.

```
> show dbs
< admin   40.00 KiB
  config  36.00 KiB
  local   40.00 KiB
```

3. Create a collection called 'two_wheelers'. (use capping) and Create a collection called 'four_wheelers'.

```
> db.createCollection("two_wheelers", { capped: true, size: 500000 })
< { ok: 1 }
> db.createCollection("four_wheelers")
< { ok: 1 }
```

4. Add 5 two-wheeler details to the collection named 'two_wheelers'. Each document consists of following fields as bike_name, model (gear or gearless), category (100cc, 125cc, 150cc, 200cc), colors_available (red, black, blue, sport red etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
>_MONGOSH
< { ok: 1 }
> db.two_wheelers.insertMany([
  {
  bike_name: "Hero Splendor",
  model: "gear",
  category: "100cc",
  colors_available: ["black","red","blue"],
  manufacturer: "Hero",
  performance: 7,
  timestamp: new Date("2018-01-10"),
  price: 75000
  },

  {
  bike_name: "Honda Activa",
  model: "gearless",
  category: "125cc",
  colors_available: ["white","black","blue"],
  manufacturer: "Honda",
  performance: 8,
  timestamp: new Date("2020-03-15"),
  price: 85000
  },

  {
  bike_name: "Yamaha R15",
  model: "gear",
  category: "150cc",
  colors_available: ["sport red","black"],
  manufacturer: "Yamaha",
  performance: 9,
  timestamp: new Date("2019-05-20"),
  price: 180000
  },
```

```
>_MONGOSH
  {
  bike_name: "Bajaj Pulsar",
  model: "gear",
  category: "200cc",
  colors_available: ["black","blue"],
  manufacturer: "Bajaj",
  performance: 8,
  timestamp: new Date("2021-07-25"),
  price: 160000
  },

  {
  bike_name: "TVS Jupiter",
  model: "gearless",
  category: "125cc",
  colors_available: ["silver","black"],
  manufacturer: "TVS",
  performance: 7,
  timestamp: new Date("2022-02-12"),
  price: 90000
  }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b14a75fa7e1dd49711e5b5'),
      '1': ObjectId('69b14a75fa7e1dd49711e5b6'),
      '2': ObjectId('69b14a75fa7e1dd49711e5b7'),
      '3': ObjectId('69b14a75fa7e1dd49711e5b8'),
      '4': ObjectId('69b14a75fa7e1dd49711e5b9')
    }
  }
```

5. Add 5 four-wheeler details to the collection named ‘four_wheelers’. Each document consists of following fields as vehicle_name, model (commercial or own), category (car, lorry, bus, mini truck, heavy truck, containers), variants (vxi, zxi, petrol, diesel etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
>_MONGOSH
> db.four_wheelers.insertMany([
  {
  vehicle_name: "Maruti Swift",
  model: "own",
  category: "car",
  variants: ["vxi","petrol"],
  manufacturer: "Maruti",
  performance: 8,
  timestamp: new Date("2019-04-12"),
  price: 700000
  },

  {
  vehicle_name: "Tata Bus",
  model: "commercial",
  category: "bus",
  variants: ["diesel"],
  manufacturer: "Tata",
  performance: 7,
  timestamp: new Date("2018-06-15"),
  price: 2500000
  },

  {
  vehicle_name: "Ashok Leyland Truck",
  model: "commercial",
  category: "heavy truck",
  variants: ["diesel"],
  manufacturer: "Ashok Leyland",
  performance: 8,
  timestamp: new Date("2020-09-18"),
  price: 3000000
  },
```

```
>_MONGOSH
  {
  vehicle_name: "Mahindra Bolero",
  model: "own",
  category: "car",
  variants: ["zxi","diesel"],
  manufacturer: "Mahindra",
  performance: 7,
  timestamp: new Date("2021-11-20"),
  price: 950000
  },

  {
  vehicle_name: "Eicher Container",
  model: "commercial",
  category: "containers",
  variants: ["diesel"],
  manufacturer: "Eicher",
  performance: 6,
  timestamp: new Date("2017-01-10"),
  price: 3500000
  }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b14a80fa7e1dd49711e5ba'),
      '1': ObjectId('69b14a80fa7e1dd49711e5bb'),
      '2': ObjectId('69b14a80fa7e1dd49711e5bc'),
      '3': ObjectId('69b14a80fa7e1dd49711e5bd'),
      '4': ObjectId('69b14a80fa7e1dd49711e5be')
    }
  }
```

6. Write a MongoDB query to display all documents available in two_wheelers and four_wheelers.

```
>_MONGOSH
> db.two_wheelers.find()
< {
    _id: ObjectId('69b14a75fa7e1dd49711e5b5'),
    bike_name: 'Hero Splendor',
    model: 'gear',
    category: '100cc',
    colors_available: [
      'black',
      'red',
      'blue'
    ],
    manufacturer: 'Hero',
    performance: 7,
    timestamp: 2018-01-10T00:00:00.000Z,
    price: 75000
  }
  {
    _id: ObjectId('69b14a75fa7e1dd49711e5b6'),
    bike_name: 'Honda Activa',
    model: 'gearless',
    category: '125cc',
    colors_available: [
      'white',
      'black',
      'blue'
    ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: 2020-03-15T00:00:00.000Z,
    price: 85000
  }
  {
    _id: ObjectId('69b14a75fa7e1dd49711e5b7'),
    bike_name: 'Yamaha R15',
    model: 'gear',
```

```
>_MONGOSH
    model: 'gear',
    category: '150cc',
    colors_available: [
      'sport red',
      'black'
    ],
    manufacturer: 'Yamaha',
    performance: 9,
    timestamp: 2019-05-20T00:00:00.000Z,
    price: 180000
  }
  {
    _id: ObjectId('69b14a75fa7e1dd49711e5b8'),
    bike_name: 'Bajaj Pulsar',
    model: 'gear',
    category: '200cc',
    colors_available: [
      'black',
      'blue'
    ],
    manufacturer: 'Bajaj',
    performance: 8,
    timestamp: 2021-07-25T00:00:00.000Z,
    price: 160000
  }
  {
    _id: ObjectId('69b14a75fa7e1dd49711e5b9'),
    bike_name: 'TVS Jupiter',
    model: 'gearless',
    category: '125cc',
    colors_available: [
      'silver',
      'black'
    ],
    manufacturer: 'TVS',
    performance: 7,
    timestamp: 2022-02-12T00:00:00.000Z,
    price: 90000
  }
```

```
>_MONGOSH
> db.four_wheelers.find()
< {
    _id: ObjectId('69b14a80fa7e1dd49711e5ba'),
    vehicle_name: 'Maruti Swift',
    model: 'own',
    category: 'car',
    variants: [
      'vxi',
      'petrol'
    ],
    manufacturer: 'Maruti',
    performance: 8,
    timestamp: 2019-04-12T00:00:00.000Z,
    price: 700000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5bb'),
    vehicle_name: 'Tata Bus',
    model: 'commercial',
    category: 'bus',
    variants: [
      'diesel'
    ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: 2018-06-15T00:00:00.000Z,
    price: 2500000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5bc'),
    vehicle_name: 'Ashok Leyland Truck',
    model: 'commercial',
    category: 'heavy truck',
    variants: [
      'diesel'
    ],
    manufacturer: 'Ashok Leyland',
    performance: 8,
    timestamp: 2020-09-18T00:00:00.000Z,
```

```
>_MONGOSH
    timestamp: 2020-09-18T00:00:00.000Z,
    price: 3000000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5bd'),
    vehicle_name: 'Mahindra Bolero',
    model: 'own',
    category: 'car',
    variants: [
      'zxi',
      'diesel'
    ],
    manufacturer: 'Mahindra',
    performance: 7,
    timestamp: 2021-11-20T00:00:00.000Z,
    price: 950000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5be'),
    vehicle_name: 'Eicher Container',
    model: 'commercial',
    category: 'containers',
    variants: [
      'diesel'
    ],
    manufacturer: 'Eicher',
    performance: 6,
    timestamp: 2017-01-10T00:00:00.000Z,
    price: 3500000
  }
> db.two_wheelers.find({}, {bike_name:1, price:1, _id:0})
```

7. Write a MongoDB query to display only vehicle name and price in all the collection of the database

```
>_MONGOSH
> db.two_wheelers.find({}, {bike_name:1, price:1, _id:0})
< {
    bike_name: 'Hero Splendor',
    price: 75000
  }
  {
    bike_name: 'Honda Activa',
    price: 85000
  }
  {
    bike_name: 'Yamaha R15',
    price: 180000
  }
  {
    bike_name: 'Bajaj Pulsar',
    price: 160000
  }
  {
    bike_name: 'TVS Jupiter',
    price: 90000
  }
```

```
> db.four_wheelers.find({}, {vehicle_name:1, price:1, _id:0})
< {
    vehicle_name: 'Maruti Swift',
    price: 700000
  }
  {
    vehicle_name: 'Tata Bus',
    price: 2500000
  }
  {
    vehicle_name: 'Ashok Leyland Truck',
    price: 3000000
  }
  {
    vehicle_name: 'Mahindra Bolero',
    price: 950000
  }
  {
    vehicle_name: 'Eicher Container',
    price: 3500000
  }
```

8. Write a MongoDB query to display two_wheelers from a particular company

```
> db.two_wheelers.find({manufacturer:"Honda"})
< {
    _id: ObjectId('69b14a75fa7e1dd49711e5b6'),
    bike_name: 'Honda Activa',
    model: 'gearless',
    category: '125cc',
    colors_available: [
      'white',
      'black',
      'blue'
    ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: 2020-03-15T00:00:00.000Z,
    price: 85000
  }
```

9. Write a MongoDB query to display four_wheelers available in diesel variants

```
>_MONGOSH
> db.four_wheelers.find({variants:"diesel"})
< {
    _id: ObjectId('69b14a80fa7e1dd49711e5bb'),
    vehicle_name: 'Tata Bus',
    model: 'commercial',
    category: 'bus',
    variants: [
      'diesel'
    ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: 2018-06-15T00:00:00.000Z,
    price: 2500000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5bc'),
    vehicle_name: 'Ashok Leyland Truck',
    model: 'commercial',
    category: 'heavy truck',
    variants: [
      'diesel'
    ],
    manufacturer: 'Ashok Leyland',
    performance: 8,
    timestamp: 2020-09-18T00:00:00.000Z,
    price: 3000000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5bd'),
    vehicle_name: 'Mahindra Bolero',
    model: 'own',
    category: 'car',
    variants: [
      'zxi',
      'diesel'
```

```
      'diesel'
    ],
    manufacturer: 'Mahindra',
    performance: 7,
    timestamp: 2021-11-20T00:00:00.000Z,
    price: 950000
  }
  {
    _id: ObjectId('69b14a80fa7e1dd49711e5be'),
    vehicle_name: 'Eicher Container',
    model: 'commercial',
    category: 'containers',
    variants: [
      'diesel'
    ],
    manufacturer: 'Eicher',
    performance: 6,
    timestamp: 2017-01-10T00:00:00.000Z,
    price: 3500000
  }
```

10. Write a MongoDB query to display vehicles name, category and manufacturer details whose rating is more than 5.

```
>_MONGOSH
> db.two_wheelers.find(
  {performance: {$gt:5}},
  {bike_name:1, category:1, manufacturer:1, _id:0}
  )
< {
    bike_name: 'Hero Splendor',
    category: '100cc',
    manufacturer: 'Hero'
  }
  {
    bike_name: 'Honda Activa',
    category: '125cc',
    manufacturer: 'Honda'
  }
  {
    bike_name: 'Yamaha R15',
    category: '150cc',
    manufacturer: 'Yamaha'
  }
  {
    bike_name: 'Bajaj Pulsar',
    category: '200cc',
    manufacturer: 'Bajaj'
  }
  {
    bike_name: 'TVS Jupiter',
    category: '125cc',
    manufacturer: 'TVS'
  }
> db.four_wheelers.find(
  {performance: {$gt:5}},
  {vehicle_name:1, category:1, manufacturer:1, _id:0}
  )
< {
    vehicle_name: 'Maruti Swift',
    category: 'car',
    manufacturer: 'Maruti'
  }
  {
    vehicle_name: 'Tata Bus',
    category: 'bus',
    manufacturer: 'Tata'
```

```
    manufacturer: 'Tata'
  }
  {
    vehicle_name: 'Ashok Leyland Truck',
    category: 'heavy truck',
    manufacturer: 'Ashok Leyland'
  }
  {
    vehicle_name: 'Mahindra Bolero',
    category: 'car',
    manufacturer: 'Mahindra'
  }
  {
    vehicle_name: 'Eicher Container',
    category: 'containers',
    manufacturer: 'Eicher'
  }
vehicles>
```

2. Use MongoDB to implement the following DB operations for a Zoo

1. Create a database called 'animal' and *write* a MongoDB query to select database as 'animal'.

```
>_MONGOSH
> use animal
< switched to db animal
```

2. Write a MongoDB query to display all the databases.

```
> show dbs
< admin     40.00 KiB
  config    72.00 KiB
  local     40.00 KiB
  vehicles  80.00 KiB
```

3. Create a collection called 'wild_animals'.(use capping) and Create a collection called 'domestic_animals'.

```
> db.createCollection("wild_animals",{capped:true,size:500000})
< { ok: 1 }
> db.createCollection("domestic_animals")
< { ok: 1 }
```

4. Add 5 wild_animal details to the collection named 'wild_animals'. Each document consists of following fields as animal_name, nature (harm or harmless), favorite_foods (meat, rabbits, deer etc) as array, care_taker_name, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
> db.wild_animals.insertMany([
  {
  animal_name:"Lion",
  nature:"harm",
  favorite_foods:["meat","deer"],
  care_taker_name:"Ramesh",
  life_span:15,
  timestamp:new Date("2020-05-10"),
  expenses:50000
  },

  {
  animal_name:"Tiger",
  nature:"harm",
  favorite_foods:["meat","rabbits"],
  care_taker_name:"Suresh",
  life_span:16,
  timestamp:new Date("2019-03-12"),
  expenses:55000
  },

  {
  animal_name:"Elephant",
  nature:"harmless",
  favorite_foods:["grass","fruits"],
  care_taker_name:"Ramesh",
  life_span:60,
  timestamp:new Date("2018-07-20"),
  expenses:70000
  },

  {
  animal_name:"Wolf",
  nature:"harm",
  favorite_foods:["meat","rabbits"],
  care_taker_name:"Mahesh",
  life_span:14,
  timestamp:new Date("2021-02-18"),
```

```
  timestamp:new Date("2021-02-18"),
  expenses:40000
  },

  {
  animal_name:"Bear",
  nature:"harm",
  favorite_foods:["fish","honey"],
  care_taker_name:"Suresh",
  life_span:25,
  timestamp:new Date("2017-11-25"),
  expenses:45000
  }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b151487d0fd223d0e2dcb5'),
      '1': ObjectId('69b151487d0fd223d0e2dcb6'),
      '2': ObjectId('69b151487d0fd223d0e2dcb7'),
      '3': ObjectId('69b151487d0fd223d0e2dcb8'),
      '4': ObjectId('69b151487d0fd223d0e2dcb9')
    }
  }
```

5. Add 5 domestic-animal details to the collection named 'domestic_animals'. Each document consists of following fields as animal_name, gender (male or female), favorite_foods (meat, rabbits, deer etc) as array, animal_petname, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
>_MONGOSH
> db.domestic_animals.insertMany([
  {
  animal_name:"Dog",
  gender:"male",
  favorite_foods:["meat","bones"],
  animal_petname:"Tommy",
  life_span:12,
  timestamp:new Date("2022-01-10"),
  expenses:10000
  },

  {
  animal_name:"Cat",
  gender:"female",
  favorite_foods:["fish","milk"],
  animal_petname:"Kitty",
  life_span:15,
  timestamp:new Date("2021-06-12"),
  expenses:8000
  },

  {
  animal_name:"Cow",
  gender:"female",
  favorite_foods:["grass","fodder"],
  animal_petname:"Lakshmi",
  life_span:20,
  timestamp:new Date("2020-09-05"),
  expenses:15000
  },

  {
  animal_name:"Goat",
  gender:"male",
  favorite_foods:["grass","leaves"],
  animal_petname:"Ramu",
  life_span:10,
  timestamp:new Date("2019-04-22"),
```

```
  timestamp:new Date("2019-04-22"),
  expenses:7000
  },

  {
  animal_name:"Rabbit",
  gender:"female",
  favorite_foods:["carrot","grass"],
  animal_petname:"Bunny",
  life_span:8,
  timestamp:new Date("2023-03-15"),
  expenses:5000
  }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b151507d0fd223d0e2dcba'),
      '1': ObjectId('69b151507d0fd223d0e2dcbb'),
      '2': ObjectId('69b151507d0fd223d0e2dcbc'),
      '3': ObjectId('69b151507d0fd223d0e2dcbd'),
      '4': ObjectId('69b151507d0fd223d0e2dcbe')
    }
  }
```

6. Write a MongoDB query to display all documents available in wild_animals and domastic_animals.

```
>_MONGOSH
> db.wild_animals.find()
< {
    _id: ObjectId('69b151487d0fd223d0e2dcb5'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [
      'meat',
      'deer'
    ],
    care_taker_name: 'Ramesh',
    life_span: 15,
    timestamp: 2020-05-10T00:00:00.000Z,
    expenses: 50000
  }
  {
    _id: ObjectId('69b151487d0fd223d0e2dcb6'),
    animal_name: 'Tiger',
    nature: 'harm',
    favorite_foods: [
      'meat',
      'rabbits'
    ],
    care_taker_name: 'Suresh',
    life_span: 16,
    timestamp: 2019-03-12T00:00:00.000Z,
    expenses: 55000
  }
  {
    _id: ObjectId('69b151487d0fd223d0e2dcb7'),
    animal_name: 'Elephant',
    nature: 'harmless',
    favorite_foods: [
      'grass',
      'fruits'
    ],
    care_taker_name: 'Ramesh',
    life_span: 60,
    timestamp: 2018-07-20T00:00:00.000Z,
```

```
>_MONGOSH
    expenses: 70000
  }
  {
    _id: ObjectId('69b151487d0fd223d0e2dcb8'),
    animal_name: 'Wolf',
    nature: 'harm',
    favorite_foods: [
      'meat',
      'rabbits'
    ],
    care_taker_name: 'Mahesh',
    life_span: 14,
    timestamp: 2021-02-18T00:00:00.000Z,
    expenses: 40000
  }
  {
    _id: ObjectId('69b151487d0fd223d0e2dcb9'),
    animal_name: 'Bear',
    nature: 'harm',
    favorite_foods: [
      'fish',
      'honey'
    ],
    care_taker_name: 'Suresh',
    life_span: 25,
    timestamp: 2017-11-25T00:00:00.000Z,
    expenses: 45000
  }
```

```
>_MONGOSH
> db.domestic_animals.find()
< {
    _id: ObjectId('69b151507d0fd223d0e2dcba'),
    animal_name: 'Dog',
    gender: 'male',
    favorite_foods: [
      'meat',
      'bones'
    ],
    animal_petname: 'Tommy',
    life_span: 12,
    timestamp: 2022-01-10T00:00:00.000Z,
    expenses: 10000
  }
  {
    _id: ObjectId('69b151507d0fd223d0e2dcbb'),
    animal_name: 'Cat',
    gender: 'female',
    favorite_foods: [
      'fish',
      'milk'
    ],
    animal_petname: 'Kitty',
    life_span: 15,
    timestamp: 2021-06-12T00:00:00.000Z,
    expenses: 8000
  }
  {
    _id: ObjectId('69b151507d0fd223d0e2dcbc'),
    animal_name: 'Cow',
    gender: 'female',
    favorite_foods: [
      'grass',
      'fodder'
    ],
    animal_petname: 'Lakshmi',
    life_span: 20,
    timestamp: 2020-09-05T00:00:00.000Z,
```

```
    expenses: 15000
  }
  {
    _id: ObjectId('69b151507d0fd223d0e2dcbd'),
    animal_name: 'Goat',
    gender: 'male',
    favorite_foods: [
      'grass',
      'leaves'
    ],
    animal_petname: 'Ramu',
    life_span: 10,
    timestamp: 2019-04-22T00:00:00.000Z,
    expenses: 7000
  }
  {
    _id: ObjectId('69b151507d0fd223d0e2dcbe'),
    animal_name: 'Rabbit',
    gender: 'female',
    favorite_foods: [
      'carrot',
      'grass'
    ],
    animal_petname: 'Bunny',
    life_span: 8,
    timestamp: 2023-03-15T00:00:00.000Z,
    expenses: 5000
  }
```

7. Write a MongoDB query to display only animal name and expenses in all the collection of the database

```
> db.wild_animals.find({}, {animal_name:1, expenses:1, _id:0})
< {
    animal_name: 'Lion',
    expenses: 50000
  }
  {
    animal_name: 'Tiger',
    expenses: 55000
  }
  {
    animal_name: 'Elephant',
    expenses: 70000
  }
  {
    animal_name: 'Wolf',
    expenses: 40000
  }
  {
    animal_name: 'Bear',
    expenses: 45000
  }
```

```
> db.domestic_animals.find({}, {animal_name:1, expenses:1, _id:0})
< {
    animal_name: 'Dog',
    expenses: 10000
  }
  {
    animal_name: 'Cat',
    expenses: 8000
  }
  {
    animal_name: 'Cow',
    expenses: 15000
  }
  {
    animal_name: 'Goat',
    expenses: 7000
  }
  {
    animal_name: 'Rabbit',
    expenses: 5000
  }
```

8. Write a MongoDB query to display domestic_animals whose life is a particular year

```
> db.domestic_animals.find({life_span:10})
< {
    _id: ObjectId('69b151507d0fd223d0e2dcbd'),
    animal_name: 'Goat',
    gender: 'male',
    favorite_foods: [
      'grass',
      'leaves'
    ],
    animal_petname: 'Ramu',
    life_span: 10,
    timestamp: 2019-04-22T00:00:00.000Z,
    expenses: 7000
  }
```

9. Write a MongoDB query to display wild_animals available under a particular care_taker

```
> db.wild_animals.find({care_taker_name:"Ramesh"})
< {
    _id: ObjectId('69b151487d0fd223d0e2dcb5'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [
      'meat',
      'deer'
    ],
    care_taker_name: 'Ramesh',
    life_span: 15,
    timestamp: 2020-05-10T00:00:00.000Z,
    expenses: 50000
  }
  {
    _id: ObjectId('69b151487d0fd223d0e2dcb7'),
    animal_name: 'Elephant',
    nature: 'harmless',
    favorite_foods: [
      'grass',
      'fruits'
    ],
    care_taker_name: 'Ramesh',
    life_span: 60,
    timestamp: 2018-07-20T00:00:00.000Z,
    expenses: 70000
  }
```

10. Write a MongoDB query to display animal name, favorite_foods and expenses details whose lifespan is more than 5 years.

```
> db.wild_animals.find(
  {life_span:{$gt:5}},
  {animal_name:1,favorite_foods:1,expenses:1,_id:0}
  )
< {
    animal_name: 'Lion',
    favorite_foods: [
      'meat',
      'deer'
    ],
    expenses: 50000
  }
  {
    animal_name: 'Tiger',
    favorite_foods: [
      'meat',
      'rabbits'
    ],
    expenses: 55000
  }
  {
    animal_name: 'Elephant',
    favorite_foods: [
      'grass',
      'fruits'
    ],
    expenses: 70000
  }
  {
    animal_name: 'Wolf',
    favorite_foods: [
      'meat',
      'rabbits'
    ],
    expenses: 40000
  }
  {
    animal_name: 'Bear',
    favorite_foods: [
      'fish',
      'honey'
    ],
    expenses: 45000
  }
```

```
> db.domestic_animals.find(
  {life_span:{$gt:5}},
  {animal_name:1,favorite_foods:1,expenses:1,_id:0}
  )
< {
    animal_name: 'Dog',
    favorite_foods: [
      'meat',
      'bones'
    ],
    expenses: 10000
  }
  {
    animal_name: 'Cat',
    favorite_foods: [
      'fish',
      'milk'
    ],
    expenses: 8000
  }
  {
    animal_name: 'Cow',
    favorite_foods: [
      'grass',
      'fodder'
    ],
    expenses: 15000
  }
  {
    animal_name: 'Goat',
    favorite_foods: [
      'grass',
      'leaves'
    ],
    expenses: 7000
  }
  {
    animal_name: 'Rabbit',
    favorite_foods: [
      'carrot',
      'grass'
    ],
    expenses: 5000
  }
animal>
```