	Logo
2281240	STUDENT REPORT  TABLE  Name 2812 12812 2812 2812 2812 2812 2812 28
	ETAILS ASADIT 2812ADSADIT REPORT 22812ADSADIT 22812ADSADI
DI	TAILS SADI 27 1812 ADSADI 27 12812 ADSADI 21 20 20 20 20 20 20 20 20 20 20 20 20 20
10	
	Roll Number 12 15th 12th 15th 12th 15th 12th 15th 15th 15th 15th 15th 15th 15th 15
281214	S SABA ANJUM  Roll Number  22BI24DS402-T
E)	RERIMENT SHOT THE RESIDENCE TO THE SHOT THE PROPERTY OF THE PR
Tit	
,	ANT ON RAIL TO THE TOTAL STATE OF THE STATE
228124	Description 12 State Sta
	gets exhausted. Given an integer array A of size N which consists of integer 1 and -1 only representing ant's moves.
,05A02	Where 1 means ant moved unit distance towards the right side and -1 means it moved unit distance towards the left . Your task is to find and return the integer value representing how many times the ant reaches back to original starting position.
	Note:
228121	Assume 1-based indexing
	<ul> <li>Assume 1-based indexing</li> <li>Assume that the railing extends infinitely on the either sides</li> </ul>
٠ ٥.	Input Format:
AD5A02	input1 : An integer value N representing the number of moves made by the ant. input2 : An integer array A consisting of the ant's moves towards either side
,  X	input2 : An integer array A consisting of the ant's moves towards either side
22	Overalla Long I
1228121	5
	1-11-11
102	Sample Output
ADSA02	
22	Source Code:  1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.
	2281 22812405402 (228)2402 (228)2402 (2
	22 Bill O 2 BILL SAO? SAO? 2 BILL SAO? ARREST REPORT OF THE SAO? WEST SAFER THE SAFER TO SAFER THE SAFER T

```
def count_returns_to_start(N, A):
    current_position = 0
    return_count = 0

for move in A:
    current_position += move
    if current_position == 0:
        return_count += 1

    return return_count

# Example usage:
N = int(input())
A = list(map(int,input().split())) # Example moves
    result = count_returns_to_start(N, A)
    print(result) # Output: 3

RESULT

5/5 Test Cases Passed | 100 %
```