

Flood Detection System

Prince Ibne Abir (011201061)

Saba Islam Jasi (011221005)

Sourav Karmakar (011221387)

Anantha Debnath (011221534)

Mst. Rifat Ara Rimi (011221549)

Abstract—Floods pose a significant threat to both human settlements and livestock, causing loss of life and property damage.

To address this issue, we have developed an autonomous flood detection system incorporating sensors, communication modules, and an alert mechanism. The system features real-time water level monitoring using ultrasonic sensors, automated sluice gate control, an uplifted bridge and shelter for animals, and remote alerts via Bluetooth and email notifications.

The implemented system demonstrates reliable performance with accurate water level detection, timely alerts, and effective flood prevention mechanisms, ensuring enhanced safety and preparedness.

I. INTRODUCTION

Flooding is a major natural disaster that causes loss of life, property damage, and environmental disruption. The increasing frequency of floods due to climate change has necessitated the development of efficient flood detection and prevention systems. Our project, a *Flood Detection System*, is designed to monitor rising water levels and take preventive actions to minimize damage. The system integrates sensors, actuators, and communication modules to provide real-time monitoring and alerts.

Several studies have been conducted on flood detection and mitigation using sensor-based systems. Existing flood detection systems primarily rely on ultrasonic or float sensors to detect water levels and send warnings. Some systems also integrate GSM or IoT-based alert mechanisms. However, many of these implementations lack additional safety measures such as automatic sluice gate control, shelter for animals, or solar-powered operation. Our project improves upon these limitations by incorporating autonomous bridges, elevated shelters, real-time monitoring via Bluetooth, and ESP32-based alert emails.

Unlike traditional flood detection systems, our project includes multiple innovative features:

- Autonomous uplifted bridge for smooth water passage when water levels rise.
- Elevated shelter for animals to protect livestock during floods.
- Real-time water level monitoring using an HC-05 Bluetooth module.
- Buzzer alarm system for immediate local alerts.
- Automated sluice gate to prevent flooding in villages.
- Email alerts through ESP32 for remote notifications.

Identify applicable funding agency here. If none, delete this.




Fig. 1. Circuit Diagram




Fig. 2. Block Diagram

- Solar-powered system for sustainable operation.
- Real-time display of water levels for easy monitoring.

II. PROPOSED METHOD

A. Circuit diagram

fig 1

B. Block diagram

fig 2

C. System Explanation

1. Ultrasonic Sensor: Measures water level and sends data to the microcontroller.
2. Microcontroller (Arduino/ESP32): Processes sensor data and takes necessary actions.
3. HC-05 Bluetooth Module: Transmits real-time water level data.
4. Buzzer Alarm: Activates when water levels exceed a critical threshold.
5. Sluice Gate Mechanism: Automatically closes when flooding conditions are detected.
6. Elevated Shelter Autonomous Bridge: Provides safety measures for animals and allows smooth water flow.
7. ESP32 for Email Alerts: Sends email notifications when flood levels rise.
8. Solar Panel System: Powers the entire system for continuous operation.



Fig. 3. ESP-32



Fig. 5. ultrasonic Sensor



Fig. 4. Servo Motor




Fig. 6. Hc05 Bluetooth module

III. IMPLEMENTED HARDWARE SYSTEM

A. List of the hardwares and software Components

Hardware Components:

- Arduino Uno/ESP32 (Microcontroller)
- HC-SR04 Ultrasonic Sensor (Water level measurement)
- HC-05 Bluetooth Module (Data transmission)
- Servo Motors (Gate control and bridge lifting)
- Buzzer (Siren for alert)
- OLED Display (Real-time data visualization)
- Solar Panel (Autonomous power supply)
- Battery Module (Energy storage)

Software Environment:

- Arduino IDE (Programming and uploading code)
- MIT App Inventor (Mobile app for Bluetooth monitoring)
- ESP32 Email Notification Library (For sending alerts)

IV. RESULTS

System Output

1. Water Level Detection: The ultrasonic sensor accurately measures the water level and transmits data.
2. Real-time Bluetooth Data Display: HC-05 module successfully sends data to the mobile app.
3. Automatic Sluice Gate Operation: The gate closes when water level crosses a threshold.
4. Buzzer Activation: The siren sounds when a flood is detected.
5. Email Alerts: ESP32 successfully sends email notifications.



Fig. 7. Buzzer




Fig. 8. Ardduino Uno




Fig. 9. Display



Fig. 10. Our project: Flood Detection System

6. Solar Power Functionality: The system runs autonomously using solar energy.

V. DISCUSSION

Limitations:

- Sensor Accuracy: Ultrasonic sensors may be affected by environmental conditions.
- Internet Dependency: ESP32 email alerts require a stable internet connection.
- Power Storage: Battery efficiency depends on sunlight availability.

Alternative Designs:

1. Using IoT Cloud Services: Instead of Bluetooth, data can be uploaded to a cloud platform for remote monitoring.
2. GSM-Based Alert System: SMS-based notifications can be integrated for areas with poor internet connectivity.

Impact and Ethical Considerations:

- The project contributes to disaster management and environmental safety.
- Ethical Compliance: Ensuring proper data privacy and security in communication protocols.
- Stakeholder Involvement: Discussed with local authorities to assess implementation feasibility.

VI. CONCLUSION

The Flood Detection System is a cost-effective and sustainable solution to mitigate flood risks. It efficiently monitors water levels, sends alerts, and takes preventive measures such as gate closure and shelter elevation. Future improvements can include AI-based flood prediction and expanded IoT connectivity for global monitoring.

ACKNOWLEDGMENT

We express our gratitude to Md. Shafqat Talukder Rakin sir, United International University, and everyone who supported us throughout this project. Special thanks to team mates for technical guidance and suggestions.

REFERENCES

- https://youtu.be/c-Zxa_dV7nk?si=9MhtOpzKOqBhh8T =
- <https://youtu.be/PNr8bkHz1VY?si=C9GXsIadxrwpdVB>
- <https://youtu.be/OgmWD7I5Uac?si=G88GiKzGdOWZ39fP>