| | |
|---|---|
| **Status** | Finished |
| **Started** | Sunday, 18 October 2026, 12:20 PM |
| **Completed** | Sunday, 18 October 2026, 12:24 PM |
| **Duration** | 3 mins 27 secs |
| **Grade** | **14.00** out of 15.00 (**93.33**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

a. The name of the file
b. The current position of the file cursor
c. The access mode in which the file was opened ✓
d. The size of the file

The correct answer is: The access mode in which the file was opened

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readline(size)
b. readlines()
c. readline() ✓
d. read()

The correct answer is: readline()

Question **3**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. None
b. EOFError
c. 0
d. An empty string ✓

The correct answer is: An empty string

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. Text file
b. Binary file
c. none of the given choices
d. Both text and binary file ✓

The correct answer is: Both text and binary file

Question **5**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. read()
b. readline()
c. readlist()
d. readlines() ✓

The correct answer is: readlines()

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. writelines() ✓
b. write_all()
c. write()
d. write_list()

The correct answer is: writelines()

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. readline() ✓
- b. line()
- c. readlines(1)
- d. read(1)

The correct answer is: readline()

Question **8**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

- a. The buffer size for the file operations ✓
- b. The file's read/write position
- c. The encoding of the file
- d. The access mode of the file

The correct answer is: The buffer size for the file operations

Question **9**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

- a. An empty file object is returned
- b. The operation is ignored
- c. A new file is created
- d. An error is raised ✓

The correct answer is: An error is raised

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. r
b. r+ ✓
c. a
d. w

The correct answer is: r+

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. insert()
b. append()
c. write() ✓
d. read()

The correct answer is: write()

Question **12**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints each line of the file
b. Prints the entire content of the file ✓
c. Prints an error message
d. Prints the first 10 characters of the file

The correct answer is: Prints the entire content of the file

Question **13**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The buffer size
b. The mode of the file
c. The size of the file
d. The encoding format of the file ✓

The correct answer is: The encoding format of the file

Question **14**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. moves the file pointer to the end of a file

b. move the file pointer five characters ahead from the current position ✓
c. move the file pointer to beginning of the file
d. move the file pointer five characters behind from the current position

The correct answer is:
move the file pointer five characters ahead from the current position

Question **15**

Incorrect

Mark 0.00 out of 1.00

What is the use of seek() method in files?

a. sets the file's current position within the file ✗
b. sets the file's previous position at the offset
c. sets the file's current position at the offset
d. none of the mentioned

The correct answer is:
sets the file's current position at the offset