Environment Variables Configuration

This document contains the configuration template and environment variables used for the application setup, including authentication, email services, database connections, and AI integrations (referencing src/lib/auth.js).

Overview & Security Note

- **Confidentiality:** This file contains sensitive credentials and session secrets. It is git-ignored (.env* in .gitignore) and should never be committed to version control.
- **Setup Instructions:** Change these values as needed for your environment, then restart the development server to apply changes.

Configuration Variables Reference (Project 1 → Allied One)

Variable Name	Description / Purpose	Example / Value Note
`AUTH_SECRET`	Random secret used to sign the admin session cookie. Regenerating it logs every admin out.	`fb031000c13e47947ae7cad9ddf69f9be4f7a586fb97689f0da823d8fe28575`
`ADMIN_EMAIL`	Administrator login email used for the `/admin` panel access.	`admin@alliedone.com`
`CONTACT_TO_EMAIL`	Recipient email address for contact form submissions.	`info@alliedoneltd.com`
`RESEND_API_KEY`	API key utilized for sending emails via Resend.	`re_VzZ8X1rd_Hb3xjwJCFQKnQYnj43orshau`
`CONTACT_FROM_EMAIL`	Sender identity address. Must be on a domain verified at Resend (`alliedoneltd.com` added on 2026-10-03; requires 4 DNS records configured).	`"AlliedOne Website <no-reply@alliedoneltd.com>"`
`ADMIN_PASSWORD`	Secure password assigned for administrator authentication.	`AlliedOne@2026`

Variable Name	Description / Purpose	Example / Value Note
GEMINI_API_KEY	API key for Gemini model integrations.	AQ.Ab8RN6KxbNxmjg92biBFu2x23n2nYy-35VFYtzZOlclR6X19gg
MONGODB_URI	Connection string URI for MongoDB cluster access.	mongodb+srv://Allied_one:k1UHcjPJUDejuQq3@cluster0.pf04c6g.mongodb.net/?appName=Cluster0
MONGODB_DB	Target database name within the MongoDB cluster.	alliedone

Configuration Variables Reference (Project 2 - B2B Trade & Auth)

Variable Name	Description / Purpose	Example / Value Note
BETTER_AUTH_SECRET	Secret used to sign Better Auth sessions.	J4vS7TRjMldk4yKZIcsg61ocWbWTo81P
BETTER_AUTH_URL	Base URL for Better Auth.	http://localhost:3000
MONGODB_URI	Connection string URI for MongoDB cluster access (b2b_trade).	mongodb+srv://B2B:WnDdha2SBcoGoQwA@cluster0.pf04c6g.mongodb.net/b2b_trade?appName=Cluster0
OTP_TTL_MINUTES	Time-to-live expiration minutes for OTP codes.	10
OTP_RESEND_SECONDS	Cooldown period in seconds before resending OTP.	60
OTP_MAX_ATTEMPTS	Maximum allowed OTP verification attempts before lockout.	5
SMTP_HOST	Gmail SMTP host server address.	smtp.gmail.com
SMTP_PORT	Gmail SMTP port number.	465

Variable Name	Description / Purpose	Example / Value Note
`SMTP_USER`	Authenticated Gmail account username/email.	`mdsabbirahmad943@gmail.com`
`SMTP_PASS`	Gmail App Password (spaces removed).	`attfojzgjgzusnvd`
`SMTP_FROM`	Sender identity header for outgoing emails via SMTP.	`"AlliedOne <mdsabbirahmad943@gmail.com>"`