

Project 2: Multithread LCS Milestone 1 Report

November 25, 2017

Sabbir Ahmed & Zafar Mamarakhimov

1 Description

The longest common subsequence (LCS) problem is to be implemented for the assignment. The objective of this project is to design, analyze, and implement a multi-threaded version of the LCS length algorithm. A memoized or bottom-up approach. In either case, the goal is to design an algorithm that makes efficient use of multiple processors.

Analysis is required once the LCS length algorithm is designed. The work $T_1(m, n)$ and the span $T_\infty(m, n)$ are to be computed, where m and n are the lengths of the input sequences X and Y , respectively. Finally, the parallelism is to be computed along with an estimate of a range of parameters (m , n , and P) for which linear or near-linear speed-up may be expected.

The last part of the project is to implement the LCS length algorithm in C or C++ using OpenMP on UMBC's maya cluster and measure its performance empirically using 1, 2, 4, and 8 processors (optionally, it may be tested on 16 processors; most maya nodes have eight cores, but some have 16). Test data and LCS lengths of various sizes are to be generated to demonstrate the performance characteristics of the algorithm. The algorithm to recover the LCS must also be implemented, but this need not be multithreaded.

2 Serial Algorithm

Milestone 1 required implementation of the serial LCS algorithm and its analysis. Algorithm 2.1 provides the pseudocode for computing the length of the LCS. The serial algorithm utilizes the memoization method to compute the LCS.

Algorithm 2.1: Serial Longest Common Subsequence Length

```
1  function serial_lcs(X, Y, m, n)
2      // allocate (m + 1) * (n + 1) LCS matrix
3      lcs = new matrix[1, 2, ..., m + 1][1, 2, ..., n + 1]
4      for i = 0 to m
5          for j = 0 to n
6              if (i == 0 or j == 0) // upper-leftmost cell
7                  lcsi,j = 0
8              else if (Xi-1 == Yj-1)
9                  // incremented left diagonal cell value
10                 lcsi,j = lcsi-1,j-1 + 1
11             else
12                 // maximum between previous row and previous column
13                 lcsi,j = max(lcsi-1,j , lcsi,j-1)
14     return lcsm,n // the last value of the table is the length
```

2.1 Time Complexity

The running time of the serial algorithm provides the work, T_1 , of the algorithm. Simple analysis of the algorithm provided in the snippet Algorithm 2.1 suggests a non-linear running time from the nested loop. The inner loop (line 5) iterates n times with several constant conditional checks, while the outer loop (line 4) iterates m times. The runtime is therefore:

$$T_1(m, n) = O(m \times n)$$

The work for the algorithm, $O(m \times n)$, is quadratic if $m = n$.

Algorithm 2.2: Serial Longest Common Subsequence Printing

```
1  function serial_lcs_print(X, Y, m, n, lcs, lcslen)
2      lcsstr = new string
3      cursor = lcslen  // cursor of the table
4      i = m, j = n  // init from the bottom-rightmost cell
5      while (i > 0 and j > 0)
6          // if current character in X[] and Y[] are same
7          if ( $X_{i-1} == Y_{j-1}$ )
8              lcsstrcursor-1 =  $X_{i-1}$  // result gets current character
9              i--, j--, cursor-- // decrement i, j and cursor
10
11         // find the larger of two and go to that direction
12         else if ( $lcs_{i-1,j} > lcs_{i,j-1}$ )
13             i--
14         else
15             j--
16     print lcsstr
```