CMPE 310
Systems Design and Programming

L3: Chapter 1 – *Introduction to the Microprocessor and Computer*

UMBC
AN HONORS UNIVERSITY IN MARYLAND

L3 Objectives

* Describe the memory address space
* Describe the IO space
* Describe how data is organized in the memory/ IO space
* Discuss the importance of data alignment
* Describe the data types

Memory and Input/Output

- Architecture implements independent memory and input/output address spaces
  - Why?
- Memory address space- 1,048,576 bytes long (1MB)
- Input/output address space- 65,536 bytes long (64KB)



I/O Address Space



- I/O addresses are NOT memory-mapped addresses on the x86
- Input/output address space
  - Place where I/O devices are normally implemented
  - I/O addresses are only 16-bits in length
  - Independent 64K-byte address space
  - Address range 0000H through FFFFH
- Page 0
  - First 256 byte addresses → 0000H - 00FFH
  - Can be accessed with direct or variable I/O instructions
  - Ports F8H through FF reserved

Organization of the I/O Data



- Input/output data organization
  - Supports byte, word, and double-word I/O ports
    - 64K independent byte-wide I/O ports
    - 32K independent word-wide I/O ports
    - 16K independent double-word-wide I/O ports
  - **What determines the size use for a given port?**
- Examples (aligned I/O ports):
  - Byte ports 0,1,2 →addresses 0000H, 0001H, and 0002H
  - Word ports 0,1,2 → addresses 0000H, 0002H, 0004H
  - Double-word ports 0,1,2 → addresses 0000H, 0004H, 0008H
- Advantages of Isolated I/O
  - Complete memory address space available for use by memory
  - I/O instructions tailored to maximize performance
- Disadvantage of Isolated I/O
  - All inputs/outputs must take place between I/O port and accumulator register

Address Space



- Memory organized as individual bytes
- Memory address space corresponds to the 1M addresses in the range 00000H to FFFFFH
- 00000H= 00000000000000000000_2
- FFFFFH= 11111111111111111111_2
- 2^{20}= 1,048,576 = 1M unique addresses
- Data organization:
  - Byte: content of any individual byte address
  - Word: contents of two contiguous byte addresses
  - Double-word: contents of 4 contiguous byte addresses

Dedicated and General Use of Memory



- Memory address space is partitioned into general use and dedicated use areas
- Dedicated (0H – 3FFH):
  - Interrupt vector table
  - 1st 1024 bytes
    - Addresses 0H → 3FFH
  - 256 4-byte pointers
    - 16-bit segment base address
    - 16-bit offset
- General use:
  - 400H → FFFFFH
  - Used for stack, code, and data

Aligned Words, Double words



- Words and double words of data can be stored in memory at an even or odd address boundary
  - Examples of even address boundaries:

    00000_{16}, 00002_{16}, 00004_{16}
  - Examples of odd address boundaries:

    00001_{16}, 00003_{16}, 00005_{16}
- Aligned double-words are stored at **even addresses** that are a multiple of 4
  - Examples: double words 0 and 4

Misaligned Words



- 80x86 architecture supports access of aligned or misaligned data
- Words stored across a double-word boundary are said to be "misaligned or unaligned words"
  - Examples: words 3 and 7
- Misaligned double-words are stored at addresses that are not a multiple of 4
  - Examples: double words 1, 2, 3 and 5
- There is a performance impact for accessing unaligned data in memory (16-bit data bus)
  - Why?

Examples of Words of Data



- "Little endian" organization
- Most significant byte at high address
- Least significant byte at low address

Unsigned Integers



All numbers are binary in memory
All bits represent data
Types:

Sizes	Range
8-bit	$0 \rightarrow 255_{10}$
16-bit	$0 \rightarrow 65{,}535_{10}$
32-bit	$0 \rightarrow 4{,}294{,}967{,}295_{10}$

Signed Integers



MSB is sign bit (0/1 → +/-)
Remaining bits represent value
Negative numbers expressed in 2's complement notation
Types:

Sizes	Range
8-bit	-128 → +127
16-bit	-32,768 → +32,767
32-bit	-2,147,483,648 → +2,147,483,647

BCD Numbers



- Direct coding of numbers as binary coded decimal (BCD) numbers supported
- Unpacked BCD [Fig (b)]
  - Lower four bits contain a digit of a BCD number
  - Upper four bits filled with zeros (zero filled)
- Packed BCD [Fig (c)]
  - Lower significant BCD digit held in lower 4 bits of byte
  - More significant BCD digit held in upper 4 bits of byte
  - Example: At memory address 01000H is 10010001
    - **What number does that represent in BCD?**

Character Code

- ***ASCII***: American Standard Code for Information Interchange
  - Represent each character with a **7-bit string**
  - 128 different characters (see ASCII table)
  - Uppercase & lowercase alphabet, numerals, punctuation, nonprinting control characters
- Eighth bit may be used for parity (forcing number of 1s to be even or odd)
- Check out www.asciitable.com
- ASCII is somewhat eclipsed now by Unicode

Standard ASCII

ASCII	MSBs - $b_6b_5b_4$							
$b_3b_2b_1b_0$	000 - 0	001 - 1	010 - 2	011 - 3	100 - 4	101 – 5	110 - 6	111 - 7
0000 – 0	NUL	DLE	SP	0	@	P	`	p
0001 – 1	SOH	DC1	!	1	A	Q	a	q
0010 – 2	STX	DC2	"	2	B	R	b	r
0011 – 3	ETX	DC3	#	3	C	S	c	s
0100 – 4	EOT	DC4	$	4	D	T	d	t
0101 – 5	ENQ	NAK	%	5	E	U	e	u
0110 – 6	ACK	SYN	&	6	F	V	f	v
0111 – 7	BEL	ETB	'	7	G	W	g	w
1000 – 8	BS	CAN	(	8	H	X	h	x
1001 – 9	HT	EM	)	9	I	Y	i	y
1010 – A	LF	SUB	*	:	J	Z	j	z
1011 – B	VT	ESC	+	;	K	[	k	{
1100 – C	FF	FS	,	<	L	\	l	|
1101 – D	CR	GS	-	=	M	]	m	}
1110 – E	SO	RS	.	>	N	^	n	~
1111 - F	SI	US	/	?	O	_	o	DEL

* "Yeccch!"
* 1011001 1100101 1100011 1100011 1100011 1101000 01000001

ASCII Data

b_4 b_3 b_2 b_1	b_7 b_6 b_5 / H_1 H_0	0 0 0	0 0 1	0 1 0	0 1 1	1 0 0	1 0 1	1 1 0	1 1 1
		0	1	2	3	4	5	6	7
0 0 0 0	0	NUL	DLE	SP	0	@	P	`	p
0 0 0 1	1	SOH	DC1	!	1	A	Q	a	q
0 0 1 0	2	STX	DC2	"	2	B	R	b	r
0 0 1 1	3	ETX	DC3	#	3	C	S	c	s
0 1 0 0	4	EOT	DC4	$	4	D	T	d	t
0 1 0 1	5	ENQ	NAK	%	5	E	U	e	u
0 1 1 0	6	ACK	SYN	&	6	F	V	f	v
0 1 1 1	7	BEL	ETB	'	7	G	W	g	w
1 0 0 0	8	BS	CAN	(	8	H	X	h	x
1 0 0 1	9	HT	EM	)	9	I	Y	i	y
1 0 1 0	A	LF	SUB	*	:	J	Z	j	z
1 0 1 1	B	V	ESC	+	;	K	[	k	{
1 1 0 0	C	FF	FS	,	<	L	\	l	|
1 1 0 1	D	CR	GS	-	=	M	]	m	}
1 1 1 0	E	SO	RS	.	>	N	^	n	~
1 1 1 1	F	SI	US	/	?	O	-	o	DEL

(a)

(b)

* American Code for Information Interchange (ASCII) code
* ASCII information storage in memory
  * Coded one character per byte
  * 7 LS-bits = $b_7b_6b_5b_4b_3b_2b_1$
  * MS-bit filled with 0
  * **How will we represent 'A' in ASCII?**

So we discussed…

* Describe the memory address space
* Describe the IO space
* Describe how data is organized in the address/ IO space
* Discuss the importance of data alignment
* Describe the data types

Next time

* 80x86 Hardware Specification