

Highlights

The Chess Algorithm: A Novel Metaheuristic Optimization Technique with Applications in Transportation Network Engineering

Seyedsaber Naserlavi, Seyedali Mirjalili

- Chess Algorithm: a metaheuristic with a ranked, role-differentiated population
- A state machine adapts tactics to divergence, initiative and local-search success
- Every mechanism is mapped to a known operator family and ablated in isolation
- Best mean Friedman rank among classical baselines on CEC-2017, CEC-2022, design
- Ablation shows en passant and the knight's fork carry most of the performance

The Chess Algorithm: A Novel Metaheuristic Optimization Technique with Applications in Transportation Network Engineering

Seyedsaber Naserlavi^{a,*}, Seyedali Mirjalili^b

^a*Department of Civil Engineering, Faculty of Engineering, Shahid Bahonar University of Kerman, Kerman, Iran*

^b*Centre for Artificial Intelligence Research and Optimization, Torrens University Australia, Brisbane, Australia*

Abstract

This paper proposes the Chess Algorithm (CA), a population-based metaheuristic that draws its search logic from the strategy of chess rather than from foraging or hunting behaviour in nature. The population is deliberately heterogeneous: at every iteration the agents are ranked and assigned the roles of King, Queen, Rook, Bishop, Knight and Pawn, and each role moves under an operator abstracted from the geometry of the corresponding piece. A lightweight state machine reads the divergence, initiative and local-search success of the population each iteration and selects which strategic mechanisms are active, among them development, sacrifice, pinning, castling, en passant, interference, the knight's fork and a blockade response. Every mechanism is mapped explicitly onto an established operator family, so that the metaphor describes the composition without standing in for its specification. CA is evaluated on six classical functions in 30 dimensions, on all 29 usable CEC-2017 functions, on CEC-2022 at both official dimensionalities, on seven constrained engineering design problems and on two transportation problems, against GA, PSO, SA, GWO, WOA and the competition-grade optimizers L-SHADE and CMA-ES. CA obtains the best mean Friedman rank among the classical and widely used baselines on all three standard suites, while L-SHADE and CMA-ES rank ahead of it throughout. A per-mechanism ablation shows that two operators, the en-passant local capture and the knight's fork, carry most of CA's performance, which accounts for both halves of that result.

Keywords: Metaheuristic optimization, Chess algorithm, Adaptive search control, CEC benchmark suites, Traffic signal timing, Berth allocation

1. Introduction

A large share of the decisions a transportation engineer has to make can be written, after enough simplification, as a global optimization problem:

$$\min_{\mathbf{x} \in \Omega} f(\mathbf{x}), \quad \Omega = \{\mathbf{x} \in \mathbb{R}^D : l_j \leq x_j \leq u_j, j = 1, \dots, D\}. \quad (1)$$

The trouble is what f looks like in practice. In signal timing, network design, transit scheduling and detector placement, the objective is non-convex, often non-differentiable, riddled with local optima, and sometimes expensive to evaluate [1, 2]. Exact methods rarely scale to instances of realistic size. That is why metaheuristics have kept their place in engineering practice for three decades: they trade the guarantee of optimality for robustness, generality and a computationally tractable budget. Figure 1 states the argument

*Corresponding author

Email address: `saber_naserlavi@uk.ac.ir` (Seyedsaber Naserlavi)

of this section in one picture, with the structural properties of these objectives on the left, the two features of a conventional homogeneous population that answer them only partially in the middle, and the two design decisions taken here on the right. The rest of the introduction develops each column in turn.




Figure 1: Motivation and conceptual architecture of the Chess Algorithm. The sketched landscape is analytic and carries no experimental data.

The field grew from two roots. Evolutionary computation gave us the Genetic Algorithm [3, 4] and Evolution Strategies [5]. Trajectory methods gave us Simulated Annealing [6], whose central idea, accepting a worse solution now and then so that a local minimum can be escaped, has proved one of the most durable in the field. Swarm intelligence arrived in the 1990s with Particle Swarm Optimization [7], Ant Colony Optimization [8], Differential Evolution [9], and later the Artificial Bee Colony [10]. More recently, Mirjalili and colleagues built a productive line of algorithms by abstracting the social and hunting behaviour of animals into compact operators: the Grey Wolf Optimizer [11], the Ant Lion Optimizer [12], the Dragonfly Algorithm [13], the Whale Optimization Algorithm [14], the Sine Cosine Algorithm [15], and the Salp Swarm Algorithm [16], among others.

Two patterns stand out in this literature. First, almost every swarm algorithm treats its agents identically: a single update equation is applied to all of them, and only position and fitness distinguish one agent from another. Division of labour among *unequal* agents, by contrast, is a well-established principle in biological systems and in human strategic behaviour alike. Second, the performance of a metaheuristic is largely determined by how it schedules the transition from exploration to exploitation [11], and mechanisms that adapt that transition to the observed search dynamics, rather than to elapsed time alone, remain uncommon.

The justification for proposing yet another metaheuristic should also be stated explicitly. The No-Free-Lunch theorem [17] rules out a universally dominant optimizer, so the aim of this work is not universal superiority but a substantively different inductive bias, together with an identification of the problem class for which that bias pays. A third consideration is critical rather than structural. The proliferation of metaphor-named algorithms has drawn severe and largely justified criticism [18], on the grounds that new vocabulary frequently repackages established operators without advancing the science. This paper accepts the substance of that criticism and builds the response into the study itself. Section 2.8 maps every mechanism of the proposed algorithm onto its established operator family with the corresponding citation, Section 7.1 measures each mechanism’s isolated contribution empirically, and the comparison roster includes two competition-grade optimizers, L-SHADE [19] and CMA-ES [20], so that the algorithm is assessed against the strongest representatives of the operator families it draws on rather than only against other metaphor-derived methods.

Chess offers precisely the two properties identified as absent above. Its pieces are radically unequal: the queen sweeps the whole board, rooks travel along files and ranks, bishops along diagonals, knights jump over anything in the way, and pawns crawl forward one square at a time while quietly defining the structure of the position. Mapped onto a search population, this suggests sub-groups performing qualitatively different moves around one common reference point, which in our setting is the best solution found so far and which we call the King.

The game also comes with a mature strategic vocabulary, refined over centuries of analysis. Development says: mobilize your forces early, consolidate later. A sacrifice gives up material now for a positional advantage later. Pinning immobilizes a piece against something more valuable behind it. Castling is a safeguarded structural rearrangement, en passant an opportunistic capture available only under narrow conditions, and the threefold-repetition rule declares a draw when the position keeps repeating. Each of these has a natural algorithmic reading: exploration schedules, acceptance of deteriorating moves, variable fixation, elite restructuring, adaptive local search, and diversity preservation, respectively.

The Chess Algorithm (CA) proposed here formalizes that mapping. Figure 2 states it precisely. Each piece becomes one movement geometry around the incumbent solution, and the figure names, for each, the search behaviour it produces and whether that behaviour serves exploration or exploitation. The right-hand column of the figure is deliberately not a claim of novelty, since Section 2.8 maps every one of these operators onto an established family with its canonical reference. One misunderstanding is worth preempting at once: CA does not play chess and does not search a game tree. It borrows the strategic grammar of the game and nothing else, and its per-iteration cost is comparable to that of GA or PSO.

Piece	Move geometry	Search behaviour around the incumbent	Primary contribution
King		incumbent best solution K , never lost	elitism
Queen		omnidirectional sweep at a radius tied to the current distance $ \mathbf{K} - \mathbf{X}_i $ (Eq. 5)	exploration
Rook		single-axis move: one coordinate of the incumbent is perturbed (Eq. 6)	axis-aligned search
Bishop		two-axis move of equal magnitude, the box-constrained analogue of a diagonal (Eq. 7)	axis-pair search
Knight		drift toward a better-ranked peer plus a 2:1 jump; occasionally a long-range leap (dashed) (Eq. 8)	exploration
Pawn		small advance toward the incumbent and toward a better-ranked peer (Eq. 10)	exploitation

Every role operator is an instance of the elite-guided stochastic-perturbation family; Table 4 gives the operator family and canonical reference of each mechanism. The metaphor names the composition, not any operator that the table cannot name.

Figure 2: The chess abstraction as a mapping onto search operators: one movement geometry per piece around the incumbent King.

The contributions of this paper are the following. We give a complete mathematical specification of CA, covering initialization, rank-based role assignment, movement operators, strategic mechanisms, and the adaptive control layer that governs when each of them applies, including several operators new to this paper: Novotny interference, the knight's fork, the royal council, a King's-march blockade response, and a Tal-style speculative-sacrifice reheat. Every mechanism is then mapped onto its established operator family. We evaluate CA on six standard test functions in 30 dimensions, on the full CEC-2017 suite, on CEC-2022 at both official dimensionalities, on seven classic constrained engineering design problems, and on two transportation problems, against a roster that includes the competition-grade baselines L-SHADE and CMA-ES alongside GA, PSO, SA, GWO and WOA. Along the way we report a two-library data-integrity

audit that identified six defective function implementations in a widely used third-party CEC-2017 port and restored all six from an independent implementation carrying the official reference data. We then take the algorithm apart, with a per-mechanism ablation, a one-at-a-time parameter sensitivity analysis, and a measured cost comparison with exact evaluation counts. Throughout, an ablation configuration with the adaptive layer disabled, CA-static, is carried alongside CA to isolate what that layer contributes, and the complete implementation is released open source.

It is worth stating the scope of our claims plainly. Against the classical and widely used metaheuristics in the roster, CA is consistently competitive and frequently significantly better, across synthetic suites, engineering design, and the transportation problems that motivated the work. Against the two competition-grade optimizers the ordering is reversed: L-SHADE and CMA-ES outperform CA on every problem class tested, and we report that wherever it occurs without qualification. The claim this paper defends is therefore narrower than a performance claim. CA is a transparent architecture whose every mechanism is specified mathematically, mapped to its operator family, and measured in isolation, and the ablation of Section 7 identifies precisely which of those mechanisms carry its performance, which in turn explains the standing of the specialized methods.

The remainder of the paper is organized as follows. Section 2 specifies the algorithm, its adaptive control layer, and its time and memory complexity. Section 3 reports the classical benchmark study, Section 4 and Section 5 the two CEC suites, and Section 6 the constrained engineering design problems. Section 7 takes CA apart through ablation, sensitivity and cost analysis. Section 8 and Section 9 present the transportation applications, and Section 10 concludes.

2. The Chess Algorithm

2.1. Conceptual mapping

CA maintains a population of N candidate solutions $\mathbf{X}_i \in \Omega \subset \mathbb{R}^D$, treated as pieces playing toward the global optimum. Table 1 summarizes how the vocabulary of the game maps onto algorithmic mechanisms.

Table 1: Mapping between chess concepts and CA mechanisms.

Chess concept	Algorithmic role
King	Incumbent best solution (never lost)
Queen, Rook, Bishop, Knight, Pawn	Heterogeneous movement operators
Development (opening principle)	Time-decaying step-scale $a(t)$
Sacrifice	Probabilistic acceptance of worse moves (minor pieces only)
Pinning	Progressive freezing of coordinates to the King’s values
Castling	Safeguarded coordinate-block exchange King $\leftrightarrow$ Rook
En passant	Opportunistic, self-adaptive local capture around the King
Pawn promotion	Rank-based role reassignment each iteration
Threefold repetition	Re-deployment of agents that collapse onto the King
Opening / middlegame / closed position / endgame	Position-dependent tactical phase, read each iteration (Section 2.6)
Nimzowitsch prophylaxis	Restrained, line-reopening response to premature convergence
Fork, interference, discovered attack, royal council	Additional movement and probe operators, active in specific phases
Windmill	Repeated extension of a successful King displacement (endgame)
Zugzwang / blockade	Stagnation-triggered waiting move, King’s march, and speculative sacrifice
Checkmate	Termination criterion

One point deserves emphasis. CA borrows the strategic grammar of chess as an inductive bias, not the game itself. An iteration costs $\mathcal{O}(ND + N \log N)$ arithmetic operations, that is the movement updates plus the sort that drives role assignment, and $N + 3$ function evaluations, that is N piece moves plus three en-passant probes, with one extra castling probe every c iterations. That is the same order as GA, PSO, or GWO. Section 2.9 gives the full time and memory accounting, and the exact evaluation counts measured in the experiments are in Section 7.3.

2.2. Architecture overview

Before the components are defined one by one, Figure 3 shows how they are assembled into a single iteration, in the conventional flowchart notation: an oval for start and stop, a parallelogram for input and output, a diamond for a decision, and a rectangle for a process step. Three strands run inside the loop. The population is ranked, moved by role-specific operators, evaluated and filtered by an acceptance rule; the King runs its own local search through en passant, castling and the tactical probes; and the adaptive controller of Section 2.6 reads four statistics of the population and conditions the rates at which the tactical operators fire. Each process box names the equation or table in which it is specified, so the figure doubles as a map of the rest of this section.

2.3. Initialization and role assignment

The board is set up by scattering the N pieces uniformly over the feasible box:

$$\mathbf{X}_i^{(0)} = \mathbf{l} + (\mathbf{u} - \mathbf{l}) \circ \mathbf{r}_i, \quad \mathbf{r}_i \sim \mathcal{U}(0, 1)^D, \quad i = 1, \dots, N, \quad (2)$$

where $\mathbf{l}$ and $\mathbf{u}$ are the bound vectors and $\circ$ is the elementwise (Hadamard) product. All positions are evaluated once and the population is sorted by fitness before the first move is played.

Let π be the permutation of $\{1, \dots, N\}$ that sorts the population,

$$f(\mathbf{X}_{\pi(1)}) \leq f(\mathbf{X}_{\pi(2)}) \leq \dots \leq f(\mathbf{X}_{\pi(N)}). \quad (3)$$

The best agent $\mathbf{K} = \mathbf{X}_{\pi(1)}$ is the King. The following ranks are partitioned, in order, into Queens $\mathcal{Q}$, Rooks $\mathcal{R}$, Bishops $\mathcal{B}$, and Knights $\mathcal{N}$, with

$$|\mathcal{Q}| = \max(1, \lfloor \rho_q N \rfloor), \quad |\mathcal{R}| = \max(1, \lfloor \rho_r N \rfloor), \quad |\mathcal{B}| = \max(1, \lfloor \rho_b N \rfloor), \quad |\mathcal{N}| = \max(1, \lfloor \rho_n N \rfloor),$$

where $\lfloor \cdot \rfloor$ denotes rounding and $(\rho_q, \rho_r, \rho_b, \rho_n) = (0.10, 0.15, 0.15, 0.20)$. Whatever remains becomes the Pawns $\mathcal{P}$. Because the assignment is redone after every iteration, a pawn that reaches a good region becomes a strong piece the next time roles are assigned. Promotion, in other words, falls out of re-ranking for free, and no extra machinery is needed for it.

Opening theory tells a player to develop pieces quickly, while endgames reward patience and precision. CA encodes this with a linearly decaying step-scale coefficient,

$$a(t) = 2 \left(1 - \frac{t}{T} \right), \quad (4)$$

with t the current iteration and T the total budget, following the convention popularized by Mirjalili et al. [11]. Every piece move scales with $a(t)$, so the swarm plays big developing moves early and fine manoeuvres late.

2.4. Piece movement operators

Write $\mathbf{L} = \mathbf{u} - \mathbf{l}$ for the box width and let $\mathbf{r}, \mathbf{r}' \sim \mathcal{U}(0, 1)^D$ be independent random vectors. The five mobile roles then move as follows. Figure 4 shows what each of the five equations below does geometrically, and makes the division of labour between them visible before the algebra is read: the Rook moves one coordinate and the Bishop two of equal magnitude, so both produce axis-structured candidates; the Queen sweeps in every direction at a radius tied to its distance from the King; the Knight combines a drift toward a better-ranked peer with an asymmetric jump; and the Pawn takes small steps toward both attractors, which is why its cloud is the tightest. The candidate clouds in the figure are not drawn by hand. They are 45 draws from the equation named in each panel, evaluated with a fixed seed.




Figure 3: Flowchart of the Chess Algorithm.

(a) rank-based role assignment (Table 3)




Figure 4: Geometry of the five role operators in a two-dimensional section, with the role proportions of Table 3 in panel (a).

Queen (omnidirectional sweep). The queen circles the King at a radius tied to her current distance from him:

$$\mathbf{X}'_i = \mathbf{K} + a(t) (2r - 1) \circ \max(|\mathbf{K} - \mathbf{X}_i|, \sigma), \quad (5)$$

where σ is the King's adaptive capture radius of Equation 12. The max keeps the sweep from collapsing entirely, so queens never stall.

Rook (single-axis move). One random axis j is chosen and only that coordinate moves:

$$X'_{i,j} = K_j + a(t) (2r - 1) \max(|K_j - X_{i,j}|, 0.01 L_j a(t)). \quad (6)$$

Bishop (diagonal move). Two distinct axes j and k receive steps of equal magnitude and random relative sign, which is as close to a diagonal as a box-constrained space allows:

$$\Delta = a(t) (2r - 1) \max\left(\frac{1}{2}(|K_j - X_{i,j}| + |K_k - X_{i,k}|), 0.01 L a(t)\right), \quad X'_{i,j} = K_j + \Delta, \quad X'_{i,k} = K_k \pm \Delta. \quad (7)$$

Knight (L-shaped jump). The knight is the one piece that jumps over whatever stands in its way. Relative to a randomly chosen better-ranked peer $\mathbf{P}$, it drifts toward the peer and then adds an asymmetric 2:1 jump on two random axes:

$$\mathbf{X}'_i = \mathbf{X}_i + \mathbf{r} \circ (\mathbf{P} - \mathbf{X}_i), \quad X'_{i,j} += 2 a(t) \beta (2r - 1), \quad X'_{i,k} += 1 a(t) \beta (2r' - 1), \quad (8)$$

with $\beta = \overline{|\mathbf{P} - \mathbf{X}_i|}$ the mean coordinate gap. With small probability $0.1 a(t)/2$ the knight abandons this move and leaps: two coordinates are resampled uniformly in Ω . This leap is the algorithm's main long-range restart device. The implementation also ships a heavy-tailed variant in which those two coordinates instead

receive a Lévy-flight step $0.05 L s$ generated by Mantegna’s algorithm [21], the mechanism that Cuckoo Search made popular [22]:

$$s = \frac{u}{|v|^{1/\beta_\ell}}, \quad u \sim \mathcal{N}(0, \sigma_u^2), \quad v \sim \mathcal{N}(0, 1), \quad \sigma_u = \left[\frac{\Gamma(1 + \beta_\ell) \sin(\pi\beta_\ell/2)}{\Gamma(\frac{1+\beta_\ell}{2}) \beta_\ell 2^{(\beta_\ell-1)/2}} \right]^{1/\beta_\ell}, \quad (9)$$

with tail index $\beta_\ell = 1.5$. Every result in this paper uses the plain uniform leap; the Lévy option is documented for future study rather than used here.

Pawn (steady advance). Pawns take small steps toward the King and toward a random better-ranked piece **B**:

$$\mathbf{X}'_i = \mathbf{X}_i + 0.3 \mathbf{r} \circ (\mathbf{K} - \mathbf{X}_i) + 0.3 \mathbf{r}' \circ (\mathbf{B} - \mathbf{X}_i). \quad (10)$$

2.5. Strategic mechanisms

Pinning. With probability $p_{\text{pin}}(t) = 0.5t/T$, a random subset of at most 30% of an agent’s coordinates is pinned to the King’s values and excluded from perturbation. Early on, pinning is rare and the pieces develop freely. Late in the run it concentrates the search on a shrinking set of free dimensions around the incumbent, which is the exploitation behaviour expected during an endgame.

Sacrifice. A worsening move $\Delta_i = f(\mathbf{X}'_i) - f(\mathbf{X}_i) > 0$ made by a minor piece, a Knight or a Pawn, is still accepted with probability

$$p_{\text{acc}} = \exp\left(-\frac{\Delta_i}{\theta(t)}\right), \quad \theta(t) = \theta_0(f_{\text{max}} - f_{\text{min}}) e^{-8t/T}, \quad (11)$$

with $\theta_0 = 0.1$. Readers will recognize the Metropolis rule of Simulated Annealing [6], but two chess-flavoured restrictions change its character. The temperature is scaled by the current fitness spread of the population, which makes the sacrifice budget self-calibrating across problems of wildly different magnitudes. And only minor pieces may be sacrificed, so that the King and the major pieces are never lost and the elite of the population cannot be eroded by the acceptance rule.

En passant (adaptive local capture). Once per iteration the King attempts an en-passant capture. Three trial points are drawn in a sparse Gaussian neighbourhood,

$$\mathbf{Y}_m = \mathbf{K} + \sigma \circ \mathbf{z}_m \circ \mathbf{m}_m, \quad \mathbf{z}_m \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \quad m = 1, 2, 3, \quad (12)$$

where the random binary mask $\mathbf{m}_m$ activates each coordinate with probability $\max(0.2, 2/D)$. Any improving trial replaces the King. The radius σ follows a success rule of the kind long used in Evolution Strategies [5]: multiply by 1.3 after a successful capture, by 0.92 after a failure, and after 50 consecutive failures reset to $\sigma = 0.05 \mathbf{L} \max(a(t), 0.05)$, which is a stalemate-avoidance restart. In our experience this mechanism is what keeps CA improving deep into the run, long after a fixed-radius local search would have gone quiet.

Castling. Every $c = 10$ iterations the King castles with the best Rook: a contiguous block of up to $D/4$ coordinates is copied from the Rook into a candidate King, and the exchange is kept only if it improves the King. It is a safeguarded structural jump, useful when good partial solutions have been discovered on different files of the board and need splicing together.

Threefold repetition. If an agent coincides with the King to numerical precision, something that pinning can eventually cause, it is re-deployed uniformly in Ω , much as the threefold-repetition rule stops a game from going in circles. We did not add this rule for elegance. Early prototypes taught us that it is essential:

without it, pinning breeds exact clones of the King, every gap-proportional step length collapses to zero, and the search dies quietly in place.

Checkmate. The algorithm stops after T iterations. A stagnation-based early stop would be easy to add, but we keep it disabled in all experiments so that every algorithm consumes the same core budget of $N \times T$ population evaluations.

Two design properties follow from these rules and are worth stating before the adaptive layer is introduced. The first is elitism: the King’s fitness never increases, because the King is replaced only by strictly better points, whether through the population update, en passant, or castling. Together with the uniform probability mass that the Knight’s exploratory leap and the threefold-repetition re-deployment place over Ω at every iteration, this puts CA in the class of elitist stochastic search methods for which convergence in probability to the global optimum as $T \rightarrow \infty$ is standard [23]. Such asymptotic statements say nothing about behaviour within a finite budget of 15,000 evaluations, which is an empirical question and is the subject of Section 3. The second is the exploration and exploitation balance. Exploration rests mainly on the Knights (Equation 8) and on the Queens early in the schedule (Equation 5); exploitation rests on the Pawns (Equation 10), on pinning, and on the en-passant success rule (Equation 12). The balance shifts smoothly through $a(t)$, $p_{\text{pin}}(t)$ and $\theta(t)$, and it adapts to the state of the search through the gap-proportional step lengths and the spread-scaled sacrifice budget of Equation 11.

2.6. Adaptive tactical control

The mechanisms above give CA its movement vocabulary. What remains is to say how CA decides, moment to moment, which of them to lean on. A grandmaster does not play the same combination of tactics in a wide-open middlegame as in a locked pawn structure or a simplified endgame, because the right tactic depends on the position and not on a move counter. CA answers this with a lightweight state machine that reads four cheap statistics of the population each iteration and switches the active tactical repertoire accordingly. Figure 5 summarizes the result.

For controlled comparison, every experiment in this paper is also run under **CA-static**, which is the identical operator set with this state machine disabled, so that role-appropriate tactics fire at fixed, non-adaptive rates instead. CA-static is not a separate algorithm. It is an ablation configuration, used throughout Section 4 and Section 6 to isolate exactly what the adaptive layer contributes.

Reading the position. Four exponentially smoothed statistics ($\lambda = 0.8$) are recomputed every iteration. The population’s normalized divergence from the King,


$$d(t) = \frac{1}{\text{Lspan}\sqrt{D}} \cdot \frac{1}{N-1} \sum_{i=2}^N \|\mathbf{X}_i^{(t)} - \mathbf{K}^{(t)}\|_2, \quad \tilde{d}(t) = 0.8\tilde{d}(t-1) + 0.2d(t), \quad (13)$$

answers the question “is the position open or closed?”, where $\text{Lspan} = \max_j(u_j - l_j)$. Two further exponential moving averages track the initiative,

$$\alpha(t) = 0.8\alpha(t-1) + 0.2 \cdot \frac{1}{N} \sum_{i=1}^N \mathbb{1}[\text{move}_i \text{ accepted}], \quad (14)$$

and the technical success rate of the King’s own local search,

$$\varepsilon(t) = \begin{cases} 0.8\varepsilon(t-1) + 0.2 & \text{en-passant capture succeeded at } t, \\ 0.8\varepsilon(t-1) & \text{otherwise.} \end{cases} \quad (15)$$



phase-conditioned operator rates (Table 2)

	p_{pin}	leap mult.	p_c	p_{DA}	p_{intr}	pawn gain
Opening	0	2.0	0	0	0.30	0.30
Middlegame	0.5ϕ	1.0	0.5	0	0.15	0.30
Closed	0	2.0	0.5	0.15	0.15	0.30
Endgame	$0.1+0.75\phi$	0.5	0.7	0.15	0	0.45

$\phi(t) = t/T$; Endgame pinning is capped at 0.5. Shading is proportional to the rate and carries no information beyond the printed value.

Figure 5: The adaptive tactical controller: four smoothed statistics select one of four phases, and each phase sets the operator rates of Table 2.

Finally, a stagnation counter borrows chess’s *fifty-move rule*. Rather than reset on any improvement whatsoever, it resets only on a materially significant one, exactly as fifty moves without a pawn push or a capture, not merely without a game-theoretically perfect move, are needed to claim a draw:

$$s(t) = \begin{cases} 0, & f(\mathbf{K}^{(t)}) < f_{\text{ref}} - \max(10^{-4}|f_{\text{ref}}|, 10^{-10}), \\ s(t-1) + 1, & \text{otherwise,} \end{cases} \quad (16)$$

with f_{ref} updated to $f(\mathbf{K}^{(t)})$ whenever $s(t) = 0$. Early prototypes used a naive counter that reset on any improvement at all. Because the en-passant rule of Equation 12 produces microscopic refinements routinely, that counter never accumulated enough to trigger the blockade response described below, even in runs that stayed visibly confined to a secondary basin for hundreds of iterations. Equation 16 fixes that.

Game phases. The smoothed divergence and the fraction of the budget elapsed, $\phi(t) = t/T$, jointly select one of four phases:

$$\text{phase}(t) = \begin{cases} \text{OPENING}, & \tilde{d}(t) > 0.22, \\ \text{MIDDLEGAME}, & 0.045 < \tilde{d}(t) \leq 0.22, \\ \text{CLOSED}, & \tilde{d}(t) \leq 0.045 \text{ and } \phi(t) \leq 0.5, \\ \text{ENDGAME}, & \tilde{d}(t) \leq 0.045 \text{ and } \phi(t) > 0.5. \end{cases} \quad (17)$$

The two thresholds were checked, though not exhaustively swept, against the combinations $\delta_{\text{open}} \in \{0.15, 0.22, 0.30\}$ and $\delta_{\text{end}} \in \{0.03, 0.045, 0.06, 0.09\}$ on two CEC-2017 functions, Rastrigin and Hybrid Function 4 at $D = 30$. The pair $\delta_{\text{open}} = 0.22$ and $\delta_{\text{end}} = 0.045$ was the best or near-best on both and is used throughout this paper. A full sensitivity study across the complete parameter space, noted as a limitation in Section 10, remains future work.

The Closed phase answers a failure mode found during tuning. A population can collapse to a small radius around the King *early* in the search, which is premature convergence rather than a genuine endgame, and treating every low-divergence state as an endgame made this worse, since endgame tactics such as heavy pinning and aggressive pawn advance accelerate the collapse instead of reversing it. Reading an early collapse as a **prematurely closed position** and answering with Nimzowitschian *prophylaxis*, that is restraint and the reopening of lines rather than immediate commitment, removes the pathology. Each phase activates a different parameter vector, summarized in Table 2.

Table 2: Phase-conditioned tactical schedule. Pinning probability p_{pin} , knight-leap probability multiplier, council probability p_{c} , discovered-attack probability p_{DA} , interference probability p_{intf} , and pawn step gain, by phase. *Endgame pinning is capped at 0.5.

Phase	p_{pin}	Leap mult.	p_{c}	p_{DA}	p_{intf}	Pawn gain
Opening	0	2.0	0	0	0.30	0.30
Middlegame	$0.5 \phi(t)$	1.0	0.5	0	0.15	0.30
Closed	0	2.0	0.5	0.15	0.15	0.30
Endgame	$0.1 + 0.75 \phi(t)^*$	0.5	0.7	0.15	0	0.45

One overlay applies regardless of phase. If the population has lost the initiative and the King’s local search has gone quiet at the same time,

$$\text{Zugzwang}(t) \iff \phi(t) > 0.2 \wedge \alpha(t) < 0.04 \wedge \varepsilon(t) < 0.05, \quad (18)$$

the development coefficient is halved for that one iteration, $a(t) \leftarrow a(t)/2$. This is a *triangulation* move: change nothing structurally, spend a tempo, and let the next reading of the position be more informative before committing to a new phase.

Tactical operators. Five further operators are what the phases of Table 2 switch between. Figure 6 shows where each of them places a candidate relative to the incumbent and the elite, which is the property that distinguishes them from one another and from the role moves of Figure 4.




Figure 6: Geometry of the five tactical operators, each in a two-dimensional section, with points produced by the equation named in the panel title.

The first is *Novotny interference*, played by Bishops. Named for the classical motif in which a piece is sacrificed on a square that blocks two enemy lines of defence at once, a Bishop is occasionally interposed on the segment between two distant, higher-ranked pieces rather than moving diagonally around the King:

$$\mathbf{X}'_i = \beta \mathbf{X}_a + (1 - \beta) \mathbf{X}_b + 0.02 a(t) \mathbf{L} \circ \mathbf{z}, \quad \beta \sim \mathcal{U}(0.3, 0.7), \quad \mathbf{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \quad (19)$$

with a and b drawn without replacement from the fitter half of the population, at probability p_{intf} from Table 2. Being a convex recombination of two arbitrary population members rather than a step along a coordinate axis, it is rotation-invariant, and it is the mechanism most directly responsible for CA's gains on the CEC-2017 hybrid and composition functions (Section 4).

The second is the *knight's fork*. With probability 0.5, a Knight that does not take its exploratory leap instead plays

$$\mathbf{X}'_i = \mathbf{X}_i + \mathbf{r} \circ (\mathbf{K} - \mathbf{X}_i) + 0.8(\mathbf{X}_a - \mathbf{X}_b), \quad a, b \sim \mathcal{U}\{1, \dots, i-1\}, \quad \mathbf{r} \sim \mathcal{U}(0, 1)^D, \quad (20)$$

drifting toward the King while inheriting the differential structure of two better-ranked peers at once, which is to say attacking two targets simultaneously, in the spirit of the tactic that gives the move its name.

The third is the *discovered attack*. An early version applied the geometry below to every Rook as a population move, and tuning showed that to be tactically unsound at that scale, since the candidate is accepted by the ordinary improvement rule almost every time it is tried, collapsing the Rook sub-population onto the King-elite line within a handful of iterations. Restricted instead to a single, strictly elitist probe competing for one of the King’s own en-passant trials, and active only in the Closed and Endgame phases,

$$\mathbf{Y}_{\text{DA}} = \mathbf{X}_e + u(\mathbf{K} - \mathbf{X}_e), \quad u \sim \mathcal{U}(1.2, 2.2), \quad e \sim \mathcal{U}\{1, 2, 3\}, \quad (21)$$

it recovers the intended effect, probing the far side of the incumbent along an elite-King line, without the pathology. The finding generalizes: a tactic that is sound for a single elite piece can destabilize an entire role class, much as a discovered attack that wins material for one player becomes self-defeating if every piece on the board plays it at once.

The fourth is the *royal council*, which competes with the discovered attack for the same probe slot, the two being mutually exclusive and selected by relative probability:

$$\mathbf{Y}_{\text{council}} = \mathbf{K} + 1.5 u(\mathbf{K} - \mathbf{c}), \quad \mathbf{c} = \frac{1}{2}(\mathbf{X}_{\text{Q}_1} + \mathbf{X}_{\text{R}_1}), \quad u \sim \mathcal{U}(0, 1), \quad (22)$$

reflecting the King away from the midpoint of the best Queen and the best Rook. Where isotropic Gaussian probes are blind to the shape of the elite, this reflection is population-shaped: when the elite lies strung along a narrow curved valley, which is the typical geometry along an active inequality constraint in the engineering problems of Section 6, it points down the valley rather than across it. This single mechanism closed most of the welded-beam gap observed in early prototypes.

The fifth is the *windmill*. In the Endgame phase only, a successful en-passant or council capture with displacement $\delta = \mathbf{K}^{(t)} - \mathbf{K}_{\text{pre}}^{(t)}$ is extended,

$$\mathbf{K} \leftarrow \mathbf{K} + \delta \quad \text{while } f(\mathbf{K} + \delta) < f(\mathbf{K}), \quad \text{up to 3 repetitions}, \quad (23)$$

echoing the chess windmill’s repeating sequence of discovered checks, each one harvesting material.

Overprotection archive. Aron Nimzowitsch’s overprotection principle counsels defending a valuable point with more force than strictly necessary, so that pieces freed from other duties have a strong square to retreat to. CA archives up to five mutually distant past King positions,

$$\text{admit } \mathbf{K}^{(t)} \iff f(\mathbf{K}^{(t)}) < f(\mathbf{K}^{(t-1)}) \wedge \min_{\mathbf{a} \in \mathcal{A}} \frac{\|\mathbf{K}^{(t)} - \mathbf{a}\|}{L_{\text{span}}\sqrt{D}} > 0.15, \quad (24)$$

evicting the worst by fitness on overflow. These strongpoints are the fallback used by the blockade response.

Blockade: pawn break, King’s march, and speculative sacrifice. When the fifty-move counter reaches $s(t) \geq 25$ in Equation 16, three mechanisms fire together. All Pawns are re-deployed uniformly at random, a *pawn break* that opens lines in a closed position. The King probes six long-radius candidates at three scales,

$$\mathbf{Y}_m = \mathbf{K} + \rho_m \mathbf{L} \circ \mathbf{z}_m, \quad \rho_m \in \{0.1, 0.1, 0.2, 0.2, 0.4, 0.4\}, \quad \mathbf{z}_m \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \quad (25)$$

then *consolidates* the best candidate with an eight-step greedy local refinement of shrinking radius before comparing it against the incumbent King. The order is deliberate: refining before comparing lets the march accept a basin whose raw landing point is worse than the incumbent but whose refined optimum is better, while the final elitist comparison still guarantees that the King’s fitness sequence never worsens. At the same

time the sacrifice budget of Equation 11 is reheated tenfold for the next ten iterations, modelled on Mikhail Tal’s willingness to give up material for an unquantifiable positional initiative rather than keep playing conservative moves that have stopped producing progress, and, if the archive of Equation 24 is non-empty, the worst-ranked Queen is replaced by a random archived strongpoint, which gives the population a proven foothold rather than a blind restart.

Opening principle: opposition-based initialization. The initial population is evaluated together with its reflection through the board’s centre, $\mathbf{X}_{\text{mirror}}^{(0)} = \mathbf{l} + \mathbf{u} - \mathbf{X}^{(0)}$, and the fitter half of the combined $2N$ candidates is kept. Isolating this mechanism during tuning revealed a *mixed* effect, better on two of four micro-benchmark problems tested and worse on the other two, rather than a consistent gain. It is kept by default because it never produced a large regression and costs only one extra population evaluation, paid once; its dedicated ablation is reported in Section 7.1.

2.7. Parameter summary and pseudocode

Table 3 collects the base parameters and the single configuration used everywhere in this paper. Several of them, including the pinning probability and the knight-leap rate, are further modulated by the phase-conditioned schedule of Table 2 once the adaptive control layer is active, while CA-static uses the values below unmodulated throughout. No per-problem tuning was done, for CA, for CA-static, or for any competitor, and every result in this paper comes from this one configuration. How much that costs is measured in Section 7.2: of the parameters below, only the role fractions change performance significantly at the granularity tested.

Table 3: CA parameters and the fixed configuration used in all experiments.

Parameter	Symbol	Value
Role fractions (Queen / Rook / Bishop / Knight)	$\rho_q, \rho_r, \rho_b, \rho_n$	0.10/0.15/0.15/0.20
Development schedule	$a(t)$	$2(1 - t/T)$
Pinning probability / cap	$p_{\text{pin}}(t)$	$0.5 t/T$, at most 30% of coordinates
Sacrifice constant	θ_0	0.1
Castling period	c	10 iterations
En-passant probes per iteration	—	3
En-passant adaptation (success / failure / reset)	—	$\times 1.3$ / $\times 0.92$ / after 50 failures
Knight exploratory-leap distribution	—	uniform (Lévy, $\beta_\ell = 1.5$, optional)

The complete step is given below. Lines 4 and 5 are the controller strand of Figure 3, lines 6 to 10 the population strand, and lines 11 to 16 the King’s own local search.

Algorithm 1: Chess Algorithm (CA)

Input: f , bounds $[l, u]$, dimension D , population N , iterations T

Output: King K

```

1  X ← init( $N$ ,  $l$ ,  $u$ ) and mirror  $l+u-X$ ; evaluate; keep fitter  $N$  (Eq. 2)
2  sort  $X$ ;  $K \leftarrow X(1)$ ;  $\sigma \leftarrow 0.1 L$ ; archive  $\leftarrow \{\}$ 
3  for  $t = 0$  to  $T-1$  do
4     $a \leftarrow 2(1 - t/T)$ ; update  $d$ ,  $\alpha$ ,  $\epsilon$ ,  $s$  (Eqs. 13-16)
5    select the phase and read its rates (Eq. 17, Table 2)
6    assign roles by rank: King, Queens, Rooks, Bishops,
      Knights, Pawns (Eq. 3)
7    move every piece by its role operator (Eqs. 5-10)
8    apply the phase tactics: fork, interference, leap (Eqs. 19-20)
9    pin coordinates to  $K$  with prob.  $p_{\text{pin}}$ ; clip; evaluate
10   accept improvements; keep a worse Knight or Pawn with
      probability  $e^{-(\Delta/\theta)}$  (Eq. 11)
11   en passant: 3 masked trials around  $K$ ; adapt  $\sigma$  (Eq. 12)
12   add one council or discovered-attack probe (Eqs. 21-22)
13   if Endgame and a probe succeeded then extend it (Eq. 23)
14   if  $t \bmod c = 0$  then castle: swap a block  $K \leftrightarrow$  best Rook
15   re-deploy agents identical to  $K$ ; update  $K$  and archive (Eq. 24)
16   if  $s \geq 25$  then blockade: pawn break, King's march,
      reheat  $\theta$  (Eq. 25)
17 end for
18 return  $K$ 

```

2.8. Relation to established operator families

The criticism of metaphor-driven algorithm design articulated by Sörensen [18] deserves a direct answer rather than a defensive one. A vocabulary borrowed from a game can obscure the fact that the underlying operators are established ones, it can impede comparison with prior work, and it can inflate claims of novelty. What we owe the reader is a precise statement of what each mechanism is mathematically and where it sits in the existing taxonomy. Table 4 provides that statement for every CA mechanism.

Table 4: Every CA mechanism, its established operator family, and the canonical reference for that family.

CA mechanism	Operator family	Canonical reference
Role-based moves (Queen, Rook, Bishop, Knight, Pawn)	Elite-guided stochastic perturbation, heterogeneous step geometry	[7, 11]
Development schedule $a(t)$	Time-decreasing step-size scheduling	[11]
Sacrifice (Equation 11)	Metropolis acceptance with population-scaled temperature	[6]
En passant σ rule (Equation 12)	Success-rule step-size adaptation, $(1+\lambda)$ -ES	[5, 20]
Knight's fork (Equation 20)	Differential mutation (current-to-best with difference vector)	[9]
Novotny interference (Equation 19)	Arithmetic (convex) recombination	[4]
Royal council (Equation 22)	Simplex-type reflection away from an elite centroid	[24]
Discovered attack (Equation 21)	Line extrapolation through the incumbent	[24]
Windmill (Equation 23)	Success-directed displacement repetition	[5]
Pinning	Block-coordinate fixation (axis-aligned subspace exploitation)	—
Castling	Segment (block) crossover with elitist acceptance	[3]
Threefold repetition	Diversity maintenance by re-initialization	[4]
Blockade response (Equation 25)	Partial restart with temperature reheating	[6]
Phase state machine; zugzwang (Equation 17)	Adaptive parameter control	[25]
Opposition-based initialization	Opposition-based learning	[26]

Stated in these terms, CA is a composition of operators from the evolutionary-computation, swarm and trajectory traditions, coordinated by an adaptive control layer and organized around a heterogeneous-role architecture. The chess vocabulary contributes no operator that the table cannot name. What it contributes is a compact and internally consistent language for a particular *composition*, that is which operators are present, at what rates, and under which population states, and that composition, not any single operator, is the algorithmic claim of this paper. Two consequences follow. First, every mechanism named in Table 1 is defined mathematically in this section and measured in isolation in Section 7.1, so the metaphor never substitutes for specification or for evidence. Second, the mapping generates a falsifiable expectation: if CA’s performance rests principally on a small subset of these operator families, then specialized algorithms built purely on those families should match or exceed CA wherever their assumptions hold. The roster of Section 4 through Section 9 includes L-SHADE [19] and CMA-ES [20], the competition-refined embodiments of the differential-mutation and step-size-adaptation families respectively, precisely to test that expectation, and Section 7.1 returns to it quantitatively.

2.9. Computational and memory complexity

The cost of CA is dominated by four operations per iteration. Sorting the population to assign roles costs $\mathcal{O}(N \log N)$ comparisons. Moving every agent under its role operator, applying the pin mask, and clipping to the bounds are all elementwise over the $N \times D$ population, hence $\mathcal{O}(ND)$. Evaluating the moved population costs N objective calls. The King’s local search adds a constant number of calls per iteration: three en-passant probes, one council or discovered-attack probe, at most three windmill extensions in the Endgame phase, one castling probe every c iterations, and fourteen further calls on the rare iterations when the blockade of Equation 25 fires. The controller itself is cheap, since the divergence of Equation 13 costs $\mathcal{O}(ND)$ and the three remaining statistics $\mathcal{O}(N)$, while the archive admission test of Equation 24 costs $\mathcal{O}(|\mathcal{A}|D)$ with $|\mathcal{A}| \leq 5$.

Writing C_f for the cost of one objective evaluation, the total time complexity over the whole run is therefore

$$\mathcal{O}\left(T(ND + N \log N + (N + \kappa) C_f)\right), \quad \kappa \leq 8, \quad (26)$$

where κ collects the King’s per-iteration probes, that is three en-passant trials, one council or discovered-attack probe, up to three windmill extensions and the amortized castling probe; the fourteen blockade calls sit outside κ because they fire on a small fraction of iterations. Since C_f dominates the arithmetic on any objective of practical interest, the operative figure is the evaluation count, $T(N + \kappa)$, and the measured overhead of the κ term is 12.4% of the core budget NT (Section 7.3). The arithmetic term $\mathcal{O}(TND)$ is identical to that of GA, PSO, GWO and WOA, none of which sorts, and the $\mathcal{O}(TN \log N)$ sort that CA adds is negligible beside it whenever $D > \log N$, which holds in every experiment reported here.

Memory is likewise linear in the size of the population. CA stores the population and the candidate population, $2ND$ reals; the fitness vector and the candidate fitness vector, $2N$ reals; the per-agent pin mask, ND booleans; the adaptive radius σ , D reals; and the overprotection archive, at most $5D$ reals with its five fitness values. The convergence history adds T reals. The peak occurs once, at initialization, where the opposition step of Section 2.6 holds $2N$ candidates at the same time. The total is

$$\mathcal{O}(ND + T), \quad (27)$$

with no dependence on the number of strategic mechanisms, since every mechanism operates in place on the arrays already listed. For reference, PSO stores position, velocity and personal best, which is $3ND$ reals, and GWO stores the population plus three leaders, so CA’s footprint is of the same order and of comparable constant. Neither the time nor the memory cost of CA, in other words, is where its twelve mechanisms show up; they show up in the evaluation count, and that is measured exactly in Section 7.3.

3. Benchmark Experiments

3.1. Experimental protocol

CA is compared against its own non-adaptive ablation CA-static (Section 2.6) and four established metaheuristics: a real-coded GA with tournament selection, BLX- α crossover, Gaussian mutation and elitism [3, 4]; PSO with linearly decreasing inertia [7]; SA [6], granted a population-equivalent evaluation budget so that the comparison stays fair; and GWO [11].

The suite consists of six standard functions covering unimodal, ill-conditioned and highly multimodal terrain (Table 5):

Table 5: Benchmark functions ($D = 30$).

Function	Type	Search domain	f^*
F1 Sphere	Unimodal	$[-100, 100]^{30}$	0
F2 Rosenbrock	Unimodal, ill-conditioned valley	$[-30, 30]^{30}$	0
F3 Rastrigin	Multimodal	$[-5.12, 5.12]^{30}$	0
F4 Griewank	Multimodal	$[-600, 600]^{30}$	0
F5 Ackley	Multimodal	$[-32, 32]^{30}$	0
F6 Schwefel 2.22	Unimodal, non-separable norm	$[-10, 10]^{30}$	0

Every algorithm runs with a population of $N = 30$ for $T = 500$ iterations, a shared core budget of 15,000 population evaluations per run. CA additionally spends three en-passant probes per iteration, one castling probe every ten iterations, and occasional windmill and blockade probes (Section 2), and its measured consumption is 12.4% above the core budget, with the exact accounting given in Section 7.3. The gaps reported below span orders of magnitude, so that overhead cannot be what drives them, and GWO beats CA in spite of it. Each algorithm-function pair is repeated over 30 independent runs, and all algorithms share the same seed at a given run index, so every method faces the same initial conditions. No parameters were tuned per problem for any method.

Statistics follow the recommendations of Derrac et al. [27]: one-way ANOVA to establish that the algorithm factor matters at all, then pairwise two-sided Wilcoxon rank-sum tests of CA against each competitor at $\alpha = 0.05$, which make no normality assumption about the final-error distributions.

3.2. Results

Table 6 reports the mean and standard deviation of the final objective value for every algorithm-function pair, with the algorithms as rows and the test functions as columns. The best and worst individual runs, which do not fit that orientation, are reported for every cell in Table 32.

Table 6: Final objective value over 30 runs on the six classical benchmarks ($D = 30$), mean $\pm$ standard deviation. Best mean per function in bold. Best and worst runs are in Table 32.

Algorithm	F1 Sphere	F2 Rosenbrock	F3 Rastrigin	F4 Griewank	F5 Ackley	F6 Schwefel 2.22
CA	6.16e-05 $\pm 1.15\text{e-}04$	77.56 ± 43.83	19.53 ± 8.02	0.008177 ± 0.007777	0.06049 ± 0.3189	0.001554 $\pm 6.93\text{e-}04$
CA-static	4.63e-06 $\pm 4.25\text{e-}06$	55.13 ± 39.69	19.24 ± 4.897	0.01123 ± 0.01143	0.03902 ± 0.2073	8.41e-04 $\pm 3.82\text{e-}04$
GWO	4.68e-31 $\pm 8.19\text{e-}31$	26.83 ± 0.6174	10.23 ± 10.78	0.004303 ± 0.009094	3.32e-14 $\pm 4.37\text{e-}15$	9.93e-19 $\pm 9.46\text{e-}19$
PSO	0.8455 ± 0.7216	6445 $\pm 2.238\text{e+}04$	59.71 ± 14.84	0.6164 ± 0.2367	1.045 ± 0.5491	0.7941 ± 2.486
GA	0.09475 ± 0.05399	105.6 ± 46.33	19.54 ± 6.823	0.2816 ± 0.07971	0.07757 ± 0.01486	0.07438 ± 0.01815
SA	1.013e+04 ± 2218	2.18e+07 $\pm 5.69\text{e+}06$	210.5 ± 29.51	91.9 ± 23.24	4.483 ± 0.3618	1.12e+07 $\pm 2.88\text{e+}07$

Figure 7 shows the median best-so-far curves, and three patterns are apparent in them. On F1, F4 and F6, CA keeps improving throughout the run, because the en-passant success rule continues to find improvements deep into the later iterations, whereas GA and PSO stagnate hundreds of iterations earlier. On the ill-conditioned Rosenbrock valley (F2), convergence slows substantially for every population method, with CA and GA tracking each other closely throughout. CA and CA-static track each other almost exactly on every function, which confirms visually the near-total absence of a significant difference between them on this suite. GWO shows its well-documented strength on this classical suite, converging fastest and to the lowest values throughout. The distributions of final values underlying these curves are shown in Figure 8.




Figure 7: Convergence on the six classical benchmarks: median best-so-far objective over the 30 runs (semi-log scale).

One-way ANOVA confirms that the algorithm factor is highly significant on every function (Table 7), and the pairwise Wilcoxon tests of Table 8 give the sharper picture.

Table 7: One-way ANOVA over the six algorithms, per function.

Statistic	F1 Sphere	F2 Rosenbrock	F3 Rastrigin	F4 Griewank	F5 Ackley	F6 Schwefel 2.22
<i>F</i>	605.1	427.0	777.7	451.7	951.0	4.4
<i>p</i>	5.6e-108	1.1e-95	5.4e-117	1.2e-97	2.7e-124	8.4e-04

Table 8: Wilcoxon rank-sum tests, CA versus each competitor, *p*-value per function ($\alpha = 0.05$). (+): CA significantly better; (-): CA significantly worse; (=): not significant.

Comparison	F1 Sphere	F2 Rosenbrock	F3 Rastrigin	F4 Griewank	F5 Ackley	F6 Schwefel 2.22
CA vs CA-static	1.48e-03 (-)	6.04e-02 (=)	6.68e-01 (=)	7.01e-01 (=)	1.10e-02 (-)	5.10e-05 (-)
CA vs GWO	2.87e-11 (-)	2.95e-08 (-)	6.16e-05 (-)	1.48e-05 (-)	2.87e-11 (-)	2.87e-11 (-)
CA vs PSO	2.87e-11 (+)	2.55e-09 (+)	6.37e-11 (+)	2.87e-11 (+)	4.40e-10 (+)	2.87e-11 (+)
CA vs GA	2.87e-11 (+)	1.09e-03 (+)	5.15e-01 (=)	2.87e-11 (+)	5.32e-10 (+)	2.87e-11 (+)
CA vs SA	2.87e-11 (+)	2.87e-11 (+)	2.87e-11 (+)	2.87e-11 (+)	2.87e-11 (+)	2.87e-11 (+)




Figure 8: Distribution of final objective values over 30 runs.

3.3. Discussion

Taken together, the tables support a differentiated conclusion rather than a single summary statement. Against PSO and SA, CA is significantly better on all six functions. Against GA it wins five of six, on Sphere, Rosenbrock, Griewank, Ackley and Schwefel 2.22, while Rastrigin ends in a statistical tie. Against GWO the outcome is reversed: GWO is significantly better on all six, consistent with the aggressive exploitation it is known for on exactly this suite [11]. We state that limitation plainly. On standard unconstrained test functions with central global optima, CA does not surpass GWO.

The comparison against CA-static deserves particular attention, because it contradicts the expectation that motivated the adaptive layer in the first place. On this classical, low-structure suite, disabling the layer never hurts and sometimes helps: CA-static is significantly better than CA on Sphere, Ackley and Schwefel 2.22 and statistically tied on the other three, and there is not a single function on which the adaptive layer wins outright. We read this as an informative negative result. The phase-reading machinery is built to recognize open, closed and endgame *structure*, and a smooth unimodal or mildly multimodal function in a fixed box offers it little of that structure to exploit, so the state machine spends its overhead reading a position that barely changes. The CEC-2017 and engineering-design landscapes of Section 4 and Section 6 are exactly where that overhead should start paying for itself, and whether it does is the empirical question those sections answer.

The practical implication is that these rankings are problem-dependent, which is precisely the situation the No-Free-Lunch theorem predicts [17]. The relevant question is therefore not whether CA outperforms its competitors on the Sphere function, but whether it holds up on a harder standardized synthetic suite and on structured engineering problems. That is where we go next. Section 4 extends the comparison to the full CEC-2017 suite, Section 6 turns to constrained engineering design, and Section 8 returns to the transportation motivation that opened the paper. The ranking does change.

4. The Full CEC-2017 Benchmark Suite

4.1. Motivation and roster

The six-function suite of Section 3 is standard but narrow, and current practice in this literature, including the practice established by our own baseline GWO [11], requires that a claim of competitiveness be validated on a larger, harder, independently curated suite. CEC-2017 meets that requirement. It comprises 29 usable functions, shifted, rotated, and in many cases built by hybridizing or composing several base functions, so that no algorithm can exploit coordinate-axis alignment or a single basin shape.¹

We evaluate CA (Section 2.6) and its non-adaptive ablation CA-static against six competitors: GWO, PSO, and GA, our own implementations from Section 3; WOA [14], third-party, at `mealpy` defaults, as in Section 9; and two competition-grade adaptive optimizers included in answer to the legitimate criticism that new metaheuristics are too often benchmarked only against classical or metaphor-derived baselines [18]. These are L-SHADE [19], the success-history adaptive differential-evolution lineage that has defined the state of the art on CEC suites since 2014, via the `niapy` implementation [29], and CMA-ES [20], the canonical covariance-matrix-adaptation evolution strategy, via Hansen’s reference implementation `pycma` [30]. All algorithms run at $D = 30$ with population 30, 500 iterations, and 30 independent runs per algorithm-function pair, run r of every algorithm sharing seed $\text{SEED}_0 + r$ on the unit hypercube, with real bounds folded into the decoder as throughout this paper. Budget parity for the two additions is handled explicitly. CMA-ES runs $\lambda = 30$ for 500 generations, which is exactly the 15,000-evaluation core budget. L-SHADE, whose linear population-size reduction is intrinsic to the algorithm and shrinks the population from 30 toward 4 as the budget is consumed, is capped at 15,500 evaluations, within the measured consumption of CA itself (Section 7.3). Neither addition therefore holds a budget advantage over any incumbent.

4.2. Data integrity: auditing the reference implementation

CEC-2017 was accessed through `opfunu` v1.0.1, a third-party Python port of the official suite, and two independent checks were applied before any result was trusted. First, every candidate function was evaluated at the library’s own reported global optimizer $\mathbf{x}^*$, requiring $|f(\mathbf{x}^*) - f^*| \leq 10^{-6} \max(1, |f^*|)$. This check is necessary but not sufficient, since it verifies the function at one point and says nothing about the rest of the domain. Second, we required the landscape to be discriminative: F5 (Shifted-and-Rotated Schaffer F7) passed the first check exactly, with $f(\mathbf{x}^*) = f^* = 500.0$, yet random samples spanning the entire search box returned values between 500.15 and 500.55, a surface so nearly flat that no optimizer, ours or any competitor’s, could extract a meaningful gradient from it.

A function can pass both checks and still be broken elsewhere in the domain. Five further functions were caught only empirically, during optimization itself, because at least one algorithm in the roster, and in the worst cases nearly every algorithm including the weakest, returned a best-of-30-runs value that is impossible by definition under a correct f^* . Four surfaced in the original six-algorithm runs. A fifth, F16, surfaced only once the stronger eight-algorithm roster was added, with CMA-ES locating points 78 units below the claimed optimum, which illustrates why stronger baselines also strengthen data auditing. Table 9 collects the evidence for all six defective labels; the defective raw numbers are committed in the repository (`results/cec2017_opfunu_defect_evidence.csv`) rather than quietly dropped.

¹The official suite defines thirty functions, of which F2 (Shifted and Rotated Sum of Different Power) was withdrawn from the competition owing to numerical instability [28]. The `opfunu` library renumbers the remaining twenty-nine consecutively, and this paper’s labels follow that numbering, so label F_n corresponds to the official function $F(n+1)$ for $n \geq 2$. The distinction matters for the cross-library audit of Section 4.2, whose second implementation retains the official numbering.

Table 9: Integrity audit of the `opfunu` CEC-2017 port: the six labels excluded, with the observed evidence of an implementation defect in each case.

Label	opfunu function	Claimed f^*	Defect observed
F5	Shifted and Rotated Schaffer F7	500.0	near-flat: random samples across the box span only [500.12, 500.80] (std 0.13)
F9	Shifted and Rotated Schwefel	900.0	10-run CA probe found a best value of $-4,586.0$, a full 5,486 units below the claimed optimum
F15	Hybrid Function 6	1500.0	best-of-run value -634.7 observed below claimed optimum
F16	Hybrid Function 7	1600.0	best-of-run value -78.1 observed below claimed optimum (surfaced only under the 8-algorithm roster)
F19	Hybrid Function 10	1900.0	best-of-run value -429.3 observed below claimed optimum
F21	Composition Function 2	2100.0	best-of-run value $-9,592.4$ observed below claimed optimum

Excluding defective implementations is only half of a defensible procedure. The other half is establishing whether the *functions themselves* can be evaluated correctly from an independent source. Each excluded label was therefore cross-validated against a second, independent Python implementation, `cec2017-py` [31], which is adapted directly from the official C implementation and its reference data files and retains the official numbering, so that paper label F_n is audited against official $F(n+1)$. Each official counterpart was subjected to the full three-part audit: the one-point preflight, a landscape-discriminateness check, and a ten-run below-optimum probe under the suite protocol. All six pass all three checks, F5 included, whose official Schaffer F7 landscape is entirely discriminative, with a random-sample standard deviation of 40 against 0.1 in the `opfunu` port, and F9, whose official Schwefel landscape shows no below-optimum behaviour at all. Table 10 reports the audit in full.

Table 10: Restoration audit of the six excluded labels against the independent official-data implementation: one-point preflight error, random-sample spread, and the worst deviation below the official optimum across ten CA probe runs.

Label	Official func	$f(\text{shift}+\text{eps})$	Official f^*	Preflight err	Random-100 std	CA min (10 runs)	Worst below f^*	Verdict
F5	F6	600.000	600.0	0.0000	40.06	629.883	+0.000	Pass
F9	F10	1000.000	1000.0	0.0004	1112	3542.222	+0.000	Pass
F15	F16	1600.002	1600.0	0.0018	$6.172\text{e}+04$	2057.193	+0.000	Pass
F16	F17	1700.000	1700.0	0.0001	$5.061\text{e}+07$	1919.152	+0.000	Pass
F19	F20	2000.023	2000.0	0.0231	477.8	2205.239	+0.000	Pass
F21	F22	2200.000	2200.0	0.0000	1074	2300.241	+0.000	Pass

The six labels were consequently restored using the independent implementation, under the identical protocol and seeds, and the analysis below covers all **29 validated functions**, 23 sourced from `opfunu` and 6 from the official-data port. Two conclusions from this audit generalize beyond this paper. Every defect traced to the `opfunu` port rather than to the suite itself, and the pattern of the defects, formulas paired with mismatched shift data, is consistent with a bookkeeping misalignment introduced by the post-withdrawal renumbering. And an audit of this kind is not optional overhead: five of the six defects would silently corrupt any benchmark study that trusted the port, and one of them was detectable only because the roster contained algorithms strong enough to expose it.

4.3. Results

Table 11 gives the standing of the whole roster in one place: the mean Friedman rank of each algorithm across the 29 validated functions, its rank position, the number of functions on which it holds the best mean,

and its win/tie/loss record against CA under a two-sided Wilcoxon rank-sum test at $\alpha = 0.05$.

Table 11: CEC-2017 standing over the 29 validated functions (Friedman $\chi^2 = 150.08$, $p = 3.9 \times 10^{-29}$; lower rank is better). The last column reads as CA’s wins / ties / losses against the algorithm in that row, Wilcoxon rank-sum at $\alpha = 0.05$.

Algorithm	Mean Friedman rank	Rank	Best mean on	CA’s W / T / L against it
L-SHADE	1.76	1	12 of 29	1 / 2 / 26
CMA-ES	2.28	2	15 of 29	6 / 3 / 20
CA	3.62	3	2 of 29	–
CA-static	3.90	4	0 of 29	5 / 23 / 1
GA	4.14	5	0 of 29	10 / 9 / 10
PSO	6.03	6	0 of 29	22 / 6 / 1
GWO	6.41	7	0 of 29	27 / 1 / 1
WOA	7.86	8	0 of 29	29 / 0 / 0

The per-function evidence behind that summary is reported one table per official category of the suite, with the algorithms as rows and the functions as columns: Table 12 (unimodal), Table 13 (simple multimodal), Table 14 and Table 15 (the ten hybrid functions), and Table 16 and Table 17 (the ten composition functions). The two larger categories are split in half so that no table exceeds six function columns; best and worst runs for every cell are in Table 33.

Table 12: CEC-2017, unimodal functions: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F1	F2
CA	3011 ± 2587	107.7 ± 204.6
CA-static	4186 ± 4081	3.805 ± 6.16
GWO	4.38e+09 $\pm 3.67\text{e}+09$	1.564e+04 $\pm 1.178\text{e}+04$
PSO	2.33e+09 $\pm 2.50\text{e}+09$	2742 ± 5215
GA	2.40e+05 $\pm 1.48\text{e}+05$	10.85 ± 5.971
WOA	8.49e+09 $\pm 4.38\text{e}+09$	5.175e+04 $\pm 1.826\text{e}+04$
L-SHADE	5476 ± 5088	0.001651 ± 0.002849
CMA-ES	6069 ± 6549	0.009239 ± 0.02618

Table 13: CEC-2017, simple multimodal functions: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F3	F4	F5	F6	F7	F8	F9
CA	107.8 ± 43.4	228.9 ± 42.15	42.36 ± 7.978	273.9 ± 75.94	207.8 ± 35.02	4.821 ± 2.025	3823 ± 642.9
CA-static	99.03 ± 39.97	212.5 ± 55.14	41.98 ± 9.663	231.5 ± 47.18	215.5 ± 44.72	5.035 ± 2.34	3747 ± 635.8
GWO	411.1 ± 447.5	6084 ± 4170	26.35 ± 11.08	8.224e+04 $\pm 1.10\text{e}+05$	377 ± 140.5	6.806 ± 4.302	6687 ± 1963
PSO	310.5 ± 445.3	4978 ± 3476	22.16 ± 9.454	1.95e+05 $\pm 1.77\text{e}+05$	255 ± 77.89	4.802 ± 2.868	3984 ± 918.3
GA	86.67 ± 50.25	148 ± 35.3	33.29 ± 15.85	312.4 ± 52.84	251.2 ± 66.57	7.657 ± 3.671	3618 ± 708
WOA	1416 ± 750.8	2.64e+04 ± 8785	105.4 ± 14.87	3.72e+05 $\pm 1.60\text{e}+05$	846.4 ± 130.5	25.43 ± 10.2	6692 ± 1134
L-SHADE	38.69 ± 18.2	151.3 ± 44.19	10.27 ± 3.944	225.4 ± 96.7	99.19 ± 26.99	1.358 ± 0.991	2451 ± 350.6
CMA-ES	31.82 ± 0.03087	29.55 ± 25.34	0.01966 ± 0.04062	76.04 ± 51.97	83.15 ± 29.41	0.1453 ± 0.263	4191 ± 2609

Table 14: CEC-2017, hybrid functions F10-F14: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F10	F11	F12	F13	F14
CA	2.232e+04 ± 9882	3.29e+05 $\pm 2.64\text{e}+05$	2.525e+04 $\pm 4.452\text{e}+04$	2.21e+05 $\pm 1.87\text{e}+05$	2.36e+04 ± 7888
CA-static	2.353e+04 $\pm 1.528\text{e}+04$	5.89e+05 $\pm 6.34\text{e}+05$	3.129e+04 $\pm 4.555\text{e}+04$	1.97e+05 $\pm 1.76\text{e}+05$	3.082e+04 $\pm 1.062\text{e}+04$
GWO	2.90e+05 $\pm 7.887\text{e}+04$	1.39e+08 $\pm 2.65\text{e}+08$	1.04e+08 $\pm 4.94\text{e}+08$	1.78e+06 $\pm 2.43\text{e}+06$	1.79e+07 $\pm 3.85\text{e}+07$

Algorithm	F10	F11	F12	F13	F14
PSO	3.49e+05 ±8.76e+05	2.23e+08 ±4.74e+08	1.79e+08 ±5.06e+08	4.54e+05 ±4.29e+05	1.01e+07 ±4.10e+07
GA	2.328e+04 ±1.348e+04	5.292e+04 ±3.32e+04	8973 ±6242	2.89e+06 ±2.49e+06	2.169e+04 ±1.141e+04
WOA	3.42e+05 ±7.94e+05	4.70e+08 ±7.08e+08	1.77e+08 ±4.66e+08	5.28e+06 ±4.70e+06	5.66e+07 ±8.36e+07
L-SHADE	2862 ±2210	1.989e+04 ±2.208e+04	6974 ±5553	3.468e+04 ±1.18e+05	1.095e+04 ±6551
CMA-ES	1.682e+04 ±3.168e+04	9.959e+04 ±1.04e+05	5.567e+04 ±1.433e+04	6.904e+04 ±6.861e+04	4.704e+04 ±1.546e+04

Table 15: CEC-2017, hybrid functions F15-F19: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F15	F16	F17	F18	F19
CA	1012 ±285.4	445.4 ±184.3	5.881e+04 ±4.279e+04	1.463e+04 ±1.355e+04	298.8 ±116.5
CA-static	1042 ±310	419.8 ±194	4.293e+04 ±1.876e+04	1.025e+04 ±1.217e+04	361.7 ±133.4
GWO	1425 ±540.1	714.4 ±295.9	1.38e+05 ±5.843e+04	5.29e+09 ±1.03e+10	673.1 ±308.7
PSO	1135 ±331.1	488.6 ±218	3.84e+05 ±1.03e+06	6.05e+09 ±1.78e+10	402.3 ±160.6
GA	1114 ±302.2	700.7 ±275.5	7.11e+05 ±7.78e+05	2.014e+04 ±1.389e+04	662.6 ±246.6
WOA	2729 ±885.4	1564 ±467	1.86e+05 ±3.49e+05	9.95e+09 ±2.00e+10	939.4 ±249.4
L-SHADE	673.8 ±217.1	211.1 ±104.6	1.302e+04 ±1.287e+04	424.2 ±610.8	264.4 ±116.7
CMA-ES	269.4 ±179.1	176.1 ±95.68	5.885e+04 ±3.515e+04	8.523e+04 ±4.799e+04	259.2 ±186.8

Table 16: CEC-2017, composition functions F20-F24: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F20	F21	F22	F23	F24
CA	363.1 ±175.6	346.4 ±914.5	314.5 ±210.5	224.5 ±94.6	451.7 ±22.39
CA-static	291.4 ±184.7	728.9 ±1423	317.3 ±199.2	272 ±150.3	443.2 ±18.05
GWO	4150 ±5185	4445 ±3012	9891 ±4098	5984 ±2107	639.5 ±214.1
PSO	2035 ±1133	2070 ±1906	1.08e+04 ±5061	5347 ±2684	490 ±127.5
GA	287.8 ±107.8	3032 ±2011	265.7 ±66.79	254.3 ±78.26	435.7 ±18.28
WOA	1.446e+04 ±1.082e+04	6478 ±1179	1.72e+04 ±8057	1.296e+04 ±8319	1038 ±314.7
L-SHADE	260.6 ±140.3	774.2 ±1181	224.3 ±93.96	221.7 ±65.19	423.5 ±4.252
CMA-ES	221.1 ±61.64	2337 ±2063	248.9 ±70.27	229.2 ±52.99	420.5 ±0.0608

Table 17: CEC-2017, composition functions F25-F29: final error $f - f^*$ over 30 runs, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F25	F26	F27	F28	F29
CA	866.9 ±45.29	547.1 ±31.32	227.6 ±162.1	9.86e+04 ±1.39e+05	8.8e+04 ±1.23e+05
CA-static	871.5 ±16.87	558.8 ±49.5	229.1 ±172.3	1.29e+05 ±1.91e+05	2.22e+05 ±2.55e+05
GWO	913.7 ±30.28	558.8 ±28.63	609.3 ±182.8	2.69e+08 ±4.32e+08	5.02e+08 ±1.14e+09
PSO	1052 ±145.2	588.6 ±58.75	810.5 ±322.4	3.05e+07 ±6.48e+07	6.31e+08 ±1.99e+09
GA	840.1 ±14.75	523 ±22.3	102.6 ±145.3	1.41e+05 ±2.37e+05	6.54e+05 ±1.39e+06
WOA	2731 ±2035	1231 ±240.7	1073 ±666.2	8.63e+08 ±1.06e+09	3.19e+09 ±5.40e+09
L-SHADE	840.3 ±17.29	508.8 ±13.79	128.1 ±110.5	7281 ±5508	1.947e+04 ±1.16e+04

Algorithm	F25	F26	F27	F28	F29
CMA-ES	827.9 ± 2.203	508.4 ± 15.04	1.928 ± 4.377	6086 ± 2085	1.22e+05 $\pm 9.095\text{e}+04$

Figure 9 shows median convergence on six representative functions and Figure 10 the distribution of final errors on the same six. The six span the four official categories, one unimodal, one multimodal, two hybrid and two composition, and they are not chosen to favour CA: they include F4 and F22, on which both competition-grade methods beat it.




Figure 9: Median convergence on six representative CEC-2017 functions, one or more per official category (30 runs, semi-log scale).

The distributions answer a question the means alone cannot, namely whether a ranking is carried by typical runs or by a few outliers, and the picture is not uniform. On F1 the distributions of CA, CA-static, L-SHADE and CMA-ES overlap almost entirely; CA holds the lowest mean of the roster on that function, and its comparisons against both competition-grade methods are statistical ties at $p = 0.21$ each. On F4, F10 and F13 the two specialized methods sit roughly an order of magnitude below CA, with tighter distributions, and beat it significantly. On the two composition functions the absolute gaps are small but consistent across runs, and CA loses to both methods there as well.

4.4. Discussion

The two competition-grade methods lead decisively. L-SHADE takes the best mean Friedman rank at 1.76 and CMA-ES the second at 2.28, each beating CA on roughly ninety percent of functions, 26/29 and 20/29 losses for CA respectively, with only 1 and 6 wins. We report this as the central result of the suite, not as a caveat to it, and Section 7.1 explains it mechanistically. Among the remaining six algorithms, CA takes the best mean Friedman rank at 3.62, narrowly ahead of CA-static at 3.90 and GA at 4.14, and well ahead of PSO at 6.03, GWO at 6.41, and WOA at 7.86. Against GWO, PSO, and WOA, CA wins nearly all comparisons, 27/29, 22/29, and 29/29 respectively, with a single loss to each of GWO and PSO, both on F5,




Figure 10: Distribution of the final error over 30 runs on the six functions of Figure 9 (log scale).

the restored Schaffer F7 function, and none to WOA. Against its own non-adaptive ablation, the adaptive machinery of Section 2.6 wins 5 and loses 1 of 29, with 23 ties, which is a real but modest net gain, about what one should expect from a well-tuned control layer applied to an already competitive base algorithm.

The comparison least favourable to CA among the classical roster is against GA, where the near-tied mean rank conceals a record of 10 wins, 9 ties and 10 losses function by function. The ten losses are not scattered at random. They are F4, F5, F11, F12, F20, F22, F24, F25, F26, and F27, all Rastrigin-family, hybrid, and composition landscapes whose basins lie as far apart as the search domain is wide. The BLX- α crossover of GA routinely proposes offspring *outside* the interval spanned by two parents, an operator that can relocate a candidate across the entire domain in a single step. Every CA operator introduced in Section 2.6, by contrast, is anchored to the King, to an elite peer, or to a bounded local neighbourhood, and even the Knight’s exploratory leap resamples only two of thirty coordinates. We read this as an illustration of the No-Free-Lunch theorem [17] rather than as a deficiency to be minimized: CA was tuned against constrained engineering geometry and smooth hybrid and composition exploitation (Section 2.6), and that specialization has a measurable opportunity cost on landscapes whose defining difficulty is long-range, unstructured basin-hopping. We return to the trade-off, and to a concrete proposal for closing it, in Section 10.

5. The CEC-2022 Benchmark Suite

CEC-2017 is the more extensive suite, but it is no longer the most recent, and a reviewer is entitled to ask whether the picture it paints survives on the current generation of benchmark design. CEC-2022 [32] comprises twelve functions, namely Zakharov, Rosenbrock, expanded Schaffer F7, non-continuous Rastrigin, and Lévy under shift and rotation, plus three hybrid functions and four composition functions, defined at two official dimensionalities, $D = 10$ and $D = 20$, both of which are evaluated here. The roster is the full eight-algorithm set of Section 4: CA, CA-static, GWO, PSO, GA, WOA, L-SHADE, and CMA-ES. The protocol is likewise identical, with population 30, 500 iterations, 30 independent runs, shared seed $\text{SEED}_0 + r$ at run index r , and unit-hypercube search with bounds folded into the decoder. One departure from the official competition setup is disclosed rather than hidden. The CEC-2022 termination criteria specify budgets

of 200,000 evaluations at $D = 10$ and 1,000,000 at $D = 20$, whereas this study retains its paper-wide core budget of 15,000 so that results remain comparable across every section. The findings below therefore characterize behaviour under a modest, practice-oriented budget rather than at the official competition horizon.

5.1. Data integrity

The same two-stage audit as Section 4.2 was applied to the CEC-2022 port of **opfunu**. Unlike the CEC-2017 port, the preflight check passes for all twelve functions at both dimensionalities. The post-hoc below-optimum audit, applied after the full runs with the same tolerance, nonetheless excluded six (function, dimension) cells in which at least one algorithm’s best run fell decisively below the library’s claimed optimum: F7 and F8 at $D = 20$, F10 at both dimensionalities, and F11 and F12 at $D = 10$, with observed dips ranging from -41 to $-4,588$. This is again an implementation defect rather than a property of any algorithm, since in the worst cases nearly every algorithm in the roster, including the weakest, crossed the claimed optimum. In addition, F3 (expanded Schaffer F7, the same function family whose near-flat CEC-2017 port motivated the flatness rule in Section 4.2) proved non-discriminative at both dimensionalities under this budget: the *worst-performing* algorithm’s median final error is 0 at $D = 10$ and 0.066 at $D = 20$, so every method essentially solves it and it contributes no ranking information. Table 18 summarizes the exclusions. Sixteen validated cells remain, eight per dimensionality, and the full pre-audit numbers are committed in the repository (`results/cec2022_stats_raw_unaudited.csv`).

Table 18: CEC-2022 data-integrity audit: excluded (function, dimension) cells and the reason for each exclusion.

Function	Reason excluded
F10-D10	below-optimum (opfunu defect)
F10-D20	below-optimum (opfunu defect)
F11-D10	below-optimum (opfunu defect)
F12-D10	below-optimum (opfunu defect)
F7-D20	below-optimum (opfunu defect)
F8-D20	below-optimum (opfunu defect)
F3-D10	near-flat (worst-mean PSO median final error $0 < 1.0$)
F3-D20	near-flat (worst-mean PSO median final error $0.0657 < 1.0$)

5.2. Results and discussion

Table 19 gives the standing of the roster across the sixteen validated cells, in the same layout as Table 11. The per-cell results follow in Table 20 and Table 21, one table per official dimensionality; best and worst runs are in Table 34, and the excluded cells remain listed with their reasons in Table 18.

Table 19: CEC-2022 standing over the 16 validated (function, dimension) cells (Friedman $\chi^2 = 81.69$, $p = 6.2 \times 10^{-15}$; lower rank is better). The last column reads as CA’s wins / ties / losses against the algorithm in that row.

Algorithm	Mean Friedman rank	Rank	Best mean on	CA’s W / T / L against it
L-SHADE	1.88	1	5 of 16	1 / 4 / 11
CMA-ES	2.06	2	10 of 16	2 / 2 / 12
CA	3.63	3	1 of 16	—
CA-static	3.75	4	0 of 16	1 / 13 / 2
GA	4.75	5	0 of 16	10 / 4 / 2
PSO	5.63	6	0 of 16	12 / 2 / 2
GWO	6.44	7	0 of 16	12 / 4 / 0
WOA	7.88	8	0 of 16	16 / 0 / 0

Table 20: CEC-2022 at $D = 10$: final error $f - f^*$ over 30 runs on the eight validated functions, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F1	F2	F4	F5	F6	F7	F8	F9
CA	1.39e-07 $\pm 1.83\text{e-}07$	14.36 ± 25.33	20.36 ± 7.008	0.0996 ± 0.1728	6264 $\pm$ 4765	20.06 ± 5.306	21.15 ± 5.843	183.8 ± 183.8

Algorithm	F1	F2	F4	F5	F6	F7	F8	F9
CA-static	1.13e-07 ±4.52e-07	12.06 ±24.07	22.6 ±7.36	0.1964 ±0.2853	8690 ±7381	19.73 ±8.406	19.16 ±6.819	208.3 ±182.2
GWO	267.4 ±560.4	26 ±32.79	44.42 ±12.01	0.006198 ±0.02241	4.426e+04 ±1.849e+04	46.96 ±18.63	555.4 ±659.1	375.3 ±27.2
PSO	6.65e-10 ±1.01e-09	19.75 ±18.49	31.27 ±9.64	0.01195 ±0.03043	2.848e+04 ±1.561e+04	30.42 ±10.34	407.2 ±894.8	328.9 ±141.2
GA	0.003916 ±0.005432	10.57 ±18.76	45.8 ±19.66	0.7676 ±1.202	1.716e+04 ±1.334e+04	25.73 ±11.99	56.54 ±100.1	285.6 ±158.1
WOA	4044 ±3642	69.67 ±101	102.4 ±44.61	2.956 ±2.068	2.917e+04 ±1.893e+04	374.9 ±315	1924 ±1229	416.5 ±140.4
L-SHADE	2.46e-14 ±2.82e-14	6.451 ±2.465	18.47 ±6.212	0.002984 ±0.01607	36.77 ±186.8	12.16 ±9.212	18.93 ±5.97	275.3 ±151.9
CMA-ES	0 ±0	6.451 ±2.465	17.8 ±6.052	0 ±0	79.58 ±241.6	27.69 ±13.29	20.19 ±7.353	359.1 ±1.71e-13

Table 21: CEC-2022 at $D = 20$: final error $f - f^*$ over 30 runs on the eight validated functions, mean $\pm$ standard deviation, best mean per function in bold.

Algorithm	F1	F2	F4	F5	F6	F9	F11	F12
CA	3.01e-04 ±2.13e-04	62.75 ±18.66	95.27 ±27.17	1.588 ±0.8434	3.971e+04 ±1.667e+04	355.6 ±13.06	4.998 ±9.974	257.5 ±24.44
CA-static	1.21e-05 ±2.36e-05	61.53 ±13.45	110.2 ±28.16	1.628 ±0.767	4.312e+04 ±1.52e+04	338.8 ±63.68	152.5 ±430.6	259.3 ±29.23
GWO	2182 ±2795	101.8 ±71.86	184.4 ±68.6	1.311 ±1.174	1.14e+06 ±3.61e+06	395.7 ±43	522.2 ±695.3	269.8 ±27.88
PSO	766.9 ±3526	73.02 ±33.93	129.1 ±39.35	1.719 ±1.852	5.21e+05 ±2.36e+06	438 ±167.7	356.1 ±558.8	295 ±44.46
GA	0.1164 ±0.04908	60.24 ±12.07	141.1 ±44.2	3.179 ±2.803	5.903e+04 ±2.376e+04	343.7 ±5.018	8.723 ±11.57	256.6 ±35.34
WOA	1.277e+04 ±1.202e+04	226.4 ±125.1	408.3 ±78.42	10.22 ±4.252	7.72e+05 ±3.23e+06	615.1 ±149.3	999.4 ±1076	720.3 ±207.5
L-SHADE	3.29e-11 ±1.07e-10	48.73 ±5.444	59.64 ±17.84	0.2258 ±0.2831	3.717e+04 ±1.617e+04	335.6 ±7.72e-05	49.69 ±246.6	233 ±8.669
CMA-ES	1.08e-12 ±4.33e-12	48.67 ±1.257	43.87 ±10.54	0.002984 ±0.01607	6.225e+04 ±1.933e+04	335.6 ±5.41e-12	1.75e-08 ±3.34e-08	239.2 ±16.99

Figure 11 shows median convergence on three representative cells per dimensionality: F1 (Zakharov), F6 (Hybrid 1) and F9 (Composition 1), which span the basic, hybrid and composition classes of the suite. They are not selected for CA’s advantage. On F9, CA holds the best mean at $D = 10$ and ties both competition-grade methods there, but loses to both significantly at $D = 20$.

The ordering at the top of Table 19 is unambiguous and consistent with Section 4: the two competition-grade methods lead, with L-SHADE at 1.88 and CMA-ES at 2.06, followed by CA at 3.63 and CA-static at 3.75 as the best-ranked of the remaining six, then GA at 4.75, PSO at 5.63, GWO at 6.44, and WOA at 7.88. The pattern is stable across dimensionalities. Restricting the Friedman analysis to the eight $D = 10$ cells gives L-SHADE first and CMA-ES second ($\chi^2 = 39.3$, $p = 1.7 \times 10^{-6}$), and restricting it to the eight $D = 20$ cells gives CMA-ES first and L-SHADE second ($\chi^2 = 44.1$, $p = 2.0 \times 10^{-7}$), with CA third at $D = 20$ and effectively tied with CA-static for third at $D = 10$.

The pairwise records make both directions of the comparison explicit. Against the classical roster, CA wins 12 of 16 cells against GWO and PSO, 10 against GA, and all 16 against WOA, with at most 2 losses to any of them. Against L-SHADE it loses 11 of 16 with a single win, F11, the second composition function, at $D = 20$; against CMA-ES it loses 12 with two wins, F7 at $D = 10$ and F6 at $D = 20$, both hybrid functions. These losses are the central fact of this section rather than a footnote to it: under this budget, the specialized adaptive machinery of L-SHADE and CMA-ES is decisively stronger on shifted and rotated synthetic landscapes than CA’s chess-derived composition, at both dimensionalities. The No-Free-Lunch reading of such reversals, developed for the GA trade-off in Section 4, applies here in the same form and is not repeated. What is specific to this suite is that the GA trade-off itself does not reappear: CA beats GA 10-4-2 on CEC-2022, against a losing record on CEC-2017, which indicates that GA’s long-range crossover advantage belongs to the 30-dimensional CEC-2017 hybrid and composition geometry rather than being a




Figure 11: Median convergence on F1, F6 and F9 of CEC-2022 at each official dimensionality (30 runs, semi-log scale).

general property. Section 7.1 accounts for *why* the two specialized methods lead, which is more useful than the observation on its own.

6. Constrained Engineering Design Benchmarks

Alongside standardized synthetic suites, it is common practice in this literature to validate a new meta-heuristic on the small set of constrained engineering design problems that recur across published comparisons, because a shared, literature-anchored problem allows direct comparison against independently produced results. We use seven such problems in their commonly published formulations: welded beam design, tension/compression spring design, pressure vessel design, speed reducer design, three-bar truss design, gear train design, and cantilever beam design. Constraints are handled by the same static-penalty approach used elsewhere in this paper (Section 9), $f_{\text{pen}}(\mathbf{x}) = f(\mathbf{x}) + 10^6 \sum_i \max(0, g_i(\mathbf{x}))^2$. Roster and protocol are identical to Section 4, with all eight algorithms, population 30, 500 iterations and 30 runs.

6.1. Results and discussion

Table 22 gives the standing of the roster across the seven problems and Table 23 the per-problem results, with the algorithms as rows and the design problems as columns; best and worst runs are in Table 35. Figure 12 shows median convergence on all seven.

Table 22: Engineering design standing over the 7 problems (Friedman $\chi^2 = 33.87$, $p = 1.8 \times 10^{-5}$; lower rank is better). The last column reads as CA’s wins / ties / losses against the algorithm in that row.

Algorithm	Mean Friedman rank	Rank	Best mean on	CA’s W / T / L against it
L-SHADE	1.57	1	4 of 7	0 / 0 / 7
CMA-ES	2.14	2	2 of 7	0 / 1 / 6
CA	3.71	3	1 of 7	—
CA-static	4.14	4	0 of 7	1 / 6 / 0
GWO	5.00	5	0 of 7	3 / 4 / 0

Algorithm	Mean Friedman rank	Rank	Best mean on	CA's W / T / L against it
PSO	5.71	6	0 of 7	4 / 2 / 1
GA	6.14	7	0 of 7	6 / 1 / 0
WOA	7.57	8	0 of 7	7 / 0 / 0

Table 23: Objective value over 30 runs on the seven constrained engineering design problems, mean $\pm$ standard deviation, best mean per problem in bold. Best and worst runs are in Table 35.

Algorithm	Welded beam	Spring	Pressure vessel	Speed reducer	Three-bar truss	Gear train	Cantilever beam
CA	1.774 ± 0.1085	0.01293 $\pm 3.19\text{e-}04$	5969 ± 236.1	2994 $\pm 1.01\text{e-}12$	263.9 $\pm 1.18\text{e-}11$	7.30e-10 $\pm 1.07\text{e-}09$	1.34 $\pm 4.01\text{e-}05$
CA-static	1.778 ± 0.1323	0.01305 $\pm 8.56\text{e-}04$	5959 ± 230.6	2994 $\pm 4.79\text{e-}09$	263.9 $\pm 1.20\text{e-}11$	8.08e-10 $\pm 1.11\text{e-}09$	1.34 $\pm 1.99\text{e-}05$
GWO	1.728 ± 0.001381	0.01281 $\pm 1.67\text{e-}04$	5887 ± 191.1	3000 ± 3.543	263.9 ± 0.004537	8.50e-10 $\pm 8.07\text{e-}10$	1.34 $\pm 8.75\text{e-}05$
PSO	1.725 ± 0.001027	0.01307 $\pm 9.30\text{e-}04$	6076 ± 297.9	3032 ± 34.64	263.9 $\pm 6.86\text{e-}06$	3.17e-09 $\pm 5.92\text{e-}09$	1.34 $\pm 4.31\text{e-}05$
GA	1.803 ± 0.09243	0.01378 ± 0.001224	6408 ± 386.3	2994 $\pm 1.32\text{e-}07$	263.9 ± 0.001248	7.92e-10 $\pm 9.93\text{e-}10$	1.342 ± 0.001269
WOA	172.6 ± 910.3	0.01362 $\pm 8.43\text{e-}04$	1.621e+04 $\pm 1.109\text{e+}04$	2994 ± 1.129	266.8 ± 3.698	2.25e-08 $\pm 5.77\text{e-}08$	3.372 ± 1.118
L-SHADE	1.725 $\pm 7.00\text{e-}16$	0.01267 $\pm 2.38\text{e-}05$	5798 ± 31.37	2994 $\pm 6.27\text{e-}13$	263.9 $\pm 5.68\text{e-}14$	5.82e-11 $\pm 1.65\text{e-}10$	1.34 ± 0
CMA-ES	1.725 $\pm 2.02\text{e-}15$	0.01267 $\pm 8.98\text{e-}06$	5788 ± 0.1058	2994 $\pm 4.55\text{e-}13$	263.9 $\pm 5.96\text{e-}14$	9.38e-10 $\pm 1.39\text{e-}09$	1.34 ± 0




Figure 12: Median convergence on the seven engineering design problems (30 runs, semi-log scale).

The two competition-grade methods lead this suite as they do the synthetic ones. L-SHADE takes the best mean Friedman rank at 1.57, beating CA significantly on all seven problems, and CMA-ES is second at 2.14, beating CA on six with one statistical tie on the gear train, where CA's mean is in fact fractionally lower. The terminal precision these two reach is instructive. L-SHADE attains the welded-beam literature optimum of 1.72485 with a run-to-run standard deviation below 10^{-15} , and reproduces the best-known speed-reducer, three-bar-truss and cantilever-beam values with essentially zero variance across all thirty runs. On this problem class, success-history parameter adaptation behaves as a reliable constrained refinement engine, and that level of terminal accuracy is one CA's fixed-rate probes do not reach. On the pressure vessel, both

methods also descend below the literature reference value, which is admissible: the commonly cited 5,885.33 applies to the mixed-integer formulation in which two thicknesses are multiples of 0.0625 in, whereas the continuous relaxation solved here, by every algorithm in the roster identically, admits lower objectives.

Among the remaining six algorithms, CA is the best ranked at 3.71, ahead of CA-static at 4.14, GWO at 5.00, PSO at 5.71, GA at 6.14, and WOA at 7.57. Against that classical roster CA loses exactly once across 35 pairwise comparisons, to PSO on the welded-beam problem, where PSO’s near-zero run-to-run variance around the known optimum, 1.7251 ± 0.0010 , is difficult for any method that retains meaningful exploration to match on a low-dimensional, well-conditioned landscape. One further observation deserves note. WOA under the default hyperparameters of `mealpy` is dramatically unstable on several of these constrained problems: its mean objective on welded beam is 172.6, two orders of magnitude above the optimum of 1.725, driven by a small number of catastrophically infeasible runs (top-left panel of Figure 12). Default hyperparameters tuned for unconstrained synthetic benchmarks do not automatically transfer to constrained, penalty-shaped landscapes.

7. Component, Parameter, and Cost Analysis

The preceding sections treat CA as a unit. This one takes it apart and asks which of its mechanisms carry the performance (Section 7.1), how sensitive that performance is to the parameter configuration of Table 3 (Section 7.2), and what the algorithm actually costs in evaluations and wall-clock time (Section 7.3). An algorithm with twelve named mechanisms invites the objection that most of them are ornamental. The measurements below answer that objection directly, and several of the answers are unflattering to individual components, which is what makes the remaining ones worth believing.

7.1. Granular ablation

Each of the twelve strategic mechanisms of Section 2 is disabled one at a time, with all other mechanisms held at their published defaults, and each single-mechanism-off variant is compared against full CA over 30 runs on six problems spanning the paper: CEC-2017 F1 (Bent Cigar), F4 (Rastrigin), F13 (Hybrid 4), and F22 (Composition 3) at $D = 30$ under the suite protocol and seeds of Section 4, the welded-beam problem under the protocol of Section 6, and the berth allocation problem P2 under the protocol of Section 9. Table 24 reports, for each mechanism, the ratio of the ablated variant’s mean final error to full CA’s, averaged over the six problems, together with the number of problems on which the difference is statistically significant. The per-problem breakdown is Table 36.

Table 24: Granular ablation: each mechanism disabled in isolation, mean final-error ratio relative to full CA averaged over six problems (ratios above 1 indicate the mechanism helps), with Wilcoxon significance counts at $\alpha = 0.05$.

Mechanism disabled	Mean error ratio (ablated / full CA)	Significant on (of 6 problems)
En passant (success-rule local capture)	603.3	5
Knight’s fork	46.842	5
Threefold repetition	1.213	3
Sacrifice	1.070	0
Pinning	1.050	0
Windmill	1.043	0
Opposition-based initialization	1.030	1
Discovered attack	1.024	0
Blockade response	1.006	0
Novotny interference	0.999	0
Castling	0.999	0
Royal council	0.990	3

Two mechanisms carry most of the load, and they are not of equal kind. Disabling the en-passant capture, the success-rule local refinement of Equation 12, degrades the mean error by a factor of roughly 600 averaged over the six problems, dominated by a factor of 3.6×10^3 on Bent Cigar, and the degradation is significant on five of six problems including the welded beam (+1.9%, $p = 0.003$). CA’s terminal accuracy on smooth or




Figure 13: Mechanism contribution: (a) mean final-error ratio with each mechanism disabled, (b) the same ratio per problem for the two load-bearing mechanisms.

locally smooth landscapes rests essentially on this one mechanism. Disabling the knight’s fork, the differential move of Equation 20, costs a factor of 47 on the same average and a factor of 274 on Bent Cigar, significant on the same five problems; the fork is CA’s principal rotation-invariant recombination device.

The remaining ten mechanisms measure small individually. Threefold repetition averages a ratio of 1.21, significant on three problems but with mixed sign, protective on Bent Cigar and Rastrigin and marginally harmful on the composition function. The royal council is significantly *helpful* only on the welded beam, where removing it costs 2.9%, while being significantly harmful to retain on two synthetic functions, which is consistent with its design purpose, the constraint-valley geometry of Equation 22, and suggests constraint-conditional gating as a refinement. The other eight (sacrifice, pinning, windmill, opposition initialization, discovered attack, blockade, interference, castling) sit between 0.99 and 1.07 with at most one significant problem each. One caveat applies to all these small ratios: a one-at-a-time ablation measures each mechanism’s marginal contribution in the presence of all the others, so mechanisms with overlapping function can each look dispensable even when they are not collectively so. The CA-static configuration, which disables the adaptive gating of every mechanism at once and is carried through every experiment in this paper, supplies the complementary joint measurement.

Beyond the numbers themselves, the identity of the two load-bearing mechanisms is the most consequential finding in this evaluation, because it ties Table 4 to the benchmark tables. En passant belongs to the success-rule step-size family of Evolution Strategies; the fork belongs to the differential-mutation family of Differential Evolution. The two algorithms that dominate every comparison in Section 4, Section 5, and Section 6, CMA-ES and L-SHADE, are precisely the competition-refined members of those same two families, equipped with full adaptive machinery, covariance adaptation in one case and success-history adaptation with population reduction in the other, where CA fires fixed-rate, fixed-shape versions embedded in its role architecture. The expectation formulated at the end of Section 2.8 is therefore confirmed, not just illustrated. CA’s measured performance rests chiefly on its ES-like and DE-like components, and the specialized algorithms built purely on those components, with adaptation in place of fixed rates, outperform the composition that borrows them. This is at once an honest account of why CA does not beat the modern state of the art and a mechanism-level demonstration that the architecture’s active ingredients are real, identifiable, and correctly attributed.

7.2. Parameter sensitivity

A one-at-a-time sensitivity analysis perturbs each parameter group of Table 3 around the published default configuration, with role fractions bracketed low and high, $\theta_0 \in \{0.05, 0.2\}$, castling period $c \in \{5, 20\}$, blockade threshold in $\{15, 40\}$, and pinning cap in $\{0.15, 0.50\}$, on the same six problems and run protocol as Section 7.1. Table 25 reports each variant’s mean-error ratio relative to the default configuration, and Figure 14 shows the same quantity with its per-problem range. The phase thresholds δ_{open} and δ_{end} of Equation 17 are not re-swept here; the four-combination check reported in Section 2.6 stands.

Table 25: One-at-a-time parameter sensitivity: mean final-error ratio of each perturbed configuration relative to the default, averaged over six problems, with the number of problems deviating by more than twenty percent and the number of statistically significant deviations.

Parameter variant	Mean error ratio (variant / default)	> 20% deviation on (of 6)	Significant on (of 6)
Role fractions (.15/.20/.20/.25)	0.886	2	3
$\theta_0 = 0.2$	0.966	1	0
Castling period $c = 20$	0.978	2	0
Blockade threshold = 15	0.979	0	0
$\theta_0 = 0.05$	0.992	1	0
Pin cap = 0.15	0.993	0	0
Blockade threshold = 40	1.004	0	0
Pin cap = 0.50	1.007	0	0
Castling period $c = 5$	1.085	1	0
Role fractions (.05/.10/.10/.15)	13.410	3	5




Figure 14: Parameter sensitivity profile: mean final-error ratio of each perturbed configuration to the default, with the per-problem range. Filled markers are significant.

The pattern is sharp. Of sixty tested (variant, problem) cells, all eight statistically significant deviations belong to the role-fraction rows, and no other parameter produces a significant change on any problem, with mean ratios within ten percent of unity throughout. At the granularity tested, CA is robust to its sacrifice constant, castling period, blockade threshold, and pinning cap, so a practitioner does not need to tune them,

while the division of the population among piece roles is the one structural choice that matters. Its direction is informative in both senses. Shrinking the elite roles, which means more pawns, is harmful, catastrophically so on Bent Cigar with a factor of 73, where the elite ranks supply nearly all the useful moves. Enlarging them is *beneficial* on several problems, with a mean ratio of 0.89 and a significant improvement on three. The published default of Table 3, fixed in advance and used unchanged for every result in this paper, is therefore demonstrably not optimal everywhere. We report that headroom rather than exploit it: no result elsewhere in the paper uses the improved fractions.

Because the design is one-at-a-time, these are local sensitivities around a single configuration and not a global sensitivity analysis, so interactions between parameters remain unmeasured.

7.3. Computational cost

Cost here is measured rather than estimated. An exact counting wrapper intercepts every objective call, and wall-clock time is taken with a monotonic timer over ten runs per cell on an otherwise idle machine, for all eight algorithms on six problems spanning the paper: CEC-2017 F1, F13 and F22 at $D = 30$, CEC-2022 F8 at $D = 20$, the welded beam, and signal timing P1 at its own $T = 300$ protocol. Table 26 reports mean seconds per run for each algorithm on each problem, together with the mean ratio of evaluations consumed to the $N \times T$ core budget and the mean time relative to GA. The per-problem evaluation counts behind those two averages are in Table 37.

Table 26: Measured wall-clock time (mean seconds per run, ten runs per cell on an idle machine), with two summary columns averaged over the six timed problems. “Evals / core budget” is the ratio of consumed evaluations to $N \times T$, counted exactly by a wrapper intercepting every objective call.

Algorithm	CEC17 F1	CEC17 F13	CEC17 F22	CEC22 F8 (D20)	Welded beam	Signal P1	Evals / core budget	Time vs GA
CA	0.31	0.88	1.70	11.64	0.30	0.63	1.124	1.95
CA-static	0.31	0.82	1.85	11.79	0.30	0.58	1.116	1.91
GWO	0.09	0.54	1.35	12.05	0.05	0.19	1.002	0.83
PSO	0.08	0.53	1.41	10.02	0.04	0.19	1.002	0.76
GA	0.14	0.62	1.43	10.39	0.10	0.23	1.002	1.00
WOA	0.56	1.17	1.94	10.96	1.39	5.80	1.002	7.92
L-SHADE	1.61	2.08	3.05	11.55	1.75	6.71	1.037	10.81
CMA-ES	1.06	1.72	2.35	10.56	0.39	0.75	0.933	3.36

Three facts summarize the table. The first is CA’s evaluation overhead, that is the en-passant probes, castling probes, windmill extensions and blockade responses documented throughout Section 2, which measures 12.4% over the core budget on average, ranging from 11.4 to 13.4% across the six problems, with CA-static at 11.6%. That measured figure replaces the “ten to fifteen percent” estimate quoted in earlier drafts. The second is that the budget asymmetry runs *against* the two strongest competitors: L-SHADE is capped at 3.3% over core, and CMA-ES consumes at most exactly the core budget, stopping at sixty percent of it on the welded beam once its stagnation tests reach the numerical-precision floor. The results of Section 4 through Section 6 therefore cannot be attributed to an evaluation-budget advantage held by the winners; the only algorithm holding such an advantage in those tables is CA itself, and it is disclosed and measured. The third concerns wall-clock time, which depends on what dominates the run. On the cheapest objective CA costs about $2.2\times$ GA’s time per run, reflecting the per-iteration bookkeeping of the control layer, whereas on the most expensive objective tested, CEC-2022 F8 at $D = 20$, where a single evaluation costs roughly forty times more than on Bent Cigar, all eight algorithms fall within about fifteen percent of one another. For expensive objectives, which are the practically interesting case, the choice among these algorithms is a choice about evaluations, not about control-layer arithmetic.

7.4. Where CA stands

The three suites of Section 4, Section 5, and Section 6 were run under one roster and one protocol, so their Friedman ranks can be read side by side. Figure 15 does that, and it is the compact form of this paper’s central empirical claim. The ordering is the same on all three suites and admits no qualification: L-SHADE

and CMA-ES lead, CA follows as the best of the remaining six, and CA-static sits just behind it. CA’s position is therefore neither a sweep nor a failure, and the ablation of Section 7.1 explains why it is where it is, since CA’s two load-bearing operators are fixed-rate members of exactly the two families those two methods specialize in and adapt fully.




Figure 15: Mean Friedman rank of each algorithm (lower is better) on the three suites run under the same eight-algorithm roster and protocol.

Two qualifications belong with the figure. It compares mean ranks, which compress the per-function records of Table 11, Table 19, and Table 22, so that CA’s ten losses to GA on CEC-2017 are invisible in a mean rank that GA nonetheless trails. And a rank is relative to the roster: adding or removing an algorithm changes every rank in the figure, which is why the pairwise Wilcoxon records are reported alongside it throughout the paper rather than in place of it. The classical six-function suite of Section 3 is absent from the figure because it was run under a different roster, including SA and excluding WOA, L-SHADE, and CMA-ES.

8. Transportation Application: Arterial Signal Coordination

8.1. Problem statement and model

Coordinated fixed-time signal timing along an urban arterial is a classic of transportation network optimization, and a deceptive one. The objective surface is multimodal, because different offset combinations produce different locally good green waves. The variables are of mixed kinds: a common cycle, per-intersection splits and offsets. The delay model is nonlinear and, in practice, non-differentiable [1, 33]. It is therefore a natural first engineering test for CA.

Our test bed is an eight-intersection arterial with spacings of 450, 380, 520, 300, 610, 420, and 350 m, a progression speed of 50 km/h, near-saturation two-way traffic with eastbound approach demands between roughly 1,240 and 1,400 veh/h, and conflicting cross-street demands at every junction (Figure 16). Each intersection runs a two-phase plan.

The decision vector is

$$\mathbf{z} = (C, g_1, \dots, g_8, o_2, \dots, o_8) \in \mathbb{R}^{16}, \quad (28)$$




Figure 16: Layout of the eight-intersection arterial test bed.

with a common cycle length $C \in [60, 140]$ s, arterial green splits $g_i \in [0.30, 0.75]$, and offsets o_i expressed as fractions of the cycle, intersection 1 serving as reference. Figure 17 shows which physical object each of the sixteen variables controls. Panel (a) locates the variables on the arterial; panel (b) shows how the offsets displace each local green window in time, so that a platoon leaving one window arrives at the next either inside its green or after it. Because the arterial carries platoons in both directions, offsets that perfect one direction damage the other, and that is where the multimodality of coordination problems comes from. The objective is total network delay in $\text{veh} \cdot \text{h/h}$, built from three ingredients.




Figure 17: From the arterial to the decision vector: (a) the physical object controlled by each of the sixteen variables, (b) how offsets shift the green windows seen by a platoon.

The first is uniform delay per approach, Webster's first term [34]:

$$d_1 = \frac{C(1-g)^2}{2(1 - \min(1, x)g)}, \quad (29)$$

where g is the effective green ratio and $x = v/c$ the volume-to-capacity ratio. The second is overflow delay from the HCM time-dependent formulation [33]:

$$d_2 = 900 T_a \left[(x - 1) + \sqrt{(x - 1)^2 + \frac{8 k I x}{c T_a}} \right], \quad (30)$$

with analysis period $T_a = 0.25$ h, incremental delay factor $k = 0.5$, and upstream filtering factor $I = 1$. The third is a progression adjustment: platoons arriving from upstream are shifted by the offset difference minus the travel time, and the mismatch between platoon arrival and the local green window scales the uniform delay up or down, per direction.

Cross-street phases receive $1 - g_i$, less 4 s lost time per phase, and contribute their own delay, so greedy arterial splits are punished through cross-street oversaturation. All terms are summed over the sixteen arterial approaches and the eight cross-street approaches.

8.2. Results

CA, CA-static (Section 2.6), GA, PSO, and GWO run with $N = 30$, $T = 300$ iterations, that is 9,000 core evaluations, and 30 independent runs each, again without tuning. These are the three strongest baselines of Section 3 together with CA and its ablation; SA is dropped here given its uncompetitive showing in Section 3. Table 27 summarizes the final delays together with the pairwise tests, and Figure 18 and Figure 19 show the convergence behaviour and the spread across runs.

Table 27: Final total delay over 30 runs on the arterial signal timing problem, with the two-sided Wilcoxon rank-sum test of each algorithm against CA ($\alpha = 0.05$). Best mean in bold. Because this section evaluates a single problem instance, the algorithms are already the rows and the statistics are the columns.

Algorithm	Mean delay $\pm$ std (veh $\cdot$ h/h)	Best	Worst	p vs CA	Outcome
CA	169.963 $\pm$ 4.87131	166.525	179.149	–	–
CA-static	170.827 $\pm$ 5.07249	166.525	178.533	6.249e-02	not significant
GWO	170.506 $\pm$ 2.81774	166.739	177.987	1.471e-02	CA better
PSO	169.491 $\pm$ 3.66617	166.526	179.946	3.089e-02	CA worse
GA	171.16 $\pm$ 4.89468	166.526	178.47	2.002e-03	CA better

All five configurations land within about one percent of each other in mean delay, between 169.5 and 171.2 veh $\cdot$ h/h, yet at this scale most of the differences are still resolvable. CA is significantly better than GA ($p = 0.002$) and GWO ($p = 0.015$), statistically tied with its own ablation CA-static ($p = 0.062$), and significantly *worse* than PSO ($p = 0.031$), whose mean delay of 169.491 is the lowest in the table. That last comparison is the one result of this section unfavourable to CA, and we report it as such.

On the best-solution metric the ranking reverses. CA and CA-static both reach 166.5254 veh $\cdot$ h/h, the lowest value found by any method, fractionally ahead of the best runs of GA and PSO at 166.526 and clearly ahead of GWO’s 166.739. CA’s operators are therefore fully capable of locating the same high-quality coordination plan as the strongest baselines, even where its mean is higher than PSO’s.

The most instructive pattern, though, is that the classical-suite ranking of Section 3 does not carry over here at all. GWO, which dominated that suite, is the worst mean performer of the five on this problem. This is a clean within-paper illustration of the No-Free-Lunch theorem [17], and it is the reason we resist describing any of these results as a sweep.




Figure 18: Median convergence on the arterial signal timing problem.




Figure 19: Distribution of final delays over 30 runs.

The best plan discovered, found by CA, selects the minimum cycle $C = 60$ s, which is a sensible choice under Webster’s guidance whenever splits can be kept efficient, with the timings of Table 28 drawn as a time-space diagram in Figure 20.

Table 28: Best signal timing plan found (CA).

Parameter	Value
Cycle length C	60.0 s
Arterial green split g_1	0.633 (38.0 s)
Arterial green split g_2	0.529 (31.7 s)
Arterial green split g_3	0.667 (40.0 s)
Arterial green split g_4	0.498 (29.9 s)
Arterial green split g_5	0.624 (37.4 s)
Arterial green split g_6	0.540 (32.4 s)
Arterial green split g_7	0.678 (40.7 s)
Arterial green split g_8	0.493 (29.6 s)
Offset o_2	32.4 s
Offset o_3	59.8 s
Offset o_4	37.2 s
Offset o_5	58.8 s
Offset o_6	42.7 s
Offset o_7	13.0 s
Offset o_8	38.2 s
Total delay	166.525 veh · h/h




Figure 20: Time-space representation of the best plan found by CA.

The offsets form a coherent progression pattern in which consecutive intersections alternate between favouring the eastbound and the westbound platoon, which is the compromise structure one expects on a heavily loaded two-way arterial.

8.3. Practical remarks

For a transportation agency, the practical implication is that CA can be applied to signal-coordination studies with the same confidence as GA, PSO, or GWO, and that it offers two features of practical relevance. The sacrifice mechanism gives a principled way of escaping a poor offset basin without restarting the search,

and the en-passant refinement improves the precision of splits and offsets late in the run without a separate local-search stage. Extension to cycle-by-cycle stochastic simulation objectives, with VISSIM or SUMO in the loop, is straightforward, since CA requires only function values. The comparison against PSO deserves explicit attention: on this particular sixteen-variable periodic-offset landscape, the velocity-based search of PSO holds a genuine if small advantage in mean delay, and an agency choosing between the two on this problem class alone should not assume that CA will win by default. The case for CA rests on the broader evidence of Section 4 and Section 6 rather than on this single instance.

9. Extended Comparison on Independent Implementations

Every baseline in Section 3 and Section 8 was implemented by the present authors, in the same code style and the same array-vectorized idiom as CA itself. That is ordinary practice, but it leaves open the question of whether CA stays competitive against code written by somebody else. We therefore repeat the transportation comparison using `mealpy` [35], a large and actively maintained third-party Python library that ships several hundred metaheuristic variants behind a common `solve(problem, seed=...)` interface. Six well-known algorithms were run exactly as `mealpy` ships them, with default hyperparameters and no modification, on two transportation problems, the second of which has a global optimum known in closed form.

The six competitors are the Whale Optimization Algorithm (WOA) [14], the Sine Cosine Algorithm (SCA) [15], the Ant Lion Optimizer (ALO) [12], Moth-Flame Optimization (MFO) [36], Harris Hawks Optimization (HHO) [37], and Differential Evolution (DE) [9]. The two competition-grade baselines of Section 4, L-SHADE via `niapy` [29] and CMA-ES via `pycma` [30], are carried into both problems as well, so the transportation instances face the same strongest competitors as the synthetic suites. All methods search the identical unit hypercube, with problem-specific bounds folded into the decoding step rather than passed to the optimizers, so no algorithm gets an easier space than another. Every algorithm runs with population 30 for 300 iterations across 30 independent runs, run r of every algorithm seeded identically at $\text{SEED}_0 + r$; the evaluation-budget accounting of Section 7.3 applies here in the same proportions, with 9,000 core evaluations and L-SHADE capped at 9,500.

9.1. Problem P1: the arterial signal timing instance

This is the same sixteen-variable coordination problem as in Section 8. Table 29 reports the summary statistics and the left panel of Figure 21 the median convergence.

Table 29: CA versus six mealpy algorithms and the two competition-grade baselines on the arterial signal timing problem (P1).

Algorithm	Mean	Std	Best	Worst	p-value (vs CA)	Result ($\alpha = 0.05$)
CA	169.963	4.871	166.525	179.149	—	—
WOA	199.357	21.475	172.715	281.873	7.762e-11	CA better
SCA	174.006	2.307	171.044	180.683	2.962e-03	CA better
ALO	173.684	5.201	167.413	187.575	1.086e-03	CA better
MFO	179.765	5.849	169.539	189.142	1.306e-07	CA better
HHO	192.375	18.304	173.106	260.020	5.317e-10	CA better
DE	196.222	11.382	173.619	222.264	9.445e-11	CA better
L-SHADE	167.802	3.191	166.525	176.446	3.093e-04	CA worse
CMA-ES	167.151	1.868	166.525	176.446	1.054e-02	CA worse

CA is significantly better than every one of the six `mealpy` competitors, including SCA and ALO, its closest rivals in that group, at $p = 0.003$ and $p = 0.001$ respectively. WOA, HHO, and DE perform substantially worse and vary far more from run to run, with standard deviations of 11 to 21 veh · h/h against 4.9 for CA, which suggests that they find it harder than CA does to re-locate a good coordination plan reliably in the sixteen-dimensional periodic offset space. The two competition-grade baselines invert the comparison, as they do everywhere in this paper: L-SHADE at 167.80 and CMA-ES at 167.15 both hold significantly better mean delays than CA at 169.96, by margins of 1.3 to 1.7 percent, and all three methods reach the same best-of-thirty plan at 166.525 veh · h/h. The scope of this result is worth stating precisely. GA and

PSO, our own implementations from Section 8, perform comparably to CA on this problem (Table 27), so the conclusion is not that CA is uniquely strong on signal timing, but that its standing among widely used algorithms survives a change of author, while the specialized adaptive methods keep a small and statistically resolvable advantage in mean delay.

9.2. Problem P2: continuous berth allocation with a known optimum

Independent implementations address one concern; a problem with a *known* optimal value addresses another, namely whether an algorithm’s apparent superiority is an artifact of comparing relative suboptimality on a problem that none of the competitors can solve. We borrow Example 1.9 of Teodorović and Janić [38]: fifteen ships of known length, arrival time, and required service time must be assigned mooring times and berth positions along a continuous 1,000 m quay within a 1,920-minute horizon, so as to minimize total time spent in port. With unit weights, the mixed-integer formulation in the source has a trivial global optimum, since every ship can moor the instant it arrives and wait for nothing:

$$F^* = \sum_{i=1}^{15} p_i = 4,860 \text{ min.}$$

Reaching that bound requires the ship-pair schedule to be conflict-free along the time axis and the quay-position axis at once, which is a combinatorial matching problem embedded in a continuous one, and that is what makes the instance a substantive test for a population-based search. We encode each ship’s mooring time $u_i \in [a_i, T - p_i]$ and berth position $v_i \in [0, S - s_i]$ as decision variables and penalize, rather than hard-constrain, the pairwise rectangle overlap in the time-space diagram, so that the search can pass through momentarily infeasible plans on its way to a good one. This is the same soft-constraint treatment already used for cross-street oversaturation in Section 8.

Table 30: CA versus six mealpy algorithms and the two competition-grade baselines on the continuous berth allocation problem (P2), objective in minutes.

Algorithm	Mean	Std	Best	Worst	p-value (vs CA)	Result ($\alpha = 0.05$)
CA	7934.2	973.8	6277.9	10257.8	—	—
WOA	45507.4	21345.8	9388.5	93564.7	3.879e-11	CA better
SCA	34567.6	9683.6	19217.2	57890.7	2.872e-11	CA better
ALO	9912.0	3544.1	7345.0	27033.0	2.320e-04	CA better
MFO	21914.8	12102.4	9112.4	52125.0	4.734e-11	CA better
HHO	48415.6	25410.2	12102.0	133361.1	2.872e-11	CA better
DE	25765.7	12631.0	9768.9	54967.4	3.879e-11	CA better
L-SHADE	6269.1	688.6	5283.7	8712.7	1.256e-08	CA worse
CMA-ES	6521.8	537.5	5424.7	7620.9	1.204e-07	CA worse

Table 30 reports the results. Against the mealpy group CA’s advantage grows considerably on this problem: its mean objective is roughly a sixth of WOA’s or HHO’s, and it is significantly better than all six, ALO included at $p = 2.3 \times 10^{-4}$, which is otherwise its nearest rival in that group by a wide margin. The right panel of Figure 21 shows why. Among the seven methods plotted, CA and ALO are the only two that keep making progress past iteration 50, while WOA, SCA, MFO, HHO, and DE largely plateau within the first fifty. The two competition-grade baselines again lead: the means of L-SHADE at 6,269 and CMA-ES at 6,522 are both significantly better than CA’s 7,934, this time by the widest relative margins observed anywhere in this paper outside the synthetic suites, 18 to 21 percent in mean objective.

The distance of even the best runs from $F^* = 4,860$ should be stated explicitly. Table 31 gives the optimality gap of each algorithm’s best run together with the residual overlap of its decoded plan.





Figure 21: Median convergence on the two transportation problems over 30 runs. The berth-allocation panel marks the known global optimum.

Table 31: Optimality gap and feasibility of the best plan found by each algorithm on P2.

Algorithm	Best objective (min)	Gap to optimum	Overlap of best plan (min · m)
CA	6277.9	29.17%	0.0
WOA	9388.5	93.18%	878.9
SCA	19217.2	295.42%	11752.0
ALO	7345.0	51.13%	0.0
MFO	9112.4	87.50%	1873.6
HHO	12102.0	149.01%	1963.4
DE	9768.9	101.01%	0.0
L-SHADE	5283.7	8.72%	0.5
CMA-ES	5424.7	11.62%	0.0

CA’s best run sits 29% above the true optimum, which is a substantial gap and we state it without obfuscation. Three aspects of the table deserve separate comment. The smallest gaps belong to the competition-grade methods: L-SHADE reaches 8.7%, with a numerically negligible residual overlap of 0.5 min · m in its best plan, and CMA-ES 11.6% on a fully feasible plan. These are the closest any general-purpose method in this study comes to the combinatorial optimum, and they show that the instance rewards stronger adaptive machinery rather than being uniformly hard. Among the seven remaining methods, CA’s gap is the smallest by a considerable margin, 22 to 266 percentage points closer to F^* than the six meaply competitors and 22 points ahead of ALO, its nearest rival there. The overlap column shows that CA’s best plan is fully feasible, so ships do not actually collide in the time-space diagram, which is not true of WOA, SCA, MFO, or HHO, whose reported objectives still carry unresolved penalty mass; ALO and DE also land on feasible plans, but at much larger gaps. Figure 22 shows CA’s best schedule. Every ship occupies its own rectangle with no overlap, but several ships wait appreciably longer than their arrival time, and that waiting time is the whole of the remaining 29% gap.



allocation to global optimality; a 29% gap remains, against 9 to 12% for the two specialized methods, and the problem plainly deserves algorithms tuned to its combinatorial structure rather than any general-purpose search evaluated here.

10. Conclusion

This paper proposed the Chess Algorithm, a population-based metaheuristic built around a deliberately heterogeneous population. Agents are ranked at every iteration and play as Queens, Rooks, Bishops, Knights and Pawns around an elite King, each role moving under its own geometry, while strategic mechanisms taken from chess theory (development, sacrifice, pinning, castling, en passant and threefold repetition) govern the search throughout. A lightweight state machine reads the divergence, initiative and local-search success of the population at each iteration and decides which of a richer tactical set applies at that moment. Every mechanism is specified mathematically in Section 2, and Table 4 names the established operator family to which each belongs, so that the chess vocabulary describes the composition without standing in for it. A non-adaptive configuration, CA-static, was carried through every experiment as a control.

The experimental picture is consistent across five problem families. On six classical 30-dimensional functions, CA is significantly better than PSO and SA on all of them and better than GA on five of six, while GWO keeps its established advantage on that suite. On the 29 validated CEC-2017 functions, on the 16 validated CEC-2022 cells and on seven constrained engineering design problems, CA obtains the best mean Friedman rank among the classical and widely used baselines, losing one comparison in 29 to each of GWO and PSO on CEC-2017 and exactly one of 35 comparisons on the engineering problems. On the arterial signal timing problem it is significantly better than GA and GWO and reaches the lowest delay found by any method, and on berth allocation it is significantly better than all six independent `mealpy` implementations. In every one of these comparisons L-SHADE and CMA-ES rank ahead of CA, and that result is reported without qualification.

The ablation of Section 7.1 explains this ordering instead of just recording it. Of the twelve strategic mechanisms, two carry most of the measured performance: the en-passant capture, which is a success-rule step-size adaptation, and the knight’s fork, which is a differential mutation. L-SHADE and CMA-ES are the competition-refined members of exactly those two families, with full adaptation where CA fires fixed rates. The algorithms that beat CA are therefore the specialists built on CA’s own load-bearing components, which is a more useful finding than the ranking on its own.

The boundaries of the evidence deserve to be stated as plainly as the results. Dimensions above 30, or above 20 on CEC-2022, were not tested. CA consumes 12.4% more evaluations than the shared core budget (Section 7.3), a small but real cost that does not favour it against L-SHADE at 3.3% or against CMA-ES. The transportation studies use analytic delay and penalty models rather than microsimulation. The ablation and sensitivity analyses cover six representative problems, and the two phase thresholds were checked on two functions rather than swept exhaustively. Finally, CA loses ten of the 29 CEC-2017 functions to GA, and those ten cluster on landscapes whose basins lie as far apart as the search domain is wide, where the BLX- α crossover of GA can cross the whole domain in a single step and no CA operator can.

That last gap points to the most natural extension. A promotion operator, in which an agent that survives several blockade events without improving the King is granted a macro-crossover against a distant population member for one iteration, would give CA the long-range move it currently lacks, much as a pawn reaching the eighth rank does not improve gradually but changes in kind. A second and more direct line follows from the ablation: replacing the fixed adaptation rates of en passant and the knight’s fork with success-history or covariance adaptation is now a specific and testable hypothesis about closing the gap to L-SHADE and CMA-ES rather than a speculative one. Binary, discrete and multi-objective variants of CA, a formal analysis of the en-passant rule as a $(1 + \lambda)$ evolution strategy embedded in a population method, and simulation-based transportation objectives are further directions we intend to pursue.

CRediT authorship contribution statement

Seyedsaber Naseralavi: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Visualization, Writing – original draft, Writing – review & editing. **Seyedali Mirjalili:** Conceptualization, Methodology, Writing – review & editing, Supervision.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Declaration of generative AI and AI-assisted technologies in the writing process

During the preparation of this work the authors used a large language model assistant to support code review, manuscript copy-editing and the preparation of figures and tables from committed result files. The authors reviewed and edited the content as needed and take full responsibility for the content of the published article.

Data and code availability

All source code, experiment scripts, results, and manuscript sources are openly available at the project repository, github.com/sabernaseralavi-60/2026_Chess-Algorithm, whose `README.md` documents every script and the order in which it must be run to reproduce each table and figure in this paper. Random seeds are fixed throughout, and every number reported here corresponds exactly to a committed output in the repository. The two data-integrity audits of Section 4.2 and Section 5 are reproducible rather than asserted: the raw statistics behind each exclusion are committed alongside the validated results, so a reader can re-run the same checks against a newer release of the underlying benchmark libraries rather than take our exclusion lists on faith.

Appendix A: Supplementary tables

The primary comparison tables of Section 3 through Section 7 report the mean and standard deviation of each algorithm–problem cell, in the orientation with algorithms as rows and test functions as columns. The best and worst individual runs, and the per-problem detail of the ablation and cost analyses, do not fit that orientation and are collected here rather than dropped. Every cell of a primary table has its counterpart in exactly one table below; the correspondence is checked numerically by `src/validate_presentation.py`, and both are generated from the same committed result files.

Table 32: Classical suite, full statistics: mean, standard deviation, best, and worst final objective over 30 runs, per function and algorithm (best mean per function in bold). The mean and standard deviation columns are those of Table 6.

Function	Algorithm	Mean	Std	Best	Worst
Sphere	CA	6.159e-05	1.152e-04	2.149e-07	4.760e-04
Sphere	CA-static	4.630e-06	4.253e-06	2.111e-07	1.572e-05
Sphere	GA	9.475e-02	5.399e-02	2.890e-02	2.946e-01
Sphere	PSO	8.455e-01	7.216e-01	1.194e-01	3.131e+00
Sphere	SA	1.013e+04	2.218e+03	6.628e+03	1.612e+04
Sphere	GWO	4.678e-31	8.194e-31	6.431e-33	3.925e-30
Rosenbrock	CA	7.756e+01	4.383e+01	2.431e+01	1.912e+02
Rosenbrock	CA-static	5.513e+01	3.969e+01	7.695e+00	1.414e+02
Rosenbrock	GA	1.056e+02	4.633e+01	2.895e+01	2.863e+02
Rosenbrock	PSO	6.445e+03	2.238e+04	8.896e+01	9.021e+04
Rosenbrock	SA	2.185e+07	5.693e+06	7.615e+06	3.486e+07
Rosenbrock	GWO	2.683e+01	6.174e-01	2.592e+01	2.796e+01
Rastrigin	CA	1.953e+01	8.020e+00	7.960e+00	4.477e+01
Rastrigin	CA-static	1.924e+01	4.897e+00	9.951e+00	3.383e+01

Function	Algorithm	Mean	Std	Best	Worst
Rastrigin	GA	1.954e+01	6.823e+00	1.008e+01	4.187e+01
Rastrigin	PSO	5.971e+01	1.484e+01	3.306e+01	9.545e+01
Rastrigin	SA	2.105e+02	2.951e+01	1.598e+02	2.553e+02
Rastrigin	GWO	1.023e+01	1.078e+01	5.684e-14	4.680e+01
Griewank	CA	8.177e-03	7.777e-03	2.282e-05	2.473e-02
Griewank	CA-static	1.123e-02	1.143e-02	1.617e-05	3.705e-02
Griewank	GA	2.816e-01	7.971e-02	1.217e-01	4.364e-01
Griewank	PSO	6.164e-01	2.367e-01	2.902e-02	1.025e+00
Griewank	SA	9.190e+01	2.324e+01	4.826e+01	1.563e+02
Griewank	GWO	4.303e-03	9.094e-03	0.000e+00	3.591e-02
Ackley	CA	6.049e-02	3.189e-01	1.561e-04	1.778e+00
Ackley	CA-static	3.902e-02	2.073e-01	1.508e-04	1.155e+00
Ackley	GA	7.757e-02	1.486e-02	4.767e-02	1.099e-01
Ackley	PSO	1.045e+00	5.491e-01	8.837e-02	2.341e+00
Ackley	SA	4.483e+00	3.618e-01	3.807e+00	5.247e+00
Ackley	GWO	3.325e-14	4.369e-15	2.176e-14	4.308e-14
Schwefel 2.22	CA	1.554e-03	6.928e-04	3.858e-04	3.011e-03
Schwefel 2.22	CA-static	8.415e-04	3.824e-04	3.074e-04	1.562e-03
Schwefel 2.22	GA	7.438e-02	1.815e-02	4.451e-02	1.138e-01
Schwefel 2.22	PSO	7.941e-01	2.486e+00	3.962e-02	1.010e+01
Schwefel 2.22	SA	1.121e+07	2.877e+07	1.033e+03	1.180e+08
Schwefel 2.22	GWO	9.928e-19	9.462e-19	1.034e-19	4.919e-18

Table 33: CEC-2017, full statistics on all 29 validated functions: mean, standard deviation, best, and worst final error $f - f^*$ over 30 runs (best mean per function in bold). The mean and standard deviation columns are those of Table 12 through Table 17.

Func	Algorithm	Mean	Std	Best	Worst
F1	CA	3011	2587	197.2	1.223e+04
F1	CA-static	4186	4081	190.5	1.709e+04
F1	GWO	4.3781e+09	3.6738e+09	1.2942e+07	1.4000e+10
F1	PSO	2.3283e+09	2.5019e+09	6.4555e+05	9.9419e+09
F1	GA	2.4003e+05	1.4751e+05	2.947e+04	6.9702e+05
F1	WOA	8.4880e+09	4.3850e+09	2.2548e+09	2.3894e+10
F1	L-SHADE	5476	5088	86.8	1.951e+04
F1	CMA-ES	6069	6549	83.66	2.07e+04
F2	CA	107.7	204.6	0.06075	780.8
F2	CA-static	3.805	6.16	0.02656	24.72
F2	GWO	1.564e+04	1.178e+04	2454	4.541e+04
F2	PSO	2742	5215	113.1	2.82e+04
F2	GA	10.85	5.971	2.576	26.3
F2	WOA	5.175e+04	1.826e+04	2.045e+04	8.45e+04
F2	L-SHADE	0.001651	0.002849	1.5418e-05	0.0153
F2	CMA-ES	0.009239	0.02618	2.2054e-09	0.1215
F3	CA	107.8	43.4	22.7	198.6
F3	CA-static	99.03	39.97	16.04	177.3
F3	GWO	411.1	447.5	42.44	1871
F3	PSO	310.5	445.3	35.29	2096
F3	GA	86.67	50.25	31.86	202.1
F3	WOA	1416	750.8	479.5	3244
F3	L-SHADE	38.69	18.2	20.11	90.38
F3	CMA-ES	31.82	0.03087	31.81	31.98
F4	CA	228.9	42.15	133.3	327.4
F4	CA-static	212.5	55.14	121.7	391
F4	GWO	6084	4170	688.8	1.571e+04
F4	PSO	4978	3476	1089	1.357e+04
F4	GA	148	35.3	87.11	219.2
F4	WOA	2.64e+04	8785	1.119e+04	5.035e+04
F4	L-SHADE	151.3	44.19	97.74	297.3
F4	CMA-ES	29.55	25.34	13.15	161.7
F5	CA	42.36	7.978	28.05	59.72
F5	CA-static	41.98	9.663	22.17	70.16
F5	GWO	26.35	11.08	7.722	57.04
F5	PSO	22.16	9.454	7.286	51.02
F5	GA	33.29	15.85	9.368	81.4
F5	WOA	105.4	14.87	80.66	145.2
F5	L-SHADE	10.27	3.944	3.704	19.07
F5	CMA-ES	0.01966	0.04062	1.1329e-04	0.1859
F6	CA	273.9	75.94	149.4	428.3
F6	CA-static	231.5	47.18	153.4	324.8
F6	GWO	8.224e+04	1.1049e+05	1.011e+04	5.2492e+05
F6	PSO	1.9461e+05	1.7735e+05	2.719e+04	8.9813e+05
F6	GA	312.4	52.84	229.3	412.1

Func	Algorithm	Mean	Std	Best	Worst
F6	WOA	3.7174e+05	1.5982e+05	1.4091e+05	9.1497e+05
F6	L-SHADE	225.4	96.7	93.88	552.3
F6	CMA-ES	76.04	51.97	45.68	226.3
F7	CA	207.8	35.02	124	282
F7	CA-static	215.5	44.72	124	298
F7	GWO	377	140.5	111.9	604.1
F7	PSO	255	77.89	125.4	413
F7	GA	251.2	66.57	118	358
F7	WOA	846.4	130.5	649.5	1142
F7	L-SHADE	99.19	26.99	60.2	177
F7	CMA-ES	83.15	29.41	54	206
F8	CA	4.821	2.025	2.004	12.04
F8	CA-static	5.035	2.34	0.9982	9.215
F8	GWO	6.806	4.302	0.8538	19.03
F8	PSO	4.802	2.868	0.1875	10.58
F8	GA	7.657	3.671	1.908	18.69
F8	WOA	25.43	10.2	11.36	43.89
F8	L-SHADE	1.358	0.991	4.4074e-09	3.903
F8	CMA-ES	0.1453	0.263	0	0.9086
F9	CA	3823	642.9	2542	5012
F9	CA-static	3747	635.8	2168	4602
F9	GWO	6687	1963	2352	8579
F9	PSO	3984	918.3	2205	6060
F9	GA	3618	708	1778	4915
F9	WOA	6692	1134	4190	8676
F9	L-SHADE	2451	350.6	1794	3396
F9	CMA-ES	4191	2609	696.2	7817
F10	CA	2.232e+04	9882	8453	5.258e+04
F10	CA-static	2.353e+04	1.528e+04	2787	6.693e+04
F10	GWO	2.9010e+05	7.887e+04	1.5099e+05	4.7707e+05
F10	PSO	3.4876e+05	8.7568e+05	1.247e+04	3.7428e+06
F10	GA	2.328e+04	1.348e+04	3055	6.502e+04
F10	WOA	3.4194e+05	7.9388e+05	6.97e+04	4.5950e+06
F10	L-SHADE	2862	2210	712.3	1.016e+04
F10	CMA-ES	1.682e+04	3.168e+04	108.8	1.0958e+05
F11	CA	3.2870e+05	2.6355e+05	3.439e+04	1.0288e+06
F11	CA-static	5.8859e+05	6.3353e+05	3.506e+04	2.6364e+06
F11	GWO	1.3921e+08	2.6493e+08	4.3572e+06	1.1956e+09
F11	PSO	2.2279e+08	4.7394e+08	8.507e+04	2.2180e+09
F11	GA	5.292e+04	3.32e+04	1.273e+04	1.7377e+05
F11	WOA	4.7012e+08	7.0769e+08	2.6239e+07	3.1975e+09
F11	L-SHADE	1.989e+04	2.208e+04	3948	1.0511e+05
F11	CMA-ES	9.959e+04	1.0406e+05	1.079e+04	5.8073e+05
F12	CA	2.525e+04	4.452e+04	3121	2.3720e+05
F12	CA-static	3.129e+04	4.555e+04	5391	2.5447e+05
F12	GWO	1.0450e+08	4.9388e+08	6.1448e+05	2.7589e+09
F12	PSO	1.7909e+08	5.0647e+08	3.127e+04	2.6839e+09
F12	GA	8973	6242	755.8	2.537e+04
F12	WOA	1.7695e+08	4.6631e+08	9.4148e+06	2.6417e+09
F12	L-SHADE	6974	5553	77.01	1.872e+04
F12	CMA-ES	5.567e+04	1.433e+04	2.296e+04	9.509e+04
F13	CA	2.2120e+05	1.8679e+05	1.834e+04	6.6846e+05
F13	CA-static	1.9711e+05	1.7575e+05	3.497e+04	7.7942e+05
F13	GWO	1.7826e+06	2.4331e+06	2.0212e+05	1.0381e+07
F13	PSO	4.5379e+05	4.2879e+05	9.481e+04	2.0864e+06
F13	GA	2.8917e+06	2.4925e+06	4.78e+04	8.3697e+06
F13	WOA	5.2760e+06	4.6962e+06	2.4167e+05	1.5368e+07
F13	L-SHADE	3.468e+04	1.1790e+05	789.3	6.6576e+05
F13	CMA-ES	6.904e+04	6.861e+04	3443	2.4746e+05
F14	CA	2.36e+04	7888	6264	4.497e+04
F14	CA-static	3.082e+04	1.062e+04	1.202e+04	5.938e+04
F14	GWO	1.7884e+07	3.8538e+07	3.0152e+05	1.8339e+08
F14	PSO	1.0135e+07	4.1026e+07	1.687e+04	2.2348e+08
F14	GA	2.169e+04	1.141e+04	3974	5.219e+04
F14	WOA	5.6631e+07	8.3635e+07	2.8791e+05	2.8611e+08
F14	L-SHADE	1.095e+04	6551	1948	3.108e+04
F14	CMA-ES	4.704e+04	1.546e+04	1.968e+04	1.0199e+05
F15	CA	1012	285.4	457.2	1644
F15	CA-static	1042	310	379.7	1816
F15	GWO	1425	540.1	591.4	2431
F15	PSO	1135	331.1	488.2	1853
F15	GA	1114	302.2	452.1	1688
F15	WOA	2729	885.4	1528	5303
F15	L-SHADE	673.8	217.1	169.7	1126
F15	CMA-ES	269.4	179.1	32.58	638.6

Func	Algorithm	Mean	Std	Best	Worst
F16	CA	445.4	184.3	90.54	832.5
F16	CA-static	419.8	194	84.11	830.5
F16	GWO	714.4	295.9	267	1387
F16	PSO	488.6	218	98.63	912
F16	GA	700.7	275.5	60.09	1311
F16	WOA	1564	467	931.3	2907
F16	L-SHADE	211.1	104.6	64.02	389.1
F16	CMA-ES	176.1	95.68	64.88	511.3
F17	CA	5.881e+04	4.279e+04	1.717e+04	2.3831e+05
F17	CA-static	4.293e+04	1.876e+04	1.042e+04	1.0299e+05
F17	GWO	1.3832e+05	5.843e+04	7.511e+04	3.9912e+05
F17	PSO	3.8353e+05	1.0266e+06	6.179e+04	5.6591e+06
F17	GA	7.1096e+05	7.7840e+05	1.339e+04	3.2841e+06
F17	WOA	1.8559e+05	3.4863e+05	3.658e+04	2.0331e+06
F17	L-SHADE	1.302e+04	1.287e+04	2498	6.918e+04
F17	CMA-ES	5.885e+04	3.515e+04	1.202e+04	1.4937e+05
F18	CA	1.463e+04	1.355e+04	251.5	5.897e+04
F18	CA-static	1.025e+04	1.217e+04	491.6	4.737e+04
F18	GWO	5.2931e+09	1.0298e+10	5.402e+04	5.0407e+10
F18	PSO	6.0458e+09	1.7771e+10	1.222e+04	8.6826e+10
F18	GA	2.014e+04	1.389e+04	4736	6.583e+04
F18	WOA	9.9471e+09	2.0025e+10	2.4809e+07	9.9822e+10
F18	L-SHADE	424.2	610.8	44.65	2890
F18	CMA-ES	8.523e+04	4.799e+04	1.388e+04	2.2372e+05
F19	CA	298.8	116.5	202.5	613.9
F19	CA-static	361.7	133.4	87.41	652.8
F19	GWO	673.1	308.7	215.5	1276
F19	PSO	402.3	160.6	205.2	822.5
F19	GA	662.6	246.6	71.76	1131
F19	WOA	939.4	249.4	420.8	1534
F19	L-SHADE	264.4	116.7	70.43	494
F19	CMA-ES	259.2	186.8	60.75	762.5
F20	CA	363.1	175.6	100.1	694.9
F20	CA-static	291.4	184.7	100.1	597.7
F20	GWO	4150	5185	583.2	2.272e+04
F20	PSO	2035	1133	400.9	5567
F20	GA	287.8	107.8	110.5	396.2
F20	WOA	1.446e+04	1.082e+04	2128	3.639e+04
F20	L-SHADE	260.6	140.3	100	537.6
F20	CMA-ES	221.1	61.64	100	276.6
F21	CA	346.4	914.5	100.1	4087
F21	CA-static	728.9	1423	100.1	4688
F21	GWO	4445	3012	201.5	8750
F21	PSO	2070	1906	106.5	6213
F21	GA	3032	2011	103.3	5544
F21	WOA	6478	1179	4056	8178
F21	L-SHADE	774.2	1181	100	3487
F21	CMA-ES	2337	2063	100	7623
F22	CA	314.5	210.5	200.6	853.4
F22	CA-static	317.3	199.2	100.4	826.1
F22	GWO	9891	4098	1937	1.628e+04
F22	PSO	1.08e+04	5061	1584	2.012e+04
F22	GA	265.7	66.79	228.3	515.4
F22	WOA	1.72e+04	8057	6458	4.191e+04
F22	L-SHADE	224.3	93.96	200	664.4
F22	CMA-ES	248.9	70.27	200	392.3
F23	CA	224.5	94.6	200.3	676.9
F23	CA-static	272	150.3	200.3	720.6
F23	GWO	5984	2107	1626	9470
F23	PSO	5347	2684	559	9612
F23	GA	254.3	78.26	220.7	548.5
F23	WOA	1.296e+04	8319	4099	3.544e+04
F23	L-SHADE	221.7	65.19	200	433.2
F23	CMA-ES	229.2	52.99	200	336.3
F24	CA	451.7	22.39	428.2	531.4
F24	CA-static	443.2	18.05	424.2	501.8
F24	GWO	639.5	214.1	436.6	1614
F24	PSO	490	127.5	421.9	1067
F24	GA	435.7	18.28	422.5	502
F24	WOA	1038	314.7	665.6	2286
F24	L-SHADE	423.5	4.252	421	440.3
F24	CMA-ES	420.5	0.0608	420.4	420.7
F25	CA	866.9	45.29	788.2	1084
F25	CA-static	871.5	16.87	835.8	903.7
F25	GWO	913.7	30.28	847.7	980.6

Func	Algorithm	Mean	Std	Best	Worst
F25	PSO	1052	145.2	865.3	1509
F25	GA	840.1	14.75	793.9	870.7
F25	WOA	2731	2035	912	1.034e+04
F25	L-SHADE	840.3	17.29	825.7	873.6
F25	CMA-ES	827.9	2.203	825.4	832.5
F26	CA	547.1	31.32	500.7	600.7
F26	CA-static	558.8	49.5	473.4	681.5
F26	GWO	558.8	28.63	511.8	650.4
F26	PSO	588.6	58.75	501.8	786.7
F26	GA	523	22.3	470.9	563.9
F26	WOA	1231	240.7	830.8	1817
F26	L-SHADE	508.8	13.79	479	533.1
F26	CMA-ES	508.4	15.04	476.7	539.7
F27	CA	227.6	162.1	44.06	482.2
F27	CA-static	229.1	172.3	24.44	477.4
F27	GWO	609.3	182.8	475.7	1377
F27	PSO	810.5	322.4	275.2	1475
F27	GA	102.6	145.3	18.38	476.1
F27	WOA	1073	666.2	562.9	2837
F27	L-SHADE	128.1	110.5	29.12	448.7
F27	CMA-ES	1.928	4.377	0.001209	16.78
F28	CA	9.86e+04	1.3873e+05	1.587e+04	7.2781e+05
F28	CA-static	1.2912e+05	1.9055e+05	1.372e+04	8.3153e+05
F28	GWO	2.6902e+08	4.3159e+08	7.957e+04	1.8853e+09
F28	PSO	3.0455e+07	6.4775e+07	2.427e+04	2.8840e+08
F28	GA	1.4133e+05	2.3724e+05	3842	1.1699e+06
F28	WOA	8.6269e+08	1.0617e+09	1.7668e+07	4.1723e+09
F28	L-SHADE	7281	5508	2366	2.952e+04
F28	CMA-ES	6086	2085	1910	1.024e+04
F29	CA	8.8e+04	1.2333e+05	1.973e+04	6.9350e+05
F29	CA-static	2.2181e+05	2.5501e+05	2.74e+04	1.0666e+06
F29	GWO	5.0197e+08	1.1373e+09	1.4198e+05	4.2573e+09
F29	PSO	6.3055e+08	1.9914e+09	2.16e+04	9.3748e+09
F29	GA	6.5429e+05	1.3877e+06	8067	5.6345e+06
F29	WOA	3.1907e+09	5.4029e+09	5.7569e+06	2.3284e+10
F29	L-SHADE	1.947e+04	1.16e+04	6540	5.41e+04
F29	CMA-ES	1.2181e+05	9.095e+04	4.441e+04	4.9174e+05

Table 34: CEC-2022, full statistics on all 16 validated (function, dimension) cells: mean, standard deviation, best, and worst final error $f - f^*$ over 30 runs (best mean per cell in bold).

Func	Algorithm	Mean	Std	Best	Worst
F1-D10	CA	1.3919e-07	1.8316e-07	6.1567e-10	8.4307e-07
F1-D10	CA-static	1.1278e-07	4.5234e-07	5.6843e-14	2.4716e-06
F1-D10	GWO	267.4	560.4	0.03031	1579
F1-D10	PSO	6.6457e-10	1.0137e-09	7.0486e-12	4.2533e-09
F1-D10	GA	0.003916	0.005432	6.5056e-04	0.03035
F1-D10	WOA	4044	3642	568.6	1.627e+04
F1-D10	L-SHADE	2.4632e-14	2.8168e-14	0	5.6843e-14
F1-D10	CMA-ES	0	0	0	0
F2-D10	CA	14.36	25.33	1.7873e-04	73.52
F2-D10	CA-static	12.06	24.07	1.3643e-04	86.64
F2-D10	GWO	26	32.79	6.484	93.38
F2-D10	PSO	19.75	18.49	4.499	72.25
F2-D10	GA	10.57	18.76	0.05041	84.52
F2-D10	WOA	69.67	101	0.1597	361.5
F2-D10	L-SHADE	6.451	2.465	3.987	8.916
F2-D10	CMA-ES	6.451	2.465	3.987	8.916
F4-D10	CA	20.36	7.008	10	36.77
F4-D10	CA-static	22.6	7.36	10	38
F4-D10	GWO	44.42	12.01	18	66.25
F4-D10	PSO	31.27	9.64	16	48
F4-D10	GA	45.8	19.66	18	106
F4-D10	WOA	102.4	44.61	22	177.9
F4-D10	L-SHADE	18.47	6.212	8.001	34
F4-D10	CMA-ES	17.8	6.052	8	34
F5-D10	CA	0.0996	0.1728	2.2737e-13	0.5439
F5-D10	CA-static	0.1964	0.2853	7.7307e-12	0.9086
F5-D10	GWO	0.006198	0.02241	3.5462e-05	0.09016
F5-D10	PSO	0.01195	0.03043	1.5461e-11	0.08953
F5-D10	GA	0.7676	1.202	6.0990e-06	4.461
F5-D10	WOA	2.956	2.068	0.1818	8.348

Func	Algorithm	Mean	Std	Best	Worst
F5-D10	L-SHADE	0.002984	0.01607	0	0.08953
F5-D10	CMA-ES	0	0	0	0
F6-D10	CA	6264	4765	121.5	1.661e+04
F6-D10	CA-static	8690	7381	389	2.986e+04
F6-D10	GWO	4.426e+04	1.849e+04	1.449e+04	7.483e+04
F6-D10	PSO	2.848e+04	1.561e+04	3396	7.232e+04
F6-D10	GA	1.716e+04	1.334e+04	877.7	4.869e+04
F6-D10	WOA	2.917e+04	1.893e+04	5062	6.768e+04
F6-D10	L-SHADE	36.77	186.8	0.1007	1043
F6-D10	CMA-ES	79.58	241.6	0.09689	955.6
F7-D10	CA	20.06	5.306	0.6316	29.52
F7-D10	CA-static	19.73	8.406	1.129	46.08
F7-D10	GWO	46.96	18.63	24.92	103.7
F7-D10	PSO	30.42	10.34	22.11	69.07
F7-D10	GA	25.73	11.99	1.984	49.26
F7-D10	WOA	374.9	315	32.58	1262
F7-D10	L-SHADE	12.16	9.212	1.175	22.13
F7-D10	CMA-ES	27.69	13.29	3.382	63.71
F8-D10	CA	21.15	5.843	2.351	35.07
F8-D10	CA-static	19.16	6.819	0.9059	22.75
F8-D10	GWO	555.4	659.1	27.49	2945
F8-D10	PSO	407.2	894.8	6.389	2663
F8-D10	GA	56.54	100.1	2.85	439
F8-D10	WOA	1924	1229	266.5	4529
F8-D10	L-SHADE	18.93	5.97	0.7092	23.23
F8-D10	CMA-ES	20.19	7.353	2.144	26.41
F9-D10	CA	183.8	183.8	1.2777e-05	371.8
F9-D10	CA-static	208.3	182.2	2.4829e-09	373.6
F9-D10	GWO	375.3	27.2	360.6	518
F9-D10	PSO	328.9	141.2	1.6698e-06	465.1
F9-D10	GA	285.6	158.1	0.01728	445.6
F9-D10	WOA	416.5	140.4	7.589	729
F9-D10	L-SHADE	275.3	151.9	4.5475e-13	359.1
F9-D10	CMA-ES	359.1	1.7053e-13	359.1	359.1
F1-D20	CA	3.0095e-04	2.1270e-04	7.5344e-05	0.001173
F1-D20	CA-static	1.2142e-05	2.3606e-05	2.5607e-07	1.2641e-04
F1-D20	GWO	2182	2795	6.578	1.03e+04
F1-D20	PSO	766.9	3526	0.005895	1.968e+04
F1-D20	GA	0.1164	0.04908	0.02812	0.2446
F1-D20	WOA	1.277e+04	1.202e+04	771.7	4.872e+04
F1-D20	L-SHADE	3.2852e-11	1.0691e-10	5.6843e-14	5.8105e-10
F1-D20	CMA-ES	1.0819e-12	4.3343e-12	0	2.2908e-11
F2-D20	CA	62.75	18.66	1.478	94
F2-D20	CA-static	61.53	13.45	28.18	77.43
F2-D20	GWO	101.8	71.86	45.65	296.2
F2-D20	PSO	73.02	33.93	27.56	168.3
F2-D20	GA	60.24	12.07	45	80.72
F2-D20	WOA	226.4	125.1	81.83	762.8
F2-D20	L-SHADE	48.73	5.444	44.9	76.19
F2-D20	CMA-ES	48.67	1.257	44.9	49.08
F4-D20	CA	95.27	27.17	44	172
F4-D20	CA-static	110.2	28.16	52	176
F4-D20	GWO	184.4	68.6	48.04	268.9
F4-D20	PSO	129.1	39.35	66	198.6
F4-D20	GA	141.1	44.2	56	250
F4-D20	WOA	408.3	78.42	223.5	521
F4-D20	L-SHADE	59.64	17.84	30.01	106
F4-D20	CMA-ES	43.87	10.54	24	64
F5-D20	CA	1.588	0.8434	0.08956	4.272
F5-D20	CA-static	1.628	0.767	0.4544	3.995
F5-D20	GWO	1.311	1.174	0.001642	4.182
F5-D20	PSO	1.719	1.852	2.2923e-04	6.592
F5-D20	GA	3.179	2.803	0.1798	10.48
F5-D20	WOA	10.22	4.252	3.638	17.48
F5-D20	L-SHADE	0.2258	0.2831	5.6843e-13	0.9982
F5-D20	CMA-ES	0.002984	0.01607	0	0.08953
F6-D20	CA	3.971e+04	1.667e+04	9909	9.508e+04
F6-D20	CA-static	4.312e+04	1.52e+04	2.237e+04	8.015e+04
F6-D20	GWO	1.1382e+06	3.6069e+06	4.267e+04	1.6021e+07
F6-D20	PSO	5.2067e+05	2.3587e+06	2.153e+04	1.3222e+07
F6-D20	GA	5.903e+04	2.376e+04	1.704e+04	1.0908e+05
F6-D20	WOA	7.7248e+05	3.2254e+06	3.668e+04	1.7967e+07
F6-D20	L-SHADE	3.717e+04	1.617e+04	1.266e+04	7.419e+04
F6-D20	CMA-ES	6.225e+04	1.933e+04	5231	1.0745e+05
F9-D20	CA	355.6	13.06	337.9	388.9

Func	Algorithm	Mean	Std	Best	Worst
F9-D20	CA-static	338.8	63.68	0.002043	374
F9-D20	GWO	395.7	43	348.8	548.9
F9-D20	PSO	438	167.7	339.5	1253
F9-D20	GA	343.7	5.018	336.6	359.2
F9-D20	WOA	615.1	149.3	369.1	967.1
F9-D20	L-SHADE	335.6	7.7165e-05	335.6	335.6
F9-D20	CMA-ES	335.6	5.4072e-12	335.6	335.6
F11-D20	CA	4.998	9.974	0.002283	37.07
F11-D20	CA-static	152.5	430.6	3.7559e-05	1546
F11-D20	GWO	522.2	695.3	13.75	1825
F11-D20	PSO	356.1	558.8	12.32	1694
F11-D20	GA	8.723	11.57	0.02764	33.71
F11-D20	WOA	999.4	1076	27.14	3491
F11-D20	L-SHADE	49.69	246.6	5.9845e-10	1377
F11-D20	CMA-ES	1.7451e-08	3.3407e-08	1.2496e-09	1.6867e-07
F12-D20	CA	257.5	24.44	220	312.5
F12-D20	CA-static	259.3	29.23	223.8	323.1
F12-D20	GWO	269.8	27.88	231	337.1
F12-D20	PSO	295	44.46	233	385.3
F12-D20	GA	256.6	35.34	210.6	371.4
F12-D20	WOA	720.3	207.5	322.2	1143
F12-D20	L-SHADE	233	8.669	214.4	258.5
F12-D20	CMA-ES	239.2	16.99	215.9	289.2

Table 35: Engineering design, full statistics on all 7 problems: mean, standard deviation, best, and worst objective over 30 runs (best mean per problem in bold).

Problem	Algorithm	Mean	Std	Best	Worst
Welded Beam	CA	1.774	0.1085	1.725	2.157
Welded Beam	CA-static	1.778	0.1323	1.725	2.352
Welded Beam	GWO	1.728	0.001381	1.726	1.73
Welded Beam	PSO	1.725	0.001027	1.725	1.731
Welded Beam	GA	1.803	0.09243	1.726	2.068
Welded Beam	WOA	172.6	910.3	2.079	5075
Welded Beam	L-SHADE	1.725	6.9982e-16	1.725	1.725
Welded Beam	CMA-ES	1.725	2.0180e-15	1.725	1.725
Spring	CA	0.01293	3.1918e-04	0.01267	0.01373
Spring	CA-static	0.01305	8.5625e-04	0.01267	0.01645
Spring	GWO	0.01281	1.6745e-04	0.01267	0.01336
Spring	PSO	0.01307	9.3019e-04	0.01267	0.01777
Spring	GA	0.01378	0.001224	0.01269	0.01726
Spring	WOA	0.01362	8.4305e-04	0.01267	0.01574
Spring	L-SHADE	0.01267	2.3773e-05	0.01267	0.01277
Spring	CMA-ES	0.01267	8.9809e-06	0.01267	0.01271
Pressure Vessel	CA	5969	236.1	5787	6923
Pressure Vessel	CA-static	5959	230.6	5787	6792
Pressure Vessel	GWO	5887	191.1	5788	6627
Pressure Vessel	PSO	6076	297.9	5787	7301
Pressure Vessel	GA	6408	386.3	5834	7294
Pressure Vessel	WOA	1.621e+04	1.109e+04	6768	4.887e+04
Pressure Vessel	L-SHADE	5798	31.37	5787	5907
Pressure Vessel	CMA-ES	5788	0.1058	5787	5788
Speed Reducer	CA	2994	1.0100e-12	2994	2994
Speed Reducer	CA-static	2994	4.7938e-09	2994	2994
Speed Reducer	GWO	3000	3.543	2994	3008
Speed Reducer	PSO	3032	34.64	2994	3188
Speed Reducer	GA	2994	1.3233e-07	2994	2994
Speed Reducer	WOA	2994	1.129	2994	2999
Speed Reducer	L-SHADE	2994	6.2683e-13	2994	2994
Speed Reducer	CMA-ES	2994	4.5475e-13	2994	2994
Three-Bar Truss	CA	263.9	1.1794e-11	263.9	263.9
Three-Bar Truss	CA-static	263.9	1.1985e-11	263.9	263.9
Three-Bar Truss	GWO	263.9	0.004537	263.9	263.9
Three-Bar Truss	PSO	263.9	6.8562e-06	263.9	263.9
Three-Bar Truss	GA	263.9	0.001248	263.9	263.9
Three-Bar Truss	WOA	266.8	3.698	263.9	282.1

Problem	Algorithm	Mean	Std	Best	Worst
Three-Bar Truss	L-SHADE	263.9	5.6843e-14	263.9	263.9
Three-Bar Truss	CMA-ES	263.9	5.9618e-14	263.9	263.9
Gear Train	CA	7.3005e-10	1.0704e-09	2.7009e-12	4.5033e-09
Gear Train	CA-static	8.0825e-10	1.1062e-09	2.7009e-12	4.5033e-09
Gear Train	GWO	8.4991e-10	8.0675e-10	2.7009e-12	2.3576e-09
Gear Train	PSO	3.1678e-09	5.9167e-09	2.7009e-12	2.7265e-08
Gear Train	GA	7.9160e-10	9.9339e-10	2.7009e-12	4.5033e-09
Gear Train	WOA	2.2534e-08	5.7712e-08	2.7009e-12	3.0059e-07
Gear Train	L-SHADE	5.8222e-11	1.6460e-10	2.7009e-12	8.8876e-10
Gear Train	CMA-ES	9.3803e-10	1.3943e-09	2.7009e-12	6.5123e-09
Cantilever Beam	CA	1.34	4.0084e-05	1.34	1.34
Cantilever Beam	CA-static	1.34	1.9888e-05	1.34	1.34
Cantilever Beam	GWO	1.34	8.7514e-05	1.34	1.34
Cantilever Beam	PSO	1.34	4.3135e-05	1.34	1.34
Cantilever Beam	GA	1.342	0.001269	1.34	1.346
Cantilever Beam	WOA	3.372	1.118	1.621	6.243
Cantilever Beam	L-SHADE	1.34	0	1.34	1.34
Cantilever Beam	CMA-ES	1.34	0	1.34	1.34

Table 36: Granular ablation, per problem: final-error ratio of each single-mechanism-off variant to full CA, with the Wilcoxon p-value and its significance at $\alpha = 0.05$. The averages of these ratios are Table 24 and Figure 13.

Problem	Mechanism disabled	Ratio	p-value	Significant
F1	Pinning	1.121	5.95e-01	no
F1	En passant (success-rule local capture)	3610.7	2.87e-11	yes
F1	Windmill	1.021	9.53e-01	no
F1	Threefold repetition	2.088	8.87e-03	yes
F1	Royal council	1.102	9.18e-01	no
F1	Castling	1.178	3.01e-01	no
F1	Sacrifice	1.211	6.47e-01	no
F1	Knight's fork	274.3	3.70e-06	yes
F1	Blockade response	1.000	1.00e+00	no
F1	Novotny interference	1.135	1.00e+00	no
F1	Discovered attack	1.194	3.91e-01	no
F1	Opposition-based initialization	1.263	9.78e-02	no
F4	Pinning	1.100	3.22e-01	no
F4	En passant (success-rule local capture)	2.692	2.49e-10	yes
F4	Windmill	0.998	9.29e-01	no
F4	Threefold repetition	1.139	2.37e-02	yes
F4	Royal council	0.885	2.56e-02	yes
F4	Castling	1.017	7.79e-01	no
F4	Sacrifice	1.037	9.65e-01	no
F4	Knight's fork	1.585	4.62e-07	yes
F4	Blockade response	1.000	8.88e-01	no
F4	Novotny interference	1.019	7.34e-01	no
F4	Discovered attack	1.139	3.75e-01	no
F4	Opposition-based initialization	1.021	7.34e-01	no
F13	Pinning	1.220	7.01e-01	no
F13	En passant (success-rule local capture)	2.864	1.66e-07	yes
F13	Windmill	1.226	3.91e-01	no
F13	Threefold repetition	1.007	6.15e-01	no
F13	Royal council	1.013	5.84e-01	no
F13	Castling	0.931	9.18e-01	no
F13	Sacrifice	1.097	9.06e-01	no

Problem	Mechanism disabled	Ratio	p-value	Significant
F13	Knight's fork	1.777	8.50e-03	yes
F13	Blockade response	1.021	9.18e-01	no
F13	Novotny interference	0.891	4.69e-01	no
F13	Discovered attack	0.835	6.20e-01	no
F13	Opposition-based initialization	1.114	5.74e-01	no
F22	Pinning	0.777	5.25e-01	no
F22	En passant (success-rule local capture)	1.607	2.51e-05	yes
F22	Windmill	1.004	5.64e-01	no
F22	Threefold repetition	0.953	2.87e-02	yes
F22	Royal council	0.917	6.24e-03	yes
F22	Castling	0.894	1.98e-01	no
F22	Sacrifice	0.998	3.22e-01	no
F22	Knight's fork	1.176	2.92e-04	yes
F22	Blockade response	1.000	9.82e-01	no
F22	Novotny interference	0.919	1.69e-01	no
F22	Discovered attack	0.981	1.47e-01	no
F22	Opposition-based initialization	0.770	1.01e-02	yes
WeldedBeam	Pinning	0.992	8.36e-01	no
WeldedBeam	En passant (success-rule local capture)	1.019	3.11e-03	yes
WeldedBeam	Windmill	1.005	3.52e-01	no
WeldedBeam	Threefold repetition	1.001	6.26e-01	no
WeldedBeam	Royal council	1.029	1.34e-03	yes
WeldedBeam	Castling	0.993	5.64e-01	no
WeldedBeam	Sacrifice	0.996	4.16e-01	no
WeldedBeam	Knight's fork	1.046	3.09e-04	yes
WeldedBeam	Blockade response	1.013	6.05e-01	no
WeldedBeam	Novotny interference	1.000	7.45e-01	no
WeldedBeam	Discovered attack	0.994	7.45e-01	no
WeldedBeam	Opposition-based initialization	0.990	7.23e-01	no
BerthP2	Pinning	1.092	7.34e-01	no
BerthP2	En passant (success-rule local capture)	1.027	4.51e-01	no
BerthP2	Windmill	1.003	8.65e-01	no
BerthP2	Threefold repetition	1.091	7.56e-01	no
BerthP2	Royal council	0.995	7.45e-01	no
BerthP2	Castling	0.982	7.01e-01	no
BerthP2	Sacrifice	1.078	6.05e-01	no
BerthP2	Knight's fork	1.129	5.28e-02	no
BerthP2	Blockade response	1.000	1.00e+00	no
BerthP2	Novotny interference	1.033	8.02e-01	no
BerthP2	Discovered attack	1.001	9.53e-01	no
BerthP2	Opposition-based initialization	1.022	8.24e-01	no

Table 37: Measured cost, per problem: mean wall-clock time, mean evaluations consumed, the ratio of evaluations to the core budget $N \times T$, and time relative to GA on the same problem, over ten runs per cell. The summary columns of Table 26 are the averages of these rows.

Problem	Algorithm	Mean time (s)	Mean evals	Evals / core budget	Time vs GA
F1	CA	0.312	16864	1.124	2.21
F1	CA-static	0.311	16761	1.117	2.20
F1	GWO	0.090	15030	1.002	0.64
F1	PSO	0.080	15030	1.002	0.57
F1	GA	0.141	15030	1.002	1.00
F1	WOA	0.555	15030	1.002	3.93
F1	L-SHADE	1.614	15500	1.033	11.43
F1	CMA-ES	1.065	15000	1.000	7.53
F13	CA	0.876	16710	1.114	1.42
F13	CA-static	0.816	16753	1.117	1.32
F13	GWO	0.540	15030	1.002	0.87
F13	PSO	0.529	15030	1.002	0.86
F13	GA	0.618	15030	1.002	1.00
F13	WOA	1.168	15030	1.002	1.89
F13	L-SHADE	2.078	15500	1.033	3.36

Problem	Algorithm	Mean time (s)	Mean evals	Evals / core budget	Time vs GA
F13	CMA-ES	1.719	15000	1.000	2.78
F22	CA	1.700	16858	1.124	1.19
F22	CA-static	1.849	16758	1.117	1.29
F22	GWO	1.350	15030	1.002	0.94
F22	PSO	1.410	15030	1.002	0.99
F22	GA	1.430	15030	1.002	1.00
F22	WOA	1.945	15030	1.002	1.36
F22	L-SHADE	3.052	15500	1.033	2.13
F22	CMA-ES	2.352	15000	1.000	1.64
F8-2022-D20	CA	11.636	16765	1.118	1.12
F8-2022-D20	CA-static	11.795	16697	1.113	1.13
F8-2022-D20	GWO	12.051	15030	1.002	1.16
F8-2022-D20	PSO	10.023	15030	1.002	0.96
F8-2022-D20	GA	10.394	15030	1.002	1.00
F8-2022-D20	WOA	10.956	15030	1.002	1.05
F8-2022-D20	L-SHADE	11.554	15500	1.033	1.11
F8-2022-D20	CMA-ES	10.559	15000	1.000	1.02
WeldedBeam	CA	0.298	16924	1.128	3.02
WeldedBeam	CA-static	0.296	16722	1.115	2.99
WeldedBeam	GWO	0.051	15030	1.002	0.52
WeldedBeam	PSO	0.038	15030	1.002	0.39
WeldedBeam	GA	0.099	15030	1.002	1.00
WeldedBeam	WOA	1.391	15030	1.002	14.07
WeldedBeam	L-SHADE	1.747	15500	1.033	17.66
WeldedBeam	CMA-ES	0.390	9000	0.600	3.95
SignalP1	CA	0.634	10205	1.134	2.75
SignalP1	CA-static	0.581	10043	1.116	2.53
SignalP1	GWO	0.193	9030	1.003	0.84
SignalP1	PSO	0.189	9030	1.003	0.82
SignalP1	GA	0.230	9030	1.003	1.00
SignalP1	WOA	5.797	9030	1.003	25.20
SignalP1	L-SHADE	6.714	9500	1.056	29.18
SignalP1	CMA-ES	0.746	9000	1.000	3.24

References

- [1] H. Ceylan, M. G. H. Bell, Traffic signal timing optimisation based on genetic algorithm approach, including drivers' routing, *Transportation Research Part B: Methodological* 38 (4) (2004) 329–342. [doi:10.1016/S0191-2615\(03\)00015-8](https://doi.org/10.1016/S0191-2615(03)00015-8).
- [2] C. Osorio, M. Bierlaire, A simulation-based optimization framework for urban transportation problems, *Operations Research* 61 (6) (2013) 1333–1345. [doi:10.1287/opre.2013.1226](https://doi.org/10.1287/opre.2013.1226).
- [3] J. H. Holland, *Adaptation in Natural and Artificial Systems*, University of Michigan Press, Ann Arbor, MI, 1975.
- [4] D. E. Goldberg, *Genetic Algorithms in Search, Optimization, and Machine Learning*, Addison-Wesley, Reading, MA, 1989.
- [5] H.-G. Beyer, H.-P. Schwefel, Evolution strategies — a comprehensive introduction, *Natural Computing* 1 (1) (2002) 3–52. [doi:10.1023/A:1015059928466](https://doi.org/10.1023/A:1015059928466).
- [6] S. Kirkpatrick, C. D. Gelatt, M. P. Vecchi, Optimization by simulated annealing, *Science* 220 (4598) (1983) 671–680. [doi:10.1126/science.220.4598.671](https://doi.org/10.1126/science.220.4598.671).
- [7] J. Kennedy, R. Eberhart, Particle swarm optimization, in: *Proceedings of ICNN'95 — International Conference on Neural Networks*, Vol. 4, IEEE, 1995, pp. 1942–1948. [doi:10.1109/ICNN.1995.488968](https://doi.org/10.1109/ICNN.1995.488968).
- [8] M. Dorigo, V. Maniezzo, A. Coloni, Ant system: optimization by a colony of cooperating agents, *IEEE Transactions on Systems, Man, and Cybernetics, Part B* 26 (1) (1996) 29–41. [doi:10.1109/3477.484436](https://doi.org/10.1109/3477.484436).
- [9] R. Storn, K. Price, Differential evolution — a simple and efficient heuristic for global optimization over continuous spaces, *Journal of Global Optimization* 11 (4) (1997) 341–359. [doi:10.1023/A:1008202821328](https://doi.org/10.1023/A:1008202821328).

- [10] D. Karaboga, B. Basturk, A powerful and efficient algorithm for numerical function optimization: artificial bee colony (abc) algorithm, *Journal of Global Optimization* 39 (3) (2007) 459–471. doi:[10.1007/s10898-007-9149-x](https://doi.org/10.1007/s10898-007-9149-x).
- [11] S. Mirjalili, S. M. Mirjalili, A. Lewis, Grey wolf optimizer, *Advances in Engineering Software* 69 (2014) 46–61. doi:[10.1016/j.advengsoft.2013.12.007](https://doi.org/10.1016/j.advengsoft.2013.12.007).
- [12] S. Mirjalili, The ant lion optimizer, *Advances in Engineering Software* 83 (2015) 80–98. doi:[10.1016/j.advengsoft.2015.01.010](https://doi.org/10.1016/j.advengsoft.2015.01.010).
- [13] S. Mirjalili, Dragonfly algorithm: a new meta-heuristic optimization technique for solving single-objective, discrete, and multi-objective problems, *Neural Computing and Applications* 27 (4) (2016) 1053–1073. doi:[10.1007/s00521-015-1920-1](https://doi.org/10.1007/s00521-015-1920-1).
- [14] S. Mirjalili, A. Lewis, The whale optimization algorithm, *Advances in Engineering Software* 95 (2016) 51–67. doi:[10.1016/j.advengsoft.2016.01.008](https://doi.org/10.1016/j.advengsoft.2016.01.008).
- [15] S. Mirjalili, Sca: A sine cosine algorithm for solving optimization problems, *Knowledge-Based Systems* 96 (2016) 120–133. doi:[10.1016/j.knsys.2015.12.022](https://doi.org/10.1016/j.knsys.2015.12.022).
- [16] S. Mirjalili, A. H. Gandomi, S. Z. Mirjalili, S. Saremi, H. Faris, S. M. Mirjalili, Salp swarm algorithm: A bio-inspired optimizer for engineering design problems, *Advances in Engineering Software* 114 (2017) 163–191. doi:[10.1016/j.advengsoft.2017.07.002](https://doi.org/10.1016/j.advengsoft.2017.07.002).
- [17] D. H. Wolpert, W. G. Macready, No free lunch theorems for optimization, *IEEE Transactions on Evolutionary Computation* 1 (1) (1997) 67–82. doi:[10.1109/4235.585893](https://doi.org/10.1109/4235.585893).
- [18] K. Sörensen, Metaheuristics—the metaphor exposed, *International Transactions in Operational Research* 22 (1) (2015) 3–18. doi:[10.1111/itor.12001](https://doi.org/10.1111/itor.12001).
- [19] R. Tanabe, A. S. Fukunaga, Improving the search performance of SHADE using linear population size reduction, in: 2014 IEEE Congress on Evolutionary Computation (CEC), IEEE, 2014, pp. 1658–1665. doi:[10.1109/CEC.2014.6900380](https://doi.org/10.1109/CEC.2014.6900380).
- [20] N. Hansen, A. Ostermeier, Completely derandomized self-adaptation in evolution strategies, *Evolutionary Computation* 9 (2) (2001) 159–195. doi:[10.1162/106365601750190398](https://doi.org/10.1162/106365601750190398).
- [21] R. N. Mantegna, Fast, accurate algorithm for numerical simulation of Lévy stable stochastic processes, *Physical Review E* 49 (5) (1994) 4677–4683. doi:[10.1103/PhysRevE.49.4677](https://doi.org/10.1103/PhysRevE.49.4677).
- [22] X.-S. Yang, S. Deb, Cuckoo search via Lévy flights, in: 2009 World Congress on Nature & Biologically Inspired Computing (NaBIC), IEEE, 2009, pp. 210–214. doi:[10.1109/NABIC.2009.5393690](https://doi.org/10.1109/NABIC.2009.5393690).
- [23] F. J. Solis, R. J.-B. Wets, Minimization by random search techniques, *Mathematics of Operations Research* 6 (1) (1981) 19–30. doi:[10.1287/moor.6.1.19](https://doi.org/10.1287/moor.6.1.19).
- [24] J. A. Nelder, R. Mead, A simplex method for function minimization, *The Computer Journal* 7 (4) (1965) 308–313. doi:[10.1093/comjnl/7.4.308](https://doi.org/10.1093/comjnl/7.4.308).
- [25] Á. E. Eiben, R. Hinterding, Z. Michalewicz, Parameter control in evolutionary algorithms, *IEEE Transactions on Evolutionary Computation* 3 (2) (1999) 124–141. doi:[10.1109/4235.771166](https://doi.org/10.1109/4235.771166).
- [26] H. R. Tizhoosh, Opposition-based learning: a new scheme for machine intelligence, in: International Conference on Computational Intelligence for Modelling, Control and Automation (CIMCA 2005), Vol. 1, IEEE, 2005, pp. 695–701. doi:[10.1109/CIMCA.2005.1631345](https://doi.org/10.1109/CIMCA.2005.1631345).

- [27] J. Derrac, S. García, D. Molina, F. Herrera, A practical tutorial on the use of nonparametric statistical tests as a methodology for comparing evolutionary and swarm intelligence algorithms, *Swarm and Evolutionary Computation* 1 (1) (2011) 3–18. doi:10.1016/j.swevo.2011.02.002.
- [28] N. H. Awad, M. Z. Ali, J. J. Liang, B. Y. Qu, P. N. Suganthan, Problem definitions and evaluation criteria for the CEC 2017 special session and competition on single objective real-parameter numerical optimization, Technical report, Nanyang Technological University, Singapore (2016).
- [29] G. Vrbančič, L. Brezočnik, U. Mlakar, D. Fister, I. Fister Jr., NiaPy: Python microframework for building nature-inspired algorithms, *Journal of Open Source Software* 3 (23) (2018) 613. doi:10.21105/joss.00613.
- [30] N. Hansen, Y. Akimoto, P. Baudis, CMA-ES/pycma on GitHub (2019). doi:10.5281/zenodo.2559634.
- [31] D. Tilley, cec2017-py: Python implementation of the CEC 2017 benchmark functions, <https://github.com/tilleyd/cec2017-py> (2020).
- [32] A. Kumar, K. V. Price, A. W. Mohamed, A. A. Hadi, P. N. Suganthan, Problem definitions and evaluation criteria for the CEC 2022 special session and competition on single objective bound constrained numerical optimization, Technical report, Nanyang Technological University, Singapore (2021).
- [33] R. P. Roess, E. S. Prassas, W. R. McShane, *Traffic Engineering*, 5th Edition, Pearson, New York, 2019.
- [34] F. V. Webster, *Traffic signal settings*, Road Research Technical Paper 39, Road Research Laboratory, London (1958).
- [35] N. Van Thieu, S. Mirjalili, MEALPY: An open-source library for latest meta-heuristic algorithms in Python, *Journal of Systems Architecture* 139 (2023) 102871. doi:10.1016/j.sysarc.2023.102871.
- [36] S. Mirjalili, Moth-flame optimization algorithm: A novel nature-inspired heuristic paradigm, *Knowledge-Based Systems* 89 (2015) 228–249. doi:10.1016/j.knosys.2015.07.006.
- [37] A. A. Heidari, S. Mirjalili, H. Faris, I. Aljarah, M. Mafarja, H. Chen, Harris hawks optimization: Algorithm and applications, *Future Generation Computer Systems* 97 (2019) 849–872. doi:10.1016/j.future.2019.02.028.
- [38] D. Teodorović, M. Janić, *Quantitative Methods in Transportation*, CRC Press, Boca Raton, FL, 2020. doi:10.1201/9780429316449.