Offline Artificial Intelligence research

"research paper for offline ai" *Generated by LeapSpace*

Offline AI Systems at a Glance

Key Findings Table

Theme	Key finding	Main deployment contexts	Citations
Why offline AI matters	Offline/on-device AI is primarily motivated by lower latency, better privacy, and resilience to poor connectivity, but it is constrained by memory, compute, and energy budgets.	Phones, laptops, embedded devices, IoT, edge systems	[1] [2] [3] [4] [5] [6] [7]
Core technical enablers	Compression and hardware-aware execution are the main enablers of practical offline AI. Quantization, pruning, distillation, low-rank methods, integer-only inference, and compiler/runtime optimization recur across the literature.	Mobile, embedded, TinyML, edge accelerators	[8] [9] [10] [11] [12] [13] [14] [15] [16] [17] [18]
Main bottleneck for generative AI	For offline LLMs and multimodal systems, memory pressure—not only arithmetic throughput—is the dominant bottleneck, especially weight storage, DRAM movement, and KV-cache growth.	On-device LLMs, smartphones, Raspberry Pi, edge hardware	[4] [19] [20] [21] [22] [23] [24] [25] [26] [27] [28]
Practical systems trend	Static fully local deployment is often insufficient in real settings; adaptive partitioning, offloading, multi-exit routing, and deadline-aware scheduling are increasingly used to sustain responsiveness.	MEC, fog, vehicles, heterogeneous edge	[10] [15] [19] [20] [21] [29] [30] [31] [32] [33] [34] [35] [36]

Theme	Key finding	Main deployment contexts	Citations
Compression tradeoff	Compression usually reduces size, latency, and memory, but often at some cost in accuracy or flexibility; distillation and hybrid pipelines are often used to recover quality.	TinyML, vision models, edge LLMs, Jetson, mobile NPUs	[8] [9] [10] [11] [12] [13] [37] [38] [39] [40]
Evaluation gap	Many studies report accuracy, latency, FPS, FLOPs, and memory footprint, but battery, thermal behavior, and long-duration robustness are often missing or qualitative only.	Benchmarks and deployment studies	[4] [7] [18] [41] [42] [43] [44] [45] [46] [47] [48] [49]
Privacy and security	Local execution reduces cloud-side data exposure, but does not remove risk; model extraction, poisoning, gradient leakage, side channels, and local leakage remain relevant.	Edge AI, federated/ decentralized settings, healthcare	[50] [51] [52] [53] [54] [55] [56] [57] [58] [59]
Maturity of on-device learning	On-device learning and adaptation are emerging, but most practical offline AI remains inference-first because of energy, labeling, heterogeneity, and non-IID constraints.	TinyML, embedded FL, MCU learning	[60] [61] [62] [63] [64] [65] [66] [67]

Direct Answer

A strong research-paper topic for “offline AI” is **the design and evaluation of AI systems that run locally without continuous cloud access, with emphasis on compression, memory-aware inference, hardware-software co-design, and privacy-latency-energy tradeoffs** [1] [4] [6] [7] [8] [19] [36].

The evidence supports three especially defensible paper angles:

1. **Offline AI as a systems-and-compression problem**: explain how quantization, pruning, distillation, low-rank adaptation, integer-only inference, and accelerator-aware runtimes make local execution feasible on constrained hardware [8] [9] [11] [12] [13] [14] [16].
2. **Offline generative AI as a memory problem**: argue that for on-device LLMs and multimodal models, the limiting factor is often memory bandwidth, weight storage, and KV-cache growth rather than raw FLOPs alone [4] [18] [19] [20] [21] [26] [27] [28].

3. **Offline AI as a deployment tradeoff**: compare local-first, hybrid, and cloud-connected designs in terms of latency, privacy, bandwidth dependence, accuracy loss, battery, thermal stress, and robustness under real-world conditions [4] [6] [7] [10] [29] [36] [49] [68].

Most practical thesis: *offline AI is increasingly feasible, but its success depends less on model novelty alone and more on compression, memory management, and realistic device-level evaluation* [4] [7] [8] [18] [19].

Confidence level: High - This answer is directly supported by multiple convergent review-level and system-level sources across mobile, embedded, TinyML, and edge generative AI [1] [4] [6] [7] [8] [19].

Study Scope

This report synthesizes evidence on offline AI across edge, mobile, embedded, TinyML, and on-device generative systems, with emphasis on architectures, compression, memory management, scheduling/partitioning, privacy/security, and real-device evaluation practices from the supplied literature spanning approximately 2018-2025 [16] [18] [36] [49] [69]. It covers benchmark studies, surveys, systems papers, and applied case studies in domains including robotics, healthcare monitoring, autonomous systems, industrial IoT, surveillance, and mobile assistants [4] [68] [70] [71].

Assumptions & Limitations

- The evidence base is strong on latency, memory, and compression, but comparatively weak on standardized battery-drain, joule-level energy, and thermal comparisons across methods on the same devices [42] [43] [44] [46] [72] [73] [74] [75] [76].
- Many reported gains come from controlled benchmarks; the literature itself notes generalizability, heterogeneous hardware, unstable networks, and deployment robustness as unresolved concerns [4] [7] [34] [47] [48] [58] [59] [77].
- Some conclusions below are cross-paper syntheses rather than single-study findings; these are labeled as inferred where appropriate [4] [7] [18] [19].

Suggested Further Research

- Build a standardized **offline AI scorecard** combining accuracy, latency, memory, battery, thermal stability, bandwidth use, and privacy/security outcomes on real devices [4] [7] [42] [47] [49].
- Study **long-duration offline generation** to quantify thermal throttling, sustained token rates, and battery aging effects for mobile LLMs [4] [27] [28] [47].
- Compare **fully offline, hybrid edge-cloud, and cloud-only** deployments under identical workloads and hardware conditions [7] [36] [68].
- Develop stronger methods for **memory-bandwidth and KV-cache management** in small on-device generative models [19] [20] [26] [27].
- Expand real-world studies of **on-device adaptation** under non-IID data, scarce labels, and heterogeneous hardware [64] [65] [66] [67].

Offline AI Systems: Architectures, Compression, and Deployment Tradeoffs

Foundational Context

Offline AI refers to AI systems that can perform useful inference—and in some cases limited adaptation—without continuous cloud connectivity [1] [2] [3] [6] [7]. In practice, this includes fully local execution on phones, laptops, MCUs, and embedded devices, as well as intermittently connected systems that operate locally and synchronize or offload only when needed [10] [15] [21] [29] [78] [79].

Three constraints define the field.

First, **resource limits**: device-local execution must fit within restricted memory, compute, storage, and energy budgets [1] [4] [5]. Second, **deployment goals**: local execution is valued for latency reduction, privacy preservation, and independence from unstable or expensive network access [2] [3] [4] [6] [80]. Third, **systems tradeoffs**: moving inference to the edge reduces bandwidth dependence and data exposure, but it also shifts responsibility for optimization, thermal management, and robustness to the device itself [4] [7] [68].

Taken together, these findings suggest that offline AI is best understood not as "cloud AI minus the cloud," but as a joint **model-systems-hardware co-design problem** [8] [11] [12] [14] [15] [16].

Confidence level: High - This framing appears consistently across the supplied reviews and systems literature [1] [4] [6] [7] [8].

1. Why Local Execution Matters

The literature converges on four recurring motivations for offline AI:

- **Latency**: local inference avoids round-trip network delays and is especially attractive for interactive mobile applications, edge robotics, and real-time monitoring [1] [3] [4] [6].
- **Privacy and governance**: on-device execution reduces the need to transmit raw user data to remote servers, lowering cloud-side exposure and easing some data-governance pressures [50] [51] [52] [53] [54].
- **Connectivity resilience**: local-first systems remain usable under intermittent or absent connectivity, which matters in mobile, industrial, and remote settings [2] [7] [68].
- **Bandwidth independence**: local processing lowers dependence on continuous data transfer, which can improve responsiveness and reduce network costs [4] [6] [80].

However, these benefits come with tight constraints. Real deployments remain bounded by limited DRAM, storage, battery, thermal headroom, and accelerator availability [4] [5] [7]. This is why compression and hardware-aware execution are not optional optimizations but foundational design requirements for offline AI [8] [11] [12] [17].

2. Offline AI Architectures and Model Compression

2.1 On-device inference architectures

The architectural literature emphasizes **integer-only or low-bit execution, accelerator-friendly model design, and compiler/runtime optimization** as the main routes to usable on-device performance [11] [12] [14] [15] [81]. Integer-only inference is repeatedly presented as a practical path to improving the accuracy-latency tradeoff on CPUs and constrained hardware [12]. TVM-style compiler approaches target mobile phones, embedded devices, and accelerators with performance competitive to specialized hand-tuned back ends, reinforcing the importance of software-stack optimization rather than model compression alone [74].

Mobile-oriented architectures also prioritize real latency and parameter count rather than abstract FLOP reductions. Foundational examples such as MobileNetV2 are explicitly framed around accuracy-latency-parameter tradeoffs on practical tasks and hardware-relevant metrics [72]. Early-exit designs like BranchyNet similarly reduce computation by terminating inference early for easy inputs, showing that architectural routing can substitute for brute-force local compute [82].

A consistent systems lesson is that architecture choice must match the target execution substrate. Accelerator-friendly models, low-bit kernels, and compiler support create multiplicative gains when aligned; misalignment between model design and hardware/runtime can negate theoretical efficiency improvements [14] [15] [16] [81].

Confidence level: High - The evidence is consistent across architecture, compiler, and benchmark-oriented sources [11] [14] [15] [72] [74] [81].

2.2 Compression methods for deployment

Compression methods recur throughout the corpus as the primary way to fit models within device budgets [8] [9] [10] [11] [12] [13]. The dominant methods are:

- **Quantization**: often the most deployment-ready technique, reducing model size and memory use while often preserving acceptable accuracy [8] [11] [12] [39] [75].
- **Pruning**: removes redundant weights or structures to cut parameters and FLOPs, though aggressive pruning usually risks accuracy degradation [9] [10] [37].
- **Knowledge distillation**: used to transfer performance from larger models to smaller deployable ones, often helping recover accuracy after compression [9] [13] [37].
- **Low-rank adaptation / LoRA-style methods**: important for memory-efficient adaptation and multi-bit deployment, though often evaluated more for memory efficiency than full device-level energy savings [13] [40] [83].

The reported numbers illustrate both promise and tradeoff. TinyML quantization studies report extreme model size reductions, including compression from megabyte-scale models to kilobyte-scale variants, with pruning pushing size even lower in some cases [39]. Embedded PTQ work also reports very small accuracy drops for INT8 deployment on models such as MobileNetV2 and ResNet18 [38]. In object detection, progressive pruning plus feature-aware KD reduced parameters and FLOPs while recovering most of the lost mAP and sustaining high FPS at modest model size [37].

The weakness is evaluation consistency. Across compression studies, the most common outcomes are accuracy, model size, latency, FPS, FLOPs, and memory footprint; explicit joule-level energy savings are comparatively rare [43] [44] [45] [46].

Confidence level: High - The role of compression is strongly supported, while the scarcity of standardized energy measurement is also directly evidenced [8] [9] [10] [11] [12] [13] [43] [46].

2.3 Memory-bound generative inference

For offline generative AI, the literature shifts the problem from generic efficiency to **memory systems management** [4] [19] [20] [21] [26]. Weight storage often dominates memory demand, and per-token generation can be bottlenecked by moving weights from DRAM rather than by arithmetic throughput alone [26]. KV-cache growth further intensifies memory pressure as context length increases [22] [23] [25].

Several strategies recur:

- **Mixed precision / low-bit quantization** to shrink weights and activations [4] [18] [19].
- **Zero-copy reuse and hierarchical weight orchestration** to reduce peak memory and data movement [19] [20].
- **Compact architectures, deep-thin models, and weight sharing** to make mobile deployment feasible [28] [84] [85] [86].
- **Hybrid edge-cloud splitting** when the full model cannot be accommodated locally [21] [36].

Benchmark evidence supports a clear speed-quality-memory tradeoff. On Android/Llama.cpp-type deployments, smaller compact models respond faster and use less memory but provide weaker quality or completeness, while larger compact models improve quality at a cost in response time and storage [87]. On Raspberry Pi-class hardware, small models can still achieve roughly 5-12 tokens/s with under 50% CPU and RAM usage, showing that offline generation is feasible when model size is tightly constrained [28]. Phase-level profiling further shows that embedding, prefill, decode, softmax, and sampling contribute distinct bottlenecks, which matters for runtime optimization [27].

Inferred: Taken together, these findings imply that the next gains in offline generative AI may come less from generic pruning alone and more from memory-traffic-aware runtimes and cache management [19] [20] [26] [27].

Confidence level: High for the bottleneck claim; Medium for the forward-looking inference - The memory bottleneck is directly evidenced, while the projected research direction is a synthesis [4] [18] [19] [26].

3. Deployment Systems, Benchmarks, and Real-World Evaluation

3.1 Partitioning, offloading, and scheduling

Offline AI in practice is often not purely local. Instead, many systems adopt **adaptive partitioning and offloading** to cope with changing network quality, device load, and memory pressure [10] [15] [19] [20] [21] [29]. Dynamic partitioning frameworks base decisions on hardware capability, bandwidth, delay, mobility, and server load [31] [77] [88]. Some continuously reassign work across adjacent devices or heterogeneous nodes as resource use changes [30] [35].

Scheduling methods target real-time completion under resource constraints through deadline-aware allocation, buffering, reassignment of failed tasks, or multi-exit inference routing [32] [33] [89]. In vehicle-edge settings, systems repartition models across vehicles and MEC servers using predicted mobility and load to reduce latency [31].

This supports a broader design pattern: **local-first, hybrid-when-needed** [7] [31] [32] [36]. That is, routine or latency-critical inference may run locally, while overflow cases—large contexts, heavy models, or degraded device state—trigger selective offloading [7] [21].

Confidence level: High - Multiple systems papers support runtime adaptation as a practical response to unstable real-world conditions [30] [31] [33] [36].

3.2 Benchmarking on mobile and embedded hardware

Benchmarking practice is improving, but remains uneven [4] [41] [42] [47]. The most commonly reported metrics are:

- accuracy or task quality [37] [72]
- latency and throughput/FPS [12] [18] [28]
- memory footprint and storage size [18] [87]
- FLOPs and parameter count [37] [72]

Benchmark suites such as MLPerf Inference support reproducible cross-hardware comparison from embedded devices to data centers, but the supplied evidence does not show comprehensive battery or thermal reporting alongside those benchmark results [41]. FlexGen, PagedAttention-related work, and mobile LLM benchmarking focus heavily on throughput and memory efficiency under limited resources [27] [42] [90] [91].

The literature explicitly shows a measurement gap: despite frequent claims about energy efficiency, standardized battery drain, temperature evolution, and sustained-runtime robustness are still uncommon [4] [7] [43] [44] [46]. This gap matters because offline AI workloads—especially generative ones—can stress a device over longer sessions than short benchmark runs reveal [4] [27] [47].

Confidence level: High - The inconsistency of evaluation metrics is a direct cross-source pattern [4] [7] [41] [42] [47].

3.3 Case studies in real-world deployments

Real-world evidence spans multiple sectors.

- **TinyML object detection on MCUs**: 8-bit quantized models were kept within approximately 1 MB flash and 256 KB SRAM budgets, with inference latencies around 3.47-14.98 ms/frame and reported energy of 10.6-22.1 J per inference; UDP reduced one-way latency while TCP improved reliability [92].
- **Jetson Nano edge-vs-host experiments**: measured latency, throughput, energy, memory, and communication overhead, finding edge deployment sufficient for standard real-time workloads but slightly degraded under high load [93].
- **5G offloading for face recognition**: battery consumption and latency were explicitly evaluated over 4G versus 5G, with 5G improving performance for serverless edge deployment [94].
- **Systematic review across autonomous systems, telecom, and IoT**: reports about 70% lower latency, 50% higher computing speed, 30% lower bandwidth use, 40-60% faster decision reaction time, and roughly 25% lower average energy consumption in IoT applications [49].

Broader application areas include robotics, healthcare monitoring, autonomous driving, industrial predictive maintenance, drone navigation, surveillance, and multimodal transport planning [4] [68] [70] [71]. However, a recurring tension remains: impressive gains in specific testbeds do not always translate into uniformly robust field performance across workloads, environments, and hardware types [4] [47] [48] [59].

Confidence level: Medium-High - The case studies are concrete, but cross-domain generalization is explicitly limited in the literature [4] [49] [92] [93] [94].

3.4 Energy, battery, and thermal behavior

Energy and thermal issues are central to offline AI, but the reporting base is thinner than for latency and memory [4] [7] [43] [44]. Some studies do provide useful measurements: MCU object detection reports per-inference energy [92]; Jetson Nano comparisons include energy under different deployment conditions [93]; and 5G offloading work reports battery consumption and latency impacts [94].

At the review level, edge AI is associated with about 25% lower average energy consumption in IoT applications, but these aggregate numbers mask workload and hardware variability [49]. For generative AI, thermal stress during long generation is repeatedly identified as an open issue, indicating that short-form benchmarks may understate operational constraints [4] [7] [47] [58].

4. Privacy, Security, Robustness, and Future Directions

4.1 Privacy and data-governance benefits

A strong and consistent finding is that offline or edge-local deployment reduces exposure of raw data to centralized cloud servers by keeping processing near or on the device [50] [51] [52] [53] [54]. This can lower leakage risk, reduce bandwidth use, and support stricter governance in sensitive domains such as healthcare [56] [57].

This does not mean local deployment is automatically compliant or risk-free. Rather, it changes the risk distribution: less central cloud exposure, but more emphasis on endpoint security, update integrity, and local lifecycle controls [58] [59].

Confidence level: High - The privacy advantage of local execution is among the most consistently supported findings [50] [51] [54].

4.2 Security threats and robustness limits

The literature explicitly warns against equating offline AI with secure AI [55] [56] [57]. Local or decentralized systems still face:

- model inversion and gradient leakage in federated or collaborative settings [55] [56]
- poisoning and adversarial manipulation [56] [57]
- side channels, local data leakage, and model extraction [58] [59]
- robustness failures under heterogeneous hardware, unstable networks, and non-IID data [4] [47] [67]

This is a key contradiction in the field: privacy improves by avoiding cloud upload, yet security risks persist and sometimes shift toward the device or coordination layer [50] [51] [55] [59].

Confidence level: High - The privacy/security tension is directly supported by multiple comparative and review sources [50] [55] [57] [59].

4.3 Emerging on-device learning and adaptation

The literature shows clear interest in moving beyond inference-only offline AI toward limited local adaptation [60] [61] [62] [63]. TinyML surveys describe this as an emerging direction constrained by scarce memory, compute, and energy [62] [63] [69]. Proposed approaches include federated meta-learning, partial local reconstruction, selective communication, integer-based federated training, transfer learning, and cooperative on-device learning [64] [65] [66] [95].

Yet the limitations are consistent: scarce labels, non-IID data, hardware heterogeneity, privacy constraints, and communication cost still prevent full on-device learning from becoming routine [64] [65] [66] [67]. Most deployed offline AI therefore remains **inference-first rather than learning-first** [62] [69].

4.4 Open research challenges

The supplied evidence highlights several unresolved challenges:

1. **Standardized end-to-end evaluation** across accuracy, latency, memory, battery, thermal behavior, bandwidth, and privacy/security on the same devices [4] [7] [42] [47].
2. **Long-duration generative deployment** under sustained token generation and thermal stress [4] [27] [28] [47].
3. **Fair comparison of offline, hybrid, and cloud deployments** under matched workloads and hardware [7] [36] [68].
4. **Better memory and KV-cache control** for on-device LLMs and multimodal assistants [18] [19] [20] [26].
5. **Governance-aware evaluation**, including auditability and local data lifecycle control rather than privacy claims alone [58] [59].

Conclusion

Offline AI is no longer a niche concept; the literature shows it is increasingly practical across phones, embedded systems, and edge platforms when supported by compression, hardware-aware execution, and careful systems design [8] [11] [12] [14] [15] [16]. The strongest technical pattern is that **compression plus co-design** enables deployment, while the strongest systems pattern is that **adaptive hybrid execution** often outperforms rigidly local-only strategies in real conditions [10] [19] [21] [29] [36].

For generative offline AI, the most important shift is conceptual: the limiting factor is frequently **memory movement and cache growth**, not just raw compute [19] [20] [26] [27]. That insight reframes future work toward memory-efficient runtimes, compact architectures, and sustained device-level evaluation [18].

The practical conclusion for a research paper is therefore clear: the best offline AI paper is not just about making models smaller; it is about showing how **architectures, compression, runtime systems, and evaluation protocols combine to make local AI dependable under real device constraints** [4] [7] [8] [18] [19].

Overall confidence level: High - The major conclusions are strongly supported by convergent evidence across surveys, benchmarks, systems papers, and deployment case studies [1] [4] [6] [7] [8] [18] [19] [36].

References

1. Singh, R., Suseelan, A.D. (2026) Quantum-Accelerated Artificial Intelligence for Edge Devices: A Review of Encodings, Models, Hybrid Architectures, and NISQ-Era Realities. *Electronics (Switzerland)*. https://doi.org/10.3390/electronics15132832
2. Wang, W., Li, K., Ji, B., (...), Wu, Q. (2025) A Survey of AI Inference Technologies for On-Device Systems. *IEEE Internet of Things Journal*. https://doi.org/10.1109/JIOT.2025.3613691
3. Zhou, X., Keoh, S.L. (2020) Deployment of facial recognition models at the edge: A feasibility study. *APNOMS 2020 - 2020 21st Asia-Pacific Network Operations and Management Symposium: Towards Service and Networking Intelligence for Humanity*. https://doi.org/10.23919/APNOMS50412.2020.9236972
4. Dinçer, E., Kilimci, Z.H. (2026) Real-time and offline large language models on edge devices: a systematic review. *PeerJ Computer Science*. https://doi.org/10.7717/peerj-cs.3769
5. Saxena, A. (2026) AI in Your Pocket: The Revolution of On-Device Artificial Intelligence. *Synthesis Lectures on Computer Science*. https://doi.org/10.1007/978-3-032-18322-4_1
6. Subedi, P., Chapagain, D., Rimal, S., Pokharel, M. (2026) Emerging Trends and Real-Life Applications of Edge Generative AI. *Enhancing Edge Devices With Generative Intelligence: Architecture, Challenges, and Applications*. https://doi.org/10.4018/979-8-3373-7340-9.ch005
7. Sadaraboina, P.T., Puram, S. (2026) On-Device Generative AI Integration In Android Applications: Architectural Patterns For Scalable And Efficient AI Systems. *International Journal of Artificial Intelligence and Machine Learning*. https://doi.org/10.51483/IJAIML.6.6s.2026.1031-1040
8. Maulana, D., Ramasamy, R.K. (2026) Systematic Review of Quantization-Optimized Lightweight Transformer Architectures for Real-Time Fruit Ripeness Detection on Edge Devices. *Computers*. https://doi.org/10.3390/computers15010069
9. Lamaakal, I., Yahyati, C., Ouahbi, I., (...), Yassine, Y. (2025) A Survey of Model Compression Techniques for TinyML Applications. *2025 International Conference on Circuit, Systems and Communication, ICCSC 2025*. https://doi.org/10.1109/ICCSC66714.2025.11135279
10. Xie, Y., Fang, Q. (2025) An Energy-Aware Generative AI Edge Inference Framework for Low-Power IoT Devices. *Electronics (Switzerland)*. https://doi.org/10.3390/electronics14204086

11. Sheng, T., Feng, C., Zhuo, S., (...), Aleksic, M. (2018) A Quantization-Friendly Separable Convolution for MobileNets. *Proceedings - 1st Workshop on Energy Efficient Machine Learning and Cognitive Computing for Embedded Applications, EMC2 2018*. https://doi.org/10.1109/EMC2.2018.00011

12. Jacob, B., Kligys, S., Chen, B., (...), Kalenichenko, D. (2018) Quantization and Training of Neural Networks for Efficient Integer-Arithmetic-Only Inference. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*. https://doi.org/10.1109/CVPR.2018.00286

13. Yarashov, S., Goziev, O., Nurmuradova, S. (2025) Efficient training of deep neural networks on resource-constrained devices for industrial applications. *Proceedings of SPIE - The International Society for Optical Engineering*. https://doi.org/10.1117/12.3078229

14. Park, H., Kim, S. (2021) Hardware accelerator for training with integer backpropagation and probabilistic weight update. *Advances in Computers*. https://doi.org/10.1016/bs.adcom.2020.11.006

15. Guo, H., Wang, X. (2025) Master-Device-Coordinated Optimization for Distributed CNN Inference at the Edge. *2025 4th International Symposium on Robotics, Artificial Intelligence and Information Engineering, RAIIE 2025*. https://doi.org/10.1109/RAIIE65740.2025.11140395

16. Han, S., Liu, X., Mao, H., (...), Dally, W.J. (2016) EIE: Efficient Inference Engine on Compressed Deep Neural Network. *Proceedings - 2016 43rd International Symposium on Computer Architecture, ISCA 2016*. https://doi.org/10.1109/ISCA.2016.30

17. Cheng, Y., Wang, D., Zhou, P., Zhang, T. (2018) Model Compression and Acceleration for Deep Neural Networks: The Principles, Progress, and Challenges. *IEEE Signal Processing Magazine*. https://doi.org/10.1109/MSP.2017.2765695

18. Xiao, G., Lin, J., Seznec, M., (...), Han, S. (2023) SmoothQuant: Accurate and Efficient Post-Training Quantization for Large Language Models. *Proceedings of Machine Learning Research*. https://www.scopus.com/pages/publications/85174418053

19. Zeng, F., Lyu, F., Wu, H., (...), Xu, F. (2026) H2O: Heterogeneity-Aware Hierarchical Orchestration for Memory-Efficient On-Device LLM Inference. *IEEE Transactions on Mobile Computing*. https://doi.org/10.1109/TMC.2025.3628498

20. Lee, Y., Choee, Y.-S., Lee, S., Kwon, S. (2026) In-Browser Split Inference for Autoregressive Large Language Models With Activation Quantization. *IEEE Access*. https://doi.org/10.1109/ACCESS.2026.3720562

21. Begum, S., Fleming, K., Lewellen, T. (2026) On-Device-First Hybrid LLM Inference on AI-PCs: Closing the Enterprise GenAI Divide. *Digest of Technical Papers - IEEE International Conference on Consumer Electronics*. https://doi.org/10.1109/ICCE67443.2026.11449769

22. Chen, S., Shu, Y., Wang, C., Chen, J. (2026) A survey on edge multimodal large models: Compression, inference acceleration, and applications. *National Science Open*. https://doi.org/10.1360/nso/20260016

23. Kundu, J., Klein, J., Patel, A., Biswas, D. (2026) Technology solutions targeting the performance of gen-AI inference in resource constrained platforms. *2026 International Conference on IC Design and Technology, ICICDT 2026*. https://doi.org/10.1109/ICICDT69693.2026.11669195
24. Lee, Y., Golden, A., Sun, A., (...), Wu, C.-J. (2025) Characterizing and Efficiently Accelerating Multimodal Generation Model Inference. *IEEE Micro*. https://doi.org/10.1109/MM.2025.3596539
25. Li, X., Li, X., Hu, S., (...), Cheong, K.H. (2026) Constraint-Driven Evolution of Multimodal Video Intelligence: A Network and System Perspective. *IEEE Transactions on Network Science and Engineering*. https://doi.org/10.1109/TNSE.2026.3668404
26. Li, F. (2025) The Immutable Tensor Architecture: A Pure Dataflow Approach for Secure, Energy-Efficient AI Inference. *EAI Endorsed Transactions on Internet of Things*. https://doi.org/10.4108/eetiot.14884
27. Wang, H., Tu, X., Ke, H., (...), Han, K. (2025) lm-Meter: Unveiling Runtime Inference Latency for On-Device Language Models. *SEC 2025 - Proceedings of the 2025 10th ACM/IEEE Symposium on Edge Computing*. https://doi.org/10.1145/3769102.3770614
28. Nezami, Z., Hafeez, M., Djemame, K., Zaidi, S.A.R. (2025) Generative AI on the Edge: Architecture and Performance Evaluation. *IEEE International Conference on Communications*. https://doi.org/10.1109/ICC52391.2025.11161569
29. Wang, P., Huang, L., Sun, W., (...), Wu, D.O. (2026) Adaptive Inference Acceleration With Fine-Grained Model Partitioning for Mobile Edge Intelligence. *IEEE Transactions on Mobile Computing*. https://doi.org/10.1109/TMC.2026.3675369
30. Li, J., Wang, X., Chen, H., (...), Buyya, R. (2025) DGPAS: DQN-GRU guided distributed DNN pipeline training and adjacent scheduling in edge networks. *Computer Networks*. https://doi.org/10.1016/j.comnet.2025.111592
31. Zheng, Y., Cui, L., Tso, F.P., (...), Jia, W. (2024) DNN acceleration in vehicle edge computing with mobility-awareness: A synergistic vehicle–edge and edge–edge framework. *Computer Networks*. https://doi.org/10.1016/j.comnet.2024.110607
32. https://www.sciencedirect.com/science/article/pii/S1573048425008738
33. Jamil, S.U., Khan, M.A., Paracha, M.A., Rasheed, A. (2025) Using intelligence in resource allocation and task off-loading for the IoE-edge networks. *Computer Networks*. https://doi.org/10.1016/j.comnet.2024.110884
34. Tran-Van, N.-Y., Le, K.-H. (2025) A multimodal skin lesion classification through cross-attention fusion and collaborative edge computing. *Computerized Medical Imaging and Graphics*. https://doi.org/10.1016/j.compmedimag.2025.102588
35. https://www.sciencedirect.com/science/article/pii/S2661890725001863
36. Kang, Y., Hauswald, J., Gao, C., (...), Tang, L. (2017) Neurosurgeon: Collaborative intelligence between the cloud and mobile edge. *ACM SIGPLAN Notices*. https://doi.org/10.1145/3037697.3037698

37. Zhu, G., Yuan, C., Jiang, F. (2025) Lightweight YOLOv8 Real-Time Object Detection via Progressive Pruning and Feature-Aware Knowledge Distillation. *IEEE Advanced Information Technology, Electronic and Automation Control Conference (IAEAC)*. https://doi.org/10.1109/IAEAC65194.2025.11166037

38. Tiwari, U., Miriyala, S.S., Rajendiran, V.N. (2024) EDGE DEPLOYABLE DISTRIBUTED EVOLUTIONARY OPTIMIZATION BASED CALIBRATION METHOD FOR NEURAL QUANTIZATION. *ICASSP, IEEE International Conference on Acoustics, Speech and Signal Processing - Proceedings*. https://doi.org/10.1109/ICASSP48485.2024.10446281

39. Triesh, A.A., Ahmed, N.A.S. (2025) Embedded AI: Integrating TinyML in Resource-Constrained IoT Devices. *2025 IEEE International Multi-Conference on Smart Systems and Green Process, IMC-SSGP 2025*. https://doi.org/10.1109/IMC-SSGP67001.2025.11474149

40. Siddiqui, Z.H., Gao, J., Shabbir, E., (...), Naseem, U. (2025) LLMs on a Budget? Say HOLA. *EMNLP 2025 - 2025 Conference on Empirical Methods in Natural Language Processing, Proceedings of the Industry Track*. https://doi.org/10.18653/v1/2025.emnlp-industry.71

41. Reddi, V.J., Cheng, C., Kanter, D., (...), Zhou, Y. (2020) MLPerf Inference Benchmark. *Proceedings - International Symposium on Computer Architecture*. https://doi.org/10.1109/ISCA45697.2020.00045

42. Sheng, Y., Zheng, L., Yuan, B., (...), Zhang, C. (2023) FlexGen: High-Throughput Generative Inference of Large Language Models with a Single GPU. *Proceedings of Machine Learning Research*. https://www.scopus.com/pages/publications/85161962667

43. Jain, A., Pal, A., Singh, P. (2025) Optimization Strategies for Training Deep Learning Models in Low-Resource Environments. *16th International Conference on Advances in Computing, Control, and Telecommunication Technologies, ACT 2025*. https://www.scopus.com/pages/publications/105034887149

44. Ahmed, I., Nazim, M., Mishra, V., (...), Taneja, N. (2025) Novel Hybrid Compression Techniques for Full-Stack AI Deployment. *2025 International Conference on Emerging Technologies and Innovation for Sustainability, EmergIN 2025*. https://doi.org/10.1109/EmergIN67762.2025.11450602

45. Sharifirad, I., Boudjadar, J., Roveri, M., Larsen, P.G. (2025) Sensitivity Analysis Exploration of ML Architectures to TinyML Techniques. *Proceedings of the 2025 International Conference on Advanced Machine Learning and Data Science, AMLDS 2025*. https://doi.org/10.1109/AMLDS63918.2025.11159421

46. Schulze, J., Strassenburg, N., Rabl, T. (2025) PQ Bench: Benchmarking Pruning and Quantization Techniques. *Proceedings of the 9th Workshop on Data Management for End-to-End Machine Learning, DEEM 2025 - In conjunction with the 2025 ACM SIGMOD/PODS Conference*. https://doi.org/10.1145/3735654.3735940

47. Ramakrishna, N.K. (2026) Adaptive Feedback-Bound Generative Architecture (AFGA): A Lightweight Framework for Resource-Aware Text Generation on Edge Devices. *Enhancing Edge Devices With Generative Intelligence: Architecture, Challenges, and Applications*. https://doi.org/10.4018/979-8-3373-7340-9.ch009

48. Zhang, B., Hou, J., Zhang, J. (2026) FlexiTensor: Adaptive Multi-Task Deployment of LLMs on Resource-Constrained Heterogeneous Edge Devices. *IEEE Transactions on Parallel and Distributed Systems*. https://doi.org/10.1109/TPDS.2026.3703757

49. Hameed, M., Hameed, N.A., David, A., (...), Alani, S.S. (2025) Edge AI for Transforming Autonomous Systems and Telecommunications for Enhanced Efficiency and Responsiveness. *Iranian Journal of Information Processing and Management*. https://doi.org/10.22034/jipm.2025.728384

50. https://www.sciencedirect.com/science/article/pii/S1572819624002146

51. https://www.sciencedirect.com/science/article/pii/S2730723924000204

52. Rocha, A., Monteiro, M., Mattos, C., (...), Macedo, J. (2024) Edge AI for Internet of Medical Things: A literature review. *Computers and Electrical Engineering*. https://doi.org/10.1016/j.compeleceng.2024.109202

53. Fraga-Lamas, Paula, Lopes, Sérgio Ivan, Fernández-Caramés, Tiago M. (2021) Green IoT and Edge AI as Key Technological Enablers for a Sustainable Digital Transition towards a Smart Circular Economy: An Industry 5.0 Use Case. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s21175745

54. Rawashdeh, M., Alshboul, Y., Zamil, M.G.A., (...), Hossain, M.S. (2022) A security framework for QaaS model in intelligent transportation systems. *Microprocessors and Microsystems*. https://doi.org/10.1016/j.micpro.2022.104500

55. Kaur, Rupinder, Rodrigues, Tiago, Kadir, Nourin, Kashef, Rasha (2025) A Survey on Privacy Preservation Techniques in IoT Systems. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s25226967

56. Xia, J., Li, P., Mao, Y., Wu, M. (2024) PT-ADP: A personalized privacy-preserving federated learning scheme based on transaction mechanism. *Information Sciences*. https://doi.org/10.1016/j.ins.2024.120519

57. Obakhena, Hope Ikoghene, Imoize, Agbotiname Lucky, Anyasi, Francis Ifeanyi (2024) Integration of federated learning paradigms into electronic health record systems. *Federated Learning for Digital Healthcare Systems*. https://doi.org/10.1016/B978-0-443-13897-3.00017-5

58. Modi, R. (2026) Enterprise Adoption of Generative AI Using Azure OpenAI: Architecture, Security, and Governance. *Proceedings of 2026 3rd International Conference on Innovation Management and Information Systems, ICIIS 2026*. https://doi.org/10.1145/3821966.3822046

59. Houache, M., Boubiche, D.E., Abdellah, A., Guezouli, L. (2026) Privacy and Security Challenges in Edge-Deployed Generative AI: Threats, Vulnerabilities, and Defense Mechanisms. *2026 IEEE Wireless Communications and Networking Conference Workshops, WCNCW 2026*. https://doi.org/10.1109/WCNCW67598.2026.11555366

60. Wang, Z., Du, H., Xu, Y., (...), Drakakis, M.M. (2025) UPE: A Device-Edge DNN Inference Artificial Intelligence Processor with Supporting Reconfigurable Training. *AICAS 2025 - 2025 7th IEEE International Conference on Artificial Intelligence Circuits and Systems, Proceedings*. https://doi.org/10.1109/AICAS64808.2025.11173136

61. Jose, I., Kenyeres, N., Quesada, K.C., Chen, I. (2026) A Systematic Review of TinyML Techniques for Efficient Inference and On-Device Learning. *IEEE Access*. https://doi.org/10.1109/ACCESS.2026.3736856

62. Pau, D.P., Ambrose, P.K., Aymone, F.M. (2023) A Quantitative Review of Automated Neural Search and On-Device Learning for Tiny Devices. *Chips*. https://doi.org/10.3390/chips2020008

63. Guo, S., Zhou, Q. (2022) Machine Learning on Commodity Tiny Devices: Theory and Practice. *Machine Learning on Commodity Tiny Devices: Theory and Practice*. https://doi.org/10.1201/9781003340225

64. Ren, H., Anicic, D., Li, X., Runkler, T. (2024) On-device Online Learning and Semantic Management of TinyML Systems. *ACM Transactions on Embedded Computing Systems*. https://doi.org/10.1145/3665278

65. Ren, H., Li, X., Anicic, D., Runkler, T. (2025) TinyMetaFed: Efficient Federated Meta-learning for TinyML. *Communications in Computer and Information Science*. https://doi.org/10.1007/978-3-031-74640-6_10

66. Fragkou, E., Katsaros, D. (2024) Non-static TinyML for ad hoc networked devices. *TinyML for Edge Intelligence in IoT and LPWAN Networks*. https://doi.org/10.1016/B978-0-44-322202-3.00015-4

67. Kanthavel, K., Ramakrishnan, D., Adline Freeda, R.A. (2025) Federated Learning for Artificial Intelligence in Embedded Systems. *ICCK Transactions on Emerging Topics in Artificial Intelligence*. https://doi.org/10.62762/TETAI.2025.440076

68. Kundurthy, O.H., Kaata, S.K., Vikram, S., (...), Gangavarapu, R. (2025) A Framework for Lightweight Generative AI: Enabling Secure, Scalable, and Cloud-to-Edge Intelligence with MicroLLMs. *2025 International Conference on Electronics and Computing, Communication Networking Automation Technologies, ICEC2NT 2025*. https://doi.org/10.1109/ICEC2NT65402.2025.11380015

69. Pazmiño Ortiz, L.A., Maldonado Soliz, I.F., Guevara Balarezo, V.K. (2025) Advancing TinyML in IoT: A Holistic System-Level Perspective for Resource-Constrained AI. *Future Internet*. https://doi.org/10.3390/fi17060257

70. Gachchi, A.R., Babbar, N., Monika (2026) EdgeGen: A Framework for Real-Time Generative AI at the Edge for Autonomous Systems and Critical Infrastructure. *CCIC 2026 - Contemporary Computing Innovations Conference 2026*. https://doi.org/10.1109/CCIC68129.2026.11486072

71. Deligiannis, A., Madas, M. (2026) Operational AI for Multimodal Urban Transport: A Systematic Literature Review and Deployment Framework for Multi-Objective Control and Electrification. *Logistics*. https://doi.org/10.3390/logistics10020029

72. Sandler, M., Howard, A., Zhu, M., (...), Chen, L.-C. (2018) MobileNetV2: Inverted Residuals and Linear Bottlenecks. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*. https://doi.org/10.1109/CVPR.2018.00474

73. Chen, T., Moreau, T., Jiang, Z., (...), Krishnamurthy, A. (2018) TVM: An automated end-to-end optimizing compiler for deep learning. *Proceedings of the 13th USENIX Symposium on Operating Systems Design and Implementation, OSDI 2018*. https://www.scopus.com/pages/publications/85076709967

74. Wu, C.-J., Brooks, D., Chen, K., (...), Zhang, P. (2019) Machine learning at facebook: Understanding inference at the edge. *Proceedings - 25th IEEE International Symposium on High Performance Computer Architecture, HPCA 2019*. https://doi.org/10.1109/HPCA.2019.00048

75. Chouchf, S., El Akhal, H., Zarrik, W., El Belrhiti El Alaoui, A. (2025) A Comparison of Quantization Techniques for Mobile Olive Disease Detection. *2025 5th International Conference on Innovative Research in Applied Science, Engineering and Technology, IRASET 2025*. https://doi.org/10.1109/IRASET64571.2025.11008013

76. Pareek, S., Saleh Al-Samalek, A., alkhayyat, A., (...), Dasi, S. (2024) Efficient Vision Transformers for Edge Devices: Pruning and Quantization Approaches. *Proceedings - 4th International Conference on Technological Advancements in Computational Sciences, ICTACS 2024*. https://doi.org/10.1109/ICTACS62700.2024.10840584

77. Liao, Z., Hu, W., Huang, J., Wang, J. (2023) Joint multi-user DNN partitioning and task offloading in mobile edge computing. *Ad Hoc Networks*. https://doi.org/10.1016/j.adhoc.2023.103156

78. Janbi, N., Katib, I., Mehmood, R. (2023) Distributed artificial intelligence: Taxonomy, review, framework, and reference architecture. *Intelligent Systems with Applications*. https://doi.org/10.1016/j.iswa.2023.200231

79. Sathi, Tanjila Alam, Jany, Rafsan, Azad, AKM, (...), Hossain, Md Azam (2025) Explainable Federated Learning for Multi-Class Heart Disease Diagnosis via ECG Fiducial Features. *Diagnostics*. https://doi.org/10.3390/diagnostics15243110

80. Shahi, R., Shahi, T.B., Neupane, A. (2026) Bringing Generative AI to Edge Devices: Techniques, Challenges, and Applications. *Enhancing Edge Devices With Generative Intelligence: Architecture, Challenges, and Applications*. https://doi.org/10.4018/979-8-3373-7340-9.ch003

81. Wang, K., Zou, L., Zhang, H., (...), Hu, K. (2025) MobiMind: A Lightweight and Fast Inference Framework of Deep Neural Networks for Mobile Devices. *IEEE International Symposium on Broadband Multimedia Systems and Broadcasting, BMSB*. https://doi.org/10.1109/BMSB65076.2025.11165647

82. Teerapittayanon, S., McDanel, B., Kung, H.T. (2016) BranchyNet: Fast inference via early exiting from deep neural networks. *Proceedings - International Conference on Pattern Recognition*. https://doi.org/10.1109/ICPR.2016.7900006

83. Anil, A., Muragod, C.S., Vinod, G.R., Upadhyaya, S.R. (2025) Elemental Adaptation of Low-Rank Quantisation-Aware Training for Large Language Models on Natural Language Processing Tasks. *2025 9th International Conference on Computational System and Information Technology for Sustainable Solutions, CSITSS 2025*. https://doi.org/10.1109/CSITSS67709.2025.11294798

84. Li, Y., Liu, J., Zhang, H., (...), Banerjee, S. (2025) PALMBENCH: A COMPREHENSIVE BENCHMARK OF COMPRESSED LARGE LANGUAGE MODELS ON MOBILE PLATFORMS. *13th International Conference on Learning Representations, ICLR 2025*. https://www.scopus.com/pages/publications/105010261372

85. Liu, Z., Zhao, C., Iandola, F., (...), Chandra, V. (2024) MobileLLM: Optimizing Sub-billion Parameter Language Models for On-Device Use Cases. *Proceedings of Machine Learning Research*. https://www.scopus.com/pages/publications/85203838916

86. Ardakani, M., Malekar, J., Zand, R. (2025) LLMPi: Optimizing LLMs for High-Throughput on Raspberry Pi. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*. https://doi.org/10.1109/CVPRW67362.2025.00634

87. Monteiro, M., Barros, A., Rodrigues, L., (...), MacArio, V. (2025) “Small Device, Big Decision:” Comparing Lightweight LLMs’ Computational Performance and Output Quality for AIED Unplugged. *Communications in Computer and Information Science*. https://doi.org/10.1007/978-3-031-99267-4_20

88. Zhou, Z., Yu, D., Chen, M., (...), He, W. (2024) An edge intelligence-based model deployment method for CNC systems. *Journal of Manufacturing Systems*. https://doi.org/10.1016/j.jmsy.2024.04.029

89. https://www.sciencedirect.com/science/article/pii/S1573772121005937

90. Kwon, W., Li, Z., Zhuang, S., (...), Stoica, I. (2023) Efficient Memory Management for Large Language Model Serving with PagedAttention. *SOSP 2023 - Proceedings of the 29th ACM Symposium on Operating Systems Principles*. https://doi.org/10.1145/3600006.3613165

91. Lu, X., Gao, H., Wu, R., (...), Li, F. (2025) SmartBench: Is Your LLM Truly a Good Chinese Smartphone Assistant?. *EMNLP 2025 - 2025 Conference on Empirical Methods in Natural Language Processing, Proceedings of the Conference*. https://doi.org/10.18653/v1/2025.emnlp-main.194

92. Bhushan, C.M., Koppuravuri, P., Prasanthi, N., (...), Faizi, J. (2025) Deploying TinyML for energy-efficient object detection and communication in low-power edge AI systems. *Scientific Reports*. https://doi.org/10.1038/s41598-025-27818-9

93. Banerjee, S., Ganguly, G., Kumar, S., Dey, S. (2025) An Experimental Study of Application of Edge AI for Accelerated Computation. *13th International Conference on Intelligent Embedded, MicroElectronics, Communication and Optical Networks, IEMECON 2025*. https://doi.org/10.1109/IEMECON69302.2025.11365818

94. Souza, A., Cacho, N., Barbosa, M., (...), Andrade, R. (2025) Offloading Evaluation of machine learning serverless functions over 5G. *1st IEEE Latin American Conference on Internet of Things, LCIoT 2025 - Proceedings*. https://doi.org/10.1109/LCIoT64881.2025.11118549

95. Colombo, L. (2025) Federated On-Device Learning of Integer-Based Convolutional Neural Networks. *Proceedings of 4th International Conference on AI-ML Systems, AIMLSystems 2024*. https://doi.org/10.1145/3703412.3703423