## **Kathmandu University**

# Department of Computer Science and Engineering Dhulikhel, Kavre



## Lab Report #5 Compiler Design

[Course Code: COMP 409]

[For the partial fulfillment of 4<sup>th</sup> year/1<sup>st</sup> Semester in Computer Engineering]

### **Submitted by:**

Sabin Thapa

Roll no. 54

CE 4<sup>th</sup> Year

#### **Submitted to:**

Mr. Sushil Nepal

**Assistant Professor** 

Department of Computer Science and Engineering

Submission date: Nov. 16, 2022

#### **Task**

Write a program to demonstrate left factoring from a left factored grammar.

## **Background**

Left factoring is a process of factoring out the common prefixes of alternatives used when it is not clear that which of the alternatives is used to expand the non-terminal.

For a given grammar:

$$A \rightarrow \alpha \beta_1 \mid \alpha \beta_2$$

We can say that the grammar is left factored as the production alternatives have the same prefix  $\alpha$ . So, inorder to remove the left factoring, we do the following:

$$A \rightarrow \alpha A'$$

$$A \rightarrow \beta_1 \mid \beta_2$$

Now, the grammar is free from left factoring.

Left factoring transforms the grammar such that it is useful for the Top-Down parsers. We came one production for each common prefixes and the rest of the derivation is added by new productions such that the parser has only one production per prefix which makes it easier for the parser to take decisions. Using this, back-tracing of the parser can be avoided.

#### **Source Code**

```
input grammar = []
def take grammar input():
   input grammar = []
   print('Note: \n 1. e represents epsilon. \n',
           '2. Represent in the form: A=>aB \n',
           '3. Press enter after each production. \n')
   while(True):
       user input = input(f'Production: ')
       if user input == '':
           break
       input grammar.append(user input)
   for i,production in enumerate(input grammar):
       input grammar[i]=production.split('=>')
       input grammar[i][1]=input grammar[i][1].split('')
   i=0
   while i<len(input_grammar):</pre>
       j=0
       while j<len(input grammar):</pre>
           if i!=j:
                if input grammar[i][0] == input grammar[j][0]:
                    input grammar[i][1].extend(input grammar[j][1])
                    input grammar.pop(j)
           j+=1
       i+=1
   return input grammar
def left factoring():
   i=0
   while i<len(input_grammar):</pre>
       matched strings = ''
       j = 0
       while j<len(input_grammar[i][1]):</pre>
           k=0
           while k<len(input_grammar[i][1]):</pre>
                if k!=j:
```

```
while True:
                        if len(input grammar[i][1][k])>len(matched strings):
                                                                              if
input grammar[i][1][j][:len(matched strings)+1]
== input grammar[i][1][k][:len(matched strings)+1]:
                                                            matched strings +=
input_grammar[i][1][j][len(matched strings)]
                            else:
                                break
                        else:
                            break
               k+=1
           j += 1
       if len(matched strings):
           factors = []
           \dot{1} = 0
           while j<len(input grammar[i][1]):</pre>
               if len(matched strings) <= len(input grammar[i][1][j]):</pre>
                    if matched strings == input grammar[i][1][j]:
                        input grammar[i][1].pop(j)
                        factors.append('e')
                                                    elif
                                                         matched strings
input grammar[i][1][j][:len(matched strings)]:
factors.append(input grammar[i][1][j][len(matched strings):])
                        input grammar[i][1].pop(j)
                   else:
                        j+=1
               else:
                    i += 1
           if (i+1) < len(input grammar):</pre>
               if input grammar[i+1][0] == input grammar[i][0]+"'":
input_grammar[i][1].insert(0, matched_strings+input_grammar[i][0]+"''")
input grammar.insert(i+1,[input grammar[i][0]+"'',factors])
               else:
input grammar[i][1].insert(0, matched strings+input grammar[i][0]+"'")
input grammar.insert(i+1,[input grammar[i][0]+"'",factors])
           else:
input grammar[i][1].insert(0, matched strings+input grammar[i][0]+"'")
               input grammar.append([input grammar[i][0]+"'",factors])
       i+=1
```

```
def print_output(grammar):
   for production in grammar:
       output statement = ''
       output_statement+=production[0]+'=>'
       for j in range(len(production[1])):
           if j:
               output statement+='|'
           output statement+=production[1][j]
       print(output_statement)
   print()
if __name__=='__main__':
   input_grammar = take_grammar_input()
   print('\nGiven Grammar ')
   print output(input grammar)
   left factoring()
   left factoring()
   print('Left Factored Removed Grammar')
   print_output(input_grammar)
```

#### **Explanation**

When the user inputs a left factored grammar, the program checks for it and finds it and then it provides back the user with the grammar that has been freed from left factoring. There are three main functions:

- 1. take grammar input() to take the grammar input from the user.
- 2. left factoring() to eliminate the left factoring from the grammar.
- 3. print output() to display the output to the user.

### Output

```
sabinthapa pop-os .../Compiler Design/lab labs ⊙ Compiler python3 lab5.py
 Note:
  1. e represents epsilon.
  2. Represent in the form: A=>aB
  3. Press enter after each production.
 Production: A=>aaBcc|aaBc|aaB
 Production: B=>cC|d
 Production: C=>d
 Production:
 Given Grammar
 A=>aaBcc|aaBc|aaB
 B=>cC|d
 C=>d
 Left Factor Removed Grammar
 A=>aaBA''
 A''=>cA'|e
 A'=>c|e
 B=>cC|d
 C=>d
```

Here, the first production of the input grammar is left-factored. The aaB prefix of the alternatives is the same. After writing a separate production for the prefix, we can again see that, there is a presence of common prefix (A"c) again in the production. So, the production is again evaluated and the left factoring is removed. Finally, we get the productions that are free from left factoring.

#### Conclusion

In this way, the program to demonstrate and remove left factoring from the given left factored input grammar was implemented in Python. The source code and the outputs of the program are attached in the document above.