itc · STAGE MONITORS

KS-14F

Professional Three-frequency Coaxial Monitor speaker

The itc KS-14F is a professional Three-frequency Coaxial Monitor speaker from itc's Stage Monitors range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues.

Key figures: rated power 500W; peak power 2000W; frequency range 60Hz-20KHz. Highlights include one 14-inch coaxial woofer, one 100mm+65mm Italian neodymium magnetic coaxial compression driven mid-tweeter, high-quality birch wood with recise CNC machining and with hanging parts to realize stage sound monitoring.



Key features

- One 14-inch coaxial woofer
- One 100mm+65mm Italian neodymium magnetic coaxial compression driven mid-tweeter
- High-quality birch wood with recise CNC machining
- With hanging parts to realize stage sound monitoring
- Directional control with a wide frequency band

Technical specifications

Rated power	500W
Peak power	2000W
Nominal impedance	8Ω
Frequency range	60Hz-20KHz
Sensitivity	104dB(1M/1W)
Maximum SPL (rated/peak)	131dB/137dB
Woofer	14″ woofer × 1
Tweeter	100mm+65mm coaxial mid-tweeter × 1
Coverage angle (-6dB)	75°(H) 40°(V)
Net weight	26kg
Dimension (H×W×D)	420×580×480mm