itc · TC SERIES AMPLIFIERS

# TC-21200

Professional Amplifier

The itc TC-21200 is a professional Amplifier from itc's TC Series Amplifiers range, built for powering loudspeaker systems in halls, auditoriums, places of worship, banquet venues and live events.

Key figures: power at Stereo 8Ω×2 (continuous · max) 2*1200W · 2*2000W; power at Stereo 4Ω×2 (continuous · max) 2*1900W · 2*3400W; power at Stereo 2Ω×2 (continuous · max) 2*3200W · 2*4800W. Highlights include dual-channel high-power professional digital power amplifier, excellent technologies ensure high working stability, multi-track audio loop technology and audio output adaptive load power control technology.



## Key features

- Dual-channel high-power professional digital power amplifier
- Excellent technologies ensure high working stability — Adaptive variable modulation frequency Automatic stabilization technology
- Multi-track audio loop technology — Reduce audio distortion Provide ultra-high dynamic range frequency response
- Audio output adaptive load power control technology — Enhances the ability to adapt to various complex load environments
- More than 95% ultra-high efficiency — Adaptive dynamic power efficient conversion of power supply Multi-channel status detection automatic power adjustment

## Technical specifications

| | |
|---|---|
| Power cont./max — Stereo 8Ω×2 | 2*1200W · 2*2000W |
| Power cont./max — Stereo 4Ω×2 | 2*1900W · 2*3400W |
| Power cont./max — Stereo 2Ω×2 | 2*3200W · 2*4800W |
| Power cont./max — Bridge 16Ω | 2400W · 4000W |
| Power cont./max — Bridge 8Ω | 3800W · 6800W |
| Power cont./max — Bridge 4Ω | 6400W · 11600W |
| Connecting socket | XLR interface |
| Voltage Gain (@1kHz) | 41dB |
| Input sensitivity | 2.2dBU(1V), 8.2dBU(2V) |
| Input impedance | 10KΩ unbalanced, 20KΩ balanced |
| Frequency response (Under @1W power) | 20-20kHz/±1dB |
| THD+N (Under @1/8 power) | ≤0.01% |
| SNR (A-weighted) | ≥105dB |
| Damping Factor (@ 1kHz) | ≥200@ 8 ohms |
| Crosstalk (@1kHz) | ≥85dB |
| Protection method | Overvoltage protection, undervoltage protection, overcurrent protection, DC protection, short circuit protection |
| Indicator light | Power, Protection, Signal, Distortion |

Continued specifications on request.