itc · CONFERENCE & COLUMN LOUDSPEAKERS

# TS-403HB

Column Speaker

The itc TS-403HB is a column Speaker from itc's Conference & Column Loudspeakers range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues.

Key figures: rated power 100W; frequency range 150Hz-14KHz@-6dB/80Hz-20KHz@-10dB; coverage angle Vertical >20°, horizontal >120°@ (-6db). Highlights include four 3-inch high performance ferrite driver unit, constant beam technology, unique low-frequency cardioid diffusion and strong and durable cabinet.



## Key features

- Four 3-inch high performance ferrite driver unit
- Constant beam technology — Solve the problems of projection and interference of traditional speakers
- Unique low-frequency cardioid diffusion — Provide clear treble, natural timbre, and powerful bass
- Strong and durable cabinet — ABS plastic mixed glass fiber reinforced cabinet Aluminum mesh cover, anti-rust cabinet OptionalUV waterproof dip coating for IPx4 waterproof degree OptionalUL94V-0 flame retardant material Optional smart

## Technical specifications

| | |
|---|---|
| Rated power | 100W |
| Nominal resistance | 8Ω |
| Frequency range | 150Hz-14KHz@-6dB/80Hz-20KHz@-10dB |
| Sensitivity | 95dB(1M/1W) |
| Coverage angle | Vertical >20°, horizontal >120°@ (-6db) |
| Speaker unit | 3″ full-range speaker ×4 |
| Housing material | ABS + fiberglass |
| Net weight | 5.08kg |
| Dimension | 530×100×150mm |