itc · WIRELESS MICROPHONES

# TS-548MD

Microphone

The itc TS-548MD is a microphone from itc's Wireless Microphones range, built for speech, vocal and instrument pickup for conferences, lectures, worship and live performance.

Key figures: power voltage Phantom + 48V power supply; frequency response 40Hz-18kHz; sensitivity -45dB. Highlights include electret condenser microphone, advanced PLL phase-locked loop, CPU bus control system of microcomputer integrated central processor and intelligent frequency adjustment.



## Key features

- Electret condenser microphone — Resistant to mobile phone signal interference
- Advanced PLL phase-locked loop
- CPU bus control system of microcomputer integrated central processor
- Intelligent frequency adjustment — Manual frequency selection Automatic infrared frequency matching and locking
- Noise and sound code lock squelch control

## Technical specifications

| | |
|---|---|
| Transduction method | Condenser microphone |
| Frequency response | 40Hz-18kHz |
| Directivity | Super cardioid polar pattern |
| Output impedance | 75Ω |
| Sensitivity | -45dB |
| Maximum input volume | 135dB sound pressure |
| Dynamic range | 109 dB, 1KHz |
| SNR | 70 dB |
| Power voltage | Phantom + 48V power supply |
| Microphone pole | 200mm |
| Microphone weight | 0.6kg |
| Others | Iron base, resistant to interference of mobile phones, electromagnetic, and high-frequency |